Resubmission of Coding challenge 4

Dulshika Dassanayake

2026-03-02

Contents

0.1 R Markdown 1

1 Question 1 **1**

2 Question 2a **1**

3 Question 2b **2**

4 Question 2c **2**

5 DON_PLOT1 **2**

6 Question 6 **10**

6.1 Including Plots 11

Noel et al. 2022, Plant Disease Paper

my Github repository:

0.1 R Markdown

1 Question 1

Explain the following a. YAML header The YAML header is the metadata block at the very top of an R Markdown file (between — lines). It controls document settings such as the title, author(s), date, output format (HTML/PDF/Word), and options like a table of contents

b. Literate programming Literate programming means writing code together with explanations (in text) so the document reads like a report. In R Markdown, mix narrative text + code chunks, and when knit, the code runs and outputs (plots/tables) are embedded automatically.

2 Question 2a

paperlink: (https://doi.org/10.1094/PDIS-06-21-1253-RE)

3 Question 2b

```
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ------------------------ tidyverse 2.0.0 --
## v dplyr     1.1.4     v readr     2.1.6
## v forcats   1.0.1     v stringr   1.6.0
## v ggplot2   4.0.1     v tibble    3.3.1
## v lubridate 1.9.4     v tidyr     1.3.2
## v purrr     1.2.1
## -- Conflicts ------------------------------------------ tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()    masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library(ggplot2)
library(ggpubr)
mycotoxin<- read.csv("MycotoxinData.csv", na.strings="na")
mycotoxin$Treatment <- as.factor(mycotoxin$Treatment)
mycotoxin$Cultivar <- as.factor(mycotoxin$Cultivar)
mycotoxin$DON <- as.numeric(mycotoxin$DON)
mycotoxin$X15ADON <- as.numeric(mycotoxin$X15ADON)
mycotoxin$MassperSeed_mg <- as.numeric(mycotoxin$MassperSeed_mg)
str(mycotoxin)
```

```
## 'data.frame':    375 obs. of  6 variables:
##  $ Treatment     : Factor w/ 5 levels "Fg","Fg + 37",..: 1 1 1 1 1 1 1 1 1 1 ...
##  $ Cultivar      : Factor w/ 2 levels "Ambassador","Wheaton": 2 2 2 2 2 2 2 2 2 2 ...
##  $ BioRep        : int  2 2 2 2 2 2 2 2 2 3 ...
##  $ MassperSeed_mg: num  10.29 12.8 2.85 6.5 10.18 ...
##  $ DON           : num  107.3 32.6 416 211.9 124 ...
##  $ X15ADON       : num  3 0.85 3.5 3.1 4.8 3.3 6.9 2.9 2.1 0.71 ...
```

4 Question 2c

```
cbbPalette <- c("#56B4E9", "#009E73")
```

5 DON_PLOT1

```
Plot1 <- ggplot(mycotoxin, aes(x = Treatment, y = DON, fill = Cultivar)) +
  geom_boxplot(position = position_dodge(0.85)) +
  xlab("") +
  ylab("DON (ppm)") +
  geom_point(alpha = 0.6,pch = 21, color = "black") +
  scale_fill_manual(values = cbbPalette)+
  facet_wrap(~Cultivar)+
```

```
  theme_classic()
Plot1
```

```
## Warning: Removed 8 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 8 rows containing missing values or values outside the scale range
## (`geom_point()`).
```



Plot X15ADON

```
Plot2 <- ggplot(mycotoxin, aes(x = Treatment, y = X15ADON, fill = Cultivar)) +
  geom_boxplot(position = position_dodge(0.85)) +
  xlab("") +
  ylab("15ADON") +
  geom_point(alpha = 0.6,pch = 21, color = "black") +
  scale_fill_manual(values = cbbPalette)+
  facet_wrap(~Cultivar)+
  theme_classic()
Plot2
```

```
## Warning: Removed 10 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 10 rows containing missing values or values outside the scale range
## (`geom_point()`).
```



SeedMass

```
#Plot 3

Plot3<- ggplot(mycotoxin, aes(x = Treatment, y = MassperSeed_mg, fill = Cultivar)) +
geom_boxplot(position = position_dodge(0.85)) +
  xlab("") +
  ylab("Seed Mass (mg)") +
  geom_point(alpha = 0.6,pch = 21, color = "black") +
  scale_fill_manual(values = cbbPalette)+
  facet_wrap(~Cultivar)+
  theme_classic()
Plot3
```

```
## Warning: Removed 2 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 2 rows containing missing values or values outside the scale range
## (`geom_point()`).
```



#3Combined_PLOT

```
library(ggpubr)


figure=ggarrange(Plot1,Plot2,Plot3,labels = c("A", "B", "C"),nrow = 1,ncol = 3,common.legend=TRUE)
```

```
## Warning: Removed 8 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 8 rows containing missing values or values outside the scale range
## (`geom_point()`).

## Warning: Removed 8 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 8 rows containing missing values or values outside the scale range
## (`geom_point()`).

## Warning: Removed 10 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 10 rows containing missing values or values outside the scale range
## (`geom_point()`).
```

```
## Warning: Removed 2 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 2 rows containing missing values or values outside the scale range
## (`geom_point()`).
```

```
figure
```



#Combined_with_pairwisecomparison

```
## Plot 1: plot1 with pairwise comparisons
Plot1_pwc <- Plot1 +
  geom_pwc(aes(group = Treatment), method = "t.test", label = "p.adj.format") +  # Add pairwise t-tests
  theme_classic()

Plot1_pwc
```

```
## Warning: Removed 8 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 8 rows containing non-finite outside the scale range
## (`stat_pwc()`).

## Warning: Removed 8 rows containing missing values or values outside the scale range
## (`geom_point()`).
```




```
##Plot 2: plot2 with pairwise comparisons
Plot2_pwc <- Plot2 +
  geom_pwc(aes(group=Treatment), method= "t.test", label= "p.adj.format")+
  theme_classic()

Plot2_pwc
```

```
## Warning: Removed 10 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 10 rows containing non-finite outside the scale range
## (`stat_pwc()`).

## Warning: Removed 10 rows containing missing values or values outside the scale range
## (`geom_point()`).
```




```
##Plot 3: plot3 with pairwise comparisons
Plot3_pwc = Plot3 + geom_pwc(aes(group=Treatment), method="t.test", label="p.adj.format")+
  theme_classic()

Plot3_pwc
```

```
## Warning: Removed 2 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 2 rows containing non-finite outside the scale range
## (`stat_pwc()`).

## Warning: Removed 2 rows containing missing values or values outside the scale range
## (`geom_point()`).
```




```
#Combine all three plots with a common legend ----
Combined_pwc =ggarrange(Plot1_pwc,Plot2_pwc,Plot3_pwc,labels = c("D", "E", "F"),nrow = 1,ncol = 3,commo
```

```
## Warning: Removed 8 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 8 rows containing non-finite outside the scale range
## (`stat_pwc()`).

## Warning: Removed 8 rows containing missing values or values outside the scale range
## (`geom_point()`).

## Warning: Removed 8 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 8 rows containing non-finite outside the scale range
## (`stat_pwc()`).

## Warning: Removed 8 rows containing missing values or values outside the scale range
## (`geom_point()`).

## Warning: Removed 10 rows containing non-finite outside the scale range
## (`stat_boxplot()`).
```

```
## Warning: Removed 10 rows containing non-finite outside the scale range
## (`stat_pwc()`).

## Warning: Removed 10 rows containing missing values or values outside the scale range
## (`geom_point()`).

## Warning: Removed 2 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

## Warning: Removed 2 rows containing non-finite outside the scale range
## (`stat_pwc()`).

## Warning: Removed 2 rows containing missing values or values outside the scale range
## (`geom_point()`).
```

```
Combined_pwc
```



Question5 README

6 Question 6

Github my Github repository:

This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML, PDF, and MS Word documents. For more details on using R Markdown see http://rmarkdown.rstudio.com.

When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the document. You can embed an R code chunk like this:

```
summary(cars)
```

```
##      speed           dist       
##  Min.   : 4.0   Min.   :  2.00  
##  1st Qu.:12.0   1st Qu.: 26.00  
##  Median :15.0   Median : 36.00  
##  Mean   :15.4   Mean   : 42.98  
##  3rd Qu.:19.0   3rd Qu.: 56.00  
##  Max.   :25.0   Max.   :120.00  
```

6.1 Including Plots

You can also embed plots, for example:



Note that the `echo = FALSE` parameter was added to the code chunk to prevent printing of the R code that generated the plot.