# Interior Point Methods applied to Quadratic Programming\*

Daniel Bergmann 1

Abstract—Describe in a few sentences what the paper is about and why it is interesting to read it.

#### I. INTRODUCTION

Notation. Throughout this paper, we denote the set of all real numbers as  $\mathbb R$  and the set of all natural numbers as  $\mathbb N$ , respectively  $\mathbb N_0$  if zero is included. Further we denote the Jacobian of a function  $f:\mathbb R^n\longrightarrow\mathbb R^m$ , differentiated along direction v, evaluated at point  $x\in\mathbb R^n$  as  $J_vf(x)$ . The index v is omitted, if it is contextually clear. For a collection of scalar valued functions  $h_i:\mathbb R^n\longrightarrow\mathbb R, i=1,\ldots,m$  with the same domain, we define

$$h(x) := \begin{pmatrix} h_1(x) \\ \vdots \\ h_m(x) \end{pmatrix}$$

for the stacked values of all  $h_i$  evaluated at  $x \in \mathbb{R}^n$ .

# II. PROBLEM STATEMENT AND BACKGROUND

For theoretical discussions, we consider the convex constrained optimization problem

minimize 
$$f_0(x)$$
  
subject to  $f_i(x) \le 0, i = 1, ..., m$ . (1)  
 $A_{\rm eq} x = b_{\rm eq}$ .

with  $f_0: \mathbb{R}^n \longrightarrow \mathbb{R}$  convex and twice differentiable,  $f_i: \mathbb{R}^n \longrightarrow \mathbb{R}$  for  $i=1,\ldots,m$  convex and differentiable,  $A_{\rm eq} \in \mathbb{R}^{n \times p}, b_{\rm eq} \in \mathbb{R}^p$  with equality and inequality constraints. For such an optimization problem, we call its Lagrangian  $L: \mathbb{R}^n \times \mathbb{R}^m \times \mathbb{R}^p \longrightarrow \mathbb{R}$  with

$$L(x, \lambda, \nu) = f_0(x) + \lambda^T f(x) + \nu^T (A_{eq} x - b_{eq}).$$

Further, we denote its dual problem by

with

$$g(\lambda, \nu) = \inf_{x \in \mathbb{R}^n} L(x, \lambda, \nu).$$

Moreover, we give a MATLAB-implementation of a primal-dual interiorpoint method for convex quadratic optimization problems. Quadratic problems are a subclass of

\*Project within the course Convex Optimization, University of Stuttgart, July 16, 2020.

<sup>1</sup>Daniel Bergmann is a student of the Bachelor study program Mechatronics, University of Stuttgart, st108500@stud.uni-stuttgart.de (1) and denote as

minimize 
$$f_0(x) = \frac{1}{2}x^TQx + c^Tx$$
  
subject to  $A_{\text{in}}x - b_{\text{in}} \le 0, \ A_{\text{in}} \in \mathbb{R}^{m \times n}, b_{\text{in}} \in \mathbb{R}^m$  (3)  
 $A_{\text{eq}}x - b_{\text{eq}} = 0, \ A_{\text{in}} \in \mathbb{R}^{p \times n}, b_{\text{in}} \in \mathbb{R}^p$ 

with matrices  $0 \prec Q \in \mathbb{R}^{n \times n}$ ,  $c \in \mathbb{R}^n$ .

## III. MAIN RESULTS

#### A. Newton's Method

Newton's method is an iterative process to solve nonlinear equation systems

$$F(x) = 0 (4)$$

for a differentiable map  $F:\mathbb{R}^n\longrightarrow\mathbb{R}^m$ . The algorithm works as follows: At a given point  $x_k$ , the zero of the linear approximation of F around  $x_k$  is computed. This point is chosen as the next iterate  $x_{k+1}$ . In particular, a linear approximation of F in  $x_k$  is defined as

$$L(x) := F(x_k) + JF(x_k)(x - x_k) \text{ for } x \in \mathbb{R}^n, \quad (5)$$

where  $JF(x_k)$  is the Jacobian of F at the point  $x_k$ . If  $JF(x_k)$  is invertible, the point  $\tilde{x}$  with  $L(\tilde{x}) = 0$  is exactly the solution of the linear equation  $JF(x_k)x = -F(x)$ . Technical conditions and proofs about convergence rates of Newton's method can be found in [1]. The procedure executing a Newton search is summarized in (1).

#### Algorithm 1: Newton's Method

**Result:**  $\tilde{x}$ , approximate solution of nonlinear system of equalities F(x)=0, residual tolerance  $\epsilon_{res}>0$ , cauchy-tolerance  $\epsilon_c>0$ 

**Data:** Function  $F: \mathbb{R}^n \longrightarrow \mathbb{R}^n$ , initial point  $x_0$ 

while 
$$||x - x_{\text{last}}|| \ge \epsilon_c$$
 or  $||F(x)|| \ge \epsilon_{res}$  do compute Newton direction  $\Delta x$  by solving  $JF(x)\Delta x = -F(x);$  remember last interation for checking term. crit.  $x_{\text{last}} = x;$ 

update current point by  $x = x + \Delta x$ ;

end

return  $\tilde{x} = x$ ;

Remark 1: The residual and the cauchy-criterion for termination should be combined for the newton method. Easy examples are known, where one of the criteria is satisfied even though the current iteration is far from the optimal point. For details, see [1]. For theoretical reasoning, or if  $\nabla^2 f(x)^{-1}$  can be used explicitly, one can also use the

decreasement of  $\lambda^2 = \nabla f(x)^T \nabla^2 f(x)^{-1} \nabla f(x)$  (so called newton-decrement) under a certain tolerance.

For the purpose of optimizing a convex, twice differentiable objective function  $f_0$  we want to find a zero of the gradient  $\nabla f_0$ . Therefore we can apply the Newton Method to solve the non-linear equation

$$F(x) := \begin{pmatrix} \nabla f_0(x) \\ g(x) \end{pmatrix} = 0.$$

By convexity, satisfying  $\nabla f_0(x^*) = 0$  is not only neccessary, but also sufficient for  $x^*$  to be a global minimum of  $f_0$ .

## B. Concept of Barrier Methods

Convex optimization problems with no inequality constraints can be solved efficiently by using Newton's method. If inequality constraints are involved, Newton's method can not guarantee feasibility of a found solution. Hence it is desirable, to transform an inequality-constrained optimization problem into one, that is only equality-constrained. Therefore, we move the inequality constraints implicitly to the objective function. A simple and precise way to do this, would be to evaluate an indicator function

$$I_{-}(x) := \begin{cases} 0 & \text{for } u \neq 0 \\ \infty & \text{for } u > 0 \end{cases}$$
 (6)

on the values of the inequality constraints  $f_i$ , i = 1, ..., m. We obtain a problem in the following shape

This problem is equivalent to (1), since it yields an objective value of  $+\infty$  for every infeasible point while it is the same problem for every feasible one. We now have a formulation without inequality constraints. However, it is clearly neither convex nor continuous and hence not differentiable. Since we need these properties to solve the optimization problem computationally, we approximate the indicator function  $I_{-}$ by the function

$$\hat{I}_{-}(u) = \begin{cases} \frac{1}{t} \log(-u) & \text{for } u < 0, \\ \infty & \text{for } u \ge 0, \end{cases}$$
 (8)

The parameter t > 0 sets the approximation's accuracy. A higher value for t results in a better approximation of the indicator function. By replacing the indicator function by  $I_{-}$ , we obtain an approximation

of problem (1). Throughout this paper, we denote its Lagrangian by  $L_t: \mathbb{R}^n \times \mathbb{R}^p \longrightarrow \mathbb{R}$ . Note that  $\frac{1}{t} \log(-u)$  is convex, increasing in u, and

differentiable on the feasible set. Hence the entire function

 $\sum_{i=1}^{m} \hat{I}_{-}(f_{i}(x))$  is convex and (9) is a convex Problem with differentiable objective function. These properties allow us to solve (9) computationally. We call an optimal point  $x^*(t)$  of (9) with parameter t a central point and a solution to its dual problem  $(\lambda^*(t), \nu^*(t))$  a dual central point. The set of (dual) solutions of (9) for all t > 0 we call the (dual) central path. Since for points x with  $f_i(x) = 0$  for any  $x \in \{1, ..., m\}$ , the objective of (9) is  $\infty$ , all central points are in the interior of the set, satisfying the inequality constraints of (1). Thus this framework is named interior point method. One can show, that solutions  $(x^*(t), \lambda^*(t), \nu^*(t))$  of (9) converge to the solution  $(x^*, \lambda^*, \nu^*)$  of (1) for  $t \longrightarrow 0$ . The proof can be found in [2].

# C. Measure for the Approximation's quality

An immediately arising question is which conclusions about the solution  $(x^*, \lambda^*, \nu^*)$  of (1) can be drawn from knowing a solution of (9) for a certain t > 0 about the value  $f_0(x^*(t))$  of a central point  $x^*(t)$ , compared with the optimal value  $p^*$  of the original problem. For compactness, we denote the barrier term of the approximated problem as

$$\phi(x) = -\sum_{i=1}^{m} \log(-f_i(x)),$$

with its Jacobian and Hessian being

$$\nabla \phi(x) = \sum_{i=1}^{m} \frac{1}{-f_i(x)} \nabla f_i(x),$$

$$\nabla^2 \phi(x) = \sum_{i=1}^{m} \frac{1}{f_i(x)^2} \nabla f_i(x) \nabla f_i(x)^T + \sum_{i=1}^{m} \frac{1}{-f_i(x)} \nabla^2 f_i(x).$$

For the sake of simplifying notation, throughout this section we consider the problem

minimize 
$$tf_0(x) + \phi(x)$$
  
subject to  $A_{eq}x = b_{eq}$ . (10)

that is obtained by multiplying the objective in (9) with t >0. The original and the obtained problem are equivalent. Any arbitrary  $x^*(t)$  a strictly feasible point of (1). Since  $x^*(t)$ solves (10), there exists  $\hat{\nu} \in \mathbb{R}^p$ , such that

TODO!check consistency

$$\nabla L_{t}(x^{*}(t), \hat{\nu}) = t \nabla f_{0}(x^{*}(t)) + \nabla \phi(x^{*}(t)) + A_{\text{eq}}^{T} \hat{\nu} \quad (11)$$

$$= t \nabla f_{0}(x^{*}(t))$$

$$+ \sum_{i=1}^{m} \frac{1}{-f_{i}(x^{*}(t))} \nabla f_{i}(x^{*}(t)) + A_{\text{eq}}^{T} \hat{\nu}. \quad (12)$$

$$= 0 \quad (13)$$

holds. Note that the Lagrangian only depends on  $(x, \hat{\nu})$ , since there are no explicit inequality constraints involved. We keep in mind, that  $x^*(t)$  minimizes (9). Using this insight, we know that there exists a dual feasible point  $(x^*(t), \lambda^*(t), \nu^*(t))$  of the original problem (1). In partic-

$$\lambda^*(t) = -\frac{1}{tf_i(x^*(t))}$$
 for  $i = 1, \dots, m, \quad \nu^*(t) = \frac{\hat{\nu}}{t}$ .

Here,  $\lambda^*(t) > 0$  follows from  $f_i(x^*) < 0$  for all i = 1, ..., m since  $x^*$  is strictly feasible.

Note that (13) is the derivative of the Lagrangian

$$L(x, \lambda, \nu) = f_0(x) + \sum_{i=1}^{m} \lambda_i^*(t) f_i(x) + \nu^*(t)^T (A_{eq} x^*(t) - b_{eq})$$

dividied by t>0 of the original problem. The Lagrangian is convex in the first coordinate, hence we infer that  $x^*(t)$  minimizes the Lagrangian of the original problem for any fixed  $(\lambda,\nu)$ . For the dual function of the original problem, we obtain

$$g(\lambda^*(t), \nu^*(t)) = f_0(x^*(t)) + \sum_{i=1}^m \lambda_i^*(t) f_i(x^*(t))) + \nu^*(t)^T (A_{eq} x^*(t) - b_{eq})$$

$$= f_0(x^*(t)) - \frac{m}{t}.$$
(14)

The second of the three summands adds up to  $m \cdot 1$ , because of the particular choice of  $\lambda^*(t)$ , fractions cancel out. The last summand equals zero, since  $A_{\rm eq}x^*(t) - b_{\rm eq} = 0$ .

By weak duality, this means that the optimum  $x^*(t)$  of the approximated problem (9) has an objective value  $f_0(x^*(t))$  that is maximally larger by  $\frac{m}{t}$  (and hence worse) than the real optimal value  $p^*$  of the original problem. Thus, one can theoretically force a desired bound on the subobtimality  $\epsilon > 0$  by choosing t large enough, in particular  $t := \frac{m}{\epsilon}$ . However, just solving (9) with a large choice of t does not work out in general, since numerical issues can make convergence of Newton's Method dependent on the choice of the initial point  $x_0$ .

## D. Algorithmic Use of the Barrier Concept

As already mentioned in section III-C, one can not solve (9) generally without a good guess of the initial value  $x_0$ . So how to make use of the barrier concept? The idea of interior methods is, to find points along the problem's central path. Two methods are introduced in the following. Emphasis of the explanations as well as the implementation in MATLAB will be on the Primal-Dual Interior Point Method.

1) Barrier Method: As mentioned before, for large t a good initial point  $x_0$ , meaning an initial point that is not far away from the actual minimum of (1), is crucial for avoiding large numerical errors. This can be achieved by starting with optimization of (9) for small  $t=t_1$ , which leads to a rather bad approximation of the original problem, but also to better numerical behavior. After finding  $x^*(t_1)$  via Newton's method, t is increased to  $t=t_2>t_1$  by a certain rate and (9) is solved again with parameter  $t=t_2$ , with choice  $x_0=x^*(t_1)$  for the initial point.

We call finding the minimum  $x^*(t)$  of (9) the centering step or outter iteration, while we call a single Newton step inside the centering step an inner iteration.

2) Primal-Dual Interior Point Method: Like the previously introduced algorithm, the Primal-Dual Interior Point method uses the barrier concept to handle inequality constraints. It is motivated by the following idea: Since the points generated by each outer iteration converge to the

**Algorithm 2:** Barrier Method with full Newton search

 $\begin{array}{ll} \textbf{Result:} \ x^*(t), \ \text{approximate solution of (1) with} \\ f_0(x^*(t)) - p^* < \frac{m}{t} \\ \text{initialization: Matrices } 0 \prec Q \in \mathbb{R}^{n \times n}, c \in \mathbb{R}^n. \\ \text{defining the objective function, matrices} \\ A_{\text{eq}} \in \mathbb{R}^{m \times n} b_{\text{eq}} \in \mathbb{R}^p, A_{\text{in}} \mathbb{R}^{m \times n}, b_{\text{in}} \in \mathbb{R}^m \ \text{defining} \\ \text{constraints, initial point } x, \text{ initial approximation} \\ \text{parameter } t > 0, \text{ rate for increasing appprox. param.} \\ \mu > 1 \ \text{tolerance } \epsilon; \\ \textbf{while} \ \frac{m}{t} \geq \epsilon \ \textbf{do} \\ \mid \text{ Compute } x^*(t) \ \text{ by solving (9) via Newton's} \\ \end{aligned}$ 

Method, starting at x; Update  $x := x^*(t)$ ; Increase t by  $t := \mu t$ **end** 

desired optimum on the central path, one does not gain much advantage by computing the central points with a high level of accuracy. This results in many newton-steps being computed, without improving the convergence towards the optimum value of (1). Hence, it would be useful to reduce the accuracy of each outer iteration as much as possible, without losing convergence to the optimum. Therefore, in this method only one newton step will be computed for each parameter t in the approximated problem (9). Furthermore, this Newton step is computed differently. While in the barrier method with full newton search, the search directions are computed only considering the primal problem, the Primal-Dual Methodalso takes the dual problem of (9) into account. In particular Newton's method is applied to a system of residual terms, which all have to equal zero by the modified KKT-conditons, here presented like in [2].

Theorem 1 (Modified KKT-Conditions): For a convex Optimization Problem with a logarithmic barrier function (9), the following conditions on a primal-dual point  $(x,\lambda,\nu)\in\mathbb{R}^n\times\mathbb{R}^m\times\mathbb{R}^p$  are necessary and sufficient for x being a solution to the primal problem and  $(\lambda,\nu)$  being a solution to the dual problem:

$$f_i(x) \le 0, \quad \text{for } i = 1, \dots, m$$
 (15a)

$$A_{\rm eq}x - b_{\rm eq} = 0 \tag{15b}$$

$$\lambda_i \ge 0, \quad \text{for } i = 1, \dots, m$$
 (15c)

$$-\lambda_i f_i(x) = \frac{1}{t}, \quad \text{for } i = 0, \dots, m$$
 (15d)

$$\nabla f_0(x) + \sum_{i=1}^{m} \lambda_i \nabla f_i(x) + \sum_{i=1}^{p} \nu_i \nabla h_i(x) = 0.$$
 (15e)

Stacked in one vector, this yields the system of equalities

$$r_{\mu}(x, \lambda, \nu) = \begin{pmatrix} r_{\text{dual}} \\ r_{\text{cent}} \\ r_{\text{pri}} \end{pmatrix}$$

$$= \begin{pmatrix} \nabla f_0(x) + Jf(x)^T \lambda + A_{\text{eq}}^T \nu \\ -\text{diag}(\lambda)f(x) - \mu \mathbb{1} \\ A_{\text{eq}}x - b_{\text{eq}} \end{pmatrix} \stackrel{!}{=} 0.$$
(16)

to apply Newton's method on. For formulation of the linear Newton equality, we also compute the jacobian

$$J_{(x,\lambda,\nu)}r_{\mu}(x,\lambda,\nu)$$
 (17)
$$= \underbrace{\begin{pmatrix} \nabla^{2}f_{0}(x) + \sum_{i=1}^{m} \lambda_{i}\nabla^{2}f_{i}(x) & Jf(x) & A_{\text{eq}}^{T} \\ -\text{diag}(\lambda)Jf(x) & -\text{diag}(f(x)) & 0 \\ A_{\text{eq}} & 0 & 0 \end{pmatrix}}_{:=M_{\text{KKT}}}$$
 (18)

of the residual and refer to it as  $M_{\rm KKT}$ . Consequently, the Newton equality for finding the search direction  $(\Delta x, \Delta \lambda, \Delta \nu)$  in each newton step is obtained by solving the linear equation

$$M_{\text{KKT}} \begin{pmatrix} \Delta x \\ \Delta \lambda \\ \Delta \nu \end{pmatrix} = b_{\text{KKT}} \tag{19}$$

with  $b_{\text{KKT}} = -r_{\mu}(x, \lambda, \nu)$ .

Unfortunately, adding the obtained step direction  $(\Delta x, \Delta \lambda, \Delta \nu)$  to  $(x, \lambda, \nu)$ , does not in general yield a feasible point. Therefore we compute a suitable step-size  $s^*$  via a backtracking-linesearch, such that a certain decrease of the residual and feasibility is guaranteed for the next iteration point

$$\begin{pmatrix} x^+ \\ \lambda^+ \\ \nu^+ \end{pmatrix} = \begin{pmatrix} x \\ \lambda \\ \nu \end{pmatrix} + s^* \begin{pmatrix} \Delta x \\ \Delta \lambda \\ \Delta \nu \end{pmatrix}.$$

The detailed procedure of the backtracking linesearch is displayed in Algorithm 3.

Finally, we can present the entire algorithm of the Primal-Dual Method.

Remark 2: If a strictly feasible primal variable  $x \in \mathbb{R}^n$  is known,  $\lambda = -1/f_i(x) \ge 0, \nu = 0$  is always a valid choice for the initial dual variables.

Especially when results with high accuracy are needed, the Primal-Dual Method allows to omit a lot of newton steps, that would be have computed in the Barrier Method. For such problems, the Primal-Dual Method provides better performance.

Remark 3: The concept of using a barrier method to approximate inequality constraints can also be used for solving optimization problems involving generalized inequalities. Therefore, the barrier function and constraints on the dual problem have to be adjusted. Doing this, the class of problems that apply the usage of barrier methods is widely enlarged. For example it can be used for solving linear matrix inequalities or single order cone problems.

## Algorithm 3: Backtracking linesearch

```
Result: Stepsize s^*, s.t. \lambda^+ > 0, f(x^+) < 0 and r_\mu
           decreases by certain amount.
Data: Problem matrices, current x, \lambda, \nu, Newton
        direction \Delta x, \Delta \lambda, \Delta \nu, barrier parameter \mu,
        backtracking parameters \alpha \geq 0, \beta \in (0, 1).
        Initial step-size set
        s_{\text{max}} = \min\{1, \min_{i|\Delta\lambda_i < 0} -\lambda_i/\Delta\lambda_i\}
compute r_{\mu}(x, \lambda, \nu);
s = s_{\max};
found = false;
while found == false do
    set s = \beta s;
    compute (x^+, \lambda^+, \nu^+);
    compute r_{\mu}(x^+, \lambda^+, \nu^+) and f(x^+);
    if f(x^+) < 0 and
     \|r_{\mu}(x^+,\lambda^+,\nu^+)\|\leq (1-\alpha s)\,\|r_{\mu}(x,\lambda,\nu)\| \text{ then } |found=true
     end
```

## Algorithm 4: Primal-Dual Interior Point Method

**Result:** approximate optimizer  $\hat{x}^*$ , approx. opt. value  $\hat{p}^*$ , approx. dual optimizer  $(\hat{\lambda}^*, \hat{\nu}^*)$ , surrogate duality gap  $\hat{\eta}^*$  as measure of optimality

**Data:** Problem matrices, primal-dual initial point  $(x, \lambda, \nu)$  with  $f_i(x) < 0$  for all  $i = 1, \dots, m$ ,  $\lambda > 0, \nu \in \mathbb{R}^p$  (initial point strictly feasibile), reduction factor  $\gamma \in (0, 1)$ , tolerances  $\epsilon_{\text{feas}}, \epsilon_{\text{opt}} > 0$ 

Initialization;

end

```
determine problem dimensions n, m, p; set found = false;
```

Further, a higher speed of convergence can be shown for the application on some special classes of problems, such as quadratic problems or single order cone problems (SOCPs). Here the Primal-Dual Methodcan perform faster than with linear convergence.

## E. How to find a feasible inital point

The Algorithms 2 and 4 both need a strictly feasible initial point to start. Since such a point is in general not trivial to find, one can formulate the search for the initial point as another convex optimization problem, that is easier to solve than the original one. For problem (1), one way to implement this, is solving

minimize 
$$s$$
 subject to  $f_i(x) \le s, \quad i=1,\ldots,m$  (20) 
$$A_{\rm eq}x - b_{\rm eq} = 0,$$

via Newton's method. If a point with optimal value strictly smaller than zero for (20) is found, then this point is strictly feasible. Solving such a first, more simple problem is called a Phase I problem. More examples of such problems can be found in [2].

# F. Complexity Analysis for the Barrier Method

Emphasis of this article is on implementation and idea of the algorithms, so we treat complexity analysis only by presenting results without proves. We keep this restricted to the barrier method with full newton search. We discuss the time complexity of the barrier method, meaning the total number of newton steps needed to solve (1). An upper bound of these iterations can be proven for problems with objectives that are self-concordant. While linear and quadratic functions satisfy selfconcordance in general, any other convex optimization problem can be rewritten as a self-concordant one, so this condition is not very restrictive. The upper bound

$$\frac{f(x) - p^*}{\gamma} + c \tag{21}$$

on the maximal number of newton iterations that is needed to get a newton decrement (see remark 1) smaller than  $\epsilon_{\rm nt},$  where c depends on  $\epsilon_{\rm nt}$  by  $\log_2\log_2(1/\epsilon_{\rm nt}),$   $p^*$  is the primal problem's optimal value and  $\gamma$  depends on choice of the backtracking parameters  $\alpha,\beta$  with

$$\frac{1}{\gamma} = \frac{20 - 8\alpha}{\alpha\beta(1 - 2\alpha)^2}.$$

The derivation of this bound is shown in [2], section 9.

One can further show that this bound holds uniformly for any parameter t for all problems (9). Since there are exactly

$$\left\lceil \frac{\log(m/\epsilon t_0)}{\log \mu} \right\rceil$$

outer steps neccessary to solve (9) with inital parameter  $t = t_0$  and tolerance  $\epsilon$ , the entire barrier method needs maximally

$$N = \left\lceil \frac{\log(m/\epsilon t_0)}{\log \mu} \right\rceil \left( \frac{m(\mu - 1 - \log \mu)}{\gamma} + c \right)$$

inner newton iterations, where m denotes the number of inequality constraints on (9). to yield a result with a sub-optimality of  $\epsilon$  or smaller. Detailed reasoning can be found in [2], section 11.5.

## IV. EXAMPLES

We give an implementation of the Primal-Dual Method (Algorithm 4) in MATLAB, along with two example problems. One with equality constraints, one without.

## A. Numerical Examples

1) Example 1: The effectivity of the algorithm can be demonstrated with the following explicit example of (1). For the problem defined by

$$Q = 2 \cdot \begin{pmatrix} 1 & 0 \\ 0 & 2 \end{pmatrix}; \quad c = \begin{pmatrix} 1 \\ 2 \end{pmatrix}$$
$$A_{\text{eq}} = \begin{pmatrix} 1 & -1 \end{pmatrix}; \quad b_{\text{eq}} = 0;$$
$$A_{\text{in}} = \begin{pmatrix} 0 & 1 \end{pmatrix}; \quad b_{\text{eq}} = 10,$$

we choose backtracking parameters  $\alpha 0.05$ ,  $\beta = 0.5$  as well as  $\gamma = 0.1$  for the reduction of the approximation parameter. Initial points are set to  $x_0 = (1,1)^T$ ,  $\lambda_0 = 1$ ,  $\nu_0 = 0$  and tolerances to  $\epsilon_{\rm feas} = \epsilon_{\rm opt} = 10^{-4}$ .

2) Example 2: To test algorithm (4) on a problem without equality constraints, we moreover provide a second example, taken from [3]. The problem is defined

$$Q = 2 \cdot \begin{pmatrix} 3 & 1 \\ 1 & 1 \end{pmatrix}; \quad c = \begin{pmatrix} 1 \\ 6 \end{pmatrix};$$
$$A_{\text{in}} = \begin{pmatrix} -2 & -3 \\ 0 & -1 \end{pmatrix}; \quad b_{\text{in}} = \begin{pmatrix} -4 \\ 0 \\ 0 \end{pmatrix},$$

while initial values are chosen as  $x_0 = (1,1)^T$  and  $\lambda_0 = (0.2,1,1)^T$  (like suggested in remark 2). Tolerances and backtracking-paramters are chosen as in Example 1.

### B. Model Predictive Control

Quadratic optimization problems are arising in practical applications frequently. To pick one example, we here present the application of interior methods on a Model Predictive Control (MPC) problem. More precisely, a MPCof a linear system with zero terminal constraint (ZTC). We consider the discrete time linear system

$$x_{k+1} = A_d x_k + B_d u_k, \tag{22}$$

where  $x_k \in \mathbb{R}^n, u_k \in \mathbb{R}^m$  for all  $k \in \mathbb{N}_0$ , with the constraints that  $\|u_k\|_{\max} \leq l_u$  and  $\|x_k\|_{\max} \leq l_x$  for all steps  $k \in \mathbb{N}_0$ . Further we assume that (22) has an equilibrium in x=0 and the current state  $x_0$  is given. The maximum-norm is defined as the maximum absolute value over all entries of the vector,  $\|x\|_{\max} = \max_{1 \leq i \leq n} |x_i|$ . Goal is to find a input signal that steers the internal state x to zero, while additionally keeping u as small as possibly. Therefore, we consider the next  $N \in \mathbb{N}$  timesteps. We call N the prediction horizon. This leads to optimization of a certain objective function over all possible predicted steering signals  $\bar{u} = (\bar{u}_1, \dots, \bar{u}_{N-1})^T$ .

We simulate the system for the next N timestep, hence we consider the sequence of states arising from applying a predicted sequence of input signals  $\bar{u}$ . The sequence of predicted states we denote as  $(\bar{x}_0, \dots, \bar{x}_N)^T$ . We choose the quadratic objective function

$$\sum_{k=0}^{N-1} \underline{\bar{x}}_{k}^{T} Q \bar{x}_{k} + \underline{\bar{u}}_{k}^{T} R \bar{u}_{k} = \|\bar{u}_{k}\|_{R}$$
(23)

under the condition, that  $\bar{x}_N$ , the last state in the predicted time, equals zero, to minimize. The regarding predicted states directly follow from the system dynamics, in particular

$$\bar{x}_{k+1} = A_d \bar{x}_k + B_d \bar{u}_k.$$

After finding an optimal signal  $\bar{u}$  we apply  $\bar{u}_0$  in the next time step. After this first step, we again start an optimization over the next N timesteps. So even though the optimization problem is computed considering all signals up to the prediction horizon, the result is only applied for one timestep, before the next optimization is executed.

We can summarize one optimization step as an optimization problem

$$\begin{split} & \underset{\bar{u} = (\bar{u}_0, \dots, \bar{u}_{N-1})^T}{\text{minimize}} & \sum_{k=1}^{N-1} \|\bar{x}_k\|_Q + \|\bar{x}_k\|_R \\ & \text{subject to} & \bar{x}_0 = x_0, \\ & \bar{x}_N = 0, \\ & \bar{x}_{k+1} = A_d \bar{x}_k + B_d \bar{u}_k \quad \text{for all } k = 0, \dots, \\ & \|\bar{x}_k\| \leq l_{\mathbf{x}}, \|\bar{u}_k\| \leq l_{\mathbf{u}} \quad \text{for all } k = 0, \dots, \\ & (24) \end{split}$$

This problem can be transcribed into the form of (1). We therefore optimize over the whole vector

$$\tilde{x} := \begin{pmatrix} \bar{x} \\ \bar{u} \end{pmatrix}.$$

The objective function (23) then can be written as

$$f_0(\tilde{x}) = \tilde{x}^T H \tilde{x},$$

with the block diagonal matrix

$$H = \operatorname{diag}(\underbrace{Q, \dots, Q}_{N \cdot n \text{ blocks}}, \underbrace{0}_{n \times n}, \underbrace{R, \dots, R}_{N \cdot n \text{ blocks}}.)$$

We further formulate the constraints at the maximum norms of state and input as  $A_{\rm in} \tilde{x} \leq b_{\rm in}$ , with  $b_{\rm in} = 1 \in$  $\mathbb{R}^{N(n+m)+n\times 1}$  and

$$A_{\text{in}} = \begin{pmatrix} I_{n(N+1)} & 0\\ -I_{n(N+1)} & 0\\ 0 & I_{N \cdot m}\\ 0 & -I_{N \cdot m} \end{pmatrix}$$

where the indices of the identity-matrix I denote its dimensional size. Rearranging the system dynamics (22) and taking inital condition as well as zero terminal constraint into account can be written as the equality constraints  $A_{\rm eq} \tilde{x} = b_{\rm eq}$ with  $A_{\rm eq} = \begin{pmatrix} A_{\rm eq}^x & A_{\rm eq}^u \end{pmatrix}$ , where

$$A_{\text{eq}}^{x} = \begin{pmatrix} I_{n \times n} & 0 & \cdots & \cdots & 0 \\ A_{d} & -I_{n \times n} & \cdots & \cdots & \vdots \\ 0 & \ddots & \ddots & 0 \\ \vdots & & \ddots & \ddots & 0 \\ \vdots & & & \ddots & \ddots & 0 \\ \vdots & & & & A_{d} & -I_{n \times n} \\ 0 & \cdots & & & & 0 & I_{n \times n}, \end{pmatrix}$$

$$A_{\text{eq}}^{u} = \begin{pmatrix} 0 & \cdots & 0 \\ B_{d} & \ddots & \vdots \\ \vdots & \ddots & 0 \\ 0 & \cdots & B_{d} \\ 0 & \cdots & 0 \end{pmatrix}.$$

With these matrices, we rewrote (24) as an equivalent problem in shape of (1).

## V. CONCLUSIONS

Mainly, in this text we introduced the concept of barrier methods for convex optimization problems, which are applied to solve inequality-constraints that include inequality constraints. Therefore we approximate such problems by problems without inequality problems. Solving these problems yields points, that are only subobtimal in the sense of the original problem up to a certain bound. Via analyzing the Lagrangian of the original and the approximative problem,  $\bar{x}_{k+1} = A_d \bar{x}_k + B_d \bar{u}_k$  for all  $k = 0, \dots, N$ , we verified this bound, dependent on the approximation  $\|\bar{x}_k\| \le l_x$ ,  $\|\bar{u}_k\| \le l_u$  for all  $k = 0, \dots, N$  parameter and the number of inequality constraints. The explanation of the barrier concept was followed was by an explanation how it can be applied algorithmically by the barrier method. Further, we gave an idea how to find a feasible initial point and also a time complexity bound of the barrier method, without proof. As an improvement, especially when dealing with quadratic problems, the Primal-Dual Method was introduced, where only one newton step is executed before the approximation parameter is changed. Finally, we showed how quadratic programming can be applied on a linear MPC problem with zero terminal constraints by reformulating it as a quadratic problem.

```
APPENDIX
                                             37 found = 0;
                                             38 \quad \text{count} = 0;
   A. MATLAB-Implementation
     In the following, the MATLAB code of the primal-dual \overset{\circ}{40}
                                                while found == 0
   interior point method algorithm is presented
                                                    % compute surrogate duality gap
                                             41
                                             42
                                                    eta = -(Aineq*x - bineq)'*lambda;
     Algorithm main function:
                                             43
                                                    mu_barrier = gamma*eta/m;
  function [x,fval,lambda,nu,eta] =
                                             44
                                                    % Compute KKT residual vector
      ipquad_pd(Q,c,Aineq,bineq,Aeq,beq,x0,45
                                                    r_mu = res_kkt(x,lambda,nu,Q,c,Aineq
      lambda0, nu0, gamma, eps_feas, eps_opt,
                                                        , bineq, Aeq, beq, mu_barrier);
      ls_alpha, ls_beta)
                                             46
                                                    r_dual = r_mu(1:m);
   %IPQUAD_PD Quadratic optimization via
                                             47
                                                     r_{m+1} = r_{mu}((m+1):(m+p)); 
      primal-dual-interior-point-method.
                                                    r_{pri} = r_{mu}((m+p+1):(m+p+n));
   % Convex Quadr. function f(x) = (1/2)x'
      Qx + c'x with linear equality and
                                                    if norm(r pri) <= eps feas && norm(</pre>
   % inequality constraints.
                                                        r_dual) <= eps_feas && eta <=
5 % -----
                                                        eps_opt
                                             51
6 % Input Arguments:
                                                        found=1;
7 % - Q,c define objective function
                                             52
                                                        break;
8 \% \dim(Q) = nxn, \dim c = nx1
                                             53
                                                    else
  % - Aineq, bineq define inequality
                                                         % update barrier weighting
      constraints Aineq*x <= bineq</pre>
                                                           parmeter mu_barrier
     dim(Aineq) = mxn, dim(bineq) = mx1
                                                        mu_barrier = gamma*eta/m;
11 % - Aeq, beq define inequality
                                             56
                                                        % compute search vector
      constraints Aeq*x == beq
                                             57
                                                         [x, lambda, nu] = newtonquad_pd(
12 % \dim(Aineq) = pxn, \dim(beq) = px1
                                                            Q, c, Aineq, bineq, Aeq, beq,
  % - x0 init. value for the primal
                                                             ls alpha, ls beta, x, lambda,
      problem. lambda0, nu0. labda0 >= 0.
                                                             nu, mu barrier);
14 %
     Aineq*x0 \le bineq.
                                                    end
15 %
      initial values for the dual problem 59
                                                    count = count+1;
16 % - gamma is a reduction factor for
      reducing the barrier weight
                                                    disp(['Iteration No. ', num2str(count
      mu_barrier
                                                        ),'; current norm of residual: ',
17
  % in each iteration. gamma in (0,1)
                                                        num2str(norm([x;lambda;nu])),';
   % - eps_feas > 0 specifies the tolerance
                                                        eta = ', num2str(eta)])
       for the 2norms of the primal and
                                            62 end
19 % dual residual
                                             63
  % - eps_opt > 0 specifies a tolerance on 64 % evaluate obj. function at found x
                                               fval = 0.5.*x'*Q*x + c'*x;
       the surrogate duality gap
                                            65
  % - ls_alpha, ls_beta are parameters for66 end
       the backtracking linesearch,
                                                  Newton step including line-search:
       performed in each iteration. Typical
       choices: ls_alpha in [0.01,0.1].
                                             1 function [x_new, lambda_new, nu_new] =
23 %
     ls_beta in [0.3,0.8]
                                                   newtonquad_pd(Q, c, Aineq, bineq, Aeq
24 % -----
                                                    , beq, ls_alpha, ls_beta, x,lambda,
25 % Created: 24.06.20, Daniel Bergmann
                                                   nu, mu_barrier)
26 % ----- 2
                                                %NEWTONQUAD_PD Computes search direction
27
                                                     for pd-ip-algorithm via Newton's
                                                   method and step size
28 x = x0;
29 \quad lambda = lambda0;
                                              3 %via backtracking line search
30 nu = nu0;
                                                % Based on a given primal-dual point x,
31
                                                    lambda, nu, this functions returns new
32 % initialize dimensions
                                                    points
33 n = size(Q,1);
                                              5 % x_new, lambda_new, nu_new with smaller
34 \text{ m} = \text{size}(Aineq, 1);
                                                    kkt-residual.
35 p = size(Aeq, 1);
                                             6 % First, a search direction is
36
                                                    determined by applying newton's
```

```
method to
                                                        lambda(i)/deltalambda(i)];
  % the nonlinear equation system r = 0 49 end
     with r the residual of the
                                         50 end
   % kkt-conditions, second a suitable step51
      -size is determined via a
                                         52 smax = min([1 lambdaquot]);
9 % backtracking linesearch
                                         53
10 % -----54 % Backtracking-Linesearch
   % - mu barrier is the current weight on 55
                                             % Typical Parameter choices:
      the barrier function
                                          56 % alpha in [0.01,0.1]; beta in [0.3,0.8]
12 % - for other input arguments, see
                                         57 s = 0.99*smax; %S4 0.99 smax??
     comments in ipquad_pd.m
                                         58 \text{ found} = 0;
13 % -----59 while found == 0
14 % Created: 24.06.20, Daniel Bergmann
                                        60
                                                s = s*ls\_beta;
15 % -----61
                                                 x_new = x + s.*deltax;
16
                                                 lambda new = lambda + s.*deltalambda
17
  % initialize dimensions
                                                    ;
                                          63
18 n = size(Q, 1);
                                                 nu_new = nu + s.*deltanu;
19 m = size(Aineq, 1);
                                          64
                                                 r_new = res_kkt(x_new,lambda_new,
20 p = size(Aeq, 1);
                                                    nu_new, Q, c, Aineq, bineq, Aeq, beq,
                                                    mu_barrier);
21
22 % Define Matrices for KK7T-equality
                                                 r_old = res_kkt(x,lambda,nu,Q,c,
      M_kkt*deltar = b_kkt
                                                    Aineq, bineq, Aeq, beq, mu_barrier);
   if ~isempty(Aeq)
                                          66
                                                 if all(Aineq*x_new - bineq < 0) && (</pre>
24
      M_kkt = [Q]
                                                    norm(r_new) \le (1-ls_alpha*s)*
                                 Aeq';...
          Aineq'
                                                    norm(r_old))
25
           -diag(lambda) *Aineq
                                 -diag( 67
                                                    found = 1;
              Aineg*x-bineg)
                                 zeros (m, p68
                                                 end
                                         69 end
26
                                  zeros(p,70 disp(['Backtracking search yields step
          Aeq
                                             size s = ', num2str(s)])
                             zeros(p,p) ];
27
   else
28
      M_kkt = [Q]
                                              Computing KKT residual vector from problem matrices
         Aineq';
                                             and current points:
29
          -diag(lambda) *Aineq
                                  -diag(
                                          1 function r = res_kkt(x,lambda,nu,Q,c,
             Aineq*x-bineq)];
30 end
                                                Aineq, bineq, Aeq, beq, mu_barrier)
31
                                            %RES_KKT compute the current KKT-
32
   b_kkt = -res_kkt(x,lambda,nu,Q,c,Aineq,
                                                residual of a quadratic
                                            %optimization problem inside a primal-
      bineq, Aeq, beq, mu_barrier);
33
                                                dual interior point methad.
34
  % Solve KKT-equality to get search
                                          4 % For the quadr. convex opt. problem
                                                defined by Q,c,Aineq,bineq,Aeq,beq
     direction
35 deltaxln = M_kkt\b_kkt;
                                           5 % (for details see comments on ipquad_pd
36
                                                .m) and a current primal-dual point
37
                                           6 % (x, lambda, nu), this function computes
38 deltax = deltaxln(1:n);
                                                the current KKT-residual.
                                          7
39 deltalambda = deltaxln((n+1):(n+m));
40 deltanu = deltaxln((n+m+1):(n+m+p));
                                          8 % -----
41
                                          9 % Input Arguments: for detailed
42 % Perform Backtracking linesearch for
                                                explanation see comments on ipquad pd
      determining suitable step size
                                                .m and
43
                                          10 % newtonquad_pd.m.
                                          11 % -----
44 % compute maximal step size smax
  lambdaquot = [];
                                          12
                                            % Created: 24.06.20, Daniel Bergmann
46 for i = 1:length(lambda)
                                          13
47
                                          14
      if deltalambda(i) <0</pre>
48
           lambdaquot = [lambdaquot, -
                                          15
```

```
16 m = size(Aineq, 1);
17
   if ~isempty(Aeq)
18
       % if there are equality constraints
19
       r = \dots
20
            [Q*x + c + Aineq'*lambda + Aeq'*
               nu;...
21
            -diag(lambda) * (Aineq*x - bineq)
               - mu_barrier.*ones(m,1);...
22
            Aeq*x - beq];
23
   else
24
       % If there are no equality
           constraints
25
       r = [Q*x + c + Aineq'*lambda;...
26
            -diag(lambda) * (Aineq*x - bineq)
               - mu_barrier.*ones(m,1)];
27
   end
28
29
   end
```

## REFERENCES

- [1] Carsten Scherer Vorlesungsskript Einführung in die Optimierung 2019: Lehrstuhl für Mathematische Systemtheorie, Universität Stuttgart.
- [2] Stephen Boyd, Lieven Vandenberghe *Convex Optimization* 2004: Cambridge University Press.
- [3] Jack Heider, Quadratic programming 2015: online, https://optimization.mccormick.northwestern.edu/index.php/Quadratic\_programming.