```python
# Hidden states
states = ['Rainy', 'Sunny']

# Observations
observations = ['walk', 'shop', 'clean']

# Initial probabilities
start_prob = {
    'Rainy': 0.6,
    'Sunny': 0.4
}

# Transition probabilities
transition_prob = {
    'Rainy': {'Rainy': 0.7, 'Sunny': 0.3},
    'Sunny': {'Rainy': 0.4, 'Sunny': 0.6}
}

# Emission probabilities
emission_prob = {
    'Rainy': {'walk': 0.1, 'shop': 0.4, 'clean': 0.5},
    'Sunny': {'walk': 0.6, 'shop': 0.3, 'clean': 0.1}
}

# Observation sequence
obs_sequence = ['walk', 'shop', 'clean']

def forward_algorithm(states, observations, start_prob,
transition_prob, emission_prob):
    forward = []

    # Step 1: Initialization
    f0 = {}
    for state in states:
        f0[state] = start_prob[state] *
emission_prob[state][observations[0]]
    forward.append(f0)

    # Step 2: Recursion
    for t in range(1, len(observations)):
        ft = {}
        for current_state in states:
            prob = 0
            for previous_state in states:
                prob += forward[t-1][previous_state] *
transition_prob[previous_state][current_state]
            ft[current_state] = prob *
emission_prob[current_state][observations[t]]
```

```
        forward.append(ft)

    # Step 3: Termination
    total_probability = sum(forward[-1][state] for state in states)
    return total_probability

# Compute probability
result = forward_algorithm(
    states, obs_sequence, start_prob, transition_prob, emission_prob
)

print("Probability of observation sequence:", result)
```

output:

```
Probability of observation sequence: 0.033612
```