Laboratory Record of_____

Roll No.: _____

Experiment No.: _____

Sheet No.: _____

Date: _____

Index.html:

```
<!doctype html>
<html lang="en">
 <head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <title>My ToDo App</title>
 </head>
 <body>
  <div id="root"></div>
  <script type="module" src="/src/main.jsx"></script>
 </body>
</html>
```

Main Jsx:

```
import { StrictMode } from "react";
import { createRoot } from "react-dom/client";
import App from "./App.jsx";
createRoot(document.getElementById("root")).render(
 <StrictMode>
  <App />
 </StrictMode>
);
```

APP JSX:

```
import { useState, useEffect } from "react";
import "./App.css";
export default function App() {
 const [task, setTask] = useState("");
```

```
const [tasks, setTasks] = useState(() => {
  try {
    return JSON.parse(localStorage.getItem("myTasks")) || [];
  } catch {
    return [];
  }
});
useEffect(() => {
  localStorage.setItem("myTasks", JSON.stringify(tasks));
}, [tasks]);
function addTask() {
  if (task.trim() === "") return;
  setTasks([
    ...tasks,
    {
      id: Date.now(),
      text: task.trim(),
      done: false
    }
  ]);

  setTask("");
}
function toggleTask(id) {
  setTasks(tasks.map(item =>
    item.id === id
      ? { ...item, done: !item.done }
      : item
  ));
}
function deleteTask(id) {
```

```
  setTasks(tasks.filter(item => item.id !== id));
 }
 return (
  <div className="app">
   <div className="card">
    <h1>✨ My ToDo</h1>
    <p className="subtitle">Make today productive!</p>
    <div className="input-box">
     <input
      type="text"
      placeholder="Enter your task..."
      value={task}
      onChange={e => setTask(e.target.value)}
      onKeyDown={e => {
       if (e.key === "Enter") addTask();
      }}
     />
     <button onClick={addTask}>Add +</button>
    </div>
    <h3>My Tasks ({tasks.length})</h3>
    {tasks.length === 0 ? (
     <p className="empty">No tasks yet. Add your first task!</p>
    ) : (
     tasks.map(item => (
      <div className="task" key={item.id}>
       <span
        className={item.done ? "completed" : ""}
        onClick={() => toggleTask(item.id)}
       >
        {item.done ? "✅" : "⭕"} {item.text}
       </span>
```

```
            <button
              className="delete"
              onClick={() => deleteTask(item.id)}
            >
              ×
            </button>
          </div>
        ))
      )}
    </div>
  </div>
 );
}
```

APP.CSS:

```
* {
 box-sizing: border-box;
}
body {
 margin: 0;
 font-family: Arial, sans-serif;
 background: linear-gradient(135deg, #667eea, #764ba2);
 min-height: 100vh;
}
.app {
 min-height: 100vh;
 display: flex;
 justify-content: center;
 align-items: flex-start;
 padding: 60px 15px;
```

```
}
.card {
  width: 100%;
  max-width: 450px;
  padding: 30px;
  background: white;
  border-radius: 20px;
  box-shadow: 0 12px 35px #0003;
}
h1 {
  margin: 0;
  color: #6655dd;
}.subtitle {
  color: #777;
}
h3 {
  color: #333;
}
.input-box {
  display: flex;
  gap: 10px;
  margin: 25px 0;
}
input {
  flex: 1;
  min-width: 0;
  padding: 12px;
  font-size: 15px;
  border: 1px solid #ddd;
  border-radius: 8px;
  outline-color: #6655dd;
```



```
}
button {
  padding: 11px 15px;
  color: white;
  background: #6655dd;
  border: none;
  border-radius: 8px;
  cursor: pointer;
}
button:hover {
  opacity: 0.85;
}
.task {
  display: flex;
  align-items: center;
  justify-content: space-between;
  gap: 10px;
  margin-top: 10px;
  padding: 12px;
  background: #f3f2ff;
  border-radius: 9px;
}

.task span {
  cursor: pointer;
  overflow-wrap: anywhere;
}
.completed {
  text-decoration: line-through;
  color: #999;
}
```

```
.delete {
  background: #ff5364;
  flex-shrink: 0;
}
.empty {
  padding: 15px 0;
  color: #888;
  text-align: center;
}
```

Output:

