

Lecture 7: Tree Recursion

Brian Hou
June 29, 2016

Announcements

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today
 - Run **ok --submit** to check against hidden tests

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today
 - Run **ok --submit** to check against hidden tests
 - Check your submission at ok.cs61a.org

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today
 - Run **ok --submit** to check against hidden tests
 - Check your submission at ok.cs61a.org
 - Invite your partner (watch [this video](#))

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today
 - Run **ok --submit** to check against hidden tests
 - Check your submission at ok.cs61a.org
 - Invite your partner (watch [this video](#))
- Homework 2 is due today, Homework 1 solutions uploaded

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today
 - Run **ok --submit** to check against hidden tests
 - Check your submission at ok.cs61a.org
 - Invite your partner (watch [this video](#))
- Homework 2 is due today, Homework 1 solutions uploaded
- Quiz 2 is tomorrow at the beginning of lecture

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today
 - Run **ok --submit** to check against hidden tests
 - Check your submission at ok.cs61a.org
 - Invite your partner (watch [this video](#))
- Homework 2 is due today, Homework 1 solutions uploaded
- Quiz 2 is tomorrow at the beginning of lecture
 - If you have an alternate time or are not enrolled in the class, please arrive at 11:45 am

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today
 - Run **ok --submit** to check against hidden tests
 - Check your submission at ok.cs61a.org
 - Invite your partner (watch [this video](#))
- Homework 2 is due today, Homework 1 solutions uploaded
- Quiz 2 is tomorrow at the beginning of lecture
 - If you have an alternate time or are not enrolled in the class, please arrive at 11:45 am
- Week 2 checkoff must be done in lab today or tomorrow

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today
 - Run **ok --submit** to check against hidden tests
 - Check your submission at ok.cs61a.org
 - Invite your partner (watch [this video](#))
- Homework 2 is due today, Homework 1 solutions uploaded
- Quiz 2 is tomorrow at the beginning of lecture
 - If you have an alternate time or are not enrolled in the class, please arrive at 11:45 am
- Week 2 checkoff must be done in lab today or tomorrow
 - Talk about hw01, lab02, lab03 with a lab assistant

Announcements

- Project 1 is due tomorrow, +1 EC point if submitted today
 - Run **ok --submit** to check against hidden tests
 - Check your submission at ok.cs61a.org
 - Invite your partner (watch [this video](#))
- Homework 2 is due today, Homework 1 solutions uploaded
- Quiz 2 is tomorrow at the beginning of lecture
 - If you have an alternate time or are not enrolled in the class, please arrive at 11:45 am
- Week 2 checkoff must be done in lab today or tomorrow
 - Talk about hw01, lab02, lab03 with a lab assistant
- Alternate Exam Request: goo.gl/forms/FDQix4I5dNXPQDgw2

Hog Contest Rules

Hog Contest Rules

- Up to two people submit one entry;
max one entry per person

Hog Contest Rules

- Up to two people submit one entry;
max one entry per person
- Your score is the number of entries
against which you win more than
50.00001% of the time

Hog Contest Rules

- Up to two people submit one entry;
max one entry per person
- Your score is the number of entries
against which you win more than
50.00001% of the time
- All strategies must be deterministic,
pure functions of the current player
and opponent scores

Hog Contest Rules

- Up to two people submit one entry;
max one entry per person
- Your score is the number of entries
against which you win more than
50.00001% of the time
- All strategies must be deterministic,
pure functions of the current player
and opponent scores
- Top 3 entries will receive EC

Hog Contest Rules

- Up to two people submit one entry;
max one entry per person
- Your score is the number of entries
against which you win more than
50.00001% of the time
- All strategies must be deterministic,
pure functions of the current player
and opponent scores
- Top 3 entries will receive EC
- The real prize: honor and glory

Hog Contest Rules

- Up to two people submit one entry;
max one entry per person
- Your score is the number of entries
against which you win more than
50.00001% of the time
- All strategies must be deterministic,
pure functions of the current player
and opponent scores
- Top 3 entries will receive EC
- The real prize: honor and glory

Ready? cs61a.org/proj/hog_contest

Hog Contest Rules

- Up to two people submit one entry; max one entry per person
- Your score is the number of entries against which you win more than 50.00001% of the time
- All strategies must be deterministic, pure functions of the current player and opponent scores
- Top 3 entries will receive EC
- The real prize: honor and glory

Ready? cs61a.org/proj/hog_contest



Environments

- We talk about environments a lot in this class...

Roadmap

Introduction

Functions

Data

Mutability

Objects

Interpretation

Paradigms

Applications

- This week (Functions), the goals are:
 - To understand the idea of *functional abstraction*
 - To study this idea through:
 - higher-order functions
 - recursion
 - orders of growth

Recursion

The Cascade Function

```
1 def cascade(n):  
2     if n < 10:  
3         print(n)  
4     else:  
5         print(n)  
6         cascade(n//10)  
7         print(n)  
8  
9 cascade(123)
```

Global frame

cascade

func cascade(n) [p=G]

f1: cascade [p=G]

n 123

f2: cascade [p=G]

n 12

Return
value None

f3: cascade [p=G]

n 1

Return
value None

The Cascade Function

```
1 def cascade(n):
2     if n < 10:
3         print(n)
4     else:
5         print(n)
6         cascade(n//10)
7         print(n)
8
9 cascade(123)
```

Output

```
123
12
1
12
```

Global frame

cascade

func cascade(n) [p=G]

f1: cascade [p=G]

n 123

f2: cascade [p=G]

n 12

Return
value None

f3: cascade [p=G]

n 1

Return
value None

The Cascade Function

```
1 def cascade(n):
2     if n < 10:
3         print(n)
4     else:
5         print(n)
6         cascade(n//10)
7         print(n)
8
9 cascade(123)
```

Output

```
123
12
1
12
```

Global frame

cascade

func cascade(n) [p=G]

f1: cascade [p=G]

n | 123

f2: cascade [p=G]

n | 12

Return
value | None

f3: cascade [p=G]

n | 1

Return
value | None

- Each cascade frame is from a different call to cascade.

The Cascade Function

```
1 def cascade(n):
2     if n < 10:
3         print(n)
4     else:
5         print(n)
6         cascade(n//10)
7         print(n)
8
9 cascade(123)
```

Output

```
123
12
1
12
```

Global frame

cascade

func cascade(n) [p=G]

f1: cascade [p=G]

n 123

f2: cascade [p=G]

n 12

Return value None

f3: cascade [p=G]

n 1

Return value None

- Each cascade frame is from a different call to cascade.
- Until the Return value appears, that call has not completed.

The Cascade Function

```
1 def cascade(n):
2     if n < 10:
3         print(n)
4     else:
5         print(n)
6         cascade(n//10)
7         print(n)
8
9 cascade(123)
```

Output

```
123
12
1
12
```

Global frame

cascade

func cascade(n) [p=G]

f1: cascade [p=G]

n | 123

f2: cascade [p=G]

n | 12

Return
value | None

f3: cascade [p=G]

n | 1

Return
value | None

- Each cascade frame is from a different call to cascade.
- Until the Return value appears, that call has not completed.
- Any statement can appear before or after the recursive call.

The Cascade Function

```
1 def cascade(n):
2     if n < 10:
3         print(n)
4     else:
5         print(n)
6         cascade(n//10)
7         print(n)
8
9 cascade(123)
```

Output

```
123
12
1
12
```

Global frame

cascade

func cascade(n) [p=G]

f1: cascade [p=G]

n | 123

f2: cascade [p=G]

n | 12

Return value | None

f3: cascade [p=G]

n | 1

Return value | None

- Each cascade frame is from a different call to cascade.
- Until the Return value appears, that call has not completed.
- Any statement can appear **before** or after the recursive call.

The Cascade Function

```
1 def cascade(n):
2     if n < 10:
3         print(n)
4     else:
5         print(n)
6         cascade(n//10)
7         print(n)
8
9 cascade(123)
```

Output

```
123
12
1
12
```

Global frame

cascade

func cascade(n) [p=G]

f1: cascade [p=G]

n 123

f2: cascade [p=G]

n 12

Return value None

f3: cascade [p=G]

n 1

Return value None

- Each cascade frame is from a different call to cascade.
- Until the Return value appears, that call has not completed.
- Any statement can appear **before** or **after** the recursive call.

The Cascade Function

```
1 def cascade(n):
2     if n < 10:
3         print(n)
4     else:
5         print(n)
6         cascade(n//10)
7         print(n)
8
9 cascade(123)
```

Global frame

cascade

func cascade(n) [p=G]

f1: cascade [p=G]

n | 123

f2: cascade [p=G]

n | 12

Return value | None

f3: cascade [p=G]

n | 1


Return value | None

Output

123
12
1
12

- Each cascade frame is from a different call to cascade.
- Until the Return value appears, that call has not completed.
- Any statement can appear **before** or **after** the recursive call.

The Cascade Function



- Each cascade frame is from a different call to cascade.
- Until the Return value appears, that call has not completed.
- Any statement can appear **before** or **after** the recursive call.

Two Definitions of Cascade

```
def cascade(n):  
    if n < 10:  
        print(n)  
    else:  
        print(n)  
        cascade(n // 10)  
        print(n)
```

```
def cascade(n):  
    print(n)  
    if n >= 10:  
        cascade(n // 10)  
    print(n)
```

- If two implementations are equally clear, then shorter is usually better
- In this case, the longer implementation is more clear (to me)
- When learning to write recursive functions, put base cases first

Two Definitions of Cascade

(demo)

```
def cascade(n):  
    if n < 10:  
        print(n)  
    else:  
        print(n)  
        cascade(n // 10)  
        print(n)
```

```
def cascade(n):  
    print(n)  
    if n >= 10:  
        cascade(n // 10)  
    print(n)
```

- If two implementations are equally clear, then shorter is usually better
- In this case, the longer implementation is more clear (to me)
- When learning to write recursive functions, put base cases first

Inverse Cascade

Inverse Cascade

Output

```
1          def inverse_cascade(n):
12          grow(n)
123         print(n)
1234        shrink(n)
123
12
1
```

Inverse Cascade

Output

```
1      def inverse_cascade(n):      def f_then_g(f, g, n):
12      grow(n)                      if n:
123      print(n)                    f(n)
1234      shrink(n)                  g(n)
123
12
1
```

Inverse Cascade

Output

```
1      def inverse_cascade(n):      def f_then_g(f, g, n):
12          grow(n)                  if n:
123         print(n)                  f(n)
1234        shrink(n)                 g(n)
123
12
1
```

```
grow = lambda n: f_then_g(
```

```
shrink = lambda n: f_then_g(
```

Inverse Cascade

Output

```
1      def inverse_cascade(n):      def f_then_g(f, g, n):
12          grow(n)                  if n:
123         print(n)                  f(n)
1234        shrink(n)                g(n)
123
12
1
```

```
grow = lambda n: f_then_g(grow, print, n // 10)
```

```
shrink = lambda n: f_then_g(print, shrink, n // 10)
```

Fibonacci

The Fibonacci Sequence

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8, ..., 35

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8, ..., 35

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21, ..., 9,227,465

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8, ... , 35

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21, ... , 9,227,465



The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8, ... , 35

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21, ... , 9,227,465



The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,



The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):
```



The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    pred, curr = 0, 1
```



The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    pred, curr = 0, 1  
    k = 1
```



The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    pred, curr = 0, 1  
    k = 1  
    while k < n:
```



The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    pred, curr = 0, 1  
    k = 1  
    while k < n:  
        pred, curr = curr, pred + curr
```



The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):
```

```
    pred, curr = 0, 1
```

```
    k = 1
```

```
    while k < n:
```

```
        pred, curr = curr, pred + curr
```



The next Fibonacci number
is the sum of the two
previous Fibonacci numbers

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    pred, curr = 0, 1  
    k = 1  
    while k < n:  
        pred, curr = curr, pred + curr  
        k += 1
```



The next Fibonacci number
is the sum of the two
previous Fibonacci numbers

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    pred, curr = 0, 1  
    k = 1  
    while k < n:  
        pred, curr = curr, pred + curr  
        k += 1  
    return curr
```



The next Fibonacci number is the sum of the two previous Fibonacci numbers

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

def fib(n):

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):
```

```
    if n == 0:
```

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    if n == 0:  
        return 0
```

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    if n == 0:  
        return 0  
    elif n == 1:
```

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    if n == 0:  
        return 0  
    elif n == 1:  
        return 1
```

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    if n == 0:  
        return 0  
    elif n == 1:  
        return 1  
    else:
```

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    if n == 0:  
        return 0  
    elif n == 1:  
        return 1  
    else:  
        return fib(n-2) + fib(n-1)
```


The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    if n == 0:  
        return 0  
    elif n == 1:  
        return 1  
    else:  
        return fib(n-2) + fib(n-1)
```

The next Fibonacci number
is the sum of the two
previous Fibonacci numbers

The Fibonacci Sequence

n: 0, 1, 2, 3, 4, 5, 6, 7, 8,

fib(n): 0, 1, 1, 2, 3, 5, 8, 13, 21,

```
def fib(n):  
    if n == 0:  
        return 0  
    elif n == 1:  
        return 1  
    else:  
        return fib(n-2) + fib(n-1)
```

The next Fibonacci number
is the sum of the two
previous Fibonacci numbers



Tree Recursion

Tree-shaped processes arise whenever executing the body of a recursive function makes more than one recursive call


```
def fib(n):  
    if n == 0:  
        return 0  
    elif n == 1:  
        return 1  
    else:  
        return fib(n-2) + fib(n-1)
```

A Tree-Recursive Process


A Tree-Recursive Process

`fib(5)`


A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process



A Tree-Recursive Process




A Tree-Recursive Process




A Tree-Recursive Process

(demo)



A Tree-Recursive Process



Break!

Counting Partitions

Counting Partitions

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

`count_partitions(6, 4)`

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

`count_partitions(6, 4)`

How many different ways can I give out 6 pieces of chocolate if nobody can have more than 4 pieces?

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

`count_partitions(6, 4)`

How many different ways can I give out 6 pieces of chocolate if nobody can have more than 4 pieces?



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

`count_partitions(6, 4)`

How many different ways can I give out 6 pieces of chocolate if nobody can have more than 4 pieces?



$$2 + 4 = 6$$

$$1 + 1 + 4 = 6$$

$$3 + 3 = 6$$

$$1 + 2 + 3 = 6$$

$$1 + 1 + 1 + 3 = 6$$

$$2 + 2 + 2 = 6$$

$$1 + 1 + 2 + 2 = 6$$

$$1 + 1 + 1 + 1 + 2 = 6$$

$$1 + 1 + 1 + 1 + 1 + 1 = 6$$

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

$$2 + 4 = 6$$

$$1 + 1 + 4 = 6$$

$$3 + 3 = 6$$

$$1 + 2 + 3 = 6$$

$$1 + 1 + 1 + 3 = 6$$

$$2 + 2 + 2 = 6$$

$$1 + 1 + 2 + 2 = 6$$

$$1 + 1 + 1 + 1 + 2 = 6$$

$$1 + 1 + 1 + 1 + 1 + 1 = 6$$

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

$$2 + 4 = 6$$



$$1 + 1 + 4 = 6$$



$$3 + 3 = 6$$

$$1 + 2 + 3 = 6$$

$$1 + 1 + 1 + 3 = 6$$

$$2 + 2 + 2 = 6$$

$$1 + 1 + 2 + 2 = 6$$

$$1 + 1 + 1 + 1 + 2 = 6$$

$$1 + 1 + 1 + 1 + 1 + 1 = 6$$

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

$$2 + 4 = 6$$

$$1 + 1 + 4 = 6$$

$$3 + 3 = 6$$

$$1 + 2 + 3 = 6$$

$$1 + 1 + 1 + 3 = 6$$

$$2 + 2 + 2 = 6$$

$$1 + 1 + 2 + 2 = 6$$

$$1 + 1 + 1 + 1 + 2 = 6$$

$$1 + 1 + 1 + 1 + 1 + 1 = 6$$



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

$$2 + 4 = 6$$

$$1 + 1 + 4 = 6$$

$$3 + 3 = 6$$

$$1 + 2 + 3 = 6$$


$$1 + 1 + 1 + 3 = 6$$

$$2 + 2 + 2 = 6$$

$$1 + 1 + 2 + 2 = 6$$


$$1 + 1 + 1 + 1 + 2 = 6$$

$$1 + 1 + 1 + 1 + 1 + 1 = 6$$




Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.



Counting Partitions


The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.


- Recursive decomposition:
finding simpler instances
of the problem.



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.


- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.


- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.


- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.


- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.


- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`




Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:

- `count_partitions(2, 4)`


- `count_partitions(6, 3)`



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.



Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition:
finding simpler instances
of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler
problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often
involves exploring
different choices.

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

```
def count_partitions(n, m):
```

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

```
def count_partitions(n, m):
```

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

`with_m = count_partitions(n-m, m)`

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

```
def count_partitions(n, m):
```

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

`with_m = count_partitions(n-m, m)`

`without_m = count_partitions(n, m-1)`

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

```
def count_partitions(n, m):
```

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

```
    with_m = count_partitions(n-m, m)
```

```
    without_m = count_partitions(n, m-1)
```

```
    return with_m + without_m
```


Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

```
def count_partitions(n, m):
```

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

```
    if n == 0:
```

```
        with_m = count_partitions(n-m, m)
```

```
        without_m = count_partitions(n, m-1)
```

```
    return with_m + without_m
```

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

```
def count_partitions(n, m):
```

```
    if n == 0:
```

```
        return 1
```

```
    with_m = count_partitions(n-m, m)
```

```
    without_m = count_partitions(n, m-1)
```

```
    return with_m + without_m
```

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

```
def count_partitions(n, m):
```

```
    if n == 0:
```

```
        return 1
```

```
    elif n < 0:
```

```
        with_m = count_partitions(n-m, m)
```

```
        without_m = count_partitions(n, m-1)
```

```
    return with_m + without_m
```

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

```
def count_partitions(n, m):
```

```
    if n == 0:
```

```
        return 1
```

```
    elif n < 0:
```

```
        return 0
```

```
    with_m = count_partitions(n-m, m)
```

```
    without_m = count_partitions(n, m-1)
```

```
    return with_m + without_m
```

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

```
def count_partitions(n, m):
```

```
    if n == 0:
```

```
        return 1
```

```
    elif n < 0:
```

```
        return 0
```

```
    elif m == 0:
```

```
        with_m = count_partitions(n-m, m)
```

```
        without_m = count_partitions(n, m-1)
```

```
        return with_m + without_m
```

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

```
def count_partitions(n, m):
```

```
    if n == 0:
```

```
        return 1
```

```
    elif n < 0:
```

```
        return 0
```

```
    elif m == 0:
```

```
        return 0
```

```
    with_m = count_partitions(n-m, m)
```

```
    without_m = count_partitions(n, m-1)
```

```
    return with_m + without_m
```

Counting Partitions

The number of partitions of a positive integer n , using parts up to size m , is the number of ways in which n can be expressed as the sum of positive integer parts up to m in increasing order.

- Recursive decomposition: finding simpler instances of the problem.
- Explore two possibilities:
 - Use at least one 4
 - Don't use any 4
- Solve two simpler problems:
 - `count_partitions(2, 4)`
 - `count_partitions(6, 3)`
- Tree recursion often involves exploring different choices.

```
def count_partitions(n, m):  
    if n == 0:  
        return 1  
    elif n < 0:  
        return 0  
    elif m == 0:  
        return 0  
    else:  
        with_m = count_partitions(n-m, m)  
        without_m = count_partitions(n, m-1)  
        return with_m + without_m
```