Chapter 5 Intro to Networking Exam

Candidate: Dunkan Gibson (dunkan.gibson)
Date: 9/19/2021 11:02:30 am • Time spent: 01:31:53

Score: 95% Passing Score: 80%

Question 1: ✔ Correct

You've decided to use a subnet mask of 255.255.192.0 on the 172.17.0.0 network to create four separate subnets.

Which network IDs will be assigned to these subnets in this configuration? (Select two.)

- [ ] 172.17.96.0
- [x] 172.17.128.0
- [x] 172.17.0.0
- [ ] 172.17.16.0
- [ ] 172.17.32.0

EXPLANATION

The subnet mask used for the 172.17.0.0 network can be viewed in binary notation as 11111111.11111111.11000000.000000. Because the first two bits of the third octet are used for the network portion of the address, four subnets are possible:

- 172.17.0.0
- 172.17.64.0
- 172.17.128.0
- 172.17.192.0

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 2: ✔ Correct

Your network has been assigned the Class B address of 130.15.0.0 Which of the following is not an address you can assign to a node on your network?

- 130.15.60.220
- 130.15.60.0
- 130.15.0.1
- 130.16.61.3

EXPLANATION

If you plan to use the Class B address for all nodes on the network, the nodes must all have the same network address. In this case, all IP addresses must begin with 130.15.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 3: ✔ Correct

Which of the following is not a reason to use subnets on a network?

- Improve security.
- Combine different media type on to the same subnet.
- Extend the network.
- Isolate network problems.

EXPLANATION

Subnets cannot be used to combine networks of different media types on to the same subnet. Each network with a distinct media type has its own subnet. Subnets can be used to combine networks with different media types within the same internetwork.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 4: ✔ Correct

Which of the following IP address ranges is reserved for automatic private IP addressing?

- 192.168.0.0 - 192.168.255.254
- ➡ 169.254.0.1 - 169.254.255.254
- 169.192.0.0 - 169.192.254.255
- 169.168.0.1 - 169.168.255.255
- 192.168.0.1 - 192.168.254.255

EXPLANATION

The Internet Assigned Numbers Authority (IANA) has reserved 169.254.0.1 through 169.254.255.254 for automatic private IP addressing (APIPA). APIPA also sets the subnet mask on the network to 255.255.0.0.

REFERENCES

LabSim for Network Pro, Section 5.2.

Question 5: ✔ Correct

You are configuring the IP address for a host and have been asked to use the address 192.160.99.110/16. What subnet mask value would you use?

- 255.0.0.0
- ➡ 255.255.0.0
- 255.255.252.0
- 255.255.255.0

EXPLANATION

With CIDR notation, the number of bits in the subnet mask is indicated by the /16 following the IP address. A mask that uses 16 bits is written as 255.255.0.0 in decimal format. Each octet in the mask uses 8 bits, so a mask with 16 bits uses two full octets.

Use /8 for the mask 255.0.0.0 and /24 for the mask 255.255.255.0. In this example, a /24 mask would be the default subnet mask, but the address is using a non-default mask of 255.255.0.0.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 6: ✔ Correct

You need to perform a reverse lookup of the 10.0.0.3 IP address. Which command can you use to accomplish this? (Select two. Each response is a complete solution.)

- [x] nslookup 10.0.0.3
- [ ] arp 10.0.0.3
- [ ] ipconfig /dnslookup 10.0.0.3
- [ ] nbtstat -a 10.0.0.3
- [x] dig -x 10.0.0.3

EXPLANATION

To perform a reverse lookup of the 10.0.0.3 IP address, use either of the following commands:

- **dig -x 10.0.0.3**
- **nslookup 10.0.0.3**

The **ipconfig** command is used to perform a forward or reverse DNS lookup. The **arp 10.0.0.3** command displays the MAC address of the network host with an IP address of 10.0.0.3. The **nbtstat -a 10.0.0.3** command displays the NETBIOS name of the host assigned an IP address of 10.0.0.3.

REFERENCES

LabSim for Network Pro, Section 5.10.

Question 7: ✔ Correct

To answer this question, complete the lab using the information below.
You have already answered this question.
You are not allowed to view the lab again.

Launch Lab

You completed the lab correctly.

View Lab Report

Question 8: ✔ Correct

To answer this question, complete the lab using the information below.
You have already answered this question.
You are not allowed to view the lab again.

Launch Lab

You completed the lab correctly.

View Lab Report

Question 9: ✔ Correct

Your network has been assigned the Class C network address 200.78.151.0. Which of the following addresses can be assigned to hosts on your network? (Select three.)

- [x] 200.78.151.111
- [ ] 200.78.151.257
- [ ] 200.78.152.14
- [ ] 200.78.151.255
- [x] 200.78.151.252
- [x] 200.78.151.12
- [ ] 200.78.151.0

EXPLANATION

All hosts on this network must share the first three octets of the IP address (200.78.151). You cannot assign 200.78.151.0 to a host because this address indicates the address of the network. You cannot assign 200.78.151.255 because this address is reserved for the broadcast address.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 10: ✔ Correct

To answer this question, complete the lab using the information below.
You have already answered this question.
You are not allowed to view the lab again.

Launch Lab

You completed the lab correctly.

View Lab Report

Question 11: ✔ Correct

Which of the following is a valid IPv6 address?

- ➡ FEC0::AB:9007
- 199.12.254.11
- FEC0:9087:AB04:9900:7GA2:7788:CEDF:349A
- FEC0:AB04:899A
- FEC0:AB98::A7::9845:4567

EXPLANATION

FEC0::AB:9007 is a valid IPv6 address. The :: in the address replaces blocks of consecutive 0s. The longer form of this address isFEC0:0000:0000:0000:0000:0000:00AB:9007. Leading 0s within a quartet can also be omitted.

You can only omit one block of 0s using the double colon. Each number in the IPv6 address must be between 0-9 or A-F; G is not a valid number for the IPv6 address. An address without double colons should have a total of 32 hexadecimal numbers in eight blocks.

REFERENCES

LabSim for Network Pro, Section 5.6.

Question 12: ✔ Correct

Which type of address is used in a packet to address the packet to a single host?

- Multicast
- ➡ Unicast
- Full-duplex
- Simplex
- Broadcast

EXPLANATION

A unicast address is an address that identifies a single host.

A broadcast address is an address that is sent to all hosts. Broadcast traffic is typically only forwarded within (but not between) a subnet. A multicast address is an address that identifies a group of computers. Members of the group share the same multicast address.

Simplex communication uses a single channel for both sending and receiving. Full-duplex has a dedicated send and receive channel between any two hosts.

REFERENCES

LabSim for Network Pro, Section 5.7.

Question 13: ✔ Correct

A host has the address 100.55.177.99/16. Which of the following is the broadcast address for the subnet?

- 255.255.0.0
- 255.255.255.0
- ➡ 100.55.255.255
- 100.55.177.255
- 100.255.255.255

EXPLANATION

The broadcast address for the subnet is the last address on the subnet. In this example, the address uses 16 bits in the subnet mask (255.255.0.0), meaning that the first two octets indicate the subnet address (100.55.0.0), and the last two octets are used for host addresses. The last possible address on this subnet is 100.55.255.255.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 14: ✔ Correct

To answer this question, complete the lab using the information below.
You have already answered this question.
You are not allowed to view the lab again.

Launch Lab

You completed the lab correctly.

View Lab Report

Question 15: ✔ Correct

Listed below are several DNS record types. Match the record type on the left with its function on the right.

Points a host name to an IPv4 address.

✔ A

Provides alternate names to hosts that already have a host record.

✔ CNAME

Points an IP address to a host name.

✔ PTR

Points a hostname to an IPv6 address.

✔ AAAA

Identifies servers that can be used to deliver mail.

✔ MX

EXPLANATION

Records are used to store entries for host names, IP addresses, and other information in the zone database. Below are some common DNS record types:

- The A record maps an IPv4 (32-bit) DNS host name to an IP address. This is the most common resource record type.
- The AAAA record maps an IPv6 (128-bit) DNS host name to an IP address.
- The PTR record maps an IP address to a host name (in a manner of speaking, it points to an A record).
- The MX record identifies servers that can be used to deliver email.
- The CNAME record provides alternate names (or aliases) to hosts that already have a host record. Using a single A record with multiple CNAME records means that when the IP address changes, only the A record needs to be modified.

REFERENCES

LabSim for Network Pro, Section 5.5.

Question 16: ✔ Correct

You recently created a new network segment for the development department. Because the hosts are now on a different network segment, they can no longer contact the DHCP server. Both network segments are connected via a Cisco router.

Which of the following would be the best action to take in order to fix the problem?

- Install and configure a new DHCP server on the development network segment.
- Configure the router to forward broadcast messages.
- ➡ Implement an IP helper address on the router.
- Move the DHCP server to the new network segment.

EXPLANATION

When an IP helper address is implemented on the Cisco router, DHCP broadcasts are forwarded to the specified IP address of the DHCP server. This allows hosts in a different network segment to contact the DHCP server.

Installing and configuring a new DHCP would work, but it would not be the best solution. A new DHCP server would introduce additional costs and management overhead. Configuring the router to forward broadcast messages exposes the network to denial-of-service attacks. Moving the DHCP server would introduce the same problem to hosts in the other network segment.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 17: ✔ Correct

Which of the following is the last IP address that can be assigned to hosts on the 211.70.0.0 network using the default subnet mask?

- 211.70.0.255
- ➡ 211.70.0.254
- 211.70.255.255
- 211.71.0.0
- 211.70.255.254

EXPLANATION

The last address you can assign to hosts on the 211.70.0.0 network is 211.70.0.254. The network address is a Class C address and uses a default subnet mask of 255.255.255.0. The last octet is used for host addresses. 211.70.0.0 cannot be used as a host address because it is the network address. 211.70.0.255 cannot be used as a host address because it is the broadcast address.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 18: ✔ Correct

What is the default subnet mask for the IP address 203.111.3.3?

- 255.0.0.0
- 255.255.255.255
- 255.255.0.0
- ➡ 255.255.255.0

EXPLANATION

IP addresses are divided into classes. The most common of these are classes A, B, and C. Each address class has a different default subnet mask. To identify the class of an IP address, look at its first octet.

- Class A networks use a default subnet mask of 255.0.0.0 and have 0-126 as their first octet.
- Class B networks use a default subnet mask of 255.255.0.0 and have 128-191 as their first octet.
- Class C networks use a default subnet mask of 255.255.255.0 and have 192-223 as their first octet.

In this question, the IP address falls in the Class C range and, therefore, has a default subnet mask of 255.255.255.0.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 19: ✔ Correct

To answer this question, complete the lab using the information below.
You have already answered this question.
You are not allowed to view the lab again.

Launch Lab

You completed the lab correctly.

View Lab Report

Question 20: ✕ Incorrect

You have been told to assign the IP address 21.155.67.188 to a host on the network using the default subnet mask. Which mask should you use?

- 255.255.255.0
- 21.155.67.0
- ~~21.0.0.0~~
- 21.155.0.0
- 255.255.0.0
- 255.0.0.0

EXPLANATION

The default subnet mask for this address is 255.0.0.0. The address is a class A address, which begins with a number between 1 and 126 in the first octet.

21.0.0.0 is the subnet address. 255.255.0.0 is the default subnet mask for a class B address, and 255.255.255.0 is the default subnet mask for a class C address.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 21: ✓ Correct

To answer this question, complete the lab using the information below.
You have already answered this question.
You are not allowed to view the lab again.

Launch Lab

You completed the lab correctly.

View Lab Report

Question 22: ✔ Correct

To answer this question, complete the lab using the information below.
You have already answered this question.
You are not allowed to view the lab again.

Launch Lab

You completed the lab correctly.

View Lab Report

Question 23: ✔ Correct

Examine the following output:

```
Server: to.xct.mirrorxhq.net
Address: 209.53.4.130
Name: westxsim.com
Address: 64.78.193.84
```

Which of the following utilities produced this output?

- ipconfig
- ➡ **nslookup**
- tracert
- netstat

EXPLANATION

The output is from the **nslookup** command on a Windows Server system. **nslookup** is a tool that allows you to send manual DNS resolution requests to a DNS server. The output displays the IP address and host name of the DNS server that performed the resolution, and the IP address and host name of the target specified for resolution. **nslookup** can be a useful tool when troubleshooting DNS name resolution problems.

The **ipconfig** utility is used on a Windows system to view the TCP/IP configuration of network interfaces. **netstat** is used to view protocol connections that have been established by the system, as well as what incoming TCP/IP ports are in use by the system. **tracert** is a tool used to view information on the route a packet takes as it traverses the network to a remote host.

REFERENCES

LabSim for Network Pro, Section 5.10.

Question 24: ✔ Correct

Which type of address is the IP address 232.111.255.250?

- Broadcast
- Private
- Unicast
- ➡ Multicast

EXPLANATION

The address 232.111.255.250 is a multicast address. A multicast address is an address that identifies a group of computers. Members of the group share the same multicast address. Multicast addresses are in the range of 224.0.0.0 to 239.255.255.255.

A unicast address is an address that identifies a single host. A broadcast address is an address that is sent to all hosts. Broadcast addresses are the last possible address on a subnet (typically ending in 255).

The private IPv4 address ranges are:

- 10.0.0.1 to 10.255.255.254
- 172.16.0.1 to 172.31.255.254
- 192.168.0.1 to 192.168.255.254

REFERENCES

LabSim for Network Pro, Section 5.7.

Question 25: ✔ Correct

Which of the following IP addresses are Class B addresses? (Select three.)

- [ ] 64.2.2.64
- [x] 129.0.0.0
- [ ] 224.15.55.2
- [x] 132.12.0.0
- [ ] 115.33.0.0
- [ ] 195.155.0.0
- [x] 190.65.2.0

EXPLANATION

The following are Class B addresses: 129.0.0.0, 132.12.0.0, and 190.65.2.0. The first octet of Class B addresses is in the range of 128 to 191.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 26: ✕ Incorrect

To answer this question, complete the lab using the information below. **Launch Lab**

You did not attempt the lab.

Question 27: ✔ Correct

Which of the following IP addresses have a default subnet mask of 255.255.0.0? (Select all that apply.)

- ➡ ☑ 191.168.2.15
- ☐ 228.62.18.6
- ➡ ☑ 129.0.0.1
- ➡ ☑ 168.16.5.1
- ☐ 1.6.45.254
- ☐ 123.254.19.6

EXPLANATION

IP addresses are divided into classes. The most common of these are classes A, B, and C. Each address class has a different default subnet mask. To identify the class of an IP address, look at its first octet.

- Class A networks use a default subnet mask of 255.0.0.0 and have 0-126 as their first octet.
- Class B networks use a default subnet mask of 255.255.0.0 and have 128-191 as their first octet.
- Class C networks use a default subnet mask of 255.255.255.0 and have 192-223 as their first octet.

In this question, the IP addresses that fall in the Class B IP address range are 191.168.2.15, 129.0.0.1, and 168.16.5.1.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 28: ✔ Correct

You manage a subnet that uses the subnet address 198.162.1.0/23.

Which of the following best describes how addressing is configured for the subnet?

- Subnetting
- Private
- ➡ Supernetting
- Classful

EXPLANATION

The subnet address 198.162.1.0/23 is an example of a supernetted address. With supernetting, multiple smaller subnets are combined into a single larger subnet. Supernetting is performed by taking the default subnet mask and making it smaller (using less bits). For this address, the default subnet mask uses 24 bits (255.255.255.0). With supernetting, the mask is altered to use only 23 bits (255.255.254.0) to combine multiple subnets together.

Subnetting is the process of dividing a larger network into smaller networks. With the subnet address in this example, a subnetted address would use a larger subnet mask (using more bits). A subnetted address might use 25 bits (255.255.255.128) or more to subdivide the network into multiple smaller subnets. Sometimes the term "subnetting" can be used to refer to both subnetting and supernetting. But in this example, supernetting better describes what is being done.

Classful addressing uses the default subnet mask based on the address class. If classful addressing were used, the subnet would use a 24-bit mask. Private addresses are within the following ranges:

- 10.0.0.1 to 10.255.255.254
- 172.16.0.1 to 172.31.255.254
- 192.168.0.1 to 192.168.255.254

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 29: ✔ Correct

Which of the following tunneling methods is used to send IPv4 traffic through an IPv6 network?

- 6to4 tunneling
- ISATAP
- 4to6 tunneling
- Toredo tunneling

EXPLANATION

4to6 tunneling is used to send IPv4 traffic through an IPv6 network by encapsulating IPv4 packets within IPv6 packets.

6to4 tunneling is used to send IPv6 traffic through an IPv4 network. ISATAP is used to provide IPv6 communication over a private IPv4 network. Toredo tunneling establishes a tunnel between individual IPv6 hosts so they can communicate through a private or public IPv4 network.

REFERENCES

LabSim for Network Pro, Section 5.6.

Question 30: ✔ Correct

You administer a network with Windows Server 2016 and UNIX servers and Windows 10 Professional, Windows 7, and Macintosh clients. A Windows 7 computer user calls you one day and says he is unable to access resources on the network. You type **ipconfig** on the user's computer and receive the following output:

```
0 Ethernet adapter:

IP address. . . . . . . . . . : 169.254.1.17
Subnet Mask . . . . . . . . . : 255.255.0.0

Default Gateway . . . . . . . :
```

You also check your NIC and see the link light on.

What might the problem be?

- A missing default gateway.
- A misconfigured DNS server.
- A bad NIC.
- ➡ An unavailable DHCP server.
- The user changed the configuration of the computer.

EXPLANATION

If a Windows 7 client computer is configured to use DHCP and cannot locate one to receive IP addressing information, it assigns itself an IP address from the APIPA (Automatic Private IP Addressing) range of IP addresses. APIPA addresses include IP addresses from 169.254.0.0 to 169.254.255.254 and are reserved for this purpose. A lit link light on your NIC indicates a connection to the network.

REFERENCES

LabSim for Network Pro, Section 5.8.

Question 31: ✔ Correct

Which of the following are characteristics of Teredo tunneling? (Select three.)

- [x] Works through NAT.
- [ ] IPv4-only hosts communicate with IPv6-only hosts.
- [x] Dual stack hosts.
- [x] Tunnel endpoints configured on hosts.
- [ ] Dual stack routers.

EXPLANATION

Teredo tunneling has the following characteristics:

- Tunnel endpoints are configured on hosts.
- Hosts are dual-stack hosts and perform tunneling to send IPv6 packets on the IPv4 network.
- Works through NAT.

The only solution that allows IPv4-only hosts to communicate with IPv6-only hosts is network address translation-protocol translation (NAT-PT).

REFERENCES

LabSim for Network Pro, Section 5.6.

Question 32: ✔ Correct

Which of the following is a valid IPv4 address? (Select two.)

- [ ] 1.254.1.1024
- [ ] 192.168.1.512
- [x] 2.2.2.2
- [ ] 10.384.0.3
- [ ] 256.0.0.1
- [x] 172.16.1.26
- [ ] 254.7.1.417

EXPLANATION

A valid IPv4 address consists of four 8-bit (1 byte) numbers separated by periods (for example, 10.0.0.65). Because they are eight bits long, these numbers are frequently called octets.

Even though we typically express these numbers using decimal notation, it's important to remember that they are binary numbers. The lowest value one of these numbers can have is 00000000. The decimal equivalent for this number is simply 0. The highest value one these numbers can take is 11111111. The decimal equivalent of this number is 255. Therefore, in decimal notation, each octet must contain a number between 0 and 255 inclusively.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 33: ✔ Correct

You have a Windows Server 2016 system that you want to use as a DHCP relay agent.

Which Windows Server 2016 service would you use to do this?

- Network Policy Server
- Internet Information Services (IIS) Manager
- DNS
- ➡ Routing and Remote Access

EXPLANATION

In Windows Server 2016, the DHCP Relay Agent role is enabled and configured using the Routing and Remote Access service. Before a Windows server can be used as a DHCP Relay Agent, the Routing and Remote Access service (RRAS) must be installed.

REFERENCES

LabSim for Network Pro, Section 5.4.

Question 34: ✔ Correct

Which of the following terms are often synonymous with or made possible with CIDR? (Select two.)

- [ ] Classful
- [ ] OSPF
- [x] VLSM
- [ ] NAT
- [x] Classless

EXPLANATION

Classless inter-domain routing (CIDR) allows non-default subnet masks (variable-length subnet masks, or VLSMs). Routers use the following information to identify networks:

- The beginning network address in the range.
- The number of bits used in the subnet mask.

For example, the subnet 199.70.0.0 with a mask of 255.255.0.0 is represented as 199.70.0.0/16 (16 being the number of 1 bits in the subnet mask).

Classful addresses rely on the IP address class to identify the subnet mask. Network address translation (NAT) allows you to connect a private network to the internet without obtaining registered addresses for every host. Private addresses are translated to the public address of the NAT router. OSPF is a routing protocol that supports CIDR features.

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 35: ✔ Correct

Your computer is sharing information with a remote computer using the TCP/IP protocol. Suddenly, the connection stops working and appears to hang. Which command can you use to check the connection?

- ➡ **netstat**
- **nbtstat**
- **ping**
- **arp**
- **ipconfig**

EXPLANATION

Use the **netstat** command to check the status of a TCP connection.

REFERENCES

LabSim for Network Pro, Section 5.9.

Question 36: ✔ Correct

Which protocol does an IP host use to inform a router that it wants to receive specific multicast frames?

- ➡ IGMP
- ICMP
- IP
- SNMP
- MGP

EXPLANATION

IP hosts use the IGMP, or internet group management protocol, to inform multicast-enabled routers that they want to receive specific multicast frames.

REFERENCES

LabSim for Network Pro, Section 5.7.

Question 37: ✔ Correct

Assuming the network is indicated by the default portion of the IP address, which three of the following IP addresses belong to the Class A network 114.0.0.0? (Select three.)

- [ ] 115.88.0.55
- [x] 114.122.66.12
- [x] 114.58.12.0
- [ ] 115.0.0.66
- [x] 114.0.0.15
- [ ] 115.77.89.4

EXPLANATION

With a Class A network, the first octet indicates the network address. All hosts on the network must have the same value in the first octet (114).

REFERENCES

LabSim for Network Pro, Section 5.1.

Question 38: ✔ Correct

What is the network address and subnet mask used by APIPA? (Select two.)

- [ ] 255.255.255.0
- [x] 169.254.0.0
- [ ] 169.0.250.0
- [ ] 255.0.0.0
- [x] 255.255.0.0
- [ ] 169.255.0.0

EXPLANATION

Automatic private IP addressing (APIPA) uses a network address of 169.254.0.0 with the default Class B subnet mask of 255.255.0.0. Host addresses are within the range of 169.254.0.1 and 169.254.255.254.

REFERENCES

LabSim for Network Pro, Section 5.2.

Question 39: ✔ Correct

After installing a new DHCP server on the network, you need to verify that network devices are receiving IP addressing via DHCP. You reboot a Windows 10 client system and using the **ipconfig /all** command, receive the following information:

```
Ethernet adapter Local Area Connection 1:
Description . . . . . . . . . . . : Intel(R) Ethernet Connection
Physical Address. . . . . . . . . : 02-00-4C-4F-3F-50
DHCP Enabled. . . . . . . . . . . : Yes
Autoconfiguration Enabled . . . . : Yes
Autoconfiguration IPv4 Address. . : 169.254.25.129
Subnet Mask . . . . . . . . . . . : 255.255.0.0
Default Gateway . . . . . . . . . :
DNS Servers . . . . . . . . . . . :
```

Which of the following statements are true? (Select two).

- [ ] The default gateway address needs to point to the DHCP server.
- [ ] The network is configured to use static IP addressing.
- [ ] The network subnet mask is incorrect.
- [ ] DHCP is disabled on the client system.
- [x] The client system is configured to use DHCP.
- [x] The client system is unable to reach the DHCP server.

EXPLANATION

A system configured as a DHCP client will attempt to locate a DHCP server during the boot process. If the client system is unable to locate the DHCP server and obtain IP information, an APIPA assigned address will be used. The client also configures itself with a class B subnet mask of 255.255.0.0.

The output from the ipconfig command shows that the client system has been configured to receive IP information from a DHCP server. As such, the client system attempted to locate the DHCP server. When it couldn't, received the APIPA address of 169.254.25.129 and a subnet mask of 255.255.0.0. The default gateway does not have to be present to access a DHCP server.

REFERENCES

LabSim for Network Pro, Section 5.3.

Question 40: ✔ Correct

To answer this question, complete the lab using the information below.
You have already answered this question.
You are not allowed to view the lab again.

Launch Lab

You completed the lab correctly.

View Lab Report

Copyright © 2021 TestOut Corporation All rights reserved.