

## 10.4.10 Implement Application Whitelisting with AppLocker

---

### Your Performance

Your Score: 0 of 3 (0%)

Elapsed Time: 3 minutes 40 seconds



Pass Status: **Not Passed**

Required Score: 100%

### Task Summary

#### Required Actions

✗ Create the default rules [Hide Details](#)

-  Allow all files located in the Program Files folder
-  Allow all files located in the Windows folder

✗ Allow the Support group to run the call center software

✗ Configure a publisher rule to allow for future updates from the same vendor

### Explanation

Complete this lab as follows:

1. Access the CorpNet.local domain under Group Policy Management.
  - a. From Server Manager's menu bar, select **Tools > Group Policy Management**.
  - b. Maximize the window for better viewing.
  - c. Expand **Forest: CorpNet.local > Domains > CorpNet.local**.
2. Access the AppLocker policy.
  - a. Right-click **Default Domain Policy** and select **Edit**.
  - b. Maximize the window for better viewing.
  - c. Under *Computer Configuration*, expand and select:  
**Policies > Windows Settings > Security Settings > Application Control Policies > AppLocker**.
3. Configure rule enforcement.
  - a. From the right pane, select **Configure rule enforcement**.
  - b. Under Executable rules, select **Configured**.
  - c. Make sure **Enforce rules** is selected in the drop-down list.
  - d. Select **OK**.
4. Configure a Publisher rule and allow the **Support** group to run the call center software.
  - a. From the left pane, expand **AppLocker**.
  - b. Right-click **Executable Rules** and then select **Create New Rule**.
  - c. Select **Next**.
  - d. Make sure **Allow** is selected.
  - e. For *User or group*, click **Select**.
  - f. In the *Enter the object names to select* box, type **Support** and then select **OK**.
  - g. Select **Next**.
  - h. Make sure **Publisher** is selected; then select **Next**.
  - i. For the Reference file, select **Browse**.
  - j. Browse to and select the **C:\CallCenter\CallStart.exe** file.
  - k. Select **Open**.
  - l. Slide the pointer from *File version* to **Publisher** and then select **Next**.
  - m. Select **Next**.
  - n. Accept the *default name* and select **Create**.

- o. Select **Yes** to create the default rules.  
Notice that the Publisher rule was created.

---

Copyright © 2022 TestOut Corporation All rights reserved.