

14.1.6 Enable Device Logs

Your Performance

Your Score: 0 of 3 (0%)

Elapsed Time: 2 minutes 21 seconds

Pass Status: **Not Passed**

Required Score: 100%

Task Summary

Required Actions

- ✗ Enable logging and the Syslog aggregator
- ✗ Set RAM memory logging to Critical
- ✗ Set Flash memory logging to Alerts

Explanation

Complete this lab as follows:

1. Access the Log Settings for the switch.
 - a. From the left menu, expand **Administration > System Log**.
 - b. Select **Log Settings**.
2. Enable Logging and Syslog Aggregator.
 - a. For Logging, mark **Enable**.
 - b. For Syslog Aggregator, mark **Enable**.
3. Configure RAM and Flash memory logging:
 - a. Under RAM Memory Logging:
 - Mark **Emergency, Alert, and Critical**.
 - Clear **Error, Warning, Notice, Informational, and Debug**.
 - b. Under Flash Memory Logging:
 - Mark **Emergency and Alert**.
 - Clear **Critical, Error, Warning, Notice, Informational, and Debug**.
4. Select **Apply**.
5. From the top menu bar, select **Save**.
6. Under Copy/Save Configuration, select **Apply**.
7. Select **OK**.
8. Select **Done**.

Copyright © 2022 TestOut Corporation All rights reserved.