

8.3.7 Configure WIPS

Your Performance

Your Score: 3 of 3 (100%)

Elapsed Time: 1 minute 1 second

Pass Status: **Pass**

Required Score: 100%

Task Summary

Required Actions

- ✓ Configure Denial of Service protection [Show Details](#)
- ✓ Enable Wireless Intrusion Protection [Show Details](#)
- ✓ Enable Rogue DHCP Server Detection

Explanation

Complete this lab as follows:

1. Access the Ruckus zone controller.
 - a. From the taskbar, open **Google Chrome**.
 - b. In the URL field, enter **192.168.0.6** and press **Enter**.
 - c. Maximize the window for easier viewing.
2. Configure Denial of Service protection.
 - a. Select the **Configure** tab.
 - b. From the left menu, select **WIPS**.
 - c. Under *Denial of Services(DoS)*, select **Protect my wireless network against excessive wireless requests**.
 - d. Select **Temporarily block wireless clients with repeated authentication failures**.
 - e. Enter **120** seconds.
 - f. On the right, select **Apply**.
3. Configure Intrusion Detection and Prevention:
 - a. Under *Intrusion Detection and Prevention*, select **Enable report rogue devices**.
 - b. Select **Report all rogue devices**.
 - c. Select **Protect the network from malicious rogue access points**.
 - d. On the right, select **Apply**.
4. Select **Enable rogue DHCP server detection** and then select **Apply**.

Copyright © 2022 TestOut Corporation All rights reserved.