



SEARCH

Logged in as: sgwill@uark.edu | Logout

[Home](#) [My Tab](#) [About Us](#) [AASHTO Accreditation](#) [Laboratory Assessments](#) [Proficiency Samples](#) [FWD](#) [Library](#) [Resources](#)

View Sample Round Result Confirmation

AMRL Proficiency Sample Program

Hot Mix Asphalt Ignition Oven 27/28

University of Arkansas
Fayetteville, Arkansas
PSP Enrollment#: 3879
Created by sgwill@uark.edu on 12/20/2013

Your results have been received. Thank you for using our online submission system. Please [print](#) the following information for your records.

Testing Parameters

1. Asphalt Content by Ignition Method

Initial (as received) Mass of AMRL Pre-Mixed HMA Sample (for information only)

Sample 27	Sample 28
1606.5	1603.3
Version: T308-2010	Version: T308-2010
Oven Manufacturer: NCAT / Barnstead Thermolyne F85930	Oven Manufacturer: NCAT / Barnstead Thermolyne F85930
Oven Model: Set Point Temperature for Convection-Type Ignition Ovens (°C): 538	Oven Model: Set Point Temperature for Convection-Type Ignition Ovens (°C): 538
Burn Profile Used for Direct IR Irradiation-Type Ovens:	Burn Profile Used for Direct IR Irradiation-Type Ovens:
Length of Time for Ignition Process (in min) - 27 A: 45	Length of Time for Ignition Process (in min) - 27 A: 45
Length of Time for Ignition Process (in min) - 28 B: 51	Length of Time for Ignition Process (in min) - 28 B: 51

2. Asphalt Content by Ignition Method

Correction Factor for Asphalt Binder Content (for information only)

Sample 27	Sample 28
0.17	0.17
Version: T308-2010	Version: T308-2010
Oven Manufacturer: NCAT / Barnstead Thermolyne F85930	Oven Manufacturer: NCAT / Barnstead Thermolyne F85930
Oven Model: Set Point Temperature for Convection-Type Ignition Ovens (°C): 538	Oven Model: Set Point Temperature for Convection-Type Ignition Ovens (°C): 538
Burn Profile Used for Direct IR Irradiation-Type Ovens:	Burn Profile Used for Direct IR Irradiation-Type Ovens:
Length of Time for Ignition Process (in min) - 27 A: 45	Length of Time for Ignition Process (in min) - 27 A: 45
Length of Time for Ignition Process (in min) - 28 B: 51	Length of Time for Ignition Process (in min) - 28 B: 51

3. Asphalt Content by Ignition Method

Corrected Asphalt Binder Content

Sample 27	Sample 28
4.28	4.31
Version: T308-2010	Version: T308-2010
Oven Manufacturer: NCAT / Barnstead Thermolyne F85930	Oven Manufacturer: NCAT / Barnstead Thermolyne F85930
Oven Model: Set Point Temperature for Convection-Type Ignition Ovens (°C): 538	Oven Model: Set Point Temperature for Convection-Type Ignition Ovens (°C): 538
Burn Profile Used for Direct IR Irradiation-Type Ovens:	Burn Profile Used for Direct IR Irradiation-Type Ovens:
Length of Time for Ignition Process (in min) - 27 A: 45	Length of Time for Ignition Process (in min) - 27 A: 45
Length of Time for Ignition Process (in min) - 28 B: 51	Length of Time for Ignition Process (in min) - 28 B: 51

4. Mechanical Analysis of HMA

Mass Removed by Washing Over the 75-µm (No. 200) Sieve

Sample 27	Sample 28
8.0	7.5
Version: T30-2013	Version: T30-2013

Washing Procedure: Manual Washing Procedure: Manual
Time for Wash:

5. Mechanical Analysis of HMA

Total Material Passing the 12.5-mm (1/2 in.) Sieve

Sample 27
93.9

Sample 28
93.3

Version: T30-2013

Version: T30-2013

Washing Procedure: Manual
Time for Wash:

Washing Procedure: Manual
Time for Wash:

6. Mechanical Analysis of HMA

Total Material Passing the 9.5-mm (3/8 in.) Sieve

Sample 27
80.7

Sample 28
82.6

Version: T30-2013

Version: T30-2013

Washing Procedure: Manual
Time for Wash:

Washing Procedure: Manual
Time for Wash:

7. Mechanical Analysis of HMA

Total Material Passing the 4.75-mm (No. 4) Sieve

Sample 27
61.8

Sample 28
65.0

Version: T30-2013

Version: T30-2013

Washing Procedure: Manual
Time for Wash:

Washing Procedure: Manual
Time for Wash:

8. Mechanical Analysis of HMA

Total Material Passing the 2.36-mm (No. 8) Sieve

Sample 27
37.1

Sample 28
37.9

Version: T30-2013

Version: T30-2013

Washing Procedure: Manual
Time for Wash:

Washing Procedure: Manual
Time for Wash:

9. Mechanical Analysis of HMA

Total Material Passing the 1.18-mm (No. 16) Sieve

Sample 27
26.5

Sample 28
24.1

Version: T30-2013

Version: T30-2013

Washing Procedure: Manual
Time for Wash:

Washing Procedure: Manual
Time for Wash:

10. Mechanical Analysis of HMA

Total Material Passing the 600-µm (No. 30) Sieve

Sample 27
18.0

Sample 28
15.6

Version: T30-2013

Version: T30-2013

Washing Procedure: Manual
Time for Wash:

Washing Procedure: Manual
Time for Wash:

11. Mechanical Analysis of HMA

Total Material Passing the 300-µm (No. 50) Sieve

Sample 27
12.6

Sample 28
11.2

Version: T30-2013

Version: T30-2013

Washing Procedure: Manual
Time for Wash:

Washing Procedure: Manual
Time for Wash:

12. Mechanical Analysis of HMA

Total Material Passing the 150-µm (No. 100) Sieve

Sample 27
9.9

Sample 28
9.1

Version: T30-2013

Version: T30-2013

Washing Procedure: Manual
Time for Wash:

Washing Procedure: Manual
Time for Wash:

13. Mechanical Analysis of HMA

Total Material Passing the 75-µm (No. 200) Sieve

Sample 27
8.32

Sample 28
7.80

Version: T30-2013

Version: T30-2013

Washing Procedure: Manual
Time for Wash:

Washing Procedure: Manual
Time for Wash:

Laboratory Comments:

We value your feedback to make our programs better. Please [Submit Feedback](#).

REST ASSURED - It is not necessary to submit other copies of your data via fax or mail. In the event that you submit data in another format, the results submitted online will take precedence over the other methods of submittal.

[Print](#)[Overwrite Data](#)[Submit More Data](#)[View Ratings](#)[Back to My Lab](#)[Back to Home](#)

© 2013 AASHTO Materials Reference Laboratory. All Rights Reserved.
[Contact Us](#) | [Terms of Use](#) | [Privacy Policy](#)

