



Calibration complies with ISO/IEC 17025, ANSI/NCSL Z540-1, and 9001



Calibration
Certificate No. 1750.01

Cert. No.: 4339-4916274

Traceable® Certificate of Calibration for Water-Proof Thermometer °F/°C

Instrument Identification:

Model: 4339

S/N: 130079721

Manufacturer: Control Company

Standards/Equipment:

<u>Description</u>	<u>Serial Number</u>	Due Date	NIST Traceable Reference		
Temperature Calibration Bath TC-231	A79341				
Digital Thermometer	130070752	1/31/14	4000-4903643		
Temperature Calibration Bath TC-218	A73332				
Thermistor Module	A27129	11/09/13	1000327261		
Temperature Probe	5202	11/30/14	15-B15PW-1-1		

Certificate Information:

Technician: 68

Procedure: CAL-03

Cal Date: 2/07/13

Cal Due: 2/07/15

Test Conditions:

23.0°C

45.0 %RH 1012 mBar

Calibration Data: (New Instrument)

Unit(s)	Nominal	As Found	In Tol	Nominal	As Left	In Tol	Min	Max	±U	TUR
°C		N.A.		0.000	-0.4	Υ	-0.5	0.5	0.059	>4:1
°C		N.A.		100.000	99.7	Y	99.5	100.5	0.059	>4:1

This Instrument was calibrated using Instruments Traceable to National Institute of Standards and Technology.

A Test Uncertainty Ratio of at least 4:1 is maintained unless otherwise stated and is calculated using the expanded measurement uncertainty. Uncertainty evaluation includes the instrument under test and is calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM). The uncertainty represents an expanded uncertainty using a coverage factor k=2 to approximate a 95% confidence level. In tolerance conditions are based on test results falling within specified limits with no reduction by the uncertainty of the measurement. The results contained herein relate only to the item calibrated. This certificate shall not be reproduced except in full, without written approval of Control Company.

Nominal=Standard's Reading; As Left=Instrument's Reading; In Tol=In Tolerance; Min/Max=Acceptance Range; ±U=Expanded Measurement Uncertainty; TUR=Test Uncertainty Ratio; Accuracy=±(Max-Min)/2; Min = As Left Nominal(Rounded) - Tolerance; Max = As Left Nominal(Rounded) + Tolerance; Date=MM/DD/YY

Yuod Lodrigues
Nicol Rodriguez, Quality Manager

Aaron Judice Technical Manager

Maintaining Accuracy:

in our opinion once calibrated your Water-Proof Thermometer °F/°C should maintain its accuracy. There is no exact way to determine how long calibration will be maintained. Water-Proof Thermometer °F/°Cs change little, if any at all, but can be affected by aging, temperature, shock, and contamination.

Recalibration:

For factory calibration and re-certification traceable to National Institute of Standards and Technology contact Control Company,

CONTROL COMPANY 4455 Rex Road Friendswood, TX 77546 USA Phone 281 482-1714 Fax 281 482-9448 service@control3.com www.control3.com

Control Company is an ISO 17025:2005 Calibration Laboratory Accredited by (A2LA) American Association for Laboratory Accreditation, Certificate No. 1750.01.

Control Company is ISO 9001:2008 Quality Certified by (DNV) Det Norske Veritas, Certificate No. CERT-01805-2006-AQ-HOU-RvA.

International Laboratory Accreditation Cooperation (ILAC) - Multilateral Recognition Arrangement (MRA).

Page 1 of 1

Traceable® is a registered trademark of Control Company

© 2009 Control Company