

# MÓDULO 14: KUBERNETES PARA ML

## Deployments, Secrets, Resource Limits y Auto-scaling

### Guía MLOps v5.0: Senior Edition | DuqueOM | Noviembre 2025

## ❁ MÓDULO 14: Kubernetes para ML

### Orquestación Production-Ready


“Kubernetes no es complicado. Es complejo porque resuelve problemas complejos.”

Duración	Teoría	Práctica
6-7 horas	30%	70%

### Lo Que Lograrás

- 1. **Desplegar** modelos ML en Kubernetes
- 2. **Configurar** secrets y configmaps
- 3. **Implementar** resource limits y auto-scaling
- 4. **Exponer** servicios con Ingress

### 14.1 Arquitectura K8s para ML



## 14.2 Deployment Completo

```
# k8s/deployment.yaml
apiVersion: apps/v1
kind: Deployment
metadata:
  name: bankchurn-api
  labels:
    app: bankchurn-api
  version: v1
spec:
  replicas: 3
  selector:
    matchLabels:
      app: bankchurn-api
  strategy:
    type: RollingUpdate
    rollingUpdate:
      maxSurge: 1
      maxUnavailable: 0
  template:
    metadata:
      labels:
        app: bankchurn-api
        version: v1
      annotations:
        prometheus.io/scrape: "true"
        prometheus.io/port: "8000"
        prometheus.io/path: "/metrics"
    spec:
      serviceAccountName: bankchurn-api

# =====
# SECURITY CONTEXT
# =====
securityContext:
  runAsNonRoot: true
  runAsUser: 1000
  fsGroup: 1000

containers:
- name: api
  image: ghcr.io/username/bankchurn:v1.2.3
  imagePullPolicy: Always

  ports:
  - containerPort: 8000
    name: http

# =====
# RESOURCE LIMITS (Crítico para ML)
# =====
resources:
  requests:
    memory: "512Mi"
    cpu: "250m"
  limits:
    memory: "1Gi"
    cpu: "500m"

# =====
# ENVIRONMENT VARIABLES
# =====
env:
- name: LOG_LEVEL
  valueFrom:
    configMapKeyRef:
      name: bankchurn-config
      key: log_level
- name: MODEL_VERSION
  value: "1.2.3"
- name: MLFLOW_TRACKING_URI
  valueFrom:
    secretKeyRef:
      name: bankchurn-secrets
      key: mlflow_uri

# =====
# PROBES
# =====
readinessProbe:
  httpGet:
    path: /health
    port: 8000
  initialDelaySeconds: 10
  periodSeconds: 5
  failureThreshold: 3

livenessProbe:
  httpGet:
    path: /health
    port: 8000
  initialDelaySeconds: 15
  periodSeconds: 10
  failureThreshold: 3

startupProbe:
  httpGet:
    path: /health
    port: 8000
  failureThreshold: 30
  periodSeconds: 2

# =====
# TOPOLOGY SPREAD (Distribuir pods en nodos)
# =====
topologySpreadConstraints:
- maxSkew: 1
  topologyKey: kubernetes.io/hostname
  whenUnsatisfiable: ScheduleAnyway
  labelSelector:
    matchLabels:
      app: bankchurn-api
```

## 14.3 Secrets y ConfigMaps

```
# k8s/configmap.yaml
apiVersion: v1
kind: ConfigMap
metadata:
  name: bankchurn-config
data:
  log_level: "INFO"
  prediction_threshold: "0.5"
  model_path: "/app/models/pipeline.pkl"
---
# k8s/secret.yaml (NUNCA commitear valores reales)
apiVersion: v1
kind: Secret
metadata:
  name: bankchurn-secrets
type: Opaque
stringData:
  mlflow_uri: "http://mlflow.mlops.svc.cluster.local:5000"
  # En producción, usar External Secrets Operator o Sealed Secrets
```

## External Secrets (Producción)

```
# k8s/external-secret.yaml
apiVersion: external-secrets.io/v1beta1
kind: ExternalSecret
metadata:
  name: bankchurn-secrets
spec:
  refreshInterval: 1h
  secretStoreRef:
    name: aws-secrets-manager
    kind: ClusterSecretStore
  target:
    name: bankchurn-secrets
  data:
  - secretKey: mlflow_uri
    remoteRef:
      key: bankchurn/prod
      property: mlflow_uri
```

## 14.4 Service e Ingress

```
# k8s/service.yaml
apiVersion: v1
kind: Service
metadata:
  name: bankchurn-api
  labels:
    app: bankchurn-api
spec:
  type: ClusterIP
  selector:
    app: bankchurn-api
  ports:
  - name: http
    port: 80
    targetPort: 8000
---
# k8s/ingress.yaml
apiVersion: networking.k8s.io/v1
kind: Ingress
metadata:
  name: bankchurn-api
  annotations:
    nginx.ingress.kubernetes.io/rewrite-target: /
    nginx.ingress.kubernetes.io/ssl-redirect: "true"
    cert-manager.io/cluster-issuer: letsencrypt-prod
spec:
  ingressClassName: nginx
  tls:
  - hosts:
    - api.bankchurn.example.com
    secretName: bankchurn-tls
  rules:
  - host: api.bankchurn.example.com
    http:
      paths:
      - path: /
        pathType: Prefix
        backend:
          service:
            name: bankchurn-api
            port:
              number: 80
```

## 14.5 Horizontal Pod Autoscaler

```
# k8s/hpa.yaml
apiVersion: autoscaling/v2
kind: HorizontalPodAutoscaler
metadata:
  name: bankchurn-api
spec:
  scaleTargetRef:
    apiVersion: apps/v1
    kind: Deployment
    name: bankchurn-api
  minReplicas: 2
  maxReplicas: 10
  metrics:
    - type: Resource
      resource:
        name: cpu
        target:
          type: Utilization
          averageUtilization: 70
    - type: Resource
      resource:
        name: memory
        target:
          type: Utilization
          averageUtilization: 80
  behavior:
    scaleDown:
      stabilizationWindowSeconds: 300
      policies:
        - type: Percent
          value: 10
          periodSeconds: 60
    scaleUp:
      stabilizationWindowSeconds: 0
      policies:
        - type: Percent
          value: 100
          periodSeconds: 15
```

## 14.6 Comandos Esenciales

```
# Aplicar manifiestos
kubectl apply -f k8s/

# Ver deployments
kubectl get deployments
kubectl describe deployment bankchurn-api

# Ver pods
kubectl get pods -l app=bankchurn-api
kubectl logs -f deployment/bankchurn-api

# Port forward para testing local
kubectl port-forward svc/bankchurn-api 8000:80

# Ver HPA
kubectl get hpa

# Debug pod
kubectl exec -it <pod-name> -- /bin/sh

# Ver eventos
kubectl get events --sort-by='.lastTimestamp'
```

## 14.7 Ejercicio: Deploy en Minikube

```
# Iniciar minikube
minikube start --memory 4096 --cpus 2

# Habilitar ingress
minikube addons enable ingress

# Aplicar manifiestos
kubectl apply -f k8s/

# Verificar
kubectl get all -l app=bankchurn-api

# Acceder
minikube service bankchurn-api --url
```

### Checklist

```
DEPLOYMENT:
[ ] Deployment con replicas
[ ] Resource requests/limits
[ ] Probes configurados
[ ] Security context

CONFIGURACIÓN:
[ ] ConfigMap para config
[ ] Secrets para credenciales
[ ] Environment variables

NETWORKING:
[ ] Service tipo ClusterIP
[ ] Ingress con TLS
[ ] HPA configurado
```

## Siguiente Paso

---

Con K8s configurado, es hora de implementar **observabilidad**.

[Ir a Módulo 15: Observabilidad →](#)

---

*Módulo 14 completado. Tu API ahora es orquestada profesionalmente.*

*© 2025 DuqueOM - Guía MLOps v5.0: Senior Edition*