

CSC139 Operating System Principles

Fall 2019, Part 5-1

Instructor: Dr. Yuan Cheng

Outline: Protection

- Goals of Protection
- Domain of Protection
- Access Matrix
- Implementation of Access Matrix
- Revocation of Access Rights

Chapter Objectives

- Discuss the goals and principles of protection in a modern computer system
- Explain how protection domains combined with an access matrix are used to specify the resources a process may access
- Examine capability and language-based protection systems

Protection

- Operating system consists of a collection of objects, hardware or software
- Each object has a unique name and can be accessed through a well-defined set of operations
- Protection problem – ensure that each object is accessed correctly and only by those processes that are allowed to do so

Principles of Protection


- Guiding principle – **principle of least privilege**
 - Programs, users and systems should be given just enough **privileges** to perform their tasks
 - Limits damage if entity has a bug, gets abused
 - Can be static (during life of system, during life of process)
 - Or dynamic (changed by process as needed) – **domain switching, privilege escalation**
 - “Need to know” a similar concept regarding access to data

Principles of Protection (cont.)

- Must consider “grain” aspect
 - Rough-grained privilege management easier, simpler, but least privilege now done in large chunks
 - For example, traditional Unix processes either have abilities of the associated user, or of root
 - Fine-grained management more complex, more overhead, but more protective
 - File ACL lists, RBAC
- Domain can be user, process, procedure

Domain Structure

- Access-right = $\langle \textit{object-name}, \textit{rights-set} \rangle$
where *rights-set* is a subset of all valid operations that can be performed on the object
- Domain = set of access-rights




Domain Implementation (UNIX)

- Domain = user-id
- Domain switch accomplished via file system
 - Each file has associated with it a domain bit (setuid bit)
 - When file is executed and setuid = on, then user-id is set to owner of the file being executed
 - When execution completes user-id is reset
- Domain switch accomplished via passwords
 - `su` command temporarily switches to another user's domain when other domain's password provided
- Domain switching via commands
 - `sudo` command prefix executes specified command in another domain (if original domain has privilege or password given)

Domain Implementation (MULTICS)

- Let D_i and D_j be any two domain rings
- If $j < i \Rightarrow D_i \subseteq D_j$



Access Matrix

- View protection as a matrix ([access matrix](#))
- Rows represent domains
- Columns represent objects
- $Access(i, j)$ is the set of operations that a process executing in Domain_{*i*} can invoke on Object_{*j*}

domain \ object	F_1	F_2	F_3	printer
D_1	read		read	
D_2				print
D_3		read	execute	
D_4	read write		read write	

Use of Access Matrix

- If a process in Domain D_i tries to do “op” on object O_j , then “op” must be in the access matrix
- User who creates object can define access column for that object
- Can be expanded to dynamic protection
 - Operations to add, delete access rights
 - Special access rights:
 - *owner of O_i*
 - *copy op from O_i to O_j (denoted by “*”)*
 - *control – D_i can modify D_j access rights*
 - *transfer – switch from domain D_i to D_j*
 - *Copy and Owner* applicable to an object
 - *Control* applicable to domain object

Use of Access Matrix (cont.)

- **Access matrix** design separates mechanism from policy
 - Mechanism
 - Operating system provides access-matrix + rules
 - If ensures that the matrix is only manipulated by authorized agents and that rules are strictly enforced
 - Policy
 - User dictates policy
 - Who can access what object and in what mode
- But doesn't solve the general confinement problem

Access Matrix of Figure A with Domains as Objects

domain \ object	F_1	F_2	F_3	laser printer	D_1	D_2	D_3	D_4
D_1	read		read			switch		
D_2				print			switch	switch
D_3		read	execute					
D_4	read write		read write		switch			

Access Matrix with *Copy* Rights

object domain	F_1	F_2	F_3
D_1	execute		write*
D_2	execute	read*	execute
D_3	execute		

(a)

object domain	F_1	F_2	F_3
D_1	execute		write*
D_2	execute	read*	execute
D_3	execute	read	

(b)

Access Matrix with *Owner* Rights

object domain	F_1	F_2	F_3
D_1	owner execute		write
D_2		read* owner	read* owner write
D_3	execute		

(a)

object domain	F_1	F_2	F_3
D_1	owner execute		write
D_2		owner read* write*	read* owner write
D_3		write	write

(b)

Modified Access Matrix of Figure B

object domain	F_1	F_2	F_3	laser printer	D_1	D_2	D_3	D_4
D_1	read		read			switch		
D_2				print			switch	switch control
D_3		read	execute					
D_4	write		write		switch			

Implementation of Access Matrix

- Generally, a sparse matrix
- Option 1 – Global table
 - Store ordered triples `<domain, object, rights-set>` in table
 - A requested operation M on object O_j within domain D_i -> search table for `< D_i , O_j , R_k >`
 - with $M \in R_k$
 - But table could be large -> won't fit in main memory
 - Difficult to group objects (consider an object that all domains can read)

Implementation of Access Matrix (cont.)

- Option 2 – Access lists for objects
 - Each column implemented as an access list for one object
 - Resulting per-object list consists of ordered pairs `<domain, rights-set>` defining all domains with non-empty set of access rights for the object
 - Easily extended to contain default set -> If $M \in \text{default set}$, also allow access

Implementation of Access Matrix (cont.)

- Each column = Access-control list for one object
Defines who can perform what operation

Domain 1 = Read, Write
Domain 2 = Read
Domain 3 = Read

- Each Row = Capability List (like a key)
For each domain, what operations allowed on what objects

Object F1 – Read
Object F4 – Read, Write, Execute
Object F5 – Read, Write, Delete, Copy

Implementation of Access Matrix (cont.)

- Option 3 – Capability list for domains
 - Instead of object-based, list is domain based
 - **Capability list** for domain is list of objects together with operations allows on them
 - Object represented by its name or address, called a **capability**
 - Execute operation M on object O_j , process requests operation and specifies capability as parameter
 - Possession of capability means access is allowed
 - Capability list associated with domain but never directly accessible by domain
 - Rather, protected object, maintained by OS and accessed indirectly
 - Like a “secure pointer”
 - Idea can be extended up to applications

Implementation of Access Matrix (cont.)

- Option 4 – Lock-key
 - Compromise between access lists and capability lists
 - Each object has list of unique bit patterns, called **locks**
 - Each domain as list of unique bit patterns called **keys**
 - Process in a domain can only access object if domain has key that matches one of the locks

Comparison of Implementations


- Many trade-offs to consider
 - Global table is simple, but can be large
 - Access lists correspond to needs of users
 - Determining set of access rights for domain non-localized so difficult
 - Every access to an object must be checked
 - Many objects and access rights -> slow
 - Capability lists useful for localizing information for a given process
 - But revocation capabilities can be inefficient
 - Lock-key effective and flexible, keys can be passed freely from domain to domain, easy revocation

Comparison of Implementations (cont.)

- Most systems use combination of access lists and capabilities
 - First access to an object -> access list searched
 - If allowed, capability created and attached to process
 - Additional accesses need not be checked
 - After last access, capability destroyed
 - Consider file system with ACLs per file

Access Control

- Protection can be applied to non-file resources
- Oracle Solaris 10 provides **role-based access control (RBAC)** to implement least privilege
 - **Privilege** is right to execute system call or use an option within a system call
 - Can be assigned to processes
 - Users assigned **roles** granting access to privileges and programs
 - Enable role via password to gain its privileges
 - Similar to access matrix



Revocation of Access Rights

- Various options to remove the access right of a domain to an object
 - Immediate vs. delayed
 - Selective vs. general
 - Partial vs. total
 - Temporary vs. permanent
- **Access List** – Delete access rights from access list
 - Simple – search access list and remove entry
 - Immediate, general or selective, total or partial, permanent or temporary

Revocation of Access Rights (cont.)

- **Capability List** – Scheme required to locate capability in the system before capability can be revoked
 - **Reacquisition** – periodic delete, with require and denial if revoked
 - **Back-pointers** – set of pointers from each object to all capabilities of that object (Multics)
 - **Indirection** – capability points to global table entry which points to object – delete entry from global table, not selective (CAL)
 - **Keys** – unique bits associated with capability, generated when capability created
 - Master key associated with object, key matches master key for access
 - Revocation – create new master key
 - Policy decision of who can create and modify keys – object owner or others?

Summary

- Protection aims to enforce safety in the OS by limiting what processes can do
- Policy vs mechanism
- Protection schemes often broken!

Outline: Security

- The Security Problem
- Program Threats
- System and Network Threats
- Cryptography as a Security Tool
- User Authentication
- Implementing Security Defenses
- Firewalling to Protect Systems and Networks
- Computer-Security Classifications
- An Example: Windows 7

Chapter Objectives

- To discuss security threats and attacks
- To explain the fundamentals of encryption, authentication, and hashing
- To examine the uses of cryptography in computing
- To describe the various countermeasures to security attacks

The Security Problem

- System **secure** if resources used and accessed as intended under all circumstances
 - Unachievable
- **Intruders** (**crackers**) attempt to breach security
- **Threat** is potential security violation
- **Attack** is attempt to breach security
- Attack can be accidental or malicious
- Easier to protect against accidental than malicious misuse




Security Violation Categories

- **Breach of confidentiality**
 - Unauthorized reading of data
- **Breach of integrity**
 - Unauthorized modification of data
- **Breach of availability**
 - Unauthorized destruction of data
- **Theft of service**
 - Unauthorized use of resources
- **Denial of service (DoS)**
 - Prevention of legitimate use

Security Violation Methods

- **Masquerading** (breach **authentication**)
 - Pretending to be an authorized user to escalate privileges
- **Replay attack**
 - As is or with **message modification**
- **Man-in-the-middle attack**
 - Intruder sits in data flow, masquerading as sender to receiver and vice versa
- **Session hijacking**
 - Intercept an already-established session to bypass authentication

Standard Security Attacks



Security Measure Levels

- Impossible to have absolute security, but make cost to perpetrator sufficiently high to deter most intruders
- Security must occur at four levels to be effective:
 - **Physical**
 - Data centers, servers, connected terminals
 - **Human**
 - Avoid [social engineering](#), [phishing](#), [dumpster diving](#)
 - **Operating System**
 - Protection mechanisms, debugging
 - **Network**
 - Intercepted communications, interruption, DOS
- Security is as weak as the weakest link in the chain
- But can too much security be a problem?

Program Threats

- Many variations, many names
- Trojan Horse
 - Code segment that misuses its environment
 - Exploits mechanisms for allowing programs written by users to be executed by other users
 - Spyware, pop-up browser windows, covert channels
 - Up to 80% of spam delivered by spyware-infected systems
- Trap Door
 - Specific user identifier or password that circumvents normal security procedures
 - Could be included in a compiler
 - How to detect them?

Program Threats (cont.)

- Logic Bomb

- Program that initiates a security incident under certain circumstances


- Stack and Buffer Overflow

- Exploits a bug in a program (overflow either the stack or memory buffers)
 - Failure to check bounds on inputs, arguments
 - Write past arguments on the stack into the return address on stack
 - When routine returns from call, returns to hacked address
 - Pointed to code loaded onto stack that executes malicious code
 - Unauthorized user or privilege escalation

C Program with Buffer-overflow Condition

```
#include <stdio.h>
#define BUFFER SIZE 256
int main(int argc, char *argv[])
{
    char buffer[BUFFER SIZE];
    if (argc < 2)
        return -1;
    else {
        strcpy(buffer, argv[1]);
        return 0;
    }
}
```


Layout of Typical Stack Frame



Modified Shell Code

```
#include <stdio.h>
int main(int argc, char *argv[])
{
    execvp("\\bin\\sh", "\\bin \\sh", NULL);
    return 0;
}
```

Hypothetical Stack Frame



Before attack

After attack

Exit Slips

- Take 1-2 minutes to reflect on this lecture
- On a sheet of paper write:
 - One thing you learned in this lecture
 - One thing you didn't understand

Next class

- Final Exam Review

Acknowledgment

- The slides are partially based on the ones from
 - The book site of *Operating System Concepts (Tenth Edition)*: <http://os-book.com/>