Test workflow

1. Upload test data
2. Explore measurements
3. Review engineering metrics
4. Investigate events
5. Export reports
6. Compare two tests

Reset analysis settings

Thermal Test Intelligence Center

Upload → Document → Visualize → Analyze → Review → Export | TTIC 1.0 · Stage 2D.3

Upload a test file

Sample Data.xlsx
1.8MB

Worksheet

Sheet1

Timestamp column

Timestamp

Observations	Numeric channels	Duration	Median sample interval
6,899	59	11.0 min	0.094 s

① Test Setup ② Visualization ③ Engineering Analytics ④ Event Intelligence ⑤ Reports & Export ⑥ Test Comparison

Engineering analytics

All calculations use raw recorded values within the selected time window. Units and physical interpretation must be confirmed by the engineer.

Channels to analyze

TH1 × TH2 × TH3 × TSET1 × TSET2 ×

Channel	Samples	Minimum	Time of min (s)	Maximum	Time of max (s)	Mean	Std dev (sample)	Range (max-min)	First value	Last value	Endpoint change
TH1	6899	-1.3771	158.642	101.3454	325.469	53.098	46.7869	102.7225	26.8246	27.2006	0.376
TH2	6899	-1.3771	158.642	101.3112	324.441	53.1016	46.7891	102.6883	26.7904	27.2006	0.410
TH3	6899	-1.2062	392.055	102.2	528.688	55.4249	46.9924	103.4062	26.6536	26.9613	0.307
TSET1	6899	0	130.777	100	10.72	57.2245	47.8862	100	23	23	0
TSET2	6899	0	130.777	100	10.72	57.2245	47.8862	100	23	23	0

Download engineering metrics (CSV)

Trend slope is a least-squares straight-line fit over the selected window, expressed per minute. For a stepped test, it describes the overall trend, not the physical ramp rate of an individual step. Use a narrower time window to estimate a particular transition.

Compare two channels

Channel A

TH1

Channel B

TH2

Paired samples	Mean A − B	Max |A − B|	RMSE (A − B)
6,899	-0.0035231	0.34186	0.077956

Differences are computed row-by-row at shared logger timestamps. The channels must have compatible units for these comparisons to be meaningful.

Download paired channel comparison (CSV)