

009x_63


March 18, 2017

Stochastic Processes: Data Analysis and Computer Simulation

Stochastic processes in the real world
-A Stochastic Dealer Model II-

```
In [1]: % matplotlib inline
import numpy as np # import numpy library as np
import math        # use mathematical functions defined by the C standard
import matplotlib.pyplot as plt # import pyplot library as plt
import pandas as pd # import pandas library as pd
from datetime import datetime
from pandas_datareader import data as pdr
from pandas_datareader import wb as pwb
plt.style.use('ggplot') # use "ggplot" style for graphs
pltparams = {'legend.fontsize':16, 'axes.labelsize':20, 'axes.titlesize':20,
             'xtick.labelsize':12, 'ytick.labelsize':12, 'figure.figsize':(7, 5)}
plt.rcParams.update(pltparams)

In [2]: # Logarithmic return of price time series
def logreturn(St,tau=1):
    return np.log(St[tau:])-np.log(St[0:-tau]) # Eq.(J2) :  $G_{\tau}(t) = \log(S_t/S_{t-\tau})$ 
# normalize data to have unit variance ( $\langle (x - \langle x \rangle)^2 \rangle = 1$ )
def normalized(data):
    return ((data)/np.sqrt(np.var(data)))
# compute normalized probability distribution function
def pdf(data,bins=50):
    hist,edges=np.histogram(data[~np.isnan(data)],bins=bins,density=True)
    edges = (edges[:-1] + edges[1:])/2.0 # get bar center
    nonzero = hist > 0.0 # non-zero points
    return edges[nonzero], hist[nonzero]
# add logarithmic return data to pandas DataFrame data using the 'Adjusted'
def computeReturn(data, name, tau):
    data[name]=pd.Series(normalized(logreturn(data['Adj Close'].values, tau),
end_time = datetime.now()
start_time = datetime(end_time.year - 20, end_time.month, end_time.day)
toyota = pdr.DataReader('7203','yahoo',start_time,end_time) # import t
computeReturn(toyota, 'Return d1', 1)
```



0.1 The Dealer Model

- K. Yamada, H. Takayasu, T. Ito and M. Takayasu, Physical Review E 79, 051120 (2009).

- Transaction criterion

$$|p_i(t) - p_j(t)| \geq L \quad (\text{L1})$$

- Market price of transaction

$$P = \frac{1}{2} (p_1 + p_2) \quad (\text{L2})$$

- Logarithmic price return

$$G_\tau(t) \equiv \log P(t + \tau) - \log P(t) \quad (\text{L3})$$

1 The dealer model with memory (model 2)

- To improve the model, Yamada et al. (PRE 79, 051120, 2009) added the effect of “trend-following” predictions.
- Dynamics is captured by a random walk with a drift/memory term

$$p_i(t + \Delta t) = p_i(t) + d \langle \Delta P \rangle_M \Delta t + c f_i(t), \quad i = 1, 2 \quad (\text{L4})$$

$$f_i(t) = \begin{cases} +\Delta p & \text{prob. } 1/2 \\ -\Delta p & \text{prob. } 1/2 \end{cases} \quad (\text{L5})$$

- The constant d determines whether the dealer is a “trend-follower” ($d > 0$) or a “contrarian” ($d < 0$)

- The added term represents a moving average over the previous price changes

$$\langle \Delta P \rangle_M = \frac{2}{M(M+1)} \sum_{k=0}^{M-1} (M-k) \Delta P(n-k) \quad (\text{L6})$$

$\Delta P(n) = P(n) - P(n-1)$: Market price change at the n-th tick

- $\langle \Delta P \rangle_M$ is constant during the Random-Walk process, it is only updated at the transaction events

1.1 Dealer model as a 2D random walk

- The dealer model can again be understood as a standard 2D Random walk with absorbing boundaries.
- Introduce the price difference $D(t)$ and average $A(t)$

$$D(t) = p_1(t) - p_2(t) \quad (\text{L7})$$

$$A(t) = \frac{1}{2}(p_1(t) + p_2(t)) \quad (\text{L8})$$

- Dynamics of D and A describe a 2D random walk

$$D(t + \Delta t) = D(t) + \begin{cases} +2c\Delta p & \text{probability } 1/4 \\ 0 & \text{probability } 1/2 \\ -2c\Delta p & \text{probability } 1/4 \end{cases} \quad (\text{L9})$$

$$A(t + \Delta t) = A(t) + d\langle \Delta P \rangle_M \Delta t + \begin{cases} +c\Delta p & \text{probability } 1/4 \\ 0 & \text{probability } 1/2 \\ -c\Delta p & \text{probability } 1/4 \end{cases} \quad (\text{L10})$$

- When $D(t) = \pm L$ a transaction occurs and the random walk ends, the “particle” is absorbed by the boundary.

```
In [3]: params={'L':0.01, 'c':0.01, 'dp':0.01, 'dt':0.01**2, 'd':1.25, 'M':1} # define
def model2RW(params,p0,deltapm): # simulate Random-Walk for 1 transa
    price = np.array([p0[0], p0[1]]) # initialize mid-prices for dealers
    cdp = params['c']*params['dp'] # define random step size
    ddt = params['d']*params['dt'] # define trend drift term
    Dt = [price[0]-price[1]] # initialize price difference as em
    At = [np.average(price)] # initialize avg price as empty list
    while np.abs(price[0]-price[1]) < params['L']:
        price=price+np.random.choice([-cdp,cdp],size=2) # random walk step
        price=price+ddt*deltapm # Model 2 : add trend-following ter
        Dt.append(price[0]-price[1])
        At.append(np.average(price))
    return np.array(Dt),np.array(At)-At[0] # return difference array and av


In [4]: fig,ax=plt.subplots(figsize=(7.5,7.5),subplot_kw={'xlabel':r'$A(t) = \frac{1}{2}(p_1(t) + p_2(t))$'})
p0 = [100.25, 100.25]
params={'L':0.01, 'c':0.01, 'dp':0.01, 'dt':0.01**2, 'd':1.25, 'M':1} # define
for deltapm,lbl in zip([0, 0.003], ['Model 1', 'Model 2']):
    np.random.seed(123456)
    Dt,At = model2RW(params, p0, deltapm)
    ax.plot(At,Dt,alpha=0.8,label=lbl) #plot random walk trajectory
    ax.plot(At[-1],Dt[-1],marker='o',color='k', markersize=10) #last point
    print(lbl+' : number of steps = ',len(At),' , price change = ', At[-1])
    ax.plot(0, 0, marker='s', color='k', markersize=10) # starting position
    ax.plot([-0.01,0.03],[params['L'],params['L']],color='k') #top absorbing bo
    ax.plot([-0.01,0.03],[-params['L'],-params['L']],color='k') #bottom absorbi
```

```

ax.set_ylim([-0.012, 0.012])
ax.set_xlim([-0.01, 0.01])
ax.legend(loc=4, framealpha=0.8)
plt.show()

```

Model 1 : number of steps = 9248 , price change = -0.002700000000009
Model 2 : number of steps = 9248 , price change = 0.000767624991155



```

In [5]: params={'L':0.01,'c':0.01,'dp':0.01,'dt':0.01**2, 'd':1.25, 'M':1} # define
def model1(params,p0,numt):
    def avgprice(dpn): # compute running average Eq.(L6)
        M = len(dpn) #
        weights = np.array(range(1,M+1))*2.0/(M*(M+1))
        return weights.dot(dpn)

    mktprice = np.zeros(numt) # initialize market price P(n)

```

```

dmktprice= np.zeros(numt)    # initialize change in price dP(n) needed
ticktime = np.zeros(numt,dtype=np.int) #initialize array for tick times
price     = np.array([p0[0], p0[1]])    #initialize dealer's mid-price
time,tick= 0,0 # real time(t) and time time (n)
deltapm   = 0.0 # trend term d <dP>_m dt for current random walk
cdp       = params['c']*params['dp'] # define random step size
ddt       = params['d']*params['dt'] # define amplitude of trend term
while tick < numt: # loop over ticks
    while np.abs(price[0]-price[1]) < params['L']: # transaction criterion
        price = price + deltapm + np.random.choice([-cdp,cdp], size=2)
        time += 1 #update real time
    price[:] = np.average(price) #set mid-prices to new market price
    mktprice[tick] = price[0] # save market price
    dmktprice[tick]= mktprice[tick] - mktprice[np.max([0,tick-1])] # save
    ticktime[tick] = time # save transaction time
    tick += 1 #update ticks
    tick0 = np.max([0, tick - params['M']]) #compute tick start for run
    deltapm = avgprice(dmktprice[tick0:tick])*ddt #compute updated trend
return ticktime,mktprice

```

```


In [ ]: np.random.seed(0)
ticktime2,mktprice2 = model2(params, [100.25, 100.25], 5000)
np.savetxt('model2.txt',np.transpose([ticktime2, mktprice2]))

```


```

In [6]: ticktime,mktprice=np.loadtxt('model1.txt',unpack=True) # read saved data
ticktime2,mktprice2=np.loadtxt('model2.txt', unpack=True)
timeinterval=normalized((ticktime[1:]-ticktime[0:-1])*params['dt']) # compute
timeinterval2=normalized((ticktime2[1:]-ticktime2[0:-1])*params['dt'])
dprice=normalized(logreturn(mktprice,1)) # compute logarithmic return of th
dprice2=normalized(logreturn(mktprice2,1))
fig,[ax,bx,cx]=plt.subplots(figsize=(18,6),ncols=3,subplot_kw={'xlabel':r'$P_n$'})
ax.plot(mktprice2, lw=2, label='Model 2')
ax.plot(mktprice, alpha=0.5, lw=2, label='Model 1')
ax.legend()
ax.set_ylim(98,102)
ax.set_ylabel(r'Market price $P_n$')
bx.plot(dprice2, lw=2)
bx.plot(dprice, alpha=0.5, lw=2)
bx.set_ylabel(r'Price return $G_1$')
cx.plot(timeinterval2, lw=2)
cx.plot(timeinterval, alpha=0.5, lw=2)
cx.set_ylabel(r'Transaction interval')
fig.tight_layout() # get nice spacing between plots
plt.show()

```



```
In [7]: fig,ax=plt.subplots(figsize=(15,7.5),subplot_kw={'xlabel':r'Absolute price
for data,lbl in zip([dprice2, toyota['Return d1']], ['Model 2', 'Toyota']):
    edges, hist = pdf(np.abs(data), bins=50)
    ax.plot(edges, hist, label=lbl, lw=2)
x = np.linspace(0.1, 10)
ax.plot(x, 2*np.exp(-1.5*x),lw=4,color='gray',ls='--',alpha=0.5,label=r'Exp
ax.plot(x, 0.3*x**(-3), lw=4, color='k', ls='--', alpha=0.5, label=r'Power
ax.set_xlim(5e-1, 2e1)
ax.set_ylim(5e-4, 1)
ax.legend()
ax.semilogx()
ax.semilogy()
plt.show()
```



```

In [8]: params={'L':0.01,'c':0.01,'dp':0.01,'dt':0.01**2, 'd':1.00, 'M':10} # defin
def model2t(params,p0,numt):
    def avgprice(dpn): # compute running average Eq.(L6)
        M = len(dpn) #
        weights = np.array(range(1,M+1))*2.0/(M*(M+1))
        return weights.dot(dpn)
    def dtime(i, dpm): # return time varying d-coefficient
        if i <= 1000: # contrarians
            return -params['d']
        elif i <= 2000:# random walkers: no memory
            return 0.0
        elif i <= 3000:# trend-followers
            return params['d']
        elif dpm >= 0.0: # trend-followers if running average increasing
            return params['d']
        else: # contrarians if running average decreasing
            return -params['d']
    mktprice = np.zeros(numt) # initialize market price P(n)
    dmktprice= np.zeros(numt) # initialize change in price dP(n) needed
    ticktime = np.zeros(numt,dtype=np.int) #initialize array for tick times
    price = np.array([p0[0], p0[1]]) #initialize dealer's mid-price
    time,tick= 0,0 # real time(t) and time time (n)
    deltapm = 0.0 # trend term d <dP>_m dt for current random walk
    cdp = params['c']*params['dp'] # define random step size
    while tick < numt: # loop over ticks
        ddt = dtime(tick, deltapm)*params['dt'] # define amplitude of
        while np.abs(price[0]-price[1]) < params['L']: # transaction criterion
            price = price + deltapm + np.random.choice([-cdp,cdp], size=2)
            time += 1 #update real time
        price[:] = np.average(price) #set mid-prices to new market price
        mktprice[tick] = price[0] # save market price
        dmktprice[tick]= mktprice[tick] - mktprice[np.max([0,tick-1])] # save
        ticktime[tick] = time # save transaction time
        tick += 1 #update ticks
        tick0 = np.max([0, tick - params['M']]) #compute tick start for run
        deltapm = avgprice(dmktprice[tick0:tick])*ddt #compute updated trend
    return ticktime,mktprice

In [ ]: np.random.seed(0)
ticktime2t,mktprice2t = model2t(params, [100.25, 100.25], 4001)
np.savetxt('model2t.txt',np.transpose([ticktime2t, mktprice2t]))

In [9]: ticktime2t,mktprice2t=np.loadtxt('model2t.txt',unpack=True) # read saved data
fig,[ax,bx]=plt.subplots(figsize=(15,7.5),nrows=2, sharex=True)
for i,lbl in zip(range(4), [r'$d=-1$', r'$d=0$', r'$d=+1$', r'$d=d(\left\lceil\lambda$
n0,n1 = i*1000, (i+1)*1000
dprice=normalized(logreturn(mktprice2t[n0:n1],1))
ax.plot(range(n0,n1), mktprice2t[n0:n1])

```

```

ax.plot([n0,n0],[100,102], color='gray')
ax.text(n0+500, 100.05, lbl, fontsize=22)
bx.plot([n0,n0],[-6,6],color='gray')
bx.plot(range(n0+1,n1), dprice)
ax.set_ylim(100,101)
bx.set_ylim(-6,6)
ax.set_ylabel(r'Market price  $P_n$ ')
bx.set_ylabel(r'Price Return  $G_1$ ')
bx.set_xlabel(r'Time  $n$  (ticks)')
fig.tight_layout()
plt.show()

```

