

Email Header Analysis



Phishing- Email Analysis

Introduction to Phishing

- ❖ **Phishing attack** is a type of attack aimed at stealing personal data of the user in general by clicking on malicious links to the users via email or running malicious files on their computer.
- ❖ **Phishing attacks** correspond to the "**Delivery**" phase in the **Cyber Kill Chain** model created to analyze cyber-attacks. The delivery stage is the step where the attacker transmits the previously prepared harmful content to the victim systems / people.

Phases of the Intrusion Kill Chain



The Phishing attack is the most common attack vector for initial access. Of course, the only purpose of the attack is not to steal the user's password information.

The purpose of such attacks is to exploit the human factor, the weakest link in the chain. Attackers use phishing attacks as the first step to infiltrate systems.

What is phishing email analysis?

Phishing email analysis involves studying the content of phishing emails to ascertain the techniques the attacker used.

What is a common indicator of a phishing email?

Common indicators of a phishing email include suspicious addresses, links, or domain names, threatening language or a sense of urgency, errors in the email, the inclusion of suspicious attachments, and emails requesting sensitive information.

Elements of a phishing email

All phishing emails include one of two components: a link or an attachment. Getting victims to click the link or open the attachment requires a sophisticated set of tools and techniques. Below are some of the most important elements of a phishing email:

Subject line

Perhaps the most critical element of a phishing email, the subject line is designed to entice, alarm, or frighten the victim into opening the email. Hackers who have done their research write highly targeted subject lines to entice victims into opening emails.

Email spoofing

Email spoofing involves creating an email address that looks like that of a trusted business. With display name spoofing, the hacker adds the desired display name in the sender field of the email. In other cases, a hacker will use an email address resembling a legitimate business email as the display name.

Brand impersonation

Hackers impersonate the brands you trust the most. When attacking businesses, hackers impersonate brands that a business has a relationship with, such as a bank or a software vendor. To create the illusion of legitimacy, phishers use real business and product logos and other visual elements of the brand's identity.

Phishing link

A link is typically placed in the body of the email, but it can also be placed inside an attachment or inside a legitimate hosted file on a service like OneDrive or SharePoint to avoid detection from email filters scanning for known phishing links. Victims are lured into clicking on the link by the email itself, which directs the user to visit a website to log into an account.


Attachment

Attachments are included either to conceal the phishing link from an email filter or to deliver malware/ransomware. Often in the form of a Word document, PDF, or .zip file, the attachment appears to be legitimate business correspondence, such as an invoice. The link might lead to a phishing website or result in an automatic download of malware or ransomware.

Phishing page

A phishing page is a fraudulent webpage that impersonates a brand. Unsophisticated pages are easy to spot, but advanced phishers use real CSS from brand webpages to make their webpages identical to the real thing. Phishing pages impersonate login pages where victims enter their username and password to access their account. When they do so, their credentials are stolen.

Phishing attack flow



EXAMPLE OF PHISHING EMAIL

EXAMPLE OF PHISHING EMAIL

Fri 12/11/2015 10:33 AM

Urgency

Critical System Maintenance Team '<noreply@csmt.com>

URGENT: Critical System Maintenance - Validate user account

To [Redacted] Not sent to you.

Follow up. Start by Friday, December 11, 2015. Due by Friday, December 11, 2015.
This message was sent with High importance.

Dear user, Not addressed directly to you.

We are about to carry out maintenance on our user interface. Upon the receipt of this notice, you are required to validate users can access the interface. Generic reference to unidentified system.

Failure to validate account functions within this time duration, will inactive all user accounts. Contains 'threat' if you don't act on email.

To validate the user interface, click on the web-link below or copy the link in your web-browser:

<http://reviewuserinterface.com/verify> Attempts to direct you to a link

Yours in service,

Critical System Maintenance Team

Information Gathering

Spoofing

Attackers can send emails on behalf of someone else, as the emails do not necessarily have an authentication mechanism. Attackers can send mail on behalf of someone else using the technique called spoofing to make the user believe that the incoming email is reliable.

Several protocols have been created to prevent the Email Spoofing technique. With the help of **SPF, DKIM and DMARC** protocols, it can be understood whether the sender's address is fake or real. Some mail applications do these checks automatically. However, the use of these protocols is not mandatory and in some cases can cause problems.

- **Sender Policy Framework (SPF)**
- **DomainKeys Identified Mail (DKIM)**

To find out manually whether the mail is spoof or not, SMTP address of the mail should be learned first. **SPF, DKIM, DMARC and MX records** of the domain can be learned using tools such as Mxtoolbox. By comparing the information here, it can be learned whether the mail is spoof or not.

The screenshot displays the SuperTool Beta7 interface. On the left, a sidebar shows a list of tools including MX Lookup, Blacklist Check, DNS Lookup, Test Email Server, Reverse Lookup, Whois Lookup, DNS Check, SPF Record Lookup, DKIM Lookup, DMARC Lookup, AAAA Lookup, SRV Lookup, DNSKEY Lookup, CERT Lookup, LOC Lookup, IPSECKEY Lookup, and Domain Health. The main area shows the results of an MX Lookup for the domain umuttosun.com. The results are presented in a table with columns for Pref, Hostname, TTL, and Result.

Pref	Hostname	TTL	Result
0	umuttosun.com	4 hrs	No DMARC Record found
			DMARC Quarantine/Reject policy not enabled
			DNS Record found

Since the IP addresses of the big institutions using their own mail servers will belong to them, it can be examined whether the SMTP address belongs to that institution by looking at the **whois** records of the SMTP IP address.

An important point here is that if the sender address is not spoof, we cannot say mail is safe. Harmful mails can be sent on behalf of trusted persons by hacking corporate / personal email addresses. This type of cyber attacks has already happened, so this possibility should always be considered.

E-mail Traffic Analysis

Many parameters are needed when analyzing a phishing attack. We can learn the size of the attack and the target audience in the search results to be made on the mail gateway according to the following parameters.

- **Sender Address**
- **SMTP IP Address**
- **Email Address Domain**
- **Subject (sender address and SMTP address may be constantly changing).**

In the search results, it is necessary to learn the recipient addresses and time information besides the mail numbers.

If harmful e-mails are constantly forwarded to the same users, their e-mail addresses may have leaked in some way and shared on sites such as **PasteBin**.

Attackers can find email addresses with **theHarvester** tool on Kali Linux. It is recommended that such information should not be shared explicitly, as keeping personal mail addresses on websites would be a potential attack vector for attackers.

If mails are sent out of working hours, the attacker may be living on a different time-zone line. By gathering such information, we can begin to make sense of the attack.

What is an Email Header and How to Read Them?

In this section, we will explain what the header information in an email is, what can be done with this information and how to access this information. It is important to follow this section carefully as we will explain how to perform the header analysis in the next section.

What is an Email Header?

"Header" is basically a section of the mail that contains information such as sender, recipient and date. In addition, there are fields such as "Return-Path", "Reply-To", and "Received". Below you can see the header details of a sample email.

```
Delivered-To: info@letsdefend.io
Received: by 2002:ab4:8fc7:0:0:0:0:0 with SMTP id cs7csp1721687ecb;
Mon, 21 Mar 2022 06:10:11 -0700 (PDT)
X-Received: by 2002:a05:620a:2416:b0:67d:7735:4bbf with SMTP id d22-20020a05620a241600b0067d77354bbfmr12659013qkn.501.1647868211414;
Mon, 21 Mar 2022 06:10:11 -0700 (PDT)
ARC-Seal: i=1; a=rsa-sha256; t=1647868211; cv=none;
d=google.com; s=arc-20160816;
b=ZxH9+3UjmlxSK/Y/LeaLuupLgQT9gWm7l2agKamCTCU/4Tp5WIYpwXZe7PKv4gz30h
4jUc3QKLzmit8KREmbs4RRQz8E7Varx+b2ZpejUItxWixYcoOWt25rWrXlUnUU29vdT
OuGXWQYjgfJLoQeaDRSPoaPWKBrLbgflluZv7R5A9sYjVgf9jE/JfY2HqBiHWvK/Z6v55
FH7TBavChCadh7ronXI4FfxggfVgh7yEako6qHmnTwA3CsuseMKhl8P4M2ZLNAMtx2t0
Ej5MiM8BR/njjetLwcyNh37acMD7fuB4Atsu+4FS4sa8dFA9JSwR7wAUNT4znh7bG
vlpq==
ARC-Message-Signature: i=1; a=rsa-sha256; c=relaxed/relaxed; d=google.com; s=arc-20160816;
h=mime-version:delivered-to:date:message-id:subject:to:from
dkim-signature;
bh=HIAfgOlDaK3JQLpH5fJuRxxIvU9cb88FSU4V8M1V9sI=;
b=DQbcXx7COpYCaegIw+c82nMDSTR6SGHNR4p+jqBAgtIdm3/TXsiJwKXJJv/Yj6HRp9
YNm2RuORllLdAjcHuklcl7wngpFLP2678iuQsZvzPBFEMbgjRZbh/2OeIaNBpkEMzlaDo
4a6MNUzl/DJmLVQokqQ7s5hYePucKTGhpziqQDC/7aubWiaXuOzwXvNt9V2GsHOxvRh
dph2LsXWAdYDc6sAGctWR7wwIve4zoDBw/evWoH/g55aChuX8KGB7OPuP3G12fo0F296
EAVSovT/zvPl0/MN6oaSOWIYoYshyKm36ceOtbFZLgDYhxs1D+NeXEak8seecPz14LgG
lNEg==
ARC-Authentication-Results: i=1; mx.google.com;
dkim=pass header.i=@letsdefend.io header.s=google header.b=hRMogQ3u;
spf=pass (google.com: domain of ogunal@letsdefend.io designates 209.85.220.41 as permitted sender) smtp.mailfrom=ogunal@letsdefend.io
Return-Path: <ogunal@letsdefend.io>
Received: from mail-sor-f41.google.com (mail-sor-f41.google.com. [209.85.220.41])
by mx.google.com with SMTPS id d7-20020ac85447000000b002de980041b8sor9866778qtq.15.2022.03.21.06.10.11
for <info@letsdefend.io>
(Google Transport Security);
Mon, 21 Mar 2022 06:10:11 -0700 (PDT)
Received-SPF: pass (google.com: domain of ogunal@letsdefend.io designates 209.85.220.41 as permitted sender) client-ip=209.85.220.41;
Authentication-Results: mx.google.com;
dkim=pass header.i=@letsdefend.io header.s=google header.b=hRMogQ3u;
spf=pass (google.com: domain of ogunal@letsdefend.io designates 209.85.220.41 as permitted sender) smtp.mailfrom=ogunal@letsdefend.io
DKIM-Signature: v=1; a=rsa-sha256; c=relaxed/relaxed;
d=letsdefend.io; s=google;
h=from:to:subject:message-id:date:delivered-to:mime-version;
bh=HIAfgOlDaK3JQLpH5fJuRxxIvU9cb88FSU4V8M1V9sI=;
b=hRMogQ3uKL9FSba7f/JlWB2QkC0Rr8IR6YqQBjLHTp9egr9Vwpck6qHPYHskxOdgT0
7vwxxhHkRBLJwGjgXeVv+MNBXKLK52fiLw3B3esnnMdrmyysJLuRuvyRV2LakLqY9gCc
1W0yOlWFT/990p5h4GQMJOPSYQLPbZTwJEWc2UdfCHte4YHuxB1PUVZ261whpbqNdxGy
jckBbl4DN0AM3olu5tu6hVZr6kgreS7TTrShGz/73bTM0JnoExH/XU+V8RmYP60ei3Av
```

What does the Email Header do?

A. Enables Shipper and Recipient Identification

- Thanks to the "From" and "To" fields in the header, it is determined from whom an email will go to whom. If we look at the email above that you downloaded in "eml" format, we see that it was sent from the address ogunal@letsdefend.io to info@letsdefend.io

```
From: Omer Gunal <ogunal@letsdefend.io>
To: Letsdefend IO <info@letsdefend.io>
Subject: Example subject
```

B. Spam Blocker

- It is possible to detect spam emails using **Header analysis** and other various methods. This protects people from receiving SPAM emails.

C. Allows Tracking an Email's Route

- **It is important to check the route it follows to see if an email came from the right address.** If we look at the sample email above, we see that it came from the ogunal@letsdefend.io address, but did it actually come from the **letsdefend.io** domain or from a different fake server that mimics the same name? We can use the header information to answer this question.

Important Email Header Fields

From

- ❖ The "From" field in the internet header indicates the name and email address of the sender.

To

- ❖ This field in the mail header contains the email's receiver's details.
- ❖ It includes their name and their email address. Fields like CC (carbon copy) and BCC (blind carbon copy) also fall under this category as they all include details of your recipients.
- ❖ If you want to find out more about carbon copy and blind carbon copy, check out how to use CC and BCC.

Date

- ❖ This is the timestamp that shows when the email was sent.
- ❖ In Gmail, it usually follows the format of "day dd month yyyy hh:mmss"
- ❖ So if an email had been sent on the 16th of November, 2021, at 4:57:23 PM, it would show as Wed, 16 Nov 2021 16:57:23.

Subject

- ❖ The subject mentions the topic of the email. It summarizes the content of the entire message body.

Return-Path

- ❖ This mail header field is also known as Reply-To. If you reply to an email, it will go to the address mentioned in the Return-Path field.

Domain Key and DKIM Signatures

- ❖ The Domain Key and Domain Key Identified Mail (DKIM) are email signatures that help email service providers identify and authenticate your emails, similar to SPF signatures.

Message-ID

- ❖ The Message ID header field is a unique combination of letters and numbers that identifies each mail. No two emails will have the same Message ID.

MIME-Version

- ❖ Multipurpose Internet Mail Extensions (MIME) is an internet standard of encoding. It converts non-text content like images, videos, and other attachments into text so they can be attached to an email and sent through SMTP (Simple Mail Transfer Protocol).

Received

- ❖ The received field lists each mail server that went through an email before arriving in the recipient's inbox. It's listed in reverse chronological order — where the mail server on the top is the last server the email message went through, and the bottom is where the email originated.

X-Spam Status

- ❖ The X-Spam Status shows you the spam score of an email message.
- ❖ First, it'll highlight if a message is classified as spam.
- ❖ Then, the spam score of the email is shown, as well as the threshold for the spam for the email.
- ❖ An email can meet either the spam threshold of an inbox or exceed it. If it's too spammy and exceeds the threshold, it will automatically be classified as spam and sent to the spam folder.

Reference of Field Definitions: [gmass.co](https://gmass.com)

How to Access Your Email Header?

Gmail

- 1- Open the relevant e-mail
- 2- Click on the 3 points at the top right "..."
- 3- Click on the "Download message" button.

