



Universität Innsbruck

Department of Computer Science
Research Group Quality Engineering

SEMINAR PAPER

Comparison of Defect Prediction Models

Martin Durcek, Alberte Thegler

Supervisor: Ass.-Prof. Dr. Michael Felderer

Innsbruck, May 31, 2017



Abstract: Many data mining methods have already been introduced into defect predictions. In our work, we tested and compared the results obtained from Naive Bayes and J48 decision tree based defect prediction model. For prediction itself, metrics like were used. We also argue about the topic of general defect prediction model and usage of the very same model within several environments.

1 Introduction

Software Fault Prediction(SFP) is one of the most active research areas in software engineering. In spite of diligent planning, documentation, and proper process adherence in software development, occurrences of defects are inevitable. Finding and fixing defects costs companies around the world huge amounts of money and therefore any automated help in reliably predicting where faults are, and focusing the efforts of testers, has a significant impact on the cost of production and maintenance of software. Various regression techniques and recently also machine learning algorithms had been utilized to provide better insight into software repositories and help developers as well as testers to invest their time at work more effectively. Although some voices are critical about the importance and rentability of creating a defect prediction models as a part of software development projects, there is no doubt such model, if implemented correctly, represents additional tool to increase work effectiveness as well as software reliability.

2 Metrics, classifier and dataset selection

In this section we describe the reasons behind choosing specific code metrics, classifiers as well as datasets to work with. Since we don't possess any deep previous knowledge on this particular topic, we mostly refer to other paper and studies - mainly the article *Systematic Review of Machine Learning Techniques for Software Fault Prediction*[1] from Ruchika Malhotra.

2.1 Metrics

There are several metric groups and metrics itself used to describe software repositories and code itself. Besides traditional McCabe and Halstead static metrics, there are also Object-oriented metrics(cohesion, coupling and inheritance count), miscellaneous metrics(change and requirement metrics, code churn) or even hybrid metrics combining various metrics from previous groups. In her extensive research, Malhotra found that in more than 50% of 64 considered papers and articles on fault prediction, traditional procedural metrics had been used. Object-oriented metrics had also been used a lot - particularly coupling between objects(CBO) and response for class(RFC) emerged as

highly useful. On the other side, number of children(NOC) and depth of inheritance tree(DIT) didn't seem as good metrics for SFP purposes[1, p. 15].

2.2 Classifier

Choosing the right classifier is also not a straightforward process since there are many statistics and machine learning methods to be used and combined. During last ten years, many papers and articles have been published on the topic of classifier performance in SFP field. According to Malhotra in her paper, most widely used classifiers are decision trees and Bayesian learners followed by neural networks and support vector machines[1, p. 11].

2.3 Datasets

Several dataset options are available for SFP studies, but NASA Metrics Data Program data sets are definitely most widely used. In her research, Malhotra claims that they are used in more than 60% of 64 examined studies. KC1 is the most widely used (both module and class level) which is applied in 43% of studies and has 15.4% faulty modules and 40.6% faulty classes. Similarly, PC1 data set is used in 40% of studies and contains only 6.8% of faulty modules.[1, p. 17].

3 Experiment design

Since we want to gain from our experiment as much knowledge from SFP field as possible, we've decided to carry out rather simple tests of several decision tree and bayesian algorithms to see how they perform on NASA MDP data sets. We carried tests with the whole datasets as well as with data sets restricted just on chosen code metrics. To deal with the lack of data but still avoid overfitting, we're mostly using K-fold cross validation approach. Here is needed to mention, that in WEKA, K-fold validation is executed internally to estimate the generalization error and the output model is the model trained on the whole dataset (partial K-fold models are not shown to the user). We utilize this to also perform our own tests with the datasets where this is possible (due to their sufficient size).

3.1 Evaluation metrics

To compare models(classifiers) and evaluate their performance, there are several metrics which can be used. To decide which to use, we have again taken look into Malhotra's article[1] to find out that the most used ones are usually recall, precision, area under the

curve(AUC) and F-measure. WEKA outputs all of these so we utilized it to compare trained classifiers with several of these metrics.

Bibliography

- [1] Ruchika Malhotra. A systematic review of machine learning techniques for software fault prediction. *Applied Soft Computing*, 27:504–518, 2015.