Mubazi: AI-assisted water meter reading and billing

Technical report, final product. Dushime Paulette, BSc Software Engineering (Machine Learning), African Leadership University. Supervisor: Samiratu Ntoshi.
Live app: wasac-smart-billing-qt9t.vercel.app · Code: github.com/Dushimepaulette1/wasac-smart-billing

1. Overview

WASAC water meters in Kigali are read by hand, which is slow and leads to estimated bills, misread digits and late discovery of leaks. Mubazi lets a household photograph its meter. Computer vision reads the eight wheels, the household confirms them, the reading is checked against that household's history, and a suspicious reading goes to a WASAC officer before any bill is made. The main objective in the proposal was a prototype that improves the accuracy, traceability and timeliness of readings. Because the reader is right on only 55.7% of unseen photos, the central design decision is that AI assists and people decide.

2. Scope alignment and feature validation

Planned feature	Intended purpose	Status	Evidence and justification
Local labelled dataset	Reflect real Kigali conditions	Completed	652 photos, 536 readable and 98 unreadable verified by eye; notebook
React web and mobile camera interface	Let households submit without an app store	Completed	Installable web app, live tips, English and Kinyarwanda; `frontend/src/pages`
FastAPI backend, PostgreSQL records	Traceable digital record of every reading	Completed	`backend/app`; deployed on Render and Neon
MobileNetV2 quality classifier	Catch unreadable photos	Changed	Runs on the server, not the device, and advises instead of blocking: fewer than 100 real unreadable photos, so wrongly blocking a household costs more than a bad photo
CRNN reader with CTC	Read the digits	Completed	ResNet18 + BiGRU + CTC was compared with the plain CRNN and selected by a rule set before testing; Section 4
Isolation Forest and rules	Find implausible readings	Partial	Rules run live. The forest is built, but only synthetic histories exist, so it is not deployed
Tariff bill calculator	Immediate bill estimate	Completed	Versioned tariffs, marked provisional; `services/billing.py`
Officer review queue	Person decides doubtful readings	Completed	Photo, previous reading, changed wheels, location; decisions audited
SMS through Africa's Talking	Receipts and alerts	Partial	Built; sandbox only until a live account exists; staff outbox shows messages
USSD fallback	Serve basic phones	Partial	Menu built and tested; a live channel needs an Africa's Talking account
MTN MoMo sandbox payment	Show the payment step	Completed	API flow tested against a fake MTN. Added MoMo Pay with staff confirmation for use without API keys
Three-month pilot, SUS, interviews	Evaluate with 10 to 15 households and 2 to 3 officers	Not implemented	[FILL IN: what happened, and why. Add SUS results if a small test is run.]

Added beyond the plan: YOLO to find the number window before reading; staff household upload; bill corrections with a second approver and account credit. Direct integration with WASAC's billing database stayed out of scope; customer records are synthetic and marked DEMO-.

3. Technical functionality




Figure 1. System architecture.

Architecture. A React and TypeScript single-page app (Vercel) calls a FastAPI service (Render, Docker) that serves three ONNX models with no PyTorch in the image, and stores data in PostgreSQL (Neon). Files are separated into routes, services, models, schemas, and `anomaly` and `vision` packages.

- **Reading.** `POST /submit-photo` runs YOLO, the quality gate and the reader. The household confirms the wheels on an editable counter.
- **Check first.** `POST /check-reading` runs the same read-only `evaluate_reading` as `/confirm-reading`, so the household learns whether a reading would be billed, held, or refused before it is stored. `/confirm-reading` repeats every check with the meter row locked.
- **Review and billing.** A reading below the last one, three or more times usual use, a first reading with no start, a value typed well below a reliable AI read, a rollover, or an odd location is held. An accepted reading creates a bill with the tariff version recorded.
- **Payment.** With MTN keys, MTN's status settles a payment, and an uncertain answer leaves it open rather than risking a second prompt. Otherwise the household dials WASAC's MoMo Pay code and gives the transaction ID, by app or USSD, and an officer confirms it against WASAC's merchant account.
- **Corrections.** Billed readings are never overwritten. Adjustments recalculate the bill and the next one; anything that raises a charge needs a second person.




Figure 2. Household home with a bill; waiting for a MoMo Pay check; officer review with the evidence for a decision. From the automated end-to-end run with synthetic households.




Figure 3. Upload preview with mistakes found: each row says what is wrong, and nothing can be saved until they are fixed.

4. Testing approaches and results

Strategy	Why, and how	Results and improvement made
Unit and integration	Money and rules must be exact. pytest and Vitest run on every push in GitHub Actions	482 backend passed (4 skipped: need private model files), 225 frontend passed. Coverage 94% backend, 83% of frontend lines
Concurrency	Two taps must not charge twice; SQLite cannot show this. Race tests on PostgreSQL 16, with a control that shows the race without the guards	Passed in CI. Led to row locks and partial unique indexes
End-to-end	Proves the layers work together. Playwright drives a household and an officer through a real browser	25 of 25 steps, 0 problems on the merged code run locally. [FILL IN: live site result]
Model evaluation	Locked test set of 79 photos from 34 meters, split by meter, used once	55.7% reading accuracy (95% CI 42 to 69%), 70.9% right or within one digit
Performance and stress	Free servers and slow networks. Local load test; deployed timings	Production build on a phone screen: 194 KB, first paint 1.2 s on simulated fast 3G and 3.5 s on slow 3G, both with a 4x slower CPU. Local API: 0 errors at 50 concurrent users, median 143 ms for a bill. Deployed: 1.3 to 3.7 s per photo, about 1 minute after sleep. Peak memory 274 MB

Compatibility	Households use many phones. Chromium, Firefox and WebKit engines at four sizes	36 of 36 page checks passed (Chromium 141, Firefox 142, WebKit 26, 360 to 1366 px): no errors, no sideways scroll. Sizes and slow devices are simulated. [FILL IN: real phone results]

Different inputs. Tests cover a normal reading, a lower reading, three and ten times usual use, a first reading, meter rollover, repeats within 25 days, the same photo sent twice, wrong sign-in codes, malformed or reused transaction IDs, bad CSV rows, and MTN timeouts, 5xx and 404 answers. Each has an expected response; the table is in `docs/testing/README.md`.

What testing changed. Review found that an abandoned MoMo Pay attempt blocked bill corrections and held back credit, and that a top-up after a correction looked like a double payment. Each was reproduced with a failing test, then fixed. Testing also found that a meter added with no first reading billed the whole register, that readings at 3 to 10 times usual use were billed, and that blur checks fired more on readable photos, so they were turned off.

5. Code quality practices

- **Abstraction and polymorphism.** `PaymentProvider` is an abstract class with API, MoMo Pay and simulated versions, so `start_payment` never branches on a name. PyTorch and ONNX model classes can be swapped behind the same pipeline calls.
- **Encapsulation.** `BillBalance` is the single definition of what is owed; dataclasses such as `AnomalyResult` and `Evaluation` hold results; each service has its own error class.
- **Separation of concerns and SOLID.** Routes only translate HTTP; rules live in services. `anomaly` is split into scoring (pure), evaluation (read-only) and service (writes). Adding a provider needs a new class, not edits to the payment flow.
- **Reuse and maintainability.** Typed API client, shared UI components, CSS design tokens, one read-only check for preview and submit. CI runs a strict type check. Naming, docstrings and folder layout are consistent.
- **Algorithms.** CTC decoding with digit confidence, per-household features, a reset-aware history, tier walking, oldest-first credit settlement, and row locks with idempotency keys. See `docs/ALGORITHMS.md`.

6. Limitations and next steps

Accuracy is moderate on a small dataset, and the interval is wide. Thresholds and tariffs are provisional. The anomaly model has no real data, SMS and USSD need live accounts, and free hosting is slow after sleep. The Kinyarwanda text awaits review by a native speaker. Next steps are read-only access to WASAC's customer and meter records under a data-sharing agreement that complies with Law No. 058/2021, a real pilot, and retraining on those data.