Set contrasts

Table of contents

Packages 1
Inputs 1
Protein results from the saved fit 2
What each method receives 3
Tests 3
Collapsing overlapping sets 4
Sets called, one page per contrast and method 5
Every set at a glance 87
Validation 99
Summary 99
Save 100

Every gene set from `04_Gene_Sets`, tested in each of the nine contrasts by two methods that ask different questions:

- fgsea (fast gene set enrichment analysis) is competitive: it ranks every protein by its moderated t from step 02 and asks whether a set's proteins sit higher or lower in that ranking than random sets of the same size. It treats proteins as exchangeable, which they are not (proteins in one complex move together); correlation between members inflates false positives in competitive tests (Wu and Smyth 2012).
- fry (limma) is self-contained: it asks whether the set's proteins move together in the data, rotating residuals under the design, person block and within-person correlation. People are the unit, so at 8 per group it calls little.

Each method's own Benjamini-Hochberg correction runs within one contrast over every set.

Packages

```
library(here)
library(limma)
library(dplyr)
library(tidyr)
library(purrr)
library(tibble)
library(ggplot2)
library(grid)
library(ComplexHeatmap)
source(here("00_Setup", "Shared_functions", "analysis_reporting_helpers.R"))
params$grouping
```

```
[1] "Proteome_acute"
```

Inputs

The protein fit from step 02, this grouping's design, the gene sets, limpa's complete matrix (fry needs one without gaps), the set scores for the overview, and the phenotype for the trait tracks.

```
data_dir <- file.path("03_Group_comparisons", params$grouping, "c_data")
inputs <- c(
  gene_sets = "01_Processing/04_Gene_Sets/c_data/gene_sets.rds",
  fit = file.path(data_dir, "02_fit.rds"),
  design = file.path(data_dir, "01_design.rds"),
  limpa = "01_Processing/03_Quantification/c_data/DAList_limpa.rds",
  singscore = "01_Processing/05_Set_Scores/c_data/singscore.rds",
  phenotype = "00_Setup/Input/phenotype.csv"
)
paths <- map_chr(inputs, here)
stopifnot(file.exists(paths))
gs <- readRDS(paths[["gene_sets"]])
fit <- readRDS(paths[["fit"]])
d <- readRDS(paths[["design"]])
complete <- subset_for_design(readRDS(paths[["limpa"]]), d)
sets <- gs$sets
protein_map <- gs$protein_map
protein_ids <- protein_map$uniprot_id
eb <- fit$eBayes_fit
contrast_names <- colnames(fit$design$contrast_matrix)
design <- fit$design$design_matrix
subject <- fit$metadata$subject
```

A stale fit would still line up by count, so these checks compare names, not lengths.

```
stopifnot(
  identical(rownames(eb$coefficients), protein_ids),
  identical(colnames(eb$coefficients), contrast_names),
  identical(rownames(complete$data), protein_ids),
  identical(colnames(complete$data), rownames(design)),
  identical(fit$metadata$sample_id, rownames(design)),
  d$floor %in% contrast_names
)
c(sets = length(sets), proteins = length(protein_ids), runs = ncol(complete$data))
```

```
    sets proteins     runs
    1378     1900       44
```

Protein results from the saved fit

`topTable()` rebuilds the nine contrasts from the saved fit, with the same BH within contrast. Π = p^|logFC| marks the proteins the figure steps draw.

```
protein_results <- map(set_names(contrast_names), function(contrast) {
  topTable(eb, coef = contrast, number = Inf, adjust.method = "BH", sort.by = "none") |>
    rownames_to_column("uniprot_id") |>
    select(uniprot_id, logFC, AveExpr, t, p = P.Value, fdr = adj.P.Val)
}) |>
  list_rbind(names_to = "contrast") |>
```

```
  left_join(protein_map, by = "uniprot_id", relationship = "many-to-one") |>
  mutate(pi_score = p^abs(logFC))
stopifnot(nrow(protein_results) == length(protein_ids) * length(contrast_names))
protein_summary <- protein_results |>
  summarise(
    n_tested = n(), n_up = sum(fdr < 0.05 & logFC > 0), n_down = sum(fdr < 0.05 & logFC < 0),
    min_fdr = signif(min(fdr), 3), .by = contrast
  )
protein_summary
```

```
              contrast n_tested n_up n_down  min_fdr
1          Training_C1     1900    0      0 0.394000
2          Training_C2     1900    1      0 0.004170
3             Acute_C1     1900   75     34 0.000314
4             Acute_C2     1900    0      0 0.146000
5       Baseline_C1vC2     1900    0      0 0.759000
6        Trained_C1vC2     1900    0      0 0.465000
7          Acute_C1vC2     1900    9      2 0.000830
8 Training_Interaction     1900    0      0 0.626000
9    Acute_Interaction     1900   51      8 0.002630
```

What each method receives

fgsea gets one ranked vector per contrast: the moderated t of each representative protein, named by gene symbol so its leading edge comes back as genes. fry indexes rows of the matrix, so each set is mapped back to the representative protein `04_Gene_Sets` chose per gene.

```
ranked <- protein_results |>
  filter(selected) |>
  split(~contrast) |>
  map(\(result) set_names(result$t, result$gene))
ranked <- ranked[contrast_names]
gene_map <- filter(protein_map, selected)
set_rows <- map(sets, \(genes) {
  match(gene_map$uniprot_id[match(genes, gene_map$gene)], protein_ids)
})
stopifnot(!any(map_lgl(set_rows, anyNA)))
abundance <- complete$data
correlation <- duplicateCorrelation(abundance, design, block = subject)$consensus.correlation
correlation
```

```
[1] 0.204151
```

Tests

fgsea estimates p by permutation, so it is seeded. Each package returns its own BH column over the list it was given, kept as `fdr`; none is recomputed. Storey's q is added within contrast and method.

```
set.seed(1)
fgsea_raw <- map(ranked, \(stats) fgsea::fgsea(sets, stats, minSize = 15, maxSize = 500))
set_tests <- bind_rows(
  map(contrast_names, \(contrast) {
    as_tibble(fgsea_raw[[contrast]]) |>
      transmute(
        set_id = pathway, contrast, method = "fgsea", n_proteins = size,
        direction = if_else(NES > 0, "Up", "Down"), nes = NES, p = pval, fdr = padj,
        leading_edge = leadingEdge
      )
  }),
  map(contrast_names, \(contrast) {
    fry(abundance, set_rows, design, fit$design$contrast_matrix[, contrast],
      block = subject, correlation = correlation, sort = "none"
    ) |>
      rownames_to_column("set_id") |>
      transmute(
        set_id, contrast,
        method = "fry", n_proteins = NGenes,
        direction = Direction, nes = NA_real_, p = PValue, fdr = FDR,
        leading_edge = list(NULL)
      )
  })
) |>
  mutate(qvalue = storey_q(p), .by = c(contrast, method))
```

Collapsing overlapping sets

The collections overlap: glycolysis appears in Hallmark, KEGG, Reactome and GO. fgsea's `collapsePathways()` re-tests each significant set conditioned on a more significant set's leading edge and keeps it only if it stays significant. It prunes after testing rather than re-adjusting, so the survivors' FDR is conservative. Survivors are flagged `main`; nothing is dropped.

```
main_sets <- map(set_names(contrast_names), function(contrast) {
  significant <- fgsea_raw[[contrast]][padj < 0.05][order(pval)]
  if (nrow(significant) < 2) {
    return(significant$pathway)
  }
  fgsea::collapsePathways(significant, sets, ranked[[contrast]], pval.threshold =
0.05)$mainPathways
})
main_lookup <- imap(main_sets, \(ids, cn) tibble(contrast = cn, set_id = ids, kept = TRUE)) |>
  list_rbind()
set_tests <- set_tests |>
  left_join(main_lookup, by = c("contrast", "set_id")) |>
  mutate(main = if_else(method == "fgsea", coalesce(kept, FALSE), NA), kept = NULL) |>
  left_join(
    select(gs$set_catalog, set_id, collection, pathway, source_size, description),
    by = "set_id"
```

```
  ) |>
  relocate(contrast, method, set_id, collection, pathway)
```

The floor contrast sorts first, so the reference for how far apart the groups start opens the table.

```
set_summary <- set_tests |>
  summarise(
    n_tested_fry = sum(method == "fry"),
    n_tested_fgsea = sum(method == "fgsea"),
    n_fdr_fgsea = sum(method == "fgsea" & fdr < 0.05),
    n_collapsed = sum(method == "fgsea" & fdr < 0.05 & main),
    n_fdr_fry = sum(method == "fry" & fdr < 0.05),
    .by = contrast
  ) |>
  arrange(contrast != d$floor)
set_summary
```

```
# A tibble: 9 × 6
  contrast         n_tested_fry n_tested_fgsea n_fdr_fgsea n_collapsed n_fdr_fry
  <chr>                   <int>          <int>       <int>       <int>     <int>
1 Baseline_C1vC2           1378           1378         148          23         3
2 Training_C1              1378           1378          56          28         0
3 Training_C2              1378           1378         180          32         1
4 Acute_C1                 1378           1378         343         100       410
5 Acute_C2                 1378           1378         109          33         0
6 Trained_C1vC2            1378           1378          20           9         0
7 Acute_C1vC2              1378           1378         324         101       258
8 Training_Intera…         1378           1378         144          23         4
9 Acute_Interacti…         1378           1378         233          79       492
```

Sets called, one page per contrast and method

Every fgsea collapse survivor at FDR < 0.05 and every set at fry p < 0.05, 40 sets to a page. `dot_pages()` takes the rows to draw, the x variable and labels, and returns one plot per page.

```
labelled <- set_tests |>
  mutate(
    contrast = factor(contrast, levels = contrast_names),
    label = gsub("\n", " ", enrichVolcano::ev_clean_label(pathway))
  )
dot_pages <- function(rows, x, x_label, method_label) {
  rows |>
    arrange(contrast, .data[[x]]) |>
    mutate(page = (row_number() - 1) %/% 40 + 1, n_pages = max(page), .by = contrast) |>
    group_by(contrast, page) |>
    group_map(\(page_rows, key) {
      ggplot(page_rows, aes(.data[[x]], reorder(label, .data[[x]]), colour = collection)) +
        geom_vline(xintercept = 0, colour = "grey75") +
        geom_point(aes(size = n_proteins)) +
```

```
        scale_colour_brewer(palette = "Dark2", name = NULL) +
        scale_size_continuous(range = c(1.5, 5), name = "proteins") +
        labs(
          title = sprintf("%s, %s", key$contrast, method_label),
          subtitle = sprintf(
            "%d sets. Page %d of %d.",
            sum(rows$contrast == key$contrast), key$page, page_rows$n_pages[1]
          ),
          x = x_label, y = NULL
        ) +
        theme_minimal(base_size = 8) +
        theme(plot.title = element_text(face = "bold"))
    })
}
fgsea_pages <- dot_pages(
  filter(labelled, method == "fgsea", fdr < 0.05, main), "nes",
  "normalised enrichment score", "fgsea collapse survivors at FDR < 0.05"
)
fry_pages <- dot_pages(
  labelled |>
    filter(method == "fry", p < 0.05) |>
    mutate(signed = if_else(direction == "Up", 1, -1) * -log10(p)),
  "signed", "signed -log10 p (positive: up)", "fry sets at p < 0.05"
)
pages <- c(fgsea_pages, fry_pages)
stopifnot(
  sum(map_int(pages, \(g) nrow(g$data))) ==
    nrow(filter(set_tests, method == "fgsea", fdr < 0.05, main)) +
      nrow(filter(set_tests, method == "fry", p < 0.05))
)
length(pages)
```

```
[1] 81
```

```
walk(pages, print)
```




Figure 1: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 2: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 3: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 4: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 5: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 6: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 7: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 8: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 9: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 10: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 11: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 12: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 13: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 14: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 15: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 16: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 17: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 18: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 19: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 20: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 21: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 22: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 23: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 24: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 25: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 26: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 27: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 28: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 29: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 30: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 31: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 32: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 33: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 34: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 35: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 36: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 37: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 38: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 39: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 40: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 41: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 42: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 43: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 44: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 45: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 46: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 47: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.



Figure 48: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 49: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 50: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 51: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 52: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 53: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 54: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 55: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 56: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 57: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 58: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 59: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 60: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 61: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 62: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 63: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 64: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 65: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 66: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 67: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 68: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 69: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 70: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 71: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 72: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 73: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 74: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 75: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 76: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 77: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 78: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 79: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 80: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.




Figure 81: Sets called per contrast: fgsea collapse survivors, then fry sets at p < 0.05.

Every set at a glance

As for proteins: every set's singscore across biopsies (centred on the set's mean), then its fgsea NES across the nine contrasts, one pair of pages per collection. Rows follow average-linkage clustering on 1 − Pearson r of singscore within collection, for display only.


```
catalog <- filter(gs$set_catalog, qualifies)
sample_values <- subset_for_design(readRDS(paths[["singscore"]]), d)$scores[catalog$set_id, ]
feature_label <- with(catalog, set_names(enrichVolcano::ev_clean_label(pathway), set_id))
contrast_results <- set_tests |>
  filter(method == "fgsea") |>
  transmute(feature = set_id, contrast, effect = nes, p, fdr)
row_groups <- split(catalog$set_id, factor(catalog$collection, unique(catalog$collection))) |>
  map(\(ids) ids[hclust(as.dist(1 - cor(t(sample_values[ids, ]))), "average")$order])
report_arm_colours <- set_names(c("#2166AC", "#B2182B"), d$arms)
```

```
trait_table <- readr::read_csv(paths[["phenotype"]], show_col_types = FALSE)
biopsy_traits <- trait_table |>
  select(subject, matches("_(pre|post)_")) |>
  pivot_longer(-subject, names_to = c("trait", "when"), names_pattern = "(.*)_(pre|post)_.*") |
>
  pivot_wider(names_from = trait) |>
  transmute(
    subject,
    timepoint = if_else(when == "pre", "T1", "T2"), fcsa_mixed, mcsa, leg_press_1rm
  )
columns <- as_tibble(complete$metadata) |>
  transmute(sample_id, subject, arm = as.character(arm), timepoint = as.character(timepoint)) |
>
  mutate(group = factor(
    paste(arm, timepoint, sep = "_"),
    paste(rep(d$arms, each = 3), c("T1", "T2", "T3"), sep = "_")
  )) |>
  left_join(biopsy_traits, by = c("subject", "timepoint")) |>
  left_join(select(trait_table, subject, comp_hypertrophy), by = "subject") |>
  arrange(group, subject)
stopifnot(!anyDuplicated(columns$sample_id), setequal(columns$sample_id,
colnames(sample_values)))
lengths(row_groups)
```

```
   Hallmark    Reactome KEGG_Legacy        GOBP     GO_Slim
         33         328          62         897          58
```


```
grey_ramp <- \(x) circlize::colorRamp2(range(x, na.rm = TRUE), c("#F7F7F7", "#252525"))
tracks <- list(
  "fCSA mixed (um2)" = columns$fcsa_mixed,
  "mCSA (cm2)" = columns$mcsa, "leg press 1RM (kg)" = columns$leg_press_1rm,
  "comp_hypertrophy, per subject" = columns$comp_hypertrophy
)
sample_annotation <- HeatmapAnnotation(
  df = data.frame(arm = columns$arm, timepoint = columns$timepoint, tracks, check.names =
FALSE),
  col = c(
    list(arm = report_arm_colours, timepoint = c(T1 = "grey85", T2 = "grey55", T3 = "grey25")),
    map(tracks, grey_ramp)
  ),
  na_col = "grey80", annotation_name_gp = gpar(fontsize = 7), annotation_name_side = "left",
  simple_anno_size = unit(3, "mm")
)
effect_limit <- cap(contrast_results$effect)
overviews <- imap(row_groups, \(rows, group) {
  m <- sample_values[rows, columns$sample_id, drop = FALSE]
  m <- sweep(m, 1, rowMeans(m))
  limit <- cap(m)
  labelled_heat <- \(...) make_report_heatmap(..., labels = feature_label)
```

```
  biopsy_map <- labelled_heat(m, "biopsies", c(-limit, 0, limit), "singscore, centred",
    row_names = TRUE, column_title = character(0), top_annotation = sample_annotation,
    column_split = columns$group, cluster_column_slices = FALSE,
    column_labels = columns$subject, column_names_gp = gpar(fontsize = 5)
  )
  contrast_grid <- \(value) {
    results_to_matrix(contrast_results, rows, contrast_names, "contrast", value)
  }
  contrast_maps <- labelled_heat(
    contrast_grid(\(d) d$effect), "fgsea NES", c(-effect_limit, 0, effect_limit), "NES"
  ) +
    labelled_heat(contrast_grid(\(d) status_of(d$p, d$fdr)), "fgsea p and BH q", row_names =
TRUE)
  list(
    heatmap_page(biopsy_map, sprintf("Biopsy overview: %s", group), paste(
      sprintf("All %d sets by %d biopsies.", length(rows), ncol(m)),
      sprintf("Centred singscore; colours stop at %.2g.", limit)
    ), legends = list()),
    heatmap_page(contrast_maps, sprintf("Contrast overview: %s", group), paste(
      "fgsea NES; status: p and BH q within contrast, collections pooled.",
      sprintf("Colours stop at %.2g.", effect_limit)
    ))
  )
}) |>
  list_flatten()
walk(overviews, \(page) page$draw())
```



All 33 sets by 44 biopsies. Centred singscore; colours stop at 0.043.

Figure 82: Every set across biopsies, then across the nine contrasts, by collection.



fgsea NES; status: p and BH q within contrast, collections pooled. Colours stop at 2.5.

Figure 83: Every set across biopsies, then across the nine contrasts, by collection.




Figure 84: Every set across biopsies, then across the nine contrasts, by collection.






Figure 85: Every set across biopsies, then across the nine contrasts, by collection.



All 62 sets by 44 biopsies. Centred singscore; colours stop at 0.053.

Figure 86: Every set across biopsies, then across the nine contrasts, by collection.



fgsea NES; status: p and BH q within contrast, collections pooled. Colours stop at 2.5.

Figure 87: Every set across biopsies, then across the nine contrasts, by collection.




Figure 88: Every set across biopsies, then across the nine contrasts, by collection.





Figure 89: Every set across biopsies, then across the nine contrasts, by collection.



All 58 sets by 44 biopsies. Centred singscore; colours stop at 0.04.

Figure 90: Every set across biopsies, then across the nine contrasts, by collection.




Figure 91: Every set across biopsies, then across the nine contrasts, by collection.

Validation

```
stopifnot(
  nrow(filter(set_tests, method == "fry")) == length(sets) * length(contrast_names),
  all(set_tests$fdr >= set_tests$p, na.rm = TRUE),
  all(filter(set_tests, method == "fgsea")$set_id %in% names(sets))
)
```

Summary

```
fgsea_calls <- filter(set_summary, contrast != d$floor)$n_fdr_fgsea
```

1378 sets were tested per contrast. fgsea calls 20 to 343 sets at FDR < 0.05 across the contrasts other than the floor, which calls 148. fry calls 1168 set-contrast pairs at FDR < 0.05 across all nine.

Save

`03_set_tests.rds` holds every protein result and every set test; the figures and the classification step read it.

```
out <- here(data_dir)
dir.create(out, recursive = TRUE, showWarnings = FALSE)
saveRDS(
  list(protein_results = protein_results, set_tests = set_tests),
  file.path(out, "03_set_tests.rds"),
  compress = "xz"
)
write_workbook(
  list(
    set_summary = set_summary,
    significant = set_tests |>
      filter(fdr < 0.05) |>
      mutate(leading_edge = map_chr(leading_edge, paste, collapse = ";")),
    protein_summary = protein_summary,
    fry_correlation = tibble(matrix = "limpa", correlation = correlation)
  ),
  c(
    "Sets tested and called per contrast by method, and fgsea collapse survivors.",
    "Every set at FDR < 0.05, either method. The full table is set_tests in set_tests.rds.",
    "Proteins tested and at BH < 0.05 per contrast.",
    "Within-subject correlation fry used, estimated on limpa's matrix."
  ),
  file.path(out, "03_set_contrasts.xlsx"),
  inputs, paths
)
```