Design and contrasts

Table of contents

Packages 1
Inputs 1
The model 2
Nine contrasts 3
How alike one person's biopsies are 4
Validation 4
Summary 4
Save 5

Every comparison between two groups in this repository uses one model and one set of nine contrasts. This step builds them for one grouping and saves them as `01_design.rds`, which every later step in `03_Group_comparisons` reads.

Packages

limpa's fit estimates how alike one person's biopsies are; limma builds the contrasts.

```
library(here)
library(limma)
library(dplyr)
library(purrr)
library(tibble)
source(here("00_Setup", "Shared_functions", "analysis_reporting_helpers.R"))
params$grouping
```

```
[1] "Proteome_T1"
```

Inputs

`proteins.rds` holds limpa's values for every protein in every run, with the sample sheet. `groups.rds` from `02_Groups` says who is in each group and which group comes first.

```
data_dir <- file.path("03_Group_comparisons", params$grouping, "c_data")
inputs <- c(
  proteins = "01_Processing/03_Quantification/c_data/proteins.rds",
  groups = file.path("02_Groups", params$grouping, "c_data/groups.rds")
)
paths <- map_chr(inputs, here)
stopifnot(file.exists(paths))
quantified <- readRDS(paths[["proteins"]])
grouping <- readRDS(paths[["groups"]])
groups <- grouping$groups
table(grouping$group_of)
```

```
C1 C2
 9  6
```

Each run takes its person's group label. People the grouping leaves out (for example a person a clustering could not place) drop out with all their runs. `group` combines label and time point, for example `HR_T1`.

```
meta <- relabel_samples(quantified$metadata, grouping$group_of) |>
  mutate(
    group = factor(group, levels = groups),
    timepoint = factor(timepoint, levels = c("T1", "T2", "T3"))
  )
proteins <- quantified$proteins[, meta$sample_id]
stopifnot(
  identical(meta$sample_id, colnames(proteins$E)), !anyNA(meta$group_time),
  !any(is.na(meta$subject) | meta$subject == "")
)
count(meta, group_time)
```

```
# A tibble: 6 × 2
  group_time     n
  <fct>      <int>
1 C1_T1          9
2 C1_T2          8
3 C1_T3          8
4 C2_T1          6
5 C2_T2          6
6 C2_T3          6
```

The model

A cell-means model: one mean per group-by-time cell (six cells) plus the blood index as a covariate, so every comparison is made at equal blood content. The groups are different people, so person enters as a blocking factor rather than a fixed effect: a fixed person term would absorb every between-group difference. Blocking tells the fit how alike one person's biopsies are.

```
design <- model.matrix(~ 0 + group_time + blood, meta)
colnames(design) <- sub("^group_time", "", colnames(design))
rownames(design) <- meta$sample_id
stopifnot(
  qr(design)$rank == ncol(design),
  identical(make.names(colnames(design)), colnames(design))
)
head(design, 3)
```

```
       C1_T1 C1_T2 C1_T3 C2_T1 C2_T2 C2_T3     blood
S03_T1     1     0     0     0     0     0 -1.305674
```

```
S10_T1     1     0     0     0     0     0 -1.038822
S16_T1     1     0     0     0     0     0  1.072708
```

The rank check stops the script if any contrast could not be estimated; otherwise that would surface later as silent `NA`s.

Nine contrasts

A contrast is one comparison of cell means. With the first group as A and the second as B:

contrast	compares	window
`Training_A`, `Training_B`	T2 – T1 within each group	over training
`Acute_A`, `Acute_B`	T3 – T2 within each group	after the bout
`Baseline_AvB`	A – B at T1	before training
`Trained_AvB`	A – B at T2	after training
`Acute_AvB`	A – B at T3	after the bout
`Training_Interaction`	A's training change – B's	over training
`Acute_Interaction`	A's acute change – B's	after the bout

The training interaction is the primary contrast and the acute interaction the secondary. `Baseline_AvB` is the baseline reference, not a negative control: the groups come from an outcome or from the data, so a difference before training shows how far apart the split puts people to begin with.

```
contrast_vector <- stringr::str_replace_all(
  c(
    "Training_{a} = {a}_T2 - {a}_T1",
    "Training_{b} = {b}_T2 - {b}_T1",
    "Acute_{a} = {a}_T3 - {a}_T2",
    "Acute_{b} = {b}_T3 - {b}_T2",
    "Baseline_{a}v{b} = {a}_T1 - {b}_T1",
    "Trained_{a}v{b} = {a}_T2 - {b}_T2",
    "Acute_{a}v{b} = {a}_T3 - {b}_T3",
    "Training_Interaction = ({a}_T2 - {a}_T1) - ({b}_T2 - {b}_T1)",
    "Acute_Interaction = ({a}_T3 - {a}_T2) - ({b}_T3 - {b}_T2)"
  ),
  c("\\{a\\}" = groups[1], "\\{b\\}" = groups[2])
)
contrast_matrix <- makeContrasts(contrasts = sub(".*= ", "", contrast_vector), levels = design)
contrast_names <- sub(" =.*", "", contrast_vector)
colnames(contrast_matrix) <- contrast_names
baseline_reference <- paste0("Baseline_", groups[1], "v", groups[2])
roles <- tibble(
  contrast = contrast_names,
  role = case_when(
    contrast == "Training_Interaction" ~ "primary",
    contrast == "Acute_Interaction" ~ "secondary",
    contrast == baseline_reference ~ "baseline_reference",
```

```
    TRUE ~ "descriptive"
  )
)
roles
```

```
# A tibble: 9 × 2
  contrast             role
  <chr>                <chr>
1 Training_C1          descriptive
2 Training_C2          descriptive
3 Acute_C1             descriptive
4 Acute_C2             descriptive
5 Baseline_C1vC2       baseline_reference
6 Trained_C1vC2        descriptive
7 Acute_C1vC2          descriptive
8 Training_Interaction primary
9 Acute_Interaction    secondary
```

How alike one person's biopsies are

limpa's fit (`dpcDE()` with person as the block) estimates the consensus correlation between biopsies from the same person across all proteins. Later protein-level fits reuse the same design and block.

```
strata <- tibble(
  scope = "within subject, from limpa's dpcDE fit with subject blocked",
  correlation = limpa::dpcDE(proteins, design, block = meta$subject, plot = FALSE)$correlation
)
strata
```

```
# A tibble: 1 × 2
  scope                                                        correlation
  <chr>                                                              <dbl>
1 within subject, from limpa's dpcDE fit with subject blocked        0.145
```

Validation

```
stopifnot(
  ncol(contrast_matrix) == 9,
  all(colSums(abs(contrast_matrix[rownames(contrast_matrix) != "blood", ])) > 0),
  all(contrast_matrix["blood", ] == 0),
  setequal(unique(meta$group), groups)
)
```

Summary

Proteome_T1: 15 people, 43 runs, groups C1 and C2. Within-person correlation 0.145.

Save

`01_design.rds` carries the protein matrix in the object later steps read (`dal`: data, annotation, metadata, design), the contrasts and their roles, and the grouping.

```
dal <- list(
  data = proteins$E, annotation = quantified$annotation, metadata = meta,
  design = list(design_matrix = design, contrast_matrix = contrast_matrix)
)
out <- here(data_dir)
dir.create(out, recursive = TRUE, showWarnings = FALSE)
saveRDS(
  list(
    dal = dal, contrasts = contrast_vector, roles = roles, baseline_reference =
baseline_reference,
    group_of = grouping$group_of, groups = groups, defining_traits = grouping$defining_traits
  ),
  file.path(out, "01_design.rds"),
  compress = "xz"
)
write_workbook(
  list(
    contrasts = tibble(definition = contrast_vector, contrast = contrast_names) |>
      left_join(roles, by = "contrast"),
    correlation_strata = strata
  ),
  c(
    "The nine contrasts, their definitions and roles.",
    "Within-subject correlation from limpa's fit, blocked by subject."
  ),
  file.path(out, "01_design_contrasts.xlsx"), inputs, paths
)
```