

Glossary

Last updated by | Mennell, Jacob | 19 May 2026 at 12:18 BST

Glossary

Purpose

This page defines the main domain, platform, ingestion, retrieval, and orchestration terms used throughout the external wiki.

Business And Domain Terms

- Claim: The primary business record being processed by the solution.
- UCR: Unique Claim Reference.
- UMR: Unique Member Reference.
- Claim owner: The user currently assigned responsibility for a claim.
- Model: A business or operating context that influences claim routing, access, and UI behavior.

Platform Terms

- API: The FastAPI service that exposes the platform's synchronous integration surface.
- Main worker: The background service that runs extraction and check orchestration.
- Ingestion worker: The background service that parses documents, creates chunks, and generates embeddings.
- RabbitMQ: The message broker used for asynchronous job and task execution.
- PostgreSQL with pgvector: The primary data store used for both operational records and vector-backed retrieval.

Ingestion Terms

- Chunk: A retrieval-oriented segment of a document stored as its own persisted record.
- Chunk metadata: JSON metadata attached to a chunk, including structural and provenance information.
- Header path: A flattened representation of the inferred header hierarchy for a chunk.
- Section ID: A chunk-grouping identifier associated with shared structural context.
- Layout metadata: Page- or geometry-related information derived from document parsing.
- Fallback ingestion: A reduced-metadata ingestion path used when the preferred parsing path fails or is bypassed.

Retrieval Terms

- Lexical retrieval: Search based on literal text matching and ranking.

- Semantic retrieval: Search based on vector similarity between query and chunk embeddings.
- Hybrid retrieval: Retrieval that combines multiple signals such as lexical and semantic relevance.
- Reranking: A second-stage ordering step applied to an already-scoped set of candidates.
- Header boost: An additional retrieval signal based on overlap between query terms and chunk header structure.
- Recency boost: An additional signal that increases preference for more recent evidence when configured.
- Retrieval scope: The allowed claim, document type, and document ID boundaries within which evidence may be retrieved.

Orchestration Terms

- Deterministic execution: A controlled single-pass execution path with less autonomy than an agentic path.
- Agentic execution: A more tool- or policy-driven execution style used for certain workflows.
- QA: The downstream validation stage that evaluates whether an extraction or check result is acceptable.
- Progressive-stop: An execution pattern that evaluates candidate documents one at a time and stops at the first accepted answer.
- Progressive-fanin: An execution pattern that evaluates multiple documents and combines results in a later reduce step.
- Terminal fail-safe: A stable final execution path used when prior progressive attempts do not yield an accepted result.
- Fail-soft: Returning a controlled output such as `stuck` instead of causing an uncontrolled workflow failure.

Quality And Operations Terms

- Coverage: The measured proportion of code exercised by automated tests.
- SonarCloud: The analysis tool used in the pipeline for code quality reporting.
- Health check: A lightweight endpoint or runtime signal indicating that a service is responsive.
- Queue purge: An operational action that removes queued work and updates corresponding job state.