

# BDA\_2024\_MetaAnalysis\_ViralEncephalitis

Duy Nguyen

2024-07-22

## Research Guide of Meta-Analysis of Transcriptomics Profile in Viral Encephalitis

**Step 1:** Project set up with necessary packages

**Step 2:** Search for dataset in Gemma using individual search terms, including:

- Relevant search terms
- Specific virus names with capabilities for causing encephalitis

Datasets included for meta-analysis: GSE30577, GSE42264, GSE44331, GSE51365, GSE53784, GSE91074

**Step 3:** Assess gene expression range

Some datasets, especially Agilent microarray datasets, were normalized incorrectly, which may require re-normalization.

*Function:*

- `CheckGeneExpressionRange()`: Function to check expression range of the dataset

**Step 4:** Extract statistical contrasts of differential analysis in the datasets

These statistical contrasts allow us to check if the differential analyses are:

- Subsetted by brain region
- Included unwanted subjects
- Set up in an appropriate manner with the reference group

Based on the statistical contrasts, we might need to re-run the differential analysis

*Function:*

- `GettingResultSetInfoForDatasets()`: Function to extract statistical contrasts of differential analysis in each dataset

*Output object:*

- `ResultSets_toScreen`
- `ExperimentIDs`

**Step 5:** Download the differential expression (DE) results from each dataset

*Functions:*

- `DownloadingDEResults()`: Function to download DE results and extract Log2FC and T-stat for contrasts of interest
- `SavingGemmaDEResults_forEachResultSet()`: Function to save DE results for each ResultSet into the working directory

*Output objects:*

- `ResultSets_contrasts` (Rename of `ResultSets_Screened`)
- `UniqueResultSetIDs`
- `differentials`
- `DEResults_GSE#####_#####`

**Step 6:** Filter DE results for rows with good gene annotation

*Function:*

- `FilteringDEResults_GoodAnnotation()`: Function to filter rows with good gene annotation

*Output objects:*

- `DEResults_GSE#####` (Separated from “differentials”)
- `DE_Results_GSE#####_GoodAnnotation`

**Step 7:** Extract DE results for the contrasts of interest

*Functions:*

- `GetContrastIDsforResultSet()`: Function to extract the contrast ID using FC column names (Used within function `ExtractingDEResultsForContrasts()`)
- `ExtractingDEResultsForContrasts()`: Function to extract DE results for contrasts of interest
- `GetContrastStatColumns()`: Function to extract the Log2FC and T-stat of contrasts of interest

*Output objects:*

- `Contrast_Log2FC_GSE##### | Contrast_Tstat_GSE##### | ComparisonOfInterest_GSE#####`
- `DE_Results_Contrasts_GSE#####`

**Step 8:** Collapse DE results to one result per gene & Calculate standard error and sampling variance

Gene expression can be measured using multiple probes (microarray). Therefore, DE results need to be collapsed to one result per gene.

Standard error of Log2FC = Log2FC/T-statistics

Sampling variance = Average of standard error of each gene<sup>2</sup>

*Function:*

- `CollapsingDEResults_OneResultPerGene()`: Function to average Log2FC, Tstat, standard error (SE) and calculate sampling variance (SV) to one unique gene per dataset

*Output objects:*

- `NameOfFoldChangeColumns_GSE##### | NameOfTstatColumns_GSE#####`
- `Collapsing_DEResults_GSE#####` folder with 4 different objects:

`DEResults_GSE#####_GoodAnnotation_FoldChange_AveragedByGene`

`DE_Results_GSE#####_GoodAnnotation_Tstat_AveragedByGene`

`DE_Results_GSE#####_GoodAnnotation_SE_AveragedByGene`

`DE_Results_GSE#####_GoodAnnotation_SV`

**Step 9:** Align DE results from same models (either from mouse model or rat model)

As DE results from different datasets are in slightly different orders due to various experimental factors, we want to align these results so that the DE results from each dataset are columns, with each row representing a different gene.

*Function:*

- `AligningMouseDatasets()`: Function to align all mouse DE results from different datasets into a single dataframe for Log2FC and SV

*Output objects:*

- `Mouse_MetaAnalysis_FoldChanges`
- `Mouse_MetaAnalysis_SV`

**Step 10:** Align DE results from different models (combine DE results from both mouse model and rat model using the ortholog database from Jackson Lab)

Problem with extra NA when joining the original dataframe with the ortholog database

*Output Objects:*

- `MouseVsRat_NCBI_Entrez`
- `Mouse_MetaAnalysis_FoldChanges_wOrthologs`
- `Mouse_MetaAnalysis_SV_wOrthologs`
- `MetaAnalysis_FoldChanges`
- `MetaAnalysis_SV`

**Step 11:** Compare Log2FC across datasets with correlation matrix and hierarchically clustered heatmap

*Output Objects:*

- `MetaAnalysis_CorMatrix_FoldChanges`
- Hierarchically clustered heatmaps

**Step 12:** Meta-analysis with random effect models

Meta-analysis is performed using effect sizes (Log2FC) and sampling variances (SV)

*Function:*

- `RunBasicMetaAnalysis()`: Function to perform meta-analysis

*Output Objects:*

- `MetaAnalysis_FoldChanges_NAsPerRow`
- `CutOffForNAs`
- `NumberOfComparisons`
- `MetaAnalysis_Results_0NA`
- `metaOutput_0NA | MetaAnalysis_Annotation_0NA | MetaAnalysis_FoldChanges_ForMeta_0NA | MetaAnalysis_SV_ForMeta_0NA` (Separated from `MetaAnalysis_Results_0NA`)

**Step 13:** Correct p-value for each gene using Benjamini-Hochberg method for False Discovery Rate (FDR or q-value)

*Function:*

- `FalseDiscoveryCorrection()`: Function to correct FDR and extract gene with certain threshold of FDR and Log2FC

*Output Objects:*

- `HOM_MouseVsRat`
- `metaOutputFDR_all_0NA`
- `metaOutputFDR_0NA | metaOutputFDR_Annotated_0NA | metaOutputFDR_OrderByPval_0NA | metaOutputFDR_OrderbyPval_Log2FC_2_0NA | metaOutputFDR_OrderbyPval_Log2FC_1_0NA | metaOutputFDR_OrderbyPval_Log2FC_0.5_0NA` (Separated from `metaOutputFDR_all_0NA`)

**Step 14:** Create forest plots for statistically significant genes

*Function:*

- `MakeForestPlots()`: Function to generate forest plots

*Output Objects:*

- Forest plots of statistically significant genes

**Step 15:** Retrieve gene function from NCBI using Entrez ID

*Function:*

- `GetGeneFunctionByID()`: Function to get gene function from NCBI using Entrez Gene ID

*Output Objects:*

- EntrezGeneList\_Log2FC\_1\_0NA
- GeneFunction\_Log2FC\_1\_0NA

#### **Step 16:** Gene Set Enrichment Analysis with KEGG/GO/Reactome databases

*Function:*

- GSEAPerform\_KEGG\_GO\_Reactome(): Function to perform GSEA on common databases, including KEGG, GO, and Reactome

*Output Object:*

- GSEA\_Log2FC\_1\_0NA
- GSEA\_Log2FC\_1\_0NA\_KEGG
- GSEA\_Log2FC\_1\_0NA\_GO
- GSEA\_Log2FC\_1\_0NA\_Reactome

#### **Step 17:** Gene Set Enrichment Analysis with Brain.GMT database (developed by Dr. Hagenauer)

*Output Object:*

- BrainGMT\_metaOutputFDR\_#\_0NA
- BrainGMT\_metaOutputFDR\_#\_0NA\_cleaned
- BrainGMT\_metaOutputFDR\_OrderedByLog2FC\_1\_0NA
- BrainGMT\_Mouse
- GSEA\_Log2FC\_#\_0NA\_BrainGMT

### **1) Project Set Up**

```
# Load packages
library("gemma.R")
library("plyr")
library("metafor")
```

```
## Loading required package: Matrix
```

```
## Loading required package: metadat
```

```
## Loading required package: numDeriv
```

```
##
```

```
## Loading the 'metafor' package (version 4.6-0). For an
## introduction to the package please type: help(metafor)
```

```
library("tidyverse")
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.4      v readr      2.1.5
## v forcats    1.0.0      v stringr   1.5.1
## v ggplot2     3.5.1      v tibble    3.2.1
## v lubridate  1.9.3      v tidyr     1.3.1
## v purrr      1.0.2
```

```
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::arrange() masks plyr::arrange()
## x purrr::compact() masks plyr::compact()
## x dplyr::count() masks plyr::count()
## x dplyr::desc() masks plyr::desc()
## x tidyr::expand() masks Matrix::expand()
## x dplyr::failwith() masks plyr::failwith()
## x dplyr::filter() masks stats::filter()
## x dplyr::id() masks plyr::id()
## x dplyr::lag() masks stats::lag()
## x dplyr::mutate() masks plyr::mutate()
## x tidyr::pack() masks Matrix::pack()
## x dplyr::rename() masks plyr::rename()
## x dplyr::summarise() masks plyr::summarise()
## x dplyr::summarize() masks plyr::summarize()
## x tidyr::unpack() masks Matrix::unpack()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library("writexl")
library("pheatmap")
library("RColorBrewer")
library("viridis")
```

```
## Loading required package: viridisLite
```

```
library("multtest")
```

```
## Loading required package: BiocGenerics
##
## Attaching package: 'BiocGenerics'
##
## The following objects are masked from 'package:lubridate':
##
##   intersect, setdiff, union
##
## The following objects are masked from 'package:dplyr':
##
##   combine, intersect, setdiff, union
##
## The following objects are masked from 'package:stats':
##
##   IQR, mad, sd, var, xtabs
```

```
##
## The following objects are masked from 'package:base':
##
##   anyDuplicated, aperm, append, as.data.frame, basename, cbind,
##   colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,
##   get, grep, grepl, intersect, is.unsorted, lapply, Map, mapply,
##   match, mget, order, paste, pmax, pmax.int, pmin, pmin.int,
##   Position, rank, rbind, Reduce, rownames, sapply, setdiff, sort,
##   table, tapply, union, unique, unsplit, which.max, which.min
##
## Loading required package: Biobase
## Welcome to Bioconductor
##
##   Vignettes contain introductory material; view with
##   'browseVignettes()'. To cite Bioconductor, see
##   'citation("Biobase")', and for packages 'citation("pkgname")'.
```

```
library("rentrez")
library("clusterProfiler")
```

```
## Warning: package 'clusterProfiler' was built under R version 4.3.3
```

```
##
## clusterProfiler v4.10.1 For help: https://yulab-smu.top/biomedical-knowledge-mining-book/
##
## If you use clusterProfiler in published research, please cite:
## T Wu, E Hu, S Xu, M Chen, P Guo, Z Dai, T Feng, L Zhou, W Tang, L Zhan, X Fu, S Liu, X Bo, and G Yu.
##
## Attaching package: 'clusterProfiler'
##
## The following object is masked from 'package:purrr':
##
##   simplify
##
## The following objects are masked from 'package:plyr':
##
##   arrange, mutate, rename, summarise
##
## The following object is masked from 'package:stats':
##
##   filter
```

```
library("org.Mm.eg.db")
```

```
## Loading required package: AnnotationDbi
## Loading required package: stats4
## Loading required package: IRanges
## Loading required package: S4Vectors
```

```
## Warning: package 'S4Vectors' was built under R version 4.3.2
```

```
##
```

```

## Attaching package: 'S4Vectors'
##
## The following object is masked from 'package:clusterProfiler':
##
##     rename
##
## The following objects are masked from 'package:lubridate':
##
##     second, second<-
##
## The following objects are masked from 'package:dplyr':
##
##     first, rename
##
## The following object is masked from 'package:tidyr':
##
##     expand
##
## The following objects are masked from 'package:Matrix':
##
##     expand, unname
##
## The following object is masked from 'package:plyr':
##
##     rename
##
## The following object is masked from 'package:utils':
##
##     findMatches
##
## The following objects are masked from 'package:base':
##
##     expand.grid, I, unname
##
## Attaching package: 'IRanges'
##
## The following object is masked from 'package:clusterProfiler':
##
##     slice
##
## The following object is masked from 'package:lubridate':
##
##     %within%
##
## The following objects are masked from 'package:dplyr':
##
##     collapse, desc, slice
##
## The following object is masked from 'package:purrr':
##
##     reduce
##
## The following object is masked from 'package:plyr':

```



```
##
## desc
##
##
## Attaching package: 'AnnotationDbi'
##
## The following object is masked from 'package:clusterProfiler':
##
## select
##
## The following object is masked from 'package:dplyr':
##
## select
```

```
library("ReactomePA")
```

```
## ReactomePA v1.46.0 For help: https://yulab-smu.top/biomedical-knowledge-mining-book/
##
```

```
## If you use ReactomePA in published research, please cite:
```

```
## Guangchuang Yu, Qing-Yu He. ReactomePA: an R/Bioconductor package for reactome pathway analysis and
```

```
library("fgsea")
```

```
# Check loaded packages
(.packages())
```

```
## [1] "fgsea"          "ReactomePA"      "org.Mm.eg.db"    "AnnotationDbi"
## [5] "IRanges"        "S4Vectors"       "stats4"           "clusterProfiler"
## [9] "rentrez"        "multtest"        "Biobase"          "BiocGenerics"
## [13] "viridis"        "viridisLite"     "RColorBrewer"     "pheatmap"
## [17] "writexl"        "lubridate"       "forcats"          "stringr"
## [21] "dplyr"          "purrr"           "readr"            "tidyr"
## [25] "tibble"         "ggplot2"         "tidyverse"        "metafor"
## [29] "numDeriv"       "metadat"         "Matrix"           "plyr"
## [33] "gemma.R"        "stats"           "graphics"         "grDevices"
## [37] "utils"         "datasets"        "methods"          "base"
```

## 2) Gemma Dataset Search

```
# Extract datasets from Gemma based on single search terms
Sepsis <- searchDatasets("Sepsis", limit = 100)
Encephalitis <- searchDatasets("Encephalitis", limit = 100)
Viral_Encephalitis <- searchDatasets("Viral Encephalitis", limit = 100)
Neuroinflammation <- searchDatasets("Neuroinflammation", limit = 100)
Neuroimmune <- searchDatasets("Neuroimmune", limit = 100)
Neuroimmunology <- searchDatasets("Neuroimmunology", limit = 100)
Neurotoxicity <- searchDatasets("Neurotoxicity", limit = 100)
Neuroimmunity <- searchDatasets("Neuroimmunity", limit = 100)
Neuroinflame <- searchDatasets("Neuroinflame", limit = 100)
Neuroinflammatory <- searchDatasets("Neuroinflammatory", limit = 100)
Neurotropic <- searchDatasets("Neurotropic", limit = 100)
```

```

Neuroinvasive <- searchDatasets("Neuroinvasive", limit = 100)
Neurovirulence <- searchDatasets("Neurovirulence", limit = 100)
Viral <- searchDatasets("Viral", limit = 100)
Virus <- searchDatasets("Virus", limit = 100)
Infection <- searchDatasets("Infection", limit = 100)
Viral_Infection <- searchDatasets("Viral Infection", limit = 100)
Brain_Infection <- searchDatasets("Brain Infection", limit = 100)
Brain_Inflammation <- searchDatasets("Brain Inflammation", limit = 100)
Brain_Immunology <- searchDatasets("Brain Immunology", limit = 100)
Brain_Inflammatory <- searchDatasets("Brain Inflammatory", limit = 100)

# Extract datasets from Gemma based on specific viruses
Zika <- searchDatasets("Zika", limit = 100)
Chikungunya <- searchDatasets("Chikungunya", limit = 100)
West_Nile <- searchDatasets("West Nile", limit = 100)
Japanese_encephalitis <- searchDatasets("Japanese encephalitis", limit = 100)
Venezuelan_encephalitis <- searchDatasets("Venezuelan encephalitis", limit = 100)
StLouis_encephalitis <- searchDatasets("St Louis encephalitis", limit = 100)
Polio <- searchDatasets("Polio", limit = 100)
Mumps <- searchDatasets("Mumps", limit = 100)
Measles <- searchDatasets("Measles", limit = 100)
Nipah <- searchDatasets("Nipah", limit = 100)
Hendra <- searchDatasets("Hendra", limit = 100)
Herpes <- searchDatasets("Herpes", limit = 100)
Varicella <- searchDatasets("Varicella zoster", limit = 100)
Epstein_Barr <- searchDatasets("Epstein Barr", limit = 100)
Cytomegalo <- searchDatasets("Cytomegalovirus", limit = 100)
Rabies <- searchDatasets("Rabies", limit = 100)
Influenza <- searchDatasets("Influenza", limit = 100)
Corona <- searchDatasets("Coronavirus", limit = 100)
Yellow_fever <- searchDatasets("Yellow fever", limit = 100)

# Extract the data to excel file
write_xlsx(Sepsis, "Sepsis.xlsx")
write_xlsx(Encephalitis, "Encephalitis.xlsx")
write_xlsx(Viral_Encephalitis, "Viral Encephalitis.xlsx")
write_xlsx(Neuroinflammation, "Neuroinflammation.xlsx")
write_xlsx(Neuroimmunity, "Neuroimmunity.xlsx")
write_xlsx(Neuroinflammatory, "Neuroinflammatory.xlsx")
write_xlsx(Neurotoxicity, "Neurotoxicity.xlsx")
write_xlsx(Neurotropic, "Neurotropic.xlsx")
write_xlsx(Neuroinvasive, "Neuroinvasive.xlsx")
write_xlsx(Neurovirulence, "Neurovirulence")
write_xlsx(Viral, "Viral.xlsx")
write_xlsx(Viral_Infection, "Viral Infection.xlsx")
write_xlsx(Virus, "Virus.xlsx")
write_xlsx(Infection, "Infection.xlsx")

# Count the frequency of unique values in a dataframe
table(Sepsis$taxon.Name) #Count based on the model (human, mouse, rat)

```

```

# Combine and exclude datasets of other models than mouse/rat
Total_datasets = rbind(Brain_Immunology, Brain_Infection, Brain_Inflammation,
                        Corona, Cytomegalo, Encephalitis, Epstein_Barr, Hendra,
                        Herpes, Infection, Influenza, Japanese_encephalitis, Measles,
                        Neuroinflammation, Neuroinflammatory, Neuroinvasive,
                        Neurotoxicity, Neurotropic, Neurovirulence, Rabies, Sepsis,
                        Varicella, Venezuelan_encephalitis, Viral, Viral_Encephalitis,
                        Viral_Infection, Virus, West_Nile, Yellow_fever, Zika)
Total_datasets_eli_1 = subset(Total_datasets, Total_datasets$taxon.Name == "mouse")
Total_datasets_eli_2 = subset(Total_datasets, Total_datasets$taxon.Name == "rat")
Total_datasets_eli = unique(rbind(Total_datasets_eli_1, Total_datasets_eli_2))
write_xlsx(Total_datasets_eli, "Total_datasets.xlsx")

```

Through process of inclusion/exclusion criteria, 6 datasets are included in the meta-analysis, including: GSE30577, GSE42264, GSE44331, GSE51365, GSE53784, GSE91074.

### 3) Gene Expression Range Assessment

```

# Create a function to check the expression range of the dataset
# (especially for the Agilent microarray datasets)
CheckGeneExpressionRange <- function(dataset_shortcode){

  # Retrieve the processed expression data for the given dataset
  expression_data <- get_dataset_processed_expression(dataset_shortcode)

  # Print the structure of the expression data
  print(str(expression_data))

  # The first four columns are row metadata: Probe, GeneSymbol, GeneName, NCBI ID
  # The rest of the columns are gene expression values for each subject

  # Exclude metadata row (row 1-4) and convert the gene expression columns to a
  # matrix for further analysis
  expression_matrix <- as.matrix(expression_data[, -1:-4])

  # Create a histogram of the expression data
  hist(expression_matrix,
        main = paste("Histogram of Expression Data for", dataset_shortcode),
        # The y-axis is the gene frequency
        # The x-axis is log 2 gene expression - log 2 counts per million
        xlab = "Log 2 Expression", ylab = "Frequency")

  # The large spike on the left side of the histogram ("floor effect") are
  # all of the genes that are not truly expressed or have too low of expression
  # to be measurable

  # Log 2 RNA-seq dataset has the range between -5 to 12
  # Log 2 Microarray dataset has the range between 4 to 15

  # Calculate the min, median, max values of the expression data
  min_val <- min(expression_matrix)

```

```

median_val <- median(expression_matrix)
max_val <- max(expression_matrix)

# Print the calculated values
print(paste("Minimum value:", min_val))
print(paste("Median value:", median_val))
print(paste("Maximum value:", max_val))
}

```

```

# Function use
CheckGeneExpressionRange("GSE30577") # Min: -4.8 / Max: 8.6 / Agilent Microarray


```

```

## Classes 'data.table' and 'data.frame': 41252 obs. of 28 variables:
## $ Probe : chr "AT_D_3" "AT_D_5" "AT_D_M" "AT_L_3" ...
## $ GeneSymbol : chr "" "" "" "" ...
## $ GeneName : chr "" "" "" "" ...
## $ NCBIId : chr "" "" "" "" ...
## $ Rabies, Fix, Spinalcord, 7dpi(mock), 06: num 0.175 0.732 0.34 0.219 0.893 ...
## $ Rabies, Fix, Spinalcord, 7dpi(mock), 05: num -0.4457 0.0977 0.4108 0.0203 0.8468 ...
## $ Rabies, Fix, Spinalcord, 7dpi(mock), 04: num -0.845 -0.335 -0.441 0.251 -0.375 ...
## $ Rabies, Fix, Spinalcord, 7dpi(mock), 03: num 0.554 -0.353 -0.634 -0.243 -0.774 ...
## $ Rabies, Fix, Spinalcord, 7dpi(mock), 02: num 0.822 -0.283 0.209 -0.627 -0.54 ...
## $ Rabies, Fix, Spinalcord, 7dpi(mock), 01: num -0.567 0.022 0.049 -0.0055 0.0596 ...
## $ Rabies, Fix, Spinalcord, 7dpi(inf), 06 : num -0.4334 -0.0176 -0.0265 -0.1352 -0.0863 ...
## $ Rabies, Fix, Spinalcord, 7dpi(inf), 05 : num 0.541 0.809 0.94 0.77 0.838 ...
## $ Rabies, Fix, Spinalcord, 7dpi(inf), 04 : num 0.7378 -0.067 -0.0598 -0.1549 0.0719 ...
## $ Rabies, Fix, Spinalcord, 7dpi(inf), 03 : num 0.0658 0.3534 0.4016 0.7704 0.3902 ...
## $ Rabies, Fix, Spinalcord, 7dpi(inf), 02 : num 0.6398 -0.1694 -0.218 -0.0018 -0.3153 ...
## $ Rabies, Fix, Spinalcord, 7dpi(inf), 01 : num -0.6072 -0.111 -0.2676 -0.3819 -0.0674 ...
## $ Rabies, Fix, Brain, 7dpi(mock), 06 : num -0.507 -0.428 -0.427 -0.542 -0.416 ...
## $ Rabies, Fix, Brain, 7dpi(mock), 05 : num -0.85 -0.644 -0.637 -0.707 -0.68 ...
## $ Rabies, Fix, Brain, 7dpi(mock), 04 : num 0.809 0.346 0.36 0.247 1.073 ...
## $ Rabies, Fix, Brain, 7dpi(mock), 03 : num -0.149 -0.412 -0.316 -0.586 -0.552 ...
## $ Rabies, Fix, Brain, 7dpi(mock), 02 : num 0.602 0.443 0.396 0.47 0.322 ...
## $ Rabies, Fix, Brain, 7dpi(mock), 01 : num 0.195 0.761 0.764 1.686 0.698 ...
## $ Rabies, Fix, Brain, 7dpi(inf), 06 : num 0.315 0.491 0.44 0.297 0.368 ...
## $ Rabies, Fix, Brain, 7dpi(inf), 05 : num -0.262 -0.332 -0.137 -0.522 -0.49 ...
## $ Rabies, Fix, Brain, 7dpi(inf), 04 : num 0.9652 -0.1483 -0.7497 0.0347 -0.8159 ...
## $ Rabies, Fix, Brain, 7dpi(inf), 03 : num -0.0367 -0.0308 -0.1867 0.0664 -0.221 ...
## $ Rabies, Fix, Brain, 7dpi(inf), 02 : num -0.2082 0.0844 0.1173 0.0366 0.0158 ...
## $ Rabies, Fix, Brain, 7dpi(inf), 01 : num 0.7341 0.3499 0.2119 -0.0955 -0.0283 ...
## - attr(*, ".internal.selfref")=<externalptr>
## - attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/datasets/GSE30577/data/processed"
## - attr(*, "env")=<environment: 0x10d279b20>
## NULL

```

## Histogram of Expression Data for GSE30577




```
## [1] "Minimum value: -4.8043"
## [1] "Median value: -0.0612"
## [1] "Maximum value: 8.6806"
```

```
CheckGeneExpressionRange("GSE42264") # Min: 2.4 / Max: 14.6 / Affymetrix Array
```

```
## Classes 'data.table' and 'data.frame': 45101 obs. of 30 variables:
## $ Probe : chr "1415670_at" "1415671_at" "1415672_at" "1415673_at" ...
## $ GeneSymbol : chr "Copg1" "Atp6v0d1" "Golga7" "Psph" ...
## $ GeneName : chr "coatomer protein complex, subunit gamma 1" "ATPase, H+ tran
## $ NCBIid : chr "54161" "11972" "57437" "100678" ...
## $ Uninfected NT at 5 d.p.i., rep4: num 10.16 12.24 11.79 9.04 10.77 ...
## $ Uninfected NT at 5 d.p.i., rep3: num 10.25 12.2 11.69 9.03 10.67 ...
## $ Uninfected NT at 5 d.p.i., rep2: num 10.13 12.22 11.79 9.04 10.78 ...
## $ Uninfected NT at 5 d.p.i., rep1: num 10.14 12.21 11.86 9.06 10.85 ...
## $ Uninfected TG at 5 d.p.i., rep4: num 10.09 12.31 11.87 9.12 10.6 ...
## $ Uninfected TG at 5 d.p.i., rep3: num 10.23 12.26 11.78 9.04 10.59 ...
## $ Uninfected TG at 5 d.p.i., rep2: num 10.23 12.37 11.85 9.04 10.7 ...
## $ Uninfected TG at 5 d.p.i., rep1: num 10.12 12.33 11.9 9.06 10.64 ...
## $ Infected NT 10 d.p.i., rep9 : num 10.22 12.28 11.96 9.08 10.53 ...
## $ Infected NT 10 d.p.i., rep8 : num 10.28 12.3 12.05 9.08 10.54 ...
## $ Infected NT 10 d.p.i., rep7 : num 10.3 12.26 11.94 9.18 10.43 ...
## $ Infected NT 10 d.p.i., rep6 : num 10.2 12.3 12.1 9.1 10.6 ...
## $ Infected NT 10 d.p.i., rep5 : num 10.21 12.24 11.99 9.09 10.48 ...
## $ Infected NT 5 d.p.i., rep4 : num 10.21 12.18 11.81 9.08 10.7 ...
```

```
## $ Infected NT 5 d.p.i., rep3 : num 10.23 12.17 11.8 9.01 10.74 ...
## $ Infected NT 5 d.p.i., rep2 : num 10.17 12.13 11.88 9.01 10.78 ...
## $ Infected NT 5 d.p.i., rep1 : num 10.14 12.21 11.89 9.08 10.81 ...
## $ Infected TG 10 d.p.i., rep9 : num 10.24 12.29 12.07 9.07 10.47 ...
## $ Infected TG 10 d.p.i., rep8 : num 10.25 12.3 12.12 8.99 10.42 ...
## $ Infected TG 10 d.p.i., rep7 : num 10.3 12.3 12 9 10.6 ...
## $ Infected TG 10 d.p.i., rep6 : num 10.24 12.26 12.04 8.98 10.45 ...
## $ Infected TG 10 d.p.i., rep5 : num 10.28 12.33 12.04 9.04 10.49 ...
## $ Infected TG 5 d.p.i., rep4 : num 10.24 12.15 11.75 8.94 10.78 ...
## $ Infected TG 5 d.p.i., rep3 : num 10.11 12.2 11.89 9.02 10.83 ...
## $ Infected TG 5 d.p.i., rep2 : num 10.08 12.26 11.89 9.07 10.9 ...
## $ Infected TG 5 d.p.i., rep1 : num 10.16 12.22 11.87 9.06 10.84 ...
## - attr(*, ".internal.selfref")=<externalptr>
## - attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/datasets/GSE42264/data/processed"
## - attr(*, "env")=<environment: 0x12c867000>
## NULL
```

## Histogram of Expression Data for GSE42264




```
## [1] "Minimum value: 2.4635"
## [1] "Median value: 6.9608"
## [1] "Maximum value: 14.685"
```

```
CheckGeneExpressionRange("GSE44331") # Min: 2.9 / Max: 14.5 / Affymetrix Array
```

```
## Classes 'data.table' and 'data.frame': 45101 obs. of 16 variables:
## $ Probe : chr "1415670_at" "1415671_at" "1415672_at" "1415673_at"
```

```
## $ GeneSymbol      : chr "Copg1" "Atp6v0d1" "Golga7" "Psph" ...
## $ GeneName        : chr "coatomer protein complex, subunit gamma 1" "ATPase
## $ NCBIId          : chr "54161" "11972" "57437" "100678" ...
## $ KO VSV infected, biological replicate 3: num 9.1 11.98 11.74 8.74 10.1 ...
## $ KO VSV infected, biological replicate 2: num 9.14 12.07 11.76 8.69 9.99 ...
## $ KO VSV infected, biological replicate 1: num 9.06 12 11.88 8.82 9.99 ...
## $ WT VSV infected, biological replicate 3: num 9.09 12.03 11.72 8.8 10.02 ...
## $ WT VSV infected, biological replicate 2: num 9 12.1 11.75 8.77 10.07 ...
## $ WT VSV infected, biological replicate 1: num 9.08 12.06 11.79 8.74 10.09 ...
## $ KO uninfected, biological replicate 3 : num 9.13 12.07 11.84 8.77 10.04 ...
## $ KO uninfected, biological replicate 2 : num 9.13 12.03 11.89 8.8 10.01 ...
## $ KO uninfected, biological replicate 1 : num 9.19 11.98 11.94 8.77 10.03 ...
## $ WT uninfected, biological replicate 3 : num 9.07 12.07 11.79 8.74 9.99 ...
## $ WT uninfected, biological replicate 2 : num 9.12 12.06 11.87 8.83 10.22 ...
## $ WT uninfected, biological replicate 1 : num 9.09 12.09 11.86 8.7 9.79 ...
## - attr(*, ".internal.selfref")=<externalptr>
## - attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/datasets/GSE44331/data/processed"
## - attr(*, "env")=<environment: 0x12c851e00>
## NULL
```

## Histogram of Expression Data for GSE44331




```
## [1] "Minimum value: 2.9042"
## [1] "Median value: 6.5411"
## [1] "Maximum value: 14.5935"
```

```
CheckGeneExpressionRange("GSE51365") # Min: 1.2 / Max: 15.7 / Affymetrix Array
```

```
## Classes 'data.table' and 'data.frame': 45101 obs. of 32 variables:
## $ Probe : chr "1415670_at" "1415671_at" "1415672_at" "1415673_at" ...
## $ GeneSymbol : chr "Copg1" "Atp6v0d1" "Golga7" "Psph" ...
## $ GeneName : chr "coatomer protein complex, subunit gamma 1" "ATPase, H+ transporting, 1.
## $ NCBIid : chr "54161" "11972" "57437" "100678" ...
## $ BRAIN|ORF73|SC019 : num 8.97 11.98 11.31 7.92 9.46 ...
## $ BRAIN|ORF73|SC018 : num 8.78 11.95 11.33 7.97 9.39 ...
## $ BRAIN|ORF73|SC017 : num 8.86 11.96 11.36 8.11 9.5 ...
## $ BRAIN|MHV-68|SC019 : num 8.85 11.82 11.36 8.03 9.43 ...
## $ BRAIN|MHV-68|SC018 : num 8.98 12.05 11.43 8.17 9.44 ...
## $ BRAIN|MHV-68|SC017 : num 8.89 11.99 11.37 7.99 9.21 ...
## $ BRAIN|MOCK|SC019 : num 8.7 12.16 11.32 7.88 9.65 ...
## $ BRAIN|MOCK|SC018 : num 8.94 11.86 11.46 8.09 9.4 ...
## $ BRAIN|MOCK|SC017 : num 9.04 12.07 11.4 8 9.29 ...
## $ SPLEEN|ORF73|SC019 : num 8.88 10.75 11.37 7.66 9.21 ...
## $ SPLEEN|ORF73|SC3 : num 8.7 10.54 11.15 7.51 9.17 ...
## $ SPLEEN|ORF73|SC2 : num 8.62 10.45 11.08 7.53 8.99 ...
## $ SPLEEN|MHV-68|SC019 : num 8.97 10.62 11.22 7.82 9.18 ...
## $ SPLEEN|MHV-68|SC3 : num 9.12 10.75 11.34 7.78 9.17 ...
## $ SPLEEN|MHV-68|SC2 : num 8.87 10.62 11.05 7.67 8.92 ...
## $ SPLEEN|MOCK|SC019 : num 8.86 10.61 11.27 7.85 9.33 ...
## $ SPLEEN|MOCK|SC3 : num 8.72 10.61 11.28 7.48 9.12 ...
## $ SPLEEN|MOCK|SC2 : num 8.58 10.51 11 7.52 9.11 ...
## $ LIVER|ORF73|SC019 : num 9.26 10.61 10.89 7.33 9.22 ...
## $ LIVER|ORF73|SC3 : num 9.61 10.75 11.03 7.29 9.27 ...
## $ LIVER|ORF73|SC2 : num 9.41 10.88 11.05 7.41 9.33 ...
## $ LIVER|MHV-68|SC019 : num 9.31 10.62 10.91 7 9.02 ...
## $ LIVER|MHV-68|SC2 : num 9.49 10.66 11.06 7.2 9.22 ...
## $ LIVER|MHV-68|SC3 : num 9.43 10.65 11.09 7 9.08 ...
## $ LIVER|MOCK|SC019 : num 9.48 10.66 10.89 7.07 9.06 ...
## $ LIVER|MOCK|SC3 : num 9.54 10.85 10.89 7.42 9.3 ...
## $ LIVER|MOCK|SC2 : num 9.61 10.73 10.91 7.43 9.34 ...
## $ LIVER|MOCK|SC1 : num 9.43 10.75 11.01 7.21 9.17 ...
## - attr(*, ".internal.selfref")=<externalptr>
## - attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/datasets/GSE51365/data/processed"
## - attr(*, "env")=<environment: 0x10e312640>
## NULL
```



## Histogram of Expression Data for GSE51365




```
## [1] "Minimum value: 1.2468"
## [1] "Median value: 5.8355"
## [1] "Maximum value: 15.7641"
```

```
CheckGeneExpressionRange("GSE53784") # Min: 2.0 / Max: 14.1 / Affymetrix Array
```

```
## Classes 'data.table' and 'data.frame': 35556 obs. of 16 variables:
## $ Probe      : int 10338001 10338002 10338003 10338004 10338005 10338006 10338007 10338008 10338009
## $ GeneSymbol: chr "" "" "" "" ...
## $ GeneName   : chr "" "" "" "" ...
## $ NCBIId     : chr "" "" "" "" ...
## $ WNV_B8     : num 11.61 6.9 9.88 8.63 2.98 ...
## $ WNV_B7     : num 12 6.85 10.31 9.23 3.02 ...
## $ WNV_B6     : num 11.91 7.08 10.32 9.14 3 ...
## $ Mock_B6    : num 11.82 7.14 10.09 9.2 2.89 ...
## $ Mock_B5    : num 12.01 7.15 10.53 9.55 2.97 ...
## $ Mock_B4    : num 11.86 7 10.22 9.08 2.93 ...
## $ MOCK_6     : num 12.07 6.98 10.49 9.49 2.92 ...
## $ MOCK_5     : num 11.73 6.95 10.03 9.11 2.93 ...
## $ MOCK_4     : num 11.71 7.26 10.12 9.07 2.93 ...
## $ JEV_3      : num 11.77 7.3 10.18 8.79 2.93 ...
## $ JEV_2      : num 11.92 7.23 10.24 9.16 2.97 ...
## $ JEV_1      : num 11.9 7.41 10.4 9.05 2.93 ...
## - attr(*, ".internal.selfref")=<externalptr>
## - attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/datasets/GSE53784/data/processed"
```

```
## - attr(*, "env")=<environment: 0x12bdb3b20>
## NULL
```




```
## [1] "Minimum value: 2.0069"
## [1] "Median value: 6.7054"
## [1] "Maximum value: 14.1214"
```

```
CheckGeneExpressionRange("GSE91074") # Min: 2.8 | Max: 14.3 | Affymetrix Array
```

```
## Classes 'data.table' and 'data.frame': 22690 obs. of 19 variables:
## $ Probe : chr "1415670_at" "1415671_at" "1415672_at" ...
## $ GeneSymbol : chr "Copg1" "Atp6v0d1" "Golga7" "Psph" ...
## $ GeneName : chr "coatamer protein complex, subunit gamma" ...
## $ NCBIId : chr "54161" "11972" "57437" "100678" ...
## $ C57BL6/J mouse mock)-infected, biological rep2 : num 9.41 11.35 11.55 8 9.25 ...
## $ C57BL6/J mouse mock)-infected, biological rep1 : num 9.43 11.46 11.65 8.07 9.11 ...
## $ C57BL6/J mouse VEEV (TC83)-infected, biological rep3 : num 9.34 11.09 11.3 7.9 9.04 ...
## $ C57BL6/J mouse VEEV (TC83)-infected, biological rep2 : num 9.34 11.06 11.45 7.9 9.06 ...
## $ C57BL6/J mouse VEEV (TC83)-infected, biological rep1 : num 9.27 11 11.34 8.04 9.18 ...
## $ ??-TCR -/- mouse mock-infected, biological rep2 : num 9.21 11.18 11.54 8.07 9.3 ...
## $ ??-TCR -/- mouse mock-infected, biological rep1 : num 9.12 11.3 11.48 8.17 9.08 ...
## $ ??-TCR -/- mouse VEEV (TC83)-infected, biological rep3 : num 8.96 10.96 11.44 7.89 8.94 ...
## $ ??-TCR -/- mouse VEEV (TC83)-infected, biological rep2 : num 9.44 11.11 11.57 7.74 9.17 ...
## $ ??-TCR -/- mouse VEEV (TC83)-infected, biological rep1 : num 9.2 11.18 11.27 7.92 9.05 ...
## $ C3H/HeN mouse mock-infected, biological rep2 : num 9.2 11.32 11.48 8.07 9.05 ...
```

```
## $ C3H/HeN mouse mock-infected, biological rep1 : num 9.32 11.45 11.63 8.14 9.04 ...
## $ C3H/HeN mouse VEEV (TC83)-infected, biological rep3 : num 9.54 11.22 11.48 7.85 9.27 ...
## $ C3H/HeN mouse VEEV (TC83)-infected, biological rep2 : num 9.28 11.13 11.43 7.72 9.08 ...
## $ C3H/HeN mouse VEEV (TC83)-infected, biological rep1 : num 9.15 11.16 11.48 7.79 9.01 ...
## - attr(*, ".internal.selfref")=<externalptr>
## - attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/datasets/GSE91074/data/processed"
## - attr(*, "env")=<environment: 0x12bdc8028>
## NULL
```

## Histogram of Expression Data for GSE91074



```
## [1] "Minimum value: 2.8577"
## [1] "Median value: 7.4844"
## [1] "Maximum value: 14.3048"
```

Gene expression of all 6 datasets seem to be within normal range and have appropriate distribution.

### 4) Extraction of Statistical Contrasts of Differential Analysis in Each Dataset

For the meta-analysis, we will be extracting the differential expression results from Gemma. The differential expression results for each dataset may include multiple result sets (e.g., one result set for the subset of the data from the hippocampus, one result set for frontal cortex). Each of these result sets may have multiple statistical contrasts (e.g., drug1 vs. vehicle, drug2 vs. vehicle). Therefore, each of the statistical contrasts is labeled with a result ID and contrast ID within the Gemma database. We will need to know which of these IDs are relevant to our project goals to easily extract their results.

We will also need to double-check that these statistical contrasts are set up in a manner that makes sense for our experiments:

1. For experiments that include more than one brain region, we will need to double-check that the results have been subsetted by brain region (instead of including brain region ("OrganismPart") as a factor in the model). If they have not been subsetted by region, we will probably need to re-run the differential expression analysis.
2. Depending on the goals of the meta-analysis, we may also need to re-run the differential expression analysis to remove other unwanted subjects (e.g., removing subjects with genotypes that might interfere with our results).
3. We will need to double-check that the comparisons include an appropriate reference group - sometimes they are reversed in Gemma (e.g., having the drug treatment set as the baseline, with vehicle as the manipulation). If this is the case, we will need to invert the effects when we input them into our meta-analysis (multiply the effects by -1).

```
# Create a function to extract statistical contrasts of differential analysis
# in each dataset
GettingResultSetInfoForDatasets <- function(ExperimentIDs) {

  # Create a dataframe to store the results
  resultsets_toscreen <- data.frame(
    ExperimentIDs = character(),
    ResultSetIDs = character(),
    ContrastIDs = character(),
    FactorCategory = character(),
    ExperimentalFactors = character(),
    BaselineFactors = character(),
    Subsetted = logical(),
    SubsetBy = character(),
    stringsAsFactors = FALSE
  )

  # Loop through each of the datasets
  for (i in c(1:length(ExperimentIDs))) {

    # Extract the differential expression analysis from the datasets
    design <- get_dataset_differential_expression_analyses(ExperimentIDs[i])

    # Check if the design dataframe has rows
    if (nrow(design) > 0) {

      # Create the vectors to store the experimental and baseline factors
      experimental_factors <- vector(mode = "character", length = nrow(design))
      baseline_factors <- vector(mode = "character", length = nrow(design))

      # Loop through each result.ID in the design dataframe
      for (j in c(1:nrow(design))) {

        # Concatenate the experimental factors into a single string
        experimental_factors[j] <- paste(design$experimental.factors[[j]]$summary,
                                          collapse = ";")

        # Concatenate the baseline factors into a single string
        baseline_factors[j] <- paste(design$baseline.factors[[j]]$summary,
                                     collapse = ";")
      }
    }
  }
}
```

```

# Create a vector to store subset information
SubsetBy <- vector(mode = "character", length = nrow(design))

# Check if the design dataframe is subsetted or not
if (design$isSubset[1] == TRUE) {

  # Loop through each result.ID to extract and concatenate subset information
  for (j in c(1:nrow(design))) {
    SubsetBy[j] <- paste(design$subsetFactor[[j]]$summary, collapse = ";")
  }
} else {
  # If not subsetted, fill the SubsetBy vector with NA values
  SubsetBy <- rep(NA, length(design$result.ID))
}

# Create a temporary dataframe to store extracted info
resultsets_for_experiment <- data.frame(
  ExperimentIDs = ExperimentIDs[i],
  ResultSetIDs = design$result.ID,
  ContrastIDs = design$contrast.ID,
  FactorCategory = design$factor.category,
  ExperimentalFactors = experimental_factors,
  BaselineFactors = baseline_factors,
  Subsetted = design$isSubset,
  SubsetBy = SubsetBy,
  stringsAsFactors = FALSE
)

# Append the temporary dataframe with the dataframe created initially
resultsets_toscreen <- rbind(resultsets_toscreen, resultsets_for_experiment)
}
}

# Add empty columns to store screening notes
resultsets_toscreen <- cbind(
  resultsets_toscreen,
  Include = vector(mode = "character", length = nrow(resultsets_toscreen)),
  WrongBaseline = vector(mode = "character", length = nrow(resultsets_toscreen)),
  ResultsNotRegionSpecific = vector(mode = "character", length = nrow(resultsets_toscreen)),
  ReAnalyze = vector(mode = "character", length = nrow(resultsets_toscreen)),
  stringsAsFactors = FALSE
)

# Export the final dataframe into the working directory
write.csv(resultsets_toscreen, "ResultSets_toScreen.csv")

# Print a message to indicate that the results have been saved
print("Output object: ResultSets_toScreen.csv")
}

# Set up a vector of the names of all datasets
ExperimentIDs <- c("GSE30577", "GSE42264", "GSE44331",

```

```

        "GSE51365", "GSE53784", "GSE91074")

# Function use
GettingResultSetInfoForDatasets(ExperimentIDs)

```

```
## [1] "Output object: ResultSets_toScreen.csv"
```

## 5) Downloading the DE Results from Each Dataset

```

# Create a function to download DE results and extract Log2FC and T-statistics
# for contrasts of interest
DownloadingDEResults <- function(ResultSets_contrasts){

  # Identify the unique ResultSet IDs
  # Some ResultSets may have multiple statistical contrasts, but we only want unique ResultSet IDs
  UniqueResultSetIDs <- unique(ResultSets_contrasts$ResultSetIDs)

  # Print the identified unique ResultSet IDs
  print("ResultSets identified as being of interest")
  print(UniqueResultSetIDs)

  # Download DE results for each unique ResultSet ID
  differentials <- UniqueResultSetIDs %>%
    # The function returns a list because single experiment may have multiple
    # resultSets
    # Only take the first element of the output
    # The "resultSet" argument is used to directly access the results we need
    lapply(function(x) {get_differential_expression_values(resultSet = x)[[1]]})

  # Some datasets might not have all the advertised DE results due to a variety of
  # so we need to remove empty differential (only keep differential with rows present)
  non_missing_contrasts <- sapply(differentials, function(df) nrow(df) > 0)

  # Return the "differentials" object that contains the DE results of contrast of interest
  differentials <- differentials[non_missing_contrasts]
  UniqueResultSetIDs <- UniqueResultSetIDs[non_missing_contrasts]

  # Print the ResultSet IDs that had DE results
  print("ResultSets that had DE results:")
  print(UniqueResultSetIDs)

  # Print a message to inform the structure of the output "differentials"
  print("Your DE results for each of the ResultSets are stored in object differentials.")
  print("This object is structured as a list of dataframes.")
  print("Each element in the list represents a ResultSet, with the dataframe containing DE results")

  # Extract the effect sizes of Log2FC of contrasts of interest
  print("Columns of effect sizes (Log2FC) for contrasts of interest:")
  Contrasts_Log2FC <- paste("contrast_", ResultSets_contrasts$ContrastIDs,
                           "_log2fc", sep = "")
  print(Contrasts_Log2FC)

```

```

# Extract the T-statistics of contrasts of interest for calculating sampling variances
print("Columns of T-statistics for contrasts of interest:")
Contrasts_Tstat <- paste("contrast_", ResultSets_contrasts$ContrastIDs,
                        "_tstat", sep = "")
print(Contrasts_Tstat)

# Remove the temporary Log2FC and T-statistics of contrast of interest
rm(Contrasts_Log2FC, Contrasts_Tstat)
}

```

```

# Import the CSV file with contrasts of interest
ResultSets_contrasts <- read.csv("ResultSets_Screened.csv",
                                header = TRUE, stringsAsFactors = FALSE)

# Function use
DownloadingDEResults(ResultSets_contrasts)

```

```

## [1] "ResultSets identified as being of interest"
## [1] 535864 513873 546199 466082 522293 523663
## [1] "ResultSets that had DE results:"
## [1] 535864 513873 546199 466082 522293 523663
## [1] "Your DE results for each of the ResultSets are stored in object differentials."
## [1] "This object is structured as a list of dataframes."
## [1] "Each element in the list represents a ResultSet, with the dataframe containing DE results"
## [1] "Columns of effect sizes (Log2FC) for contrasts of interest:"
## [1] "contrast_84556_log2fc" "contrast_89756_log2fc" "contrast_97695_log2fc"
## [4] "contrast_99431_log2fc" "contrast_99432_log2fc" "contrast_140573_log2fc"
## [7] "contrast_140572_log2fc" "contrast_142941_log2fc"
## [1] "Columns of T-statistics for contrasts of interest:"
## [1] "contrast_84556_tstat" "contrast_89756_tstat" "contrast_97695_tstat"
## [4] "contrast_99431_tstat" "contrast_99432_tstat" "contrast_140573_tstat"
## [7] "contrast_140572_tstat" "contrast_142941_tstat"

```

```

# Check the structure of the "differentials" object
str(differentials)

```

```

## List of 6
## $ :Classes 'data.table' and 'data.frame': 22883 obs. of 11 variables:
## ..$ Probe : chr [1:22883] "A_51_P109508" "A_52_P185343" "A_52_P212756" "A_51_P
## ..$ NCBIid : chr [1:22883] "171285" "14674" "240832" "14990" ...
## ..$ GeneSymbol : chr [1:22883] "Havcr2" "Gna13" "Tor1aip2" "H2-M2" ...
## ..$ GeneName : chr [1:22883] "hepatitis A virus cellular receptor 2" "guanine nuc
## ..$ pvalue : num [1:22883] 6.67e-12 4.11e-11 2.09e-11 2.18e-10 7.72e-11 ...
## ..$ corrected_pvalue : num [1:22883] 2.28e-07 3.51e-07 3.51e-07 4.37e-07 4.37e-07 ...
## ..$ rank : num [1:22883] 2.93e-05 1.00e-04 5.86e-05 4.00e-04 1.00e-04 ...
## ..$ contrast_84556_coefficient: num [1:22883] 4.96 6.96 3.53 5.19 5.27 ...
## ..$ contrast_84556_log2fc : num [1:22883] 4.96 6.96 3.53 5.19 5.27 ...
## ..$ contrast_84556_tstat : num [1:22883] 8.91 11.63 7.13 9.77 9.96 ...
## ..$ contrast_84556_pvalue : num [1:22883] 1.14e-08 1.70e-10 4.25e-07 3.60e-09 2.58e-09 ...
## ..- attr(*, ".internal.selfref")=<externalptr>
## ..- attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/resultSets/535864"
## ..- attr(*, "env")=<environment: 0x10b2090f8>
## $ :Classes 'data.table' and 'data.frame': 30863 obs. of 11 variables:

```

```

## ..$ Probe : chr [1:30863] "1424921_at" "1451564_at" "1451777_at" "1435906_x_at"
## ..$ NCBIId : chr [1:30863] "69550" "547253" "234311" "14469" ...
## ..$ GeneSymbol : chr [1:30863] "Bst2" "Parp14" "Ddx60" "Gbp2" ...
## ..$ GeneName : chr [1:30863] "bone marrow stromal cell antigen 2" "poly (ADP-ribose)"
## ..$ pvalue : num [1:30863] 0 0 0 0 0 0 0 0 0 0 ...
## ..$ corrected_pvalue : num [1:30863] 0 0 0 0 0 0 0 0 0 0 ...
## ..$ rank : num [1:30863] 7e-04 7e-04 7e-04 7e-04 7e-04 7e-04 7e-04 7e-04 7e-04
## ..$ contrast_89756_coefficient: num [1:30863] 2.24 1.32 2.35 2.14 1.74 ...
## ..$ contrast_89756_log2fc : num [1:30863] 2.24 1.32 2.35 2.14 1.74 ...
## ..$ contrast_89756_tstat : num [1:30863] 12.01 8.9 12.97 9.51 9.34 ...
## ..$ contrast_89756_pvalue : num [1:30863] 3.67e-12 2.13e-09 6.51e-13 5.48e-10 8.08e-10 ...
## ..- attr(*, ".internal.selfref")=<externalptr>
## ..- attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/resultSets/513873"
## ..- attr(*, "env")=<environment: 0x119a93ed0>
## $ :Classes 'data.table' and 'data.frame': 30868 obs. of 11 variables:
## ..$ Probe : chr [1:30868] "1418930_at" "1453196_a_at" "1450291_s_at" "1418191_s_at"
## ..$ NCBIId : chr [1:30868] "15945" "23962" "64380" "24110" ...
## ..$ GeneSymbol : chr [1:30868] "Cxc110" "Oas12" "Ms4a4c" "Usp18" ...
## ..$ GeneName : chr [1:30868] "C-X-C motif chemokine ligand 10" "2'-5' oligoadenylate synthetase"
## ..$ pvalue : num [1:30868] 8.55e-15 3.56e-14 1.44e-13 8.20e-13 6.62e-13 ...
## ..$ corrected_pvalue : num [1:30868] 3.85e-10 8.03e-10 2.17e-09 7.39e-09 7.39e-09 ...
## ..$ rank : num [1:30868] 2.22e-05 4.44e-05 6.66e-05 1.00e-04 8.88e-05 ...
## ..$ contrast_97695_coefficient: num [1:30868] 4.78 3.26 3.89 3.76 3.28 ...
## ..$ contrast_97695_log2fc : num [1:30868] 4.78 3.26 3.89 3.76 3.28 ...
## ..$ contrast_97695_tstat : num [1:30868] 34.7 30.1 32.6 24.3 26 ...
## ..$ contrast_97695_pvalue : num [1:30868] 6.64e-14 3.90e-13 1.43e-13 5.67e-12 2.37e-12 ...
## ..- attr(*, ".internal.selfref")=<externalptr>
## ..- attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/resultSets/546199"
## ..- attr(*, "env")=<environment: 0x10e2897e8>
## $ :Classes 'data.table' and 'data.frame': 30890 obs. of 15 variables:
## ..$ Probe : chr [1:30890] "1434372_at" "1452428_a_at" "1418240_at" "1425156_at"
## ..$ NCBIId : chr [1:30890] "107350" "12010" "14469" "229900" ...
## ..$ GeneSymbol : chr [1:30890] "AW112010" "B2m" "Gbp2" "Gbp7" ...
## ..$ GeneName : chr [1:30890] "expressed sequence AW112010" "beta-2 microglobulin"
## ..$ pvalue : num [1:30890] 9.10e-07 3.19e-05 1.72e-05 7.98e-05 6.93e-05 ...
## ..$ corrected_pvalue : num [1:30890] 0.041 0.205 0.205 0.299 0.299 ...
## ..$ rank : num [1:30890] 2.22e-05 2.00e-04 6.65e-05 3.00e-04 2.00e-04 ...
## ..$ contrast_99431_coefficient: num [1:30890] 1.069 0.861 1.85 0.938 1.449 ...
## ..$ contrast_99431_log2fc : num [1:30890] 1.069 0.861 1.85 0.938 1.449 ...
## ..$ contrast_99431_tstat : num [1:30890] 19.7 12.9 13.4 10.2 10 ...
## ..$ contrast_99431_pvalue : num [1:30890] 1.11e-06 1.33e-05 1.07e-05 5.32e-05 5.67e-05 ...
## ..$ contrast_99432_coefficient: num [1:30890] -0.1711 0.1945 0.1047 0.0282 -0.0596 ...
## ..$ contrast_99432_log2fc : num [1:30890] -0.1711 0.1945 0.1047 0.0282 -0.0596 ...
## ..$ contrast_99432_tstat : num [1:30890] -3.152 2.915 0.758 0.305 -0.413 ...
## ..$ contrast_99432_pvalue : num [1:30890] 0.0198 0.0268 0.4774 0.7707 0.6941 ...
## ..- attr(*, ".internal.selfref")=<externalptr>
## ..- attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/resultSets/466082"
## ..- attr(*, "env")=<environment: 0x10e1903c8>
## $ :Classes 'data.table' and 'data.frame': 21982 obs. of 15 variables:
## ..$ Probe : int [1:21982] 10462613 10420488 10389207 10496592 10399710 10444207
## ..$ NCBIId : chr [1:21982] "15958" "219132" "20304" "14469" ...
## ..$ GeneSymbol : chr [1:21982] "Ifit2" "Phf11d" "Cc15" "Gbp2" ...
## ..$ GeneName : chr [1:21982] "interferon-induced protein with tetratricopeptide repeat"
## ..$ pvalue : num [1:21982] 0 0 0 0 0 ...

```



```
## ..$ corrected_pvalue      : num [1:21982] 0 0 0 0 0 ...
## ..$ rank                  : num [1:21982] 1e-04 1e-04 1e-04 1e-04 1e-04 3e-04 3e-04 3e-04 3e-04
## ..$ contrast_140572_coefficient: num [1:21982] 5.01 4.71 5.57 5.32 4.91 ...
## ..$ contrast_140572_log2fc   : num [1:21982] 5.01 4.71 5.57 5.32 4.91 ...
## ..$ contrast_140572_tstat   : num [1:21982] 87 68.3 67.3 71.6 66.8 ...
## ..$ contrast_140572_pvalue  : num [1:21982] 0 0 0 0 0 ...
## ..$ contrast_140573_coefficient: num [1:21982] 4.85 4.02 5.53 5.3 5.03 ...
## ..$ contrast_140573_log2fc   : num [1:21982] 4.85 4.02 5.53 5.3 5.03 ...
## ..$ contrast_140573_tstat   : num [1:21982] 84.2 58.3 66.8 71.3 68.4 ...
## ..$ contrast_140573_pvalue  : num [1:21982] 0.00 4.44e-16 0.00 0.00 0.00 ...
## ..- attr(*, ".internal.selfref")=<externalptr>
## ..- attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/resultSets/522293"
## ..- attr(*, "env")=<environment: 0x10e190eb8>
## $ :Classes 'data.table' and 'data.frame': 19466 obs. of 11 variables:
## ..$ Probe                  : chr [1:19466] "1451777_at" "1418293_at" "1419282_at" "1418825_at"
## ..$ NCBId                  : chr [1:19466] "234311" "15958" "20293" "15944" ...
## ..$ GeneSymbol             : chr [1:19466] "Ddx60" "Ifit2" "Ccl12" "Irgm1" ...
## ..$ GeneName                : chr [1:19466] "DEXD/H box helicase 60" "interferon-induced protein
## ..$ pvalue                  : num [1:19466] 0 0 0 0 0 0 0 0 0 ...
## ..$ corrected_pvalue       : num [1:19466] 0 0 0 0 0 0 0 0 0 ...
## ..$ rank                    : num [1:19466] 0.0015 0.0015 0.0015 0.0015 0.0015 0.0015 0.0015 0.0015 0.
## ..$ contrast_142941_coefficient: num [1:19466] 4.85 5.86 5.61 4.39 5.08 ...
## ..$ contrast_142941_log2fc   : num [1:19466] 4.85 5.86 5.61 4.39 5.08 ...
## ..$ contrast_142941_tstat   : num [1:19466] 51.5 86.3 56.7 62.5 55.7 ...
## ..$ contrast_142941_pvalue  : num [1:19466] 0 0 0 0 0 0 0 0 0 ...
## ..- attr(*, ".internal.selfref")=<externalptr>
## ..- attr(*, "call")= chr "https://gemma.msl.ubc.ca/rest/v2/resultSets/523663"
## ..- attr(*, "env")=<environment: 0x10e170550>
```

```
# Create a function to save DE results for each ResultSet
SavingGemmaDEResults_forEachResultSet <- function(differentials,
                                                    UniqueResultSetIDs,
                                                    ResultSets_contrasts){

  # Loop through each dataset (list element) in "differentials" object
  for (i in c(1:length(differentials))){

    # Get the current ResultSet ID
    ThisResultSet <- UniqueResultSetIDs[i]

    # Get the dataset ID corresponding to the current ResultSet ID
    # Some datasets have multiple ResultSets, so take the dataset ID from the
    # first matching entry
    ThisDataSet <- ResultSets_contrasts$ExperimentID[ResultSets_contrasts$ResultSetIDs == ThisResultSet]

    # Export the DE results for the current ResultSet ID into the working directory
    write.csv(differentials[[i]], paste("DEResults_", ThisDataSet, "_", ThisResultSet, ".csv", sep=""))

    # Remove the temporary IDs
    rm(ThisDataSet, ThisResultSet)
  }

  # Print a message to indicate the DE results have been exported into working directory
  print("Output object: DEResults_Dataset ID_ResultSet ID")
}
```

```
}
```

```
# Function use
SavingGemmaDEResults_forEachResultSet(differentials,
                                       UniqueResultSetIDs,
                                       ResultSets_contrasts)
```

```
## [1] "Output object: DEResults_Dataset ID_ResultSet ID"
```

## 6) Filter of DE results for rows with good gene annotation

```
# Create a function to filter for rows with good gene annotation
FilteringDEResults_GoodAnnotation <- function(DE_Results){

  # Print the total number of rows in the DE results
  print("# of rows in results")
  print(nrow(DE_Results))

  # Print the number of rows with missing NCBI annotation
  print("# of rows with missing NCBI annotation:")
  print(sum(DE_Results$NCBIid == "" | DE_Results$NCBIid == "null", na.rm = TRUE))

  # Print the number of rows with NA NCBI annotation
  print("# of rows with NA NCBI annotation:")
  print(sum(is.na(DE_Results$NCBIid)))

  # Print the number of rows with missing Gene Symbol annotation
  print("# of rows with missing Gene Symbol annotation:")
  print(sum(DE_Results$GeneSymbol == "" | DE_Results$GeneSymbol == "null", na.rm = TRUE))

  # Print the number of rows mapped to multiple NCBI IDs
  print("# of rows mapped to multiple NCBI IDs:")
  print(length(grep('\\|', DE_Results$NCBIid)))

  # Print the number of rows mapped to multiple Gene Symbols
  print("# of rows mapped to multiple Gene Symbols:")
  print(length(grep('\\|', DE_Results$GeneSymbol)))

  # Subset data containing rows with valid NCBI EntrezID (non-empty and non-null)
  DE_Results_NoNA <- DE_Results[(DE_Results$NCBIid == "" |
                                DE_Results$NCBIid == "null") == FALSE &
                                is.na(DE_Results$NCBIid) == FALSE,]

  # Subset data annotated with a single gene (not ambiguously mapped to more
# than one gene)
  if(length(grep('\\|', DE_Results_NoNA$NCBIid)) == 0){
    # If there are no rows with multiple NCBI IDs, use the current subset
    DE_Results_GoodAnnotation <- DE_Results_NoNA
  } else {
    # Extract only rows annotated with a single Gene Symbol (no pipe character '|')
    DE_Results_GoodAnnotation <- DE_Results_NoNA[-(grep('\\|', DE_Results_NoNA$NCBIid)),]
```

```

}

# Print the number of rows with good annotation
print("# of rows with good annotation")
print(nrow(DE_Results_GoodAnnotation))

# Get the name of the input object as a string for file naming
ID <- deparse(substitute(DE_Results))

# Export the DE results with good annotations into the working directory
write.csv(DE_Results_GoodAnnotation, paste(ID, "_GoodAnnotation.csv", sep = ""))

# Remove the temporary DE result objects
rm(DE_Results_NoNA, DE_Results)

# Print a message to the DE results with good annotations have been exported
# into working directory
print(paste("Output object:", ID, "_GoodAnnotation.csv", sep = ""))

# Return the DE results with good annotation into the environment
return(DE_Results_GoodAnnotation)
}

# Separate the DE results from object "differentials"
DEResults_GSE30577 <- differentials[[1]]
DEResults_GSE42264 <- differentials[[2]]
DEResults_GSE44331 <- differentials[[3]]
DEResults_GSE51365 <- differentials[[4]]
DEResults_GSE53784 <- differentials[[5]]
DEResults_GSE91074 <- differentials[[6]]

# Function use
DE_Results_GSE30577_GoodAnnotation <- FilteringDEResults_GoodAnnotation(DEResults_GSE30577)

## [1] "# of rows in results"
## [1] 22883
## [1] "# of rows with missing NCBI annotation:"
## [1] 0
## [1] "# of rows with NA NCBI annotation:"
## [1] 0
## [1] "# of rows with missing Gene Symbol annotation:"
## [1] 0
## [1] "# of rows mapped to multiple NCBI IDs:"
## [1] 0
## [1] "# of rows mapped to multiple Gene Symbols:"
## [1] 0
## [1] "# of rows with good annotation"
## [1] 22883
## [1] "Output object:DEResults_GSE30577_GoodAnnotation.csv"

DE_Results_GSE42264_GoodAnnotation <- FilteringDEResults_GoodAnnotation(DEResults_GSE42264)

## [1] "# of rows in results"

```

```
## [1] 30863
## [1] "# of rows with missing NCBI annotation:"
## [1] 0
## [1] "# of rows with NA NCBI annotation:"
## [1] 0
## [1] "# of rows with missing Gene Symbol annotation:"
## [1] 0
## [1] "# of rows mapped to multiple NCBI IDs:"
## [1] 0
## [1] "# of rows mapped to multiple Gene Symbols:"
## [1] 0
## [1] "# of rows with good annotation"
## [1] 30863
## [1] "Output object:DEResults_GSE42264_GoodAnnotation.csv"
```

```
DE_Results_GSE44331_GoodAnnotation <- FilteringDEResults_GoodAnnotation(DEResults_GSE44331)
```

```
## [1] "# of rows in results"
## [1] 30868
## [1] "# of rows with missing NCBI annotation:"
## [1] 0
## [1] "# of rows with NA NCBI annotation:"
## [1] 0
## [1] "# of rows with missing Gene Symbol annotation:"
## [1] 0
## [1] "# of rows mapped to multiple NCBI IDs:"
## [1] 0
## [1] "# of rows mapped to multiple Gene Symbols:"
## [1] 0
## [1] "# of rows with good annotation"
## [1] 30868
## [1] "Output object:DEResults_GSE44331_GoodAnnotation.csv"
```

```
DE_Results_GSE51365_GoodAnnotation <- FilteringDEResults_GoodAnnotation(DEResults_GSE51365)
```

```
## [1] "# of rows in results"
## [1] 30890
## [1] "# of rows with missing NCBI annotation:"
## [1] 0
## [1] "# of rows with NA NCBI annotation:"
## [1] 0
## [1] "# of rows with missing Gene Symbol annotation:"
## [1] 0
## [1] "# of rows mapped to multiple NCBI IDs:"
## [1] 0
## [1] "# of rows mapped to multiple Gene Symbols:"
## [1] 0
## [1] "# of rows with good annotation"
## [1] 30890
## [1] "Output object:DEResults_GSE51365_GoodAnnotation.csv"
```

```
DE_Results_GSE53784_GoodAnnotation <- FilteringDEResults_GoodAnnotation(DEResults_GSE53784)
```

```
## [1] "# of rows in results"
## [1] 21982
## [1] "# of rows with missing NCBI annotation:"
## [1] 0
## [1] "# of rows with NA NCBI annotation:"
## [1] 0
## [1] "# of rows with missing Gene Symbol annotation:"
## [1] 0
## [1] "# of rows mapped to multiple NCBI IDs:"
## [1] 0
## [1] "# of rows mapped to multiple Gene Symbols:"
## [1] 0
## [1] "# of rows with good annotation"
## [1] 21982
## [1] "Output object:DEResults_GSE53784_GoodAnnotation.csv"
```

```
DE_Results_GSE91074_GoodAnnotation <- FilteringDEResults_GoodAnnotation(DEResults_GSE91074)
```

```
## [1] "# of rows in results"
## [1] 19466
## [1] "# of rows with missing NCBI annotation:"
## [1] 0
## [1] "# of rows with NA NCBI annotation:"
## [1] 0
## [1] "# of rows with missing Gene Symbol annotation:"
## [1] 0
## [1] "# of rows mapped to multiple NCBI IDs:"
## [1] 0
## [1] "# of rows mapped to multiple Gene Symbols:"
## [1] 0
## [1] "# of rows with good annotation"
## [1] 19466
## [1] "Output object:DEResults_GSE91074_GoodAnnotation.csv"
```

```
# Check the structure of the DE results with good annotations
# str(DE_Results_GSE30577_GoodAnnotation)
# str(DE_Results_GSE42264_GoodAnnotation)
# str(DE_Results_GSE44331_GoodAnnotation)
# str(DE_Results_GSE51365_GoodAnnotation)
# str(DE_Results_GSE53784_GoodAnnotation)
# str(DE_Results_GSE91074_GoodAnnotation)
```

## 7) Extraction of DE results for the contrasts of interest

```
# Create a function to extract the contrast ID from FC column names
GetContrastIDsforResultSet <- function(NamesOfFoldChangeColumns){

  # Split the column names using the underscore as a delimiter
```

```

# The result is a list where each element is a vector of the split parts of
# each column name
ColumnNames_BrokenUp <- strsplit(NamesOfFoldChangeColumns, "_")

# Convert the list of split names to a matrix
MatrixOfColumnNames_BrokenUp <- do.call(rbind, ColumnNames_BrokenUp)

# Extract the contrast IDs in the second column
ContrastIDs_inCurrentDF <- MatrixOfColumnNames_BrokenUp[, 2]

# Return the extracted contrast ID
return(ContrastIDs_inCurrentDF)
}

# Create a function to extract DE results for contrasts of interest
ExtractingDEResultsForContrasts <- function(DE_Results_GoodAnnotation,
                                             Contrasts_Log2FC,
                                             Contrasts_Tstat,
                                             ResultSet_contrasts){

  # Print the column names in the DE results with good annotations for the
  # current ResultSet
  print("Columns in the DE results for the current ResultSet:")
  print(colnames(DE_Results_GoodAnnotation))

  # Print the column names that correspond to Log2FC values for contrasts of interest
  print("Columns of Log2FC for contrasts of interest within the DE results for the current ResultSet:")
  NamesOfFoldChangeColumns <- colnames(DE_Results_GoodAnnotation)[colnames(DE_Results_GoodAnnotation) %in%
  print(NamesOfFoldChangeColumns)

  # Print the column names that correspond to T-statistics values for contrasts of interest
  print("Columns of T-statistics for contrasts of interest within the DE results for the current ResultSet:")
  NamesOfTstatColumns <- colnames(DE_Results_GoodAnnotation)[colnames(DE_Results_GoodAnnotation) %in%
  print(NamesOfTstatColumns)

  # Extract contrast IDs from FC column names using the function "GetContrastIDsforResultSet"
  ContrastIDs_inCurrentDF <- GetContrastIDsforResultSet(NamesOfFoldChangeColumns)
  print("Contrast IDs for contrasts of interest within the current ResultSet:")
  print(ContrastIDs_inCurrentDF)

  # Extract dataset IDs for contrasts of interest
  DatasetIDs <- ResultSet_contrasts$ExperimentID[ResultSet_contrasts$ContrastIDs %in% ContrastIDs_inCurrentDF]
  print("Dataset ID for the ResultSet and contrasts:")
  print(DatasetIDs)

  # Extract experimental factors for contrasts of interest
  Factors_inCurrentDF <- ResultSet_contrasts$ExperimentalFactors[ResultSet_contrasts$ContrastIDs %in% ContrastIDs_inCurrentDF]
  print("Experimental factors for ResultSet and contrasts:")
  print(Factors_inCurrentDF)

  # Combine dataset IDs and experimental factors to create unique identifiers
  # for each statistical comparison
  ComparisonsOfInterest <- paste(DatasetIDs, Factors_inCurrentDF, sep = "_")

```

```

print("Current names of contrasts of interest")
print(ComparisonsOfInterest)

# Create a list to store extracted DE results and relevant metadata
DE_result_contrast <- list(
  All_Columns = colnames(DE_Results_GoodAnnotation),
  NamesOfFoldChangeColumns = NamesOfFoldChangeColumns,
  NamesOfTstatColumns = NamesOfTstatColumns,
  Contrast_ID = ContrastIDs_inCurrentDF,
  Dataset_ID = DatasetIDs,
  Experimental_Factor = Factors_inCurrentDF,
  ComparisonsOfInterest = ComparisonsOfInterest
)

# Return the list of all extracted info
return(DE_result_contrast)
}

# Create a function to extract the Log2FC and T-statistics of contrast of interest
GetContrastStatColumns <- function(ResultSets_contrasts){

  # Extract the effect sizes (Log2FC) of contrasts of interest
  Contrasts_Log2FC <- paste("contrast_", ResultSets_contrasts$ContrastIDs, "_log2fc", sep = "")

  # Extract the T-statistics of contrasts of interest for calculating sampling variances
  Contrasts_Tstat <- paste("contrast_", ResultSets_contrasts$ContrastIDs, "_tstat", sep = "")

  # Create a dataframe to store the extracted information
  Contrasts_Stat <- data.frame(
    ExperimentID = ResultSets_contrasts$ExperimentIDs,
    ContrastID = ResultSets_contrasts$ContrastIDs,
    Log2FC_Column = Contrasts_Log2FC,
    Tstat_Column = Contrasts_Tstat,
    stringsAsFactors = FALSE
  )

  # Return the resulting dataframe
  return(Contrasts_Stat)
}

# Function use
Contrasts_Stat_Columns <- GetContrastStatColumns(ResultSets_contrasts)

# Prepare "Contrast_Log2FC" and "Contrast_Tstat" arguments for extracting DE results
# of contrasts of interest

# GSE30577
Contrasts_Log2FC_GSE30577 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE30577") %>%
  pull(Log2FC_Column)

Contrasts_Tstat_GSE30577 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE30577") %>%
  pull(Tstat_Column)

```

```

# GSE42264
Contrasts_Log2FC_GSE42264 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE42264") %>%
  pull(Log2FC_Column)

Contrasts_Tstat_GSE42264 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE42264") %>%
  pull(Tstat_Column)

# GSE44331
Contrasts_Log2FC_GSE44331 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE44331") %>%
  pull(Log2FC_Column)

Contrasts_Tstat_GSE44331 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE44331") %>%
  pull(Tstat_Column)

# GSE51365
Contrasts_Log2FC_GSE51365 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE51365") %>%
  pull(Log2FC_Column)

Contrasts_Tstat_GSE51365 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE51365") %>%
  pull(Tstat_Column)

# GSE53784
Contrasts_Log2FC_GSE53784 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE53784") %>%
  pull(Log2FC_Column)

Contrasts_Tstat_GSE53784 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE53784") %>%
  pull(Tstat_Column)

# GSE91074
Contrasts_Log2FC_GSE91074 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE91074") %>%
  pull(Log2FC_Column)

Contrasts_Tstat_GSE91074 <- Contrasts_Stat_Columns %>%
  filter(ExperimentID == "GSE91074") %>%
  pull(Tstat_Column)

# Function use

# GSE30577
DE_Results_Contrasts_GSE30577 <- ExtractingDEResultsForContrasts(DE_Results_GSE30577_GoodAnnotation,
  Contrasts_Log2FC_GSE30577,
  Contrasts_Tstat_GSE30577,
  ResultSets_contrasts)

```



```
## [1] "Columns in the DE results for the current ResultSet:"
## [1] "Probe" "NCBIid"
## [3] "GeneSymbol" "GeneName"
## [5] "pvalue" "corrected_pvalue"
## [7] "rank" "contrast_84556_coefficient"
## [9] "contrast_84556_log2fc" "contrast_84556_tstat"
## [11] "contrast_84556_pvalue"
## [1] "Columns of Log2FC for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_84556_log2fc"
## [1] "Columns of T-statistics for contrasts of interest within the DE results for the current Results"
## [1] "contrast_84556_tstat"
## [1] "Contrast IDs for contrasts of interest within the current ResultSet:"
## [1] "84556"
## [1] "Dataset ID for the ResultSet and contrasts:"
## [1] "GSE30577"
## [1] "Experimental factors for ResultSet and contrasts:"
## [1] "Rabies virus has_genotype strain CVS-11"
## [1] "Current names of contrasts of interest"
## [1] "GSE30577_Rabies virus has_genotype strain CVS-11"
```

*# GSE42264*

```
DE_Results_Contrasts_GSE42264 <- ExtractingDEResultsForContrasts(DE_Results_GSE42264_GoodAnnotation,
                                                                    Contrasts_Log2FC_GSE42264,
                                                                    Contrasts_Tstat_GSE42264,
                                                                    ResultSets_contrasts)
```

```
## [1] "Columns in the DE results for the current ResultSet:"
## [1] "Probe" "NCBIid"
## [3] "GeneSymbol" "GeneName"
## [5] "pvalue" "corrected_pvalue"
## [7] "rank" "contrast_89756_coefficient"
## [9] "contrast_89756_log2fc" "contrast_89756_tstat"
## [11] "contrast_89756_pvalue"
## [1] "Columns of Log2FC for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_89756_log2fc"
## [1] "Columns of T-statistics for contrasts of interest within the DE results for the current Results"
## [1] "contrast_89756_tstat"
## [1] "Contrast IDs for contrasts of interest within the current ResultSet:"
## [1] "89756"
## [1] "Dataset ID for the ResultSet and contrasts:"
## [1] "GSE42264"
## [1] "Experimental factors for ResultSet and contrasts:"
## [1] "measles"
## [1] "Current names of contrasts of interest"
## [1] "GSE42264_measles"
```

*# GSE44331*

```
DE_Results_Contrasts_GSE44331 <- ExtractingDEResultsForContrasts(DE_Results_GSE44331_GoodAnnotation,
                                                                    Contrasts_Log2FC_GSE44331,
                                                                    Contrasts_Tstat_GSE44331,
                                                                    ResultSets_contrasts)
```

```
## [1] "Columns in the DE results for the current ResultSet:"
```

```
## [1] "Probe" "NCBIid"
## [3] "GeneSymbol" "GeneName"
## [5] "pvalue" "corrected_pvalue"
## [7] "rank" "contrast_97695_coefficient"
## [9] "contrast_97695_log2fc" "contrast_97695_tstat"
## [11] "contrast_97695_pvalue"
## [1] "Columns of Log2FC for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_97695_log2fc"
## [1] "Columns of T-statistics for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_97695_tstat"
## [1] "Contrast IDs for contrasts of interest within the current ResultSet:"
## [1] "97695"
## [1] "Dataset ID for the ResultSet and contrasts:"
## [1] "GSE44331"
## [1] "Experimental factors for ResultSet and contrasts:"
## [1] "Vesicular stomatitis Indiana virus"
## [1] "Current names of contrasts of interest"
## [1] "GSE44331_Vesicular stomatitis Indiana virus"
```

```
# GSE51365
```

```
DE_Results_Contrasts_GSE51365 <- ExtractingDEResultsForContrasts(DE_Results_GSE51365_GoodAnnotation,
                                                                    Contrasts_Log2FC_GSE51365,
                                                                    Contrasts_Tstat_GSE51365,
                                                                    ResultSets_contrasts)
```

```
## [1] "Columns in the DE results for the current ResultSet:"
## [1] "Probe" "NCBIid"
## [3] "GeneSymbol" "GeneName"
## [5] "pvalue" "corrected_pvalue"
## [7] "rank" "contrast_99431_coefficient"
## [9] "contrast_99431_log2fc" "contrast_99431_tstat"
## [11] "contrast_99431_pvalue" "contrast_99432_coefficient"
## [13] "contrast_99432_log2fc" "contrast_99432_tstat"
## [15] "contrast_99432_pvalue"
## [1] "Columns of Log2FC for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_99431_log2fc" "contrast_99432_log2fc"
## [1] "Columns of T-statistics for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_99431_tstat" "contrast_99432_tstat"
## [1] "Contrast IDs for contrasts of interest within the current ResultSet:"
## [1] "99431" "99432"
## [1] "Dataset ID for the ResultSet and contrasts:"
## [1] "GSE51365" "GSE51365"
## [1] "Experimental factors for ResultSet and contrasts:"
## [1] "murine gammaherpesvirus 68"
## [2] "murine gammaherpesvirus 68 has phenotype latency-defective"
## [1] "Current names of contrasts of interest"
## [1] "GSE51365_murine gammaherpesvirus 68"
## [2] "GSE51365_murine gammaherpesvirus 68 has phenotype latency-defective"
```

```
# GSE53784
```

```
DE_Results_Contrasts_GSE53784 <- ExtractingDEResultsForContrasts(DE_Results_GSE53784_GoodAnnotation,
                                                                    Contrasts_Log2FC_GSE53784,
                                                                    Contrasts_Tstat_GSE53784,
                                                                    ResultSets_contrasts)
```

```
## [1] "Columns in the DE results for the current ResultSet:"
## [1] "Probe" "NCBIId"
## [3] "GeneSymbol" "GeneName"
## [5] "pvalue" "corrected_pvalue"
## [7] "rank" "contrast_140572_coefficient"
## [9] "contrast_140572_log2fc" "contrast_140572_tstat"
## [11] "contrast_140572_pvalue" "contrast_140573_coefficient"
## [13] "contrast_140573_log2fc" "contrast_140573_tstat"
## [15] "contrast_140573_pvalue"
## [1] "Columns of Log2FC for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_140572_log2fc" "contrast_140573_log2fc"
## [1] "Columns of T-statistics for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_140572_tstat" "contrast_140573_tstat"
## [1] "Contrast IDs for contrasts of interest within the current ResultSet:"
## [1] "140572" "140573"
## [1] "Dataset ID for the ResultSet and contrasts:"
## [1] "GSE53784" "GSE53784"
## [1] "Experimental factors for ResultSet and contrasts:"
## [1] "West Nile virus" "Japanese encephalitis virus"
## [1] "Current names of contrasts of interest"
## [1] "GSE53784_West Nile virus"
## [2] "GSE53784_Japanese encephalitis virus"
```

*# GSE91074*

```
DE_Results_Contrasts_GSE91074 <- ExtractingDEResultsForContrasts(DE_Results_GSE91074_GoodAnnotation,
                                                                    Contrasts_Log2FC_GSE91074,
                                                                    Contrasts_Tstat_GSE91074,
                                                                    ResultSets_contrasts)
```

```
## [1] "Columns in the DE results for the current ResultSet:"
## [1] "Probe" "NCBIId"
## [3] "GeneSymbol" "GeneName"
## [5] "pvalue" "corrected_pvalue"
## [7] "rank" "contrast_142941_coefficient"
## [9] "contrast_142941_log2fc" "contrast_142941_tstat"
## [11] "contrast_142941_pvalue"
## [1] "Columns of Log2FC for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_142941_log2fc"
## [1] "Columns of T-statistics for contrasts of interest within the DE results for the current ResultSet:"
## [1] "contrast_142941_tstat"
## [1] "Contrast IDs for contrasts of interest within the current ResultSet:"
## [1] "142941"
## [1] "Dataset ID for the ResultSet and contrasts:"
## [1] "GSE91074"
## [1] "Experimental factors for ResultSet and contrasts:"
## [1] "Venezuelan equine encephalitis virus strain TC83"
## [1] "Current names of contrasts of interest"
## [1] "GSE91074_Venezuelan equine encephalitis virus strain TC83"
```

## 8) Collapse of DE results to one result per gene & Calculation of standard error

### and sampling variance

Gene expression can be measured using multiple probes (microarray). Therefore, DE results need to be collapsed to one result per gene.

Standard error of  $\text{Log2FC} = \text{Log2FC}/T\text{-statistics}$

Sampling variance = Average of standard error of each gene<sup>2</sup>

```
# Create a function to average Log2FC, Tstat, standard error to one unique gene
# per dataset
CollapsingDEResults_OneResultPerGene<-function(GSE_ID,
                                                DE_Results_GoodAnnotation,
                                                ComparisonsOfInterest,
                                                NamesOfFoldChangeColumns,
                                                NamesOfTstatColumns){

  # Print a message to check if the vectors containing FC and T-stat column names
  # are in the same order as the comparisons of interest
  print("Check if the vectors containing FC and Tstat column names contain the same order as the compar:

  # Print the number of unique NCBI IDs in the DE results
  print("# of rows with unique NCBI IDs:")
  print(length(unique(DE_Results_GoodAnnotation$NCBIid)))

  # Print the number of unique Gene Symbols in the DE results
  print("# of rows with unique Gene Symbols:")
  print(length(unique(DE_Results_GoodAnnotation$GeneSymbol)))

  # Create a folder named after the dataset ID to store results
  dir.create(paste("./", "Collapsing_DEResults_", GSE_ID, sep=""))

  # Set the working directory to the newly created folder
  setwd(paste("./", "Collapsing_DEResults_", GSE_ID, sep=""))

  # Create lists to store results
  DE_Results_GoodAnnotation_FoldChange_Average <- list()
  DE_Results_GoodAnnotation_Tstat_Average <- list()
  DE_Results_GoodAnnotation_SE_Average <- list()

  # Loop through each column containing FC and T-statistic info for the contrasts of interest
  for(i in c(1:length(NamesOfFoldChangeColumns))){

    # Select the Log2FC column of interest
    FoldChangeColumn <- select(DE_Results_GoodAnnotation, NamesOfFoldChangeColumns[i])

    # Select the T-stat column of interest
    TstatColumn <- select(DE_Results_GoodAnnotation, NamesOfTstatColumns[i])

    # Calculate the standard error (SE)
    DE_Results_GoodAnnotation_SE <- FoldChangeColumn[[1]]/TstatColumn[[1]]

    # Calculate the average Log2FC per gene
```

```

DE_Results_GoodAnnotation_FoldChange_Average[[i]] <- tapply(FoldChangeColumn[[1]],
                                                             DE_Results_GoodAnnotation$NCBIId,
                                                             mean)

# Calculate the average T-statistics per gene
DE_Results_GoodAnnotation_Tstat_Average[[i]] <- tapply(TstatColumn[[1]],
                                                         DE_Results_GoodAnnotation$NCBIId,
                                                         mean)

# Calculate the average SE per gene
DE_Results_GoodAnnotation_SE_Average[[i]] <- tapply(DE_Results_GoodAnnotation_SE,
                                                      DE_Results_GoodAnnotation$NCBIId,
                                                      mean)

}

# Combine averaged Log2FC values into a single dataframe
DE_Results_GoodAnnotation_FoldChange_AveragedByGene <- do.call(cbind, DE_Results_GoodAnnotation_FoldC

# Print the dimensions of the averaged Fold Change matrix
print("Dimensions of Fold Change matrix, averaged by gene symbol:")
print(dim(DE_Results_GoodAnnotation_FoldChange_AveragedByGene))

# Name the columns in the dataframe to describe the contrast of interest
colnames(DE_Results_GoodAnnotation_FoldChange_AveragedByGene) <- ComparisonsOfInterest

# Export the averaged Log2FC results into the working directory
write.csv(DE_Results_GoodAnnotation_FoldChange_AveragedByGene,
          paste("DEResults_", GSE_ID, "_GoodAnnotation_FoldChange_AveragedByGene.csv", sep = ""))

# Combine T-statistics values into a single dataframe
DE_Results_GoodAnnotation_Tstat_AveragedByGene<-do.call(cbind, DE_Results_GoodAnnotation_Tstat_Averag

# Name the columns in the dataframe to describe the contrast of interest
colnames(DE_Results_GoodAnnotation_Tstat_AveragedByGene) <- ComparisonsOfInterest

# Export the averaged T-statistics results into the working directory
write.csv(DE_Results_GoodAnnotation_Tstat_AveragedByGene,
          paste("DEResults_", GSE_ID, "_GoodAnnotation_Tstat_AveragedByGene.csv", sep = ""))

# Combine SE values into a single dataframe
DE_Results_GoodAnnotation_SE_AveragedByGene<-do.call(cbind, DE_Results_GoodAnnotation_SE_Average)

# Name the columns in the dataframe to describe the contrast of interest
colnames(DE_Results_GoodAnnotation_SE_AveragedByGene) <- ComparisonsOfInterest

# Export the averaged SE results into the working directory
write.csv(DE_Results_GoodAnnotation_SE_AveragedByGene,
          paste("DEResults_", GSE_ID, "_GoodAnnotation_SE_AveragedByGene.csv", sep = ""))

# Calculate the sampling variance (SV) by squaring the SE
DE_Results_GoodAnnotation_SV <- (DE_Results_GoodAnnotation_SE_AveragedByGene)^2

```

```

# Export the SV results into the working directory
write.csv(DE_Results_GoodAnnotation_SV,
          paste("DEResults_", GSE_ID, "_GoodAnnotation_SV.csv", sep = ""))

# Compile all averaged results into a single list
TempMasterResults<-list(Log2FC = DE_Results_GoodAnnotation_FoldChange_AveragedByGene,
                        Tstat = DE_Results_GoodAnnotation_Tstat_AveragedByGene,
                        SE = DE_Results_GoodAnnotation_SE_AveragedByGene,
                        SV = DE_Results_GoodAnnotation_SV)

# Print the name of the output
print(paste("Output: Collapsing_DEResults", GSE_ID, sep="_"))

# Clean up the environment by removing temporary results
rm(DE_Results_GoodAnnotation, DE_Results_GoodAnnotation_SV,
   DE_Results_GoodAnnotation_SE, DE_Results_GoodAnnotation_FoldChange_AveragedByGene,
   DE_Results_GoodAnnotation_FoldChange_Average, DE_Results_GoodAnnotation_Tstat_AveragedByGene,
   DE_Results_GoodAnnotation_Tstat_Average, DE_Results_GoodAnnotation_SE_Average,
   FoldChangeColumn, TstatColumn, GSE_ID, ComparisonsOfInterest, NamesOfFoldChangeColumns,
   NamesOfTstatColumns)

# Set the working directory back to the parent directory
setwd("../")

# Return the compiled results
return(TempMasterResults)
}

```

```

# Prepare "NamesOfFoldChangeColumns" and "NamesOfTstatColumns" arguments for
# extracting DE results of contrasts of interest

# GSE30577
NamesOfFoldChangeColumns_GSE30577 <- DE_Results_Contrasts_GSE30577[[2]]
NamesOfTstatColumns_GSE30577 <- DE_Results_Contrasts_GSE30577[[3]]
ComparisonsOfInterest_GSE30577 <- c("GSE30577_Rabies_vs_Control")

# GSE42264
NamesOfFoldChangeColumns_GSE42264 <- DE_Results_Contrasts_GSE42264[[2]]
NamesOfTstatColumns_GSE42264 <- DE_Results_Contrasts_GSE42264[[3]]
ComparisonsOfInterest_GSE42264 <- c("GSE42264_Measles_vs_Control")

# GSE44331
NamesOfFoldChangeColumns_GSE44331 <- DE_Results_Contrasts_GSE44331[[2]]
NamesOfTstatColumns_GSE44331 <- DE_Results_Contrasts_GSE44331[[3]]
ComparisonsOfInterest_GSE44331 <- c("GSE44331_VSV_vs_Control")

# GSE51365
NamesOfFoldChangeColumns_GSE51365 <- DE_Results_Contrasts_GSE51365[[2]]
NamesOfTstatColumns_GSE51365 <- DE_Results_Contrasts_GSE51365[[3]]
ComparisonsOfInterest_GSE51365 <- c("GSE51365_MVH68_WT_vs_Control", "GSE51365_MVH68_M_vs_Control")

# GSE53784
NamesOfFoldChangeColumns_GSE53784 <- DE_Results_Contrasts_GSE53784[[2]]

```

```
NamesOfTstatColumns_GSE53784 <- DE_Results_Contrasts_GSE53784[[3]]
ComparisonsOfInterest_GSE53784 <- c("GSE53784_WNV_vs_Control", "GSE53784_JEV_vs_Control")
```

```
# GSE91074
```

```
NamesOfFoldChangeColumns_GSE91074 <- DE_Results_Contrasts_GSE91074[[2]]
NamesOfTstatColumns_GSE91074 <- DE_Results_Contrasts_GSE91074[[3]]
ComparisonsOfInterest_GSE91074 <- c("GSE91074_VEEV_vs_Control")
```

```
# Function use
```

```
# GSE30577
```

```
Collapsing_DEResults_GSE30577 <- CollapsingDEResults_OneResultPerGene("GSE30577",
DE_Results_GSE30577_GoodAnnotation,
ComparisonsOfInterest_GSE30577,
NamesOfFoldChangeColumns_GSE30577,
NamesOfTstatColumns_GSE30577)
```

```
## [1] "Check if the vectors containing FC and Tstat column names contain the same order as the compari
## [1] "# of rows with unique NCBI IDs:"
## [1] 16125
## [1] "# of rows with unique Gene Symbols:"
## [1] 16125
```

```
## Warning in dir.create(paste("./", "Collapsing_DEResults_", GSE_ID, sep = "")):
## './Collapsing_DEResults_GSE30577' already exists
```

```
## [1] "Dimensions of Fold Change matrix, averaged by gene symbol:"
## [1] 16125      1
## [1] "Output: Collapsing_DEResults_GSE30577"
```

```
# GSE42264
```

```
Collapsing_DEResults_GSE42264 <- CollapsingDEResults_OneResultPerGene("GSE42264",
DE_Results_GSE42264_GoodAnnotation,
ComparisonsOfInterest_GSE42264,
NamesOfFoldChangeColumns_GSE42264,
NamesOfTstatColumns_GSE42264)
```

```
## [1] "Check if the vectors containing FC and Tstat column names contain the same order as the compari
## [1] "# of rows with unique NCBI IDs:"
## [1] 18555
## [1] "# of rows with unique Gene Symbols:"
## [1] 18555
```

```
## Warning in dir.create(paste("./", "Collapsing_DEResults_", GSE_ID, sep = "")):
## './Collapsing_DEResults_GSE42264' already exists
```

```
## [1] "Dimensions of Fold Change matrix, averaged by gene symbol:"
## [1] 18555      1
## [1] "Output: Collapsing_DEResults_GSE42264"
```



```

# GSE44331
Collapsing_DEResults_GSE44331 <- CollapsingDEResults_OneResultPerGene("GSE44331",
                                                                    DE_Results_GSE44331_GoodAnnotation,
                                                                    ComparisonsOfInterest_GSE44331,
                                                                    NamesOfFoldChangeColumns_GSE44331,
                                                                    NamesOfTstatColumns_GSE44331)

## [1] "Check if the vectors containing FC and Tstat column names contain the same order as the compari
## [1] "# of rows with unique NCBI IDs:"
## [1] 18557
## [1] "# of rows with unique Gene Symbols:"
## [1] 18557

## Warning in dir.create(paste("./", "Collapsing_DEResults_", GSE_ID, sep = "")):
## './Collapsing_DEResults_GSE44331' already exists

## [1] "Dimensions of Fold Change matrix, averaged by gene symbol:"
## [1] 18557      1
## [1] "Output: Collapsing_DEResults_GSE44331"

# GSE51365
Collapsing_DEResults_GSE51365 <- CollapsingDEResults_OneResultPerGene("GSE51365",
                                                                    DE_Results_GSE51365_GoodAnnotation,
                                                                    ComparisonsOfInterest_GSE51365,
                                                                    NamesOfFoldChangeColumns_GSE51365,
                                                                    NamesOfTstatColumns_GSE51365)

## [1] "Check if the vectors containing FC and Tstat column names contain the same order as the compari
## [1] "# of rows with unique NCBI IDs:"
## [1] 18561
## [1] "# of rows with unique Gene Symbols:"
## [1] 18561

## Warning in dir.create(paste("./", "Collapsing_DEResults_", GSE_ID, sep = "")):
## './Collapsing_DEResults_GSE51365' already exists

## [1] "Dimensions of Fold Change matrix, averaged by gene symbol:"
## [1] 18561      2
## [1] "Output: Collapsing_DEResults_GSE51365"

# GSE53784
Collapsing_DEResults_GSE53784 <- CollapsingDEResults_OneResultPerGene("GSE53784",
                                                                    DE_Results_GSE53784_GoodAnnotation,
                                                                    ComparisonsOfInterest_GSE53784,
                                                                    NamesOfFoldChangeColumns_GSE53784,
                                                                    NamesOfTstatColumns_GSE53784)

## [1] "Check if the vectors containing FC and Tstat column names contain the same order as the compari
## [1] "# of rows with unique NCBI IDs:"
## [1] 20248
## [1] "# of rows with unique Gene Symbols:"
## [1] 20248

```



```
## Warning in dir.create(paste("./", "Collapsing_DEResults_", GSE_ID, sep = "")):
## './Collapsing_DEResults_GSE53784' already exists

## [1] "Dimensions of Fold Change matrix, averaged by gene symbol:"
## [1] 20248      2
## [1] "Output: Collapsing_DEResults_GSE53784"

# GSE91074
Collapsing_DEResults_GSE91074 <- CollapsingDEResults_OneResultPerGene("GSE91074",
DE_Results_GSE91074_GoodAnnotation,
ComparisonsOfInterest_GSE91074,
NamesOfFoldChangeColumns_GSE91074,
NamesOfTstatColumns_GSE91074)

## [1] "Check if the vectors containing FC and Tstat column names contain the same order as the compari
## [1] "# of rows with unique NCBI IDs:"
## [1] 12644
## [1] "# of rows with unique Gene Symbols:"
## [1] 12644

## Warning in dir.create(paste("./", "Collapsing_DEResults_", GSE_ID, sep = "")):
## './Collapsing_DEResults_GSE91074' already exists

## [1] "Dimensions of Fold Change matrix, averaged by gene symbol:"
## [1] 12644      1
## [1] "Output: Collapsing_DEResults_GSE91074"
```

## 9) Alignment of DE results from same models (mouse & rat)

Each dataset has DE results from a slightly different list of genes.

Depending on the exact tissue dissected, the sensitivity of the transcriptional profiling platform, the representation on the transcriptional profiling platform (for microarray), and the experimental conditions, the DE results from different datasets will also be in a slightly different order.

We want to align these results so that the DE results from each dataset are columns, with each row representing a different gene.

- GSE30577 - Mouse model
- GSE42264 - Mouse model
- GSE44331 - Mouse model
- GSE51365 - Mouse model
- GSE53784 - Mouse model
- GSE91074 - Mouse model

Since there are only mouse models, we would create one aligning function. If there are both mouse and rat models, we would have to create two aligning functions, one for the mouse and one for the rat.

```

# Create a function to align all mouse DE results from different datasets into
# a single dataframe for Log2FC and SV
AligningMouseDatasets <- function(ListOfMouseDEResults){

  # Create a list to store the log2FC
  Mouse_MetaAnalysis_FoldChange_Dfs <- list()

  # Loop through all mouse DE results
  for(i in c(1:length(ListOfMouseDEResults))){
    # When did the row name become IDs?
    # Extract the Log2FC values from each dataset and put them into separate list
    # The element from the "Collapsing_DEResults_" has the format of row names
    # as Entrez Gene ID and columns containing Log2FC values
    Mouse_MetaAnalysis_FoldChange_Dfs[[i]] <- data.frame(Mouse_EntrezGene.ID = row.names(ListOfMouseDEResults[[i]]),
                                                         ListOfMouseDEResults[[i]][[1]],
                                                         stringsAsFactors = FALSE)
  }

  # Print the structure of the Log2FC lists
  print("Mouse_MetaAnalysis_FoldChange_Dfs:")
  print(str(Mouse_MetaAnalysis_FoldChange_Dfs))

  # Align the DE results by Entrez Gene ID and turn them into a single dataframe
  # join_all can be used for object of list class
  Mouse_MetaAnalysis_FoldChanges <-> join_all(Mouse_MetaAnalysis_FoldChange_Dfs,
                                              by = "Mouse_EntrezGene.ID",
                                              type = "full")

  # Print the structure of the aligned Log2FC
  print("Mouse_MetaAnalysis_FoldChanges:")
  print(str(Mouse_MetaAnalysis_FoldChanges))

  # Create a list to store the SV
  Mouse_MetaAnalysis_SV_Dfs <- list()

  # Loop through all mouse DE results
  for(i in c(1:length(ListOfMouseDEResults))){
    # Extract the SV values from each dataset and put them into separate list
    # The element from the "Collapsing_DEResults_" has the format of row names
    # as Entrez Gene ID and columns containing SV values
    Mouse_MetaAnalysis_SV_Dfs[[i]] <- data.frame(Mouse_EntrezGene.ID = row.names(ListOfMouseDEResults[[i]]),
                                                         ListOfMouseDEResults[[i]][[4]],
                                                         stringsAsFactors = FALSE)
  }

  # Print the structure of the SV lists
  print("Mouse_MetaAnalysis_SV_Dfs:")
  print(str(Mouse_MetaAnalysis_SV_Dfs))

  # Align the DE results by Entrez Gene ID and turn them into a single dataframe
  # join_all can be used for object of list class
  Mouse_MetaAnalysis_SV <-> join_all(Mouse_MetaAnalysis_SV_Dfs,
                                    by = "Mouse_EntrezGene.ID",

```

```

                                type = "full")

# Print the structure of the aligned SV
print("Mouse_MetaAnalysis_SV:")
print(str(Mouse_MetaAnalysis_SV))

# Remove the temporary lists of Log2FC and SV
rm(Mouse_MetaAnalysis_SV_Dfs, Mouse_MetaAnalysis_FoldChange_Dfs)
}

# Prepare the list of collapsed mouse DE results
ListOfMouseDEResults <- list(Collapsing_DEResults_GSE30577,
                             Collapsing_DEResults_GSE42264,
                             Collapsing_DEResults_GSE44331,
                             Collapsing_DEResults_GSE51365,
                             Collapsing_DEResults_GSE53784,
                             Collapsing_DEResults_GSE91074)

# Function use
AligningMouseDatasets(ListOfMouseDEResults)

## [1] "Mouse_MetaAnalysis_FoldChange_Dfs:"
## List of 6
## $ : 'data.frame': 16125 obs. of 2 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:16125] "100008567" "100012" "100017" "100019" ...
## ..$ GSE30577_Rabies_vs_Control: num [1:16125] 2.759 0.333 2.426 -3.133 3.728 ...
## $ : 'data.frame': 18555 obs. of 2 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:18555] "100008567" "100009600" "100012" "100017" ...
## ..$ GSE42264_Measles_vs_Control: num [1:18555] 0.1432 -0.0634 0.0232 0.2999 -0.0068 ...
## $ : 'data.frame': 18557 obs. of 2 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:18557] "100008567" "100009600" "100012" "100017" ...
## ..$ GSE44331_VSV_vs_Control: num [1:18557] -0.1186 -0.0661 0.00045 0.0126 -0.12615 ...
## $ : 'data.frame': 18561 obs. of 3 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:18561] "100008567" "100009600" "100012" "100017" ...
## ..$ GSE51365_MVH68_WT_vs_Control: num [1:18561] -0.027 0.015 -0.1365 0.3838 -0.0438 ...
## ..$ GSE51365_MVH68_M_vs_Control : num [1:18561] -0.0529 0.0899 -0.1011 0.4863 -0.1134 ...
## $ : 'data.frame': 20248 obs. of 3 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:20248] "100008567" "100009600" "100009609" "100009614" ...
## ..$ GSE53784_WNV_vs_Control: num [1:20248] -0.3712 0.3762 -0.013 0.1307 -0.0234 ...
## ..$ GSE53784_JEV_vs_Control: num [1:20248] -0.1675 0.1526 0.0452 -0.0839 0.0016 ...
## $ : 'data.frame': 12644 obs. of 2 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:12644] "100017" "100019" "100036538" "100036539" ...
## ..$ GSE91074_VEEV_vs_Control: num [1:12644] 0.7205 -0.1288 -0.1049 -0.0285 0.1944 ...
## NULL
## [1] "Mouse_MetaAnalysis_FoldChanges:"
## 'data.frame': 22542 obs. of 9 variables:
## $ Mouse_EntrezGene.ID : chr "100008567" "100012" "100017" "100019" ...
## $ GSE30577_Rabies_vs_Control : num 2.759 0.333 2.426 -3.133 3.728 ...
## $ GSE42264_Measles_vs_Control : num 0.1432 0.0232 0.2999 -0.0068 0.0324 ...
## $ GSE44331_VSV_vs_Control : num -0.1186 0.00045 0.0126 -0.12615 0.3555 ...
## $ GSE51365_MVH68_WT_vs_Control: num -0.027 -0.1365 0.3838 -0.0438 -0.0832 ...
## $ GSE51365_MVH68_M_vs_Control : num -0.0529 -0.1011 0.4863 -0.1134 0.0224 ...
## $ GSE53784_WNV_vs_Control : num -0.3712 -0.0234 0.1029 0.2022 3.5291 ...

```

```
## $ GSE53784_JEV_vs_Control : num -0.1675 0.0016 -0.2338 0.2673 2.316 ...
## $ GSE91074_VEEV_vs_Control : num NA NA 0.721 -0.129 NA ...
## NULL
## [1] "Mouse_MetaAnalysis_SV_Dfs:"
## List of 6
## $ : 'data.frame': 16125 obs. of 2 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:16125] "100008567" "100012" "100017" "100019" ...
## ..$ GSE30577_Rabies_vs_Control: num [1:16125] 1.458 1.986 0.378 0.953 0.547 ...
## $ : 'data.frame': 18555 obs. of 2 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:18555] "100008567" "100009600" "100012" "100017" ...
## ..$ GSE42264_Measles_vs_Control: num [1:18555] 0.00544 0.00205 0.00381 0.00488 0.00255 ...
## $ : 'data.frame': 18557 obs. of 2 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:18557] "100008567" "100009600" "100012" "100017" ...
## ..$ GSE44331_VSV_vs_Control: num [1:18557] 0.01038 0.00728 0.00602 0.01243 0.00568 ...
## $ : 'data.frame': 18561 obs. of 3 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:18561] "100008567" "100009600" "100012" "100017" ...
## ..$ GSE51365_MVH68_WT_vs_Control: num [1:18561] 0.00531 0.00645 0.00989 0.06474 0.00793 ...
## ..$ GSE51365_MVH68_M_vs_Control : num [1:18561] 0.00532 0.00644 0.00987 0.06476 0.00795 ...
## $ : 'data.frame': 20248 obs. of 3 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:20248] "100008567" "100009600" "100009609" "100009614" ...
## ..$ GSE53784_WNV_vs_Control: num [1:20248] 0.00481 0.00939 0.00889 0.0103 0.0035 ...
## ..$ GSE53784_JEV_vs_Control: num [1:20248] 0.00481 0.00939 0.00888 0.01031 0.00362 ...
## $ : 'data.frame': 12644 obs. of 2 variables:
## ..$ Mouse_EntrezGene.ID : chr [1:12644] "100017" "100019" "100036538" "100036539" ...
## ..$ GSE91074_VEEV_vs_Control: num [1:12644] 0.01898 0.00278 0.00226 0.00209 0.00528 ...
## NULL
## [1] "Mouse_MetaAnalysis_SV:"
## 'data.frame': 22542 obs. of 9 variables:
## $ Mouse_EntrezGene.ID : chr "100008567" "100012" "100017" "100019" ...
## $ GSE30577_Rabies_vs_Control : num 1.458 1.986 0.378 0.953 0.547 ...
## $ GSE42264_Measles_vs_Control : num 0.00544 0.00381 0.00488 0.00255 0.00586 ...
## $ GSE44331_VSV_vs_Control : num 0.01038 0.00602 0.01243 0.00568 0.01053 ...
## $ GSE51365_MVH68_WT_vs_Control: num 0.00531 0.00989 0.06474 0.00793 0.0779 ...
## $ GSE51365_MVH68_M_vs_Control : num 0.00532 0.00987 0.06476 0.00795 0.07782 ...
## $ GSE53784_WNV_vs_Control : num 0.00481 0.0035 0.00595 0.00341 0.02618 ...
## $ GSE53784_JEV_vs_Control : num 0.00481 0.00362 0.00595 0.00341 0.02618 ...
## $ GSE91074_VEEV_vs_Control : num NA NA 0.01898 0.00278 NA ...
## NULL
```

## 10) Alignment of DE results from different models (mouse & rat)

### Concept of *Gene Orthologs*:

- *Homology* refers to biological features including genes and their products that are descended from a feature present in a common ancestor.
- *Homologous gene* become separated in evolution in 2 different ways:
  1. Separation of 2 populations with the ancestral gene into 2 species. Gene separated by *speciation* are called *orthologs*.
  2. Duplication of the ancestral gene within a lineage. Gene separated by *gene duplication* are called *paralogs*.

Ref: [https://www.nlm.nih.gov/ncbi/workshops/2023-08\\_BLAST\\_evol/ortho\\_para.html](https://www.nlm.nih.gov/ncbi/workshops/2023-08_BLAST_evol/ortho_para.html)

We have the ortholog database that we downloaded from Jackson Lab on April 25, 2024. This database was trimmed and formatted using "FormattingRatMouseOrthologDatabase\_20240425.R"

```
# Import the trimmed and formatted ortholog database
MouseVsRat_NCBI_Entrez <- read.csv("MouseVsRat_NCBI_Entrez_JacksonLab_20240425.csv",
                                   header = TRUE,
                                   stringsAsFactors = FALSE,
                                   row.names = 1,
                                   colClasses = c("character", "character", "character"))

# Join the ortholog database with mouse Log2FC

#### Problem arise here with the NA in the orthologs
Mouse_MetaAnalysis_FoldChanges_wOrthologs <- join(MouseVsRat_NCBI_Entrez,
                                                  Mouse_MetaAnalysis_FoldChanges,
                                                  by = "Mouse_EntrezGene.ID",
                                                  type = "full")

# Join the ortholog database with mouse SV
Mouse_MetaAnalysis_SV_wOrthologs <- join(MouseVsRat_NCBI_Entrez,
                                          Mouse_MetaAnalysis_SV,
                                          by = "Mouse_EntrezGene.ID",
                                          type = "full")

# Check the structure of the new mouse Log2FC with ortholog info
str(Mouse_MetaAnalysis_FoldChanges_wOrthologs)
```

```
## 'data.frame': 22789 obs. of 11 variables:
## $ Rat_EntrezGene.ID : chr "114087" "191569" "246307" "65041" ...
## $ Mouse_EntrezGene.ID : chr "23825" "18585" "66514" "20480" ...
## $ MouseVsRat_EntrezGene.ID : chr "23825_114087" "18585_191569" "66514_246307" "20480_65041" ...
## $ GSE30577_Rabies_vs_Control : num -0.521 1.872 NA 0.134 0.822 ...
## $ GSE42264_Measles_vs_Control : num 0.0928 0.0906 0.0443 -0.1149 0.0472 ...
## $ GSE44331_VSV_vs_Control : num -0.00553 0.0339 -0.0275 -0.19225 -0.1228 ...
## $ GSE51365_MVH68_WT_vs_Control: num -0.011 0.1377 0.0275 0.0508 -0.0837 ...
## $ GSE51365_MVH68_M_vs_Control : num 0.00693 0.0891 0.03023 0.0812 -0.095 ...
## $ GSE53784_WNV_vs_Control : num -0.0736 -0.4003 -1.0309 -0.2629 0.8745 ...
## $ GSE53784_JEV_vs_Control : num 0.0783 0.2109 -0.996 -0.0471 0.4395 ...
## $ GSE91074_VEEV_vs_Control : num -0.1555 0.0199 -0.2302 -0.2588 0.0919 ...
```

```
# Check the structure of the new mouse SV with ortholog info
str(Mouse_MetaAnalysis_SV_wOrthologs)
```

```
## 'data.frame': 22789 obs. of 11 variables:
## $ Rat_EntrezGene.ID : chr "114087" "191569" "246307" "65041" ...
## $ Mouse_EntrezGene.ID : chr "23825" "18585" "66514" "20480" ...
## $ MouseVsRat_EntrezGene.ID : chr "23825_114087" "18585_191569" "66514_246307" "20480_65041" ...
## $ GSE30577_Rabies_vs_Control : num 0.781 3.343 NA 1.338 1.128 ...
## $ GSE42264_Measles_vs_Control : num 0.00148 0.00141 0.0018 0.00159 0.00108 ...
## $ GSE44331_VSV_vs_Control : num 0.01018 0.00379 0.00519 0.00888 0.00784 ...
## $ GSE51365_MVH68_WT_vs_Control: num 0.00552 0.00613 0.00682 0.00798 0.00881 ...
```

```
## $ GSE51365_MVH68_M_vs_Control : num 0.00545 0.00612 0.00682 0.008 0.00882 ...
## $ GSE53784_WNV_vs_Control : num 0.00586 0.00632 0.00421 0.00281 0.00332 ...
## $ GSE53784_JEV_vs_Control : num 0.00586 0.00632 0.00421 0.00282 0.00332 ...
## $ GSE91074_VEEV_vs_Control : num 0.00239 0.02259 0.00431 0.00414 0.00198 ...
```

```
# If there are rat datasets, we want to join our mouse Log2FC and SV results to
# the rat Log2FC and SV results using the ortholog info
```

```
# Join the Log2FC of the mouse datasets and rat datasets
MetaAnalysis_FoldChanges <- join(Mouse_MetaAnalysis_FoldChanges_wOrthologs,
                                Rat_MetaAnalysis_FoldChanges,
                                by = "Rat_EntrezGene.ID",
                                type = "full")
```

```
# Check the structure of the joined mouse and rat Log2FC with ortholog info
str(MetaAnalysis_FoldChanges)
```

```
# Join the SV of the mouse datasets and rat datasets
MetaAnalysis_SV <- join(Mouse_MetaAnalysis_SV_wOrthologs,
                        Rat_MetaAnalysis_FoldChanges,
                        by = "Rat_EntrezGene.ID",
                        type = "full")
```

```
# Check the structure of the joined mouse and rat SV with ortholog info
str(MetaAnalysis_SV)
```

```
# If there are no rat dataset, we rename the dataframes so the pipeline code works
MetaAnalysis_FoldChanges <- Mouse_MetaAnalysis_FoldChanges_wOrthologs
MetaAnalysis_SV <- Mouse_MetaAnalysis_SV_wOrthologs
```

```
# Rename Mouse_Rat Entrez annotation for Log2FC dataframe
MetaAnalysis_FoldChanges$MouseVsRat_EntrezGene.ID <- paste(MetaAnalysis_FoldChanges$Mouse_EntrezGene.ID,
                                                           MetaAnalysis_FoldChanges$Rat_EntrezGene.ID,
                                                           sep="_")
```

```
# Rename Mouse_Rat Entrez annotation for SV dataframe
MetaAnalysis_SV$MouseVsRat_EntrezGene.ID <- paste(MetaAnalysis_SV$Mouse_EntrezGene.ID,
                                                  MetaAnalysis_SV$Rat_EntrezGene.ID,
                                                  sep="_")
```

```
# Check the structure of the Log2FC dataframe
str(MetaAnalysis_FoldChanges)
```

```
## 'data.frame': 22789 obs. of 11 variables:
## $ Rat_EntrezGene.ID : chr "114087" "191569" "246307" "65041" ...
## $ Mouse_EntrezGene.ID : chr "23825" "18585" "66514" "20480" ...
## $ MouseVsRat_EntrezGene.ID : chr "23825_114087" "18585_191569" "66514_246307" "20480_65041" ...
## $ GSE30577_Rabies_vs_Control : num -0.521 1.872 NA 0.134 0.822 ...
## $ GSE42264_Measles_vs_Control : num 0.0928 0.0906 0.0443 -0.1149 0.0472 ...
## $ GSE44331_VSV_vs_Control : num -0.00553 0.0339 -0.0275 -0.19225 -0.1228 ...
## $ GSE51365_MVH68_WT_vs_Control: num -0.011 0.1377 0.0275 0.0508 -0.0837 ...
## $ GSE51365_MVH68_M_vs_Control : num 0.00693 0.0891 0.03023 0.0812 -0.095 ...
## $ GSE53784_WNV_vs_Control : num -0.0736 -0.4003 -1.0309 -0.2629 0.8745 ...
```

```
## $ GSE53784_JEV_vs_Control : num 0.0783 0.2109 -0.996 -0.0471 0.4395 ...
## $ GSE91074_VEEV_vs_Control : num -0.1555 0.0199 -0.2302 -0.2588 0.0919 ...
```

```
# Check the structure of the SV dataframe
str(MetaAnalysis_SV)
```

```
## 'data.frame': 22789 obs. of 11 variables:
## $ Rat_EntrezGene.ID : chr "114087" "191569" "246307" "65041" ...
## $ Mouse_EntrezGene.ID : chr "23825" "18585" "66514" "20480" ...
## $ MouseVsRat_EntrezGene.ID : chr "23825_114087" "18585_191569" "66514_246307" "20480_65041" ...
## $ GSE30577_Rabies_vs_Control : num 0.781 3.343 NA 1.338 1.128 ...
## $ GSE42264_Measles_vs_Control : num 0.00148 0.00141 0.0018 0.00159 0.00108 ...
## $ GSE44331_VSV_vs_Control : num 0.01018 0.00379 0.00519 0.00888 0.00784 ...
## $ GSE51365_MVH68_WT_vs_Control : num 0.00552 0.00613 0.00682 0.00798 0.00881 ...
## $ GSE51365_MVH68_M_vs_Control : num 0.00545 0.00612 0.00682 0.008 0.00882 ...
## $ GSE53784_WNV_vs_Control : num 0.00586 0.00632 0.00421 0.00281 0.00332 ...
## $ GSE53784_JEV_vs_Control : num 0.00586 0.00632 0.00421 0.00282 0.00332 ...
## $ GSE91074_VEEV_vs_Control : num 0.00239 0.02259 0.00431 0.00414 0.00198 ...
```

## 11) Comparison of Log2FC across datasets

```
# Check the column names in the MetaAnalysis dataframes
colnames(MetaAnalysis_FoldChanges)
```

```
## [1] "Rat_EntrezGene.ID" "Mouse_EntrezGene.ID"
## [3] "MouseVsRat_EntrezGene.ID" "GSE30577_Rabies_vs_Control"
## [5] "GSE42264_Measles_vs_Control" "GSE44331_VSV_vs_Control"
## [7] "GSE51365_MVH68_WT_vs_Control" "GSE51365_MVH68_M_vs_Control"
## [9] "GSE53784_WNV_vs_Control" "GSE53784_JEV_vs_Control"
## [11] "GSE91074_VEEV_vs_Control"
```

There are different ways to plot relationships across datasets:

1. Rank-rank hypergeometric overlap plots
2. Hierarchically clustered heatmaps

We can generally compare the DE results associated with different contrasts using a scatter plot and correlation analysis.

```
# Create a correlation matrix for Log2FC across datasets
# "pairwise.complete.obs" ignore any rows of DE results that do not have Log2FC
# for one of our columns
MetaAnalysis_CorMatrix_FoldChanges <- cor(as.matrix(MetaAnalysis_FoldChanges[, -c(1:3)]),
                                           use = "pairwise.complete.obs",
                                           method = "spearman")

# Check the correlation matrix
MetaAnalysis_CorMatrix_FoldChanges
```

##	GSE30577_Rabies_vs_Control		
##	GSE30577_Rabies_vs_Control	1.00000000	
##	GSE42264_Measles_vs_Control	0.14675164	
##	GSE44331_VSV_vs_Control	0.19172649	
##	GSE51365_MVH68_WT_vs_Control	0.01774524	
##	GSE51365_MVH68_M_vs_Control	-0.01817159	
##	GSE53784_WNV_vs_Control	0.35176909	
##	GSE53784_JEV_vs_Control	0.33712002	
##	GSE91074_VEEV_vs_Control	0.46330095	
##	GSE42264_Measles_vs_Control		
##	GSE30577_Rabies_vs_Control	0.14675164	
##	GSE42264_Measles_vs_Control	1.00000000	
##	GSE44331_VSV_vs_Control	0.16058484	
##	GSE51365_MVH68_WT_vs_Control	-0.00418835	
##	GSE51365_MVH68_M_vs_Control	0.02661880	
##	GSE53784_WNV_vs_Control	0.24596626	
##	GSE53784_JEV_vs_Control	0.24290161	
##	GSE91074_VEEV_vs_Control	0.30976676	
##	GSE44331_VSV_vs_Control		
##	GSE30577_Rabies_vs_Control	0.1917265	
##	GSE42264_Measles_vs_Control	0.1605848	
##	GSE44331_VSV_vs_Control	1.0000000	
##	GSE51365_MVH68_WT_vs_Control	0.1150817	
##	GSE51365_MVH68_M_vs_Control	0.1133153	
##	GSE53784_WNV_vs_Control	0.1612147	
##	GSE53784_JEV_vs_Control	0.1862596	
##	GSE91074_VEEV_vs_Control	0.2502848	
##	GSE51365_MVH68_WT_vs_Control		
##	GSE30577_Rabies_vs_Control	0.01774524	
##	GSE42264_Measles_vs_Control	-0.00418835	
##	GSE44331_VSV_vs_Control	0.11508169	
##	GSE51365_MVH68_WT_vs_Control	1.00000000	
##	GSE51365_MVH68_M_vs_Control	0.52913023	
##	GSE53784_WNV_vs_Control	-0.03381511	
##	GSE53784_JEV_vs_Control	-0.02096606	
##	GSE91074_VEEV_vs_Control	0.01657012	
##	GSE51365_MVH68_M_vs_Control		
##	GSE30577_Rabies_vs_Control	-0.018171586	
##	GSE42264_Measles_vs_Control	0.026618798	
##	GSE44331_VSV_vs_Control	0.113315346	
##	GSE51365_MVH68_WT_vs_Control	0.529130232	
##	GSE51365_MVH68_M_vs_Control	1.000000000	
##	GSE53784_WNV_vs_Control	-0.059384072	
##	GSE53784_JEV_vs_Control	-0.054283220	
##	GSE91074_VEEV_vs_Control	-0.009155205	
##	GSE53784_WNV_vs_Control	GSE53784_JEV_vs_Control	
##	GSE30577_Rabies_vs_Control	0.35176909	0.33712002
##	GSE42264_Measles_vs_Control	0.24596626	0.24290161
##	GSE44331_VSV_vs_Control	0.16121467	0.18625956
##	GSE51365_MVH68_WT_vs_Control	-0.03381511	-0.02096606
##	GSE51365_MVH68_M_vs_Control	-0.05938407	-0.05428322
##	GSE53784_WNV_vs_Control	1.00000000	0.77150650
##	GSE53784_JEV_vs_Control	0.77150650	1.00000000
##	GSE91074_VEEV_vs_Control	0.63233330	0.61308916




```
##                                GSE91074_VEEV_vs_Control
## GSE30577_Rabies_vs_Control      0.463300945
## GSE42264_Measles_vs_Control     0.309766756
## GSE44331_VSV_vs_Control         0.250284764
## GSE51365_MVH68_WT_vs_Control    0.016570117
## GSE51365_MVH68_M_vs_Control     -0.009155205
## GSE53784_WNV_vs_Control         0.632333296
## GSE53784_JEV_vs_Control         0.613089157
## GSE91074_VEEV_vs_Control        1.000000000
```

Each cell includes the correlation coefficient reflecting the similarity of the effect sizes for the comparison of between the contrast in the row and the according contrast in the column.

Correlation coefficient ranges between -1 to 1, with -1 being a perfect negative correlation and +1 being a perfect positive correlation


*# Illustrate the correlation matrix with hierarchically clustered heatmap*

```
# Blues Palette
# png("MetaAnalysis_CorMatrix_FoldChanges_1.png", 8, 5, "in", res = 300)
pheatmap(MetaAnalysis_CorMatrix_FoldChanges,
  display_numbers = TRUE,
  fontsize = 10,
  number_format = "%.2f",
  color = colorRampPalette(brewer.pal(5, "Blues"))(100),
  border_color = "black",
  number_color = "black")
```




```
# dev.off()

# Oranges Palette
# png("MetaAnalysis_CorMatrix_FoldChanges_2.png", 8, 5, "in", res = 300)
pheatmap(MetaAnalysis_CorMatrix_FoldChanges,
  display_numbers = TRUE,
  fontsize = 10,
  number_format = "%.2f",
  color = colorRampPalette(brewer.pal(5, "Oranges"))(100),
  border_color = "black",
  number_color = "black")
```




```
# dev.off()

# Blues-Yellows Palette
# png("MetaAnalysis_CorMatrix_FoldChanges_3.png", 8, 5, "in", res = 300)
pheatmap(MetaAnalysis_CorMatrix_FoldChanges,
  display_numbers = TRUE,
  fontsize = 10,
  number_format = "%.2f",
  color = hcl.colors(5, "BluYl"),
  border_color = "black",
  number_color = "black")
```



```
# dev.off()

# Viridis Palette
# png("MetaAnalysis_CorMatrix_FoldChanges_4.png", 8, 5, "in", res = 300)
pheatmap(MetaAnalysis_CorMatrix_FoldChanges,
  display_numbers = TRUE,
  fontsize = 10,
  number_format = "%.2f",
  color = viridis(5),
  border_color = "black",
  number_color = "black")
```



```
# dev.off()
```

```
# The groups are placed in order by similarity, as determined by hierarchical clustering
# The lines ("tree branches") on the left and top illustrate that similarity (clustering)
# using a "dendrogram"
```

## 12) Meta-analysis with random effect models

The meta-analysis is performed using the effect sizes (Log2FC) and sampling variances (SV) for each gene stored in the objects *MetaAnalysis\_FoldChanges* and *MetaAnalysis\_SV*.

For any particular gene, it is likely that some datasets may be missing DE results. This is especially true for genes that have low levels of expression and may not be detected by less sensitive assays. It is also likely to be true for genes that were discovered more recently (i.e., not targeted by older microarray platforms) or that lack a clear ortholog in rat/mouse.


We can only run a meta-analysis if there DE results from more than 1 statistical contrast. Since the DE results from the same study (dataset) are often artificially correlated (especially if they use the same control group as the comparison), we would prefer that there are results from more than 1 dataset (not just more than 1 statistical contrast)

Before the meta-analysis, we need to decide the minimum number of DE results allowed for a gene to be included.

```
# Calculate the number of NAs (the number of statistical contrasts lacking DE
# results) in each row (for each gene)
```

```
MetaAnalysis_FoldChanges_NAsPerRow <- apply(MetaAnalysis_FoldChanges[, -c(1:3)],
      1,
      function(y) sum(is.na(y)))

# Visualize the distribution of the NAs with histogram
hist(MetaAnalysis_FoldChanges_NAsPerRow)
```



```
# Visualize the distribution of the NAs with table
table(MetaAnalysis_FoldChanges_NAsPerRow)
```

```
## MetaAnalysis_FoldChanges_NAsPerRow
##  0  1  2  3  4  5  6  7  8
## 9979 5767 1307 578 929 1497 1874 611 247
```

```
# This table tells us how many genes (rows) contain each number of NAs
# Ex: There are 9979 genes that contain no NA, meaning that these 9979 genes can
# be found across all datasets
# Ex: There are 5767 genes that contain 1 NA in 1 of the 8 contrasts
```

```
# Create a function to run the meta-analysis
RunBasicMetaAnalysis <- function(NumberOfComparisons,
      CutoffForNAs,
      MetaAnalysis_FoldChanges,
      MetaAnalysis_SV){
```

```

# Calculate the number of NAs (the number of statistical contrasts lacking DE
# results) in each row (for each gene)
MetaAnalysis_FoldChanges_NAsPerRow <- apply(MetaAnalysis_FoldChanges[, -c(1:3)],
      1,
      function(y) sum(is.na(y)))

# Print the number of NAs per gene
print("Table of # of NAs per Row (Gene):")
print(table(MetaAnalysis_FoldChanges_NAsPerRow))

# Filter the genes with too many NAs
MetaAnalysis_FoldChanges_ForMeta <- MetaAnalysis_FoldChanges[MetaAnalysis_FoldChanges_NAsPerRow < CutOffForNAs,]
MetaAnalysis_SV_ForMeta <- MetaAnalysis_SV[MetaAnalysis_FoldChanges_NAsPerRow < CutOffForNAs,]

# Print the structure of the filtered FC
print("MetaAnalysis_FoldChanges_ForMeta:")
print(str(MetaAnalysis_FoldChanges_ForMeta))

# Print the structure of the filtered SV
print("MetaAnalysis_SV_ForMeta:")
print(str(MetaAnalysis_SV_ForMeta))

# Create a matrix with 6 columns filled with NAs to store the meta-analysis results
metaOutput <- matrix(NA, nrow(MetaAnalysis_FoldChanges_ForMeta), 6)

# Loop through each gene to perform meta-analysis
for(i in c(1:nrow(MetaAnalysis_FoldChanges_ForMeta))){

  # Extract the Log2FC and SV value for the current gene in numeric format
  # Remove the annotation columns prior to extraction
  fc <- as.numeric(MetaAnalysis_FoldChanges_ForMeta[i, -c(1:3)])
  sv <- as.numeric(MetaAnalysis_SV_ForMeta[i, -c(1:3)])

  # Perform meta-analysis using random-effect model that treat Log2FC across
  # studies as random effects

  # Set the flag as FALSE
  # This flag is used to determine if the current iteration should be skipped
  # due to an error
  skip_to_next <- FALSE

  # The "tryCatch" function will execute the code within "{}" block. If an error
  # occurs, the code in the "error" block is executed
  tryCatch({
    # Perform meta-analysis that treat Log2FC across studies as random effects
    TempMeta <- rma(fc, sv)
    # Store estimated Log2FC
    metaOutput[i,1] <- TempMeta$b
    # Store standard error of estimate
    metaOutput[i,2] <- TempMeta$se
    # Store p-value
    metaOutput[i,3] <- TempMeta$pval
    # Store lower bound of the confidence interval

```

```

    metaOutput[i,4] <- TempMeta$ci.lb
    # Store the upper bound of the confidence interval
    metaOutput[i,5] <- TempMeta$ci.ub
    # Store the number of comparisons with available data
    metaOutput[i,6] <- NumberOfComparisons-sum(is.na(fc))
  },
  # If an error occurs during the meta-analysis, the "error" function sets
  # "skip_to_next" to TRUE
  error = function(e){skip_to_next <- TRUE})

  # If "skip_to_next" is TRUE, the "next" statement skips the current iteration
  # and move to the next gene
  if(skip_to_next) next

  # Remove temporary variables
  rm(fc, sv)
}

# Name the columns in the output
colnames(metaOutput) <- c("Log2FC_estimate",
                          "SE",
                          "pval",
                          "CI_lb",
                          "CI_ub",
                          "Number_Of_Comparisons")

# Assign the combined mouse-rat entrez ID as row names of the output
row.names(metaOutput) <- MetaAnalysis_FoldChanges_ForMeta[,3]

# Print the structure of the output
print("metaOutput:")
print(str(metaOutput))

# Print the top of the output
print("Top of metaOutput:")
print(head(metaOutput))

# Print the bottom of the output
print("Bottom of metaOutput:")
print(tail(metaOutput))

# Change the format of the output to dataframe for the final list
metaOutput <- as.data.frame(metaOutput)

# Return the output and the annotation as separated lists
return(list(metaOutput = metaOutput,
            MetaAnalysis_Annotation = MetaAnalysis_FoldChanges_ForMeta[, c(1:3)],
            MetaAnalysis_FoldChanges_ForMeta = MetaAnalysis_FoldChanges_ForMeta,
            MetaAnalysis_SV_ForMeta = MetaAnalysis_SV_ForMeta))
}

# Set up number of comparisons and cut off for NAs
# The number of NA = CutOffForNAs - 1

```

```

# Ex: 0 NA => CutOffForNA = 1
# Ex: 1 NA => CutOffForNA = 2

# There are 8 contrasts and we want genes that are available in all 8 contrasts
NumberOfComparisons = 8
CutOffForNAs = 1

# Function use
# Meta-analysis with 0 NA
MetaAnalysis_Results_ONA <- suppressWarnings(
  RunBasicMetaAnalysis(NumberOfComparisons,
                        CutOffForNAs,
                        MetaAnalysis_FoldChanges,
                        MetaAnalysis_SV)
)

## [1] "Table of # of NAs per Row (Gene):"
## MetaAnalysis_FoldChanges_NAsPerRow
##    0    1    2    3    4    5    6    7    8
## 9979 5767 1307  578  929 1497 1874  611  247
## [1] "MetaAnalysis_FoldChanges_ForMeta:"
## 'data.frame':    9979 obs. of  11 variables:
## $ Rat_EntrezGene.ID      : chr  "114087" "191569" "65041" "25437" ...
## $ Mouse_EntrezGene.ID    : chr  "23825" "18585" "20480" "13726" ...
## $ MouseVsRat_EntrezGene.ID : chr  "23825_114087" "18585_191569" "20480_65041" "13726_25437" ...
## $ GSE30577_Rabies_vs_Control : num -0.521 1.872 0.134 0.822 4.32 ...
## $ GSE42264_Measles_vs_Control : num 0.0928 0.0906 -0.1149 0.0472 0.164 ...
## $ GSE44331_VSV_vs_Control : num -0.00553 0.0339 -0.19225 -0.1228 0.2894 ...
## $ GSE51365_MVH68_WT_vs_Control: num -0.011 0.1377 0.0508 -0.0837 0.0858 ...
## $ GSE51365_MVH68_M_vs_Control : num 0.00693 0.0891 0.0812 -0.095 0.0631 ...
## $ GSE53784_WNV_vs_Control : num -0.0736 -0.4003 -0.2629 0.8745 0.5851 ...
## $ GSE53784_JEV_vs_Control : num 0.0783 0.2109 -0.0471 0.4395 1.3745 ...
## $ GSE91074_VEEV_vs_Control : num -0.1555 0.0199 -0.2588 0.0919 1.5468 ...
## NULL
## [1] "MetaAnalysis_SV_ForMeta:"
## 'data.frame':    9979 obs. of  11 variables:
## $ Rat_EntrezGene.ID      : chr  "114087" "191569" "65041" "25437" ...
## $ Mouse_EntrezGene.ID    : chr  "23825" "18585" "20480" "13726" ...
## $ MouseVsRat_EntrezGene.ID : chr  "23825_114087" "18585_191569" "20480_65041" "13726_25437" ...
## $ GSE30577_Rabies_vs_Control : num 0.781 3.343 1.338 1.128 0.501 ...
## $ GSE42264_Measles_vs_Control : num 0.00148 0.00141 0.00159 0.00108 0.0075 ...
## $ GSE44331_VSV_vs_Control : num 0.01018 0.00379 0.00888 0.00784 0.00616 ...
## $ GSE51365_MVH68_WT_vs_Control: num 0.00552 0.00613 0.00798 0.00881 0.02459 ...
## $ GSE51365_MVH68_M_vs_Control : num 0.00545 0.00612 0.008 0.00882 0.0246 ...
## $ GSE53784_WNV_vs_Control : num 0.00586 0.00632 0.00281 0.00332 0.00912 ...
## $ GSE53784_JEV_vs_Control : num 0.00586 0.00632 0.00282 0.00332 0.00912 ...
## $ GSE91074_VEEV_vs_Control : num 0.00239 0.02259 0.00414 0.00198 0.02045 ...
## NULL
## [1] "metaOutput:"
## num [1:9979, 1:6] -0.0108 0.0309 -0.1138 0.1782 0.9453 ...
## - attr(*, "dimnames")=List of 2
## ..$ : chr [1:9979] "23825_114087" "18585_191569" "20480_65041" "13726_25437" ...
## ..$ : chr [1:6] "Log2FC_estimate" "SE" "pval" "CI_lb" ...

```



```
## NULL
## [1] "Top of metaOutput:"
##           Log2FC_estimate      SE      pval      CI_lb      CI_ub
## 23825_114087    -0.01078298 0.03937450 0.78419462 -0.087955577 0.06638962
## 18585_191569      0.03088441 0.07607720 0.68477087 -0.118224148 0.17999298
## 20480_65041     -0.11381481 0.05041799 0.02398155 -0.212632242 -0.01499737
## 13726_25437      0.17821127 0.13728824 0.19425947 -0.090868738 0.44729128
## 16952_25380      0.94531851 0.42587215 0.02643753 0.110624426 1.78001259
## 338355_362528    0.11954213 0.06416940 0.06247423 -0.006227578 0.24531184
##           Number_Of_Comparisons
## 23825_114087              8
## 18585_191569              8
## 20480_65041              8
## 13726_25437              8
## 16952_25380              8
## 338355_362528            8
## [1] "Bottom of metaOutput:"
##           Log2FC_estimate      SE      pval      CI_lb      CI_ub
## 93694_NA      1.106428030 0.38228846 0.003800982 0.35715641 1.85569965
## 94175_NA      0.009214019 0.02539712 0.716755989 -0.04056343 0.05899147
## 97775_NA     -0.035928004 0.02458445 0.143902466 -0.08411264 0.01225663
## 97848_NA      0.186988885 0.11793637 0.112851308 -0.04416216 0.41813993
## 99100_NA     -0.068228497 0.04832398 0.157980227 -0.16294176 0.02648477
## 99662_NA     -0.080573165 0.03286429 0.014218582 -0.14498600 -0.01616033
##           Number_Of_Comparisons
## 93694_NA              8
## 94175_NA              8
## 97775_NA              8
## 97848_NA              8
## 99100_NA              8
## 99662_NA              8
```

```
# Separate the meta-analysis output and annotation
# 0 NA
metaOutput_ONA <- MetaAnalysis_Results_ONA[[1]]
MetaAnalysis_Annotation_ONA <- MetaAnalysis_Results_ONA[[2]]
MetaAnalysis_FoldChanges_ForMeta_ONA <- MetaAnalysis_Results_ONA[[3]]
MetaAnalysis_SV_ForMeta_ONA <- MetaAnalysis_Results_ONA[[4]]
```

### 13) Correction of p-value using Benjamini-Hochberg method

```
# Import database containing more detailed gene annotation
HOM_MouseVsRat <- read.csv("HOM_MouseVsRat_20240425.csv", header = TRUE, row.names = 1)

# Check the names of the columns of the database
colnames(HOM_MouseVsRat)
```

```
## [1] "DB.Class.Key"
## [2] "Mouse_Common.Organism.Name"
## [3] "Mouse_NCBI.Taxon.ID"
## [4] "Mouse_Symbol"
```

```
## [5] "Mouse_EntrezGene.ID"
## [6] "Mouse_Mouse.MGI.ID"
## [7] "Mouse_HGNC.ID"
## [8] "Mouse_OMIM.Gene.ID"
## [9] "Mouse_Genetic.Location"
## [10] "Mouse_Genome.Coordinates..mouse..GRCh38.human..GRCh38."
## [11] "Mouse_Name"
## [12] "Mouse_Synonyms"
## [13] "Rat_Common.Organism.Name"
## [14] "Rat_NCBI.Taxon.ID"
## [15] "Rat_Symbol"
## [16] "Rat_EntrezGene.ID"
## [17] "Rat_Mouse.MGI.ID"
## [18] "Rat_HGNC.ID"
## [19] "Rat_OMIM.Gene.ID"
## [20] "Rat_Genetic.Location"
## [21] "Rat_Genome.Coordinates..mouse..GRCh38.human..GRCh38."
## [22] "Rat_Name"
## [23] "Rat_Synonyms"
```

*# Change the format of the column names to character*

```
HOM_MouseVsRat$Mouse_EntrezGene.ID <- as.character(HOM_MouseVsRat$Mouse_EntrezGene.ID)
HOM_MouseVsRat$Rat_EntrezGene.ID <- as.character(HOM_MouseVsRat$Rat_EntrezGene.ID)
```

*# Create a function to correct FDR and extract genes with certain threshold of FDR  
# and Log2FC*

```
FalseDiscoveryCorrection <- function(NumberOfNAs,
                                     metaOutput,
                                     HOM_MouseVsRat,
                                     MetaAnalysis_Annotation){
```

*# Calculate the FDR (q-value) for each p-value using the Benjamini-Hochberg method*  
tempPvalAdjMeta <- mt.rawp2adjp(metaOutput[, 3], proc = c("BH"))

*# Re-order the FDR to match with the original order*  
metaPvalAdj <- tempPvalAdjMeta\$adjp[order(tempPvalAdjMeta\$index), ]

*# Add the FDR column to the meta-analysis output*  
metaOutputFDR <- cbind(metaOutput, FDR = metaPvalAdj[, 2])

*# Rename the column to "FDR"*  
colnames(metaOutputFDR)[7] <- "FDR"

*# Print the structure of meta-analysis output with FDR*  
print("Meta-analysis output with FDR:")  
print(str(metaOutputFDR))

*# Add annotations to the output*  
TempDF <- cbind(metaOutputFDR, MetaAnalysis\_Annotation)

*# Add detailed gene annotations for mouse genes*  
TempDF2 <- join(TempDF,  
 HOM\_MouseVsRat[, c(4:5, 9:11)],  
 by = "Mouse\_EntrezGene.ID",

```

        type = "left",
        match = "first")

# Add detailed gene annotations for rat genes
TempDF3 <- join(TempDF2,
               HOM_MouseVsRat[, c(15:16, 20:22)],
               by = "Rat_EntrezGene.ID",
               type = "left",
               match = "first")

# Save the annotated results to the meta-analysis output
metaOutputFDR_annotated <- TempDF3

# Export the annotated meta-analysis output into the working directory
# (remove the row names as entrez ID have been merged into the dataframe)
write.csv(metaOutputFDR_annotated,
         paste("metaOutputFDR_Annotated_", NumberOfNAs, "NA.csv", sep = ""),
         row.names = FALSE)

# Order the results by p-value
# The results are ordered by p-values because close p-values can result in the same
# FDR due to the restriction of the algorithm (the bending of FDR)
metaOutputFDR_OrderbyPval <- metaOutputFDR_annotated[order(metaOutputFDR_annotated$pval), ]

# Filter the ordered results by Log2FC threshold at 2
metaOutputFDR_OrderbyPval_Log2FC_2 <- metaOutputFDR_annotated %>%
  filter(abs(Log2FC_estimate) >= 2) %>%
  arrange(pval)

# Filter the ordered results by Log2FC threshold at 1
metaOutputFDR_OrderbyPval_Log2FC_1 <- metaOutputFDR_annotated %>%
  filter(abs(Log2FC_estimate) >= 1) %>%
  arrange(pval)

# Filter the ordered results by Log2FC threshold at 0.5
metaOutputFDR_OrderbyPval_Log2FC_0.5 <- metaOutputFDR_annotated %>%
  filter(abs(Log2FC_estimate) >= 0.5) %>%
  arrange(pval)

# Export the ordered, annotated meta-analysis output into the working directory
# (remove the row names as entrez ID have been merged into the dataframe)
write.csv(metaOutputFDR_OrderbyPval,
         paste("metaOutputFDR_OrderedByPval_", NumberOfNAs, "NA.csv", sep = ""),
         row.names = FALSE)

# Export the ordered, annotated, filtered results at Log2FC of 2
write.csv(metaOutputFDR_OrderbyPval_Log2FC_2,
         paste("metaOutputFDR_OrderedByPval_Log2FC_2_", NumberOfNAs, "NA.csv", sep = ""),
         row.names = FALSE)

# Export the ordered, annotated, filtered results at Log2FC of 1
write.csv(metaOutputFDR_OrderbyPval_Log2FC_1,
         paste("metaOutputFDR_OrderedByPval_Log2FC_1_", NumberOfNAs, "NA.csv", sep = ""),

```

```

        row.names = FALSE)

# Export the ordered, annotated, filtered results at Log2FC of 0.5
write.csv(metaOutputFDR_OrderbyPval_Log2FC_0.5,
          paste("metaOutputFDR_OrderedByPval_Log2FC_0.5_", NumberOfNAs, "NA.csv", sep = ""),
          row.names = FALSE)

# Print genes with FDR < 0.1
print("# of genes that are statistically significant following loose FDR correction (FDR < 0.10):")
print(sum(metaOutputFDR_annotated$FDR < 0.10, na.rm = TRUE))

# Print genes with FDR < 0.05
print("# of genes that are statistically significant following traditional FDR correction (FDR < 0.05):")
print(sum(metaOutputFDR_annotated$FDR < 0.05, na.rm = TRUE))

print("# of genes that are statistically significant following traditional FDR correction (FDR < 0.05):")
print(sum(metaOutputFDR_OrderbyPval_Log2FC_2$FDR < 0.05, na.rm = TRUE))

print("# of genes that are statistically significant following traditional FDR correction (FDR < 0.05):")
print(sum(metaOutputFDR_OrderbyPval_Log2FC_1$FDR < 0.05, na.rm = TRUE))

print("# of genes that are statistically significant following traditional FDR correction (FDR < 0.05):")
print(sum(metaOutputFDR_OrderbyPval_Log2FC_0.5$FDR < 0.05, na.rm = TRUE))

# Print top results in mouse genes
print("Top 20 results ordered by p-values in mouse genes:")
print(head(metaOutputFDR_OrderbyPval$Mouse_Symbol, 20))

# Print top results in rat genes
print("Top 20 results ordered by p-values in rat genes:")
print(head(metaOutputFDR_OrderbyPval$Rat_Symbol, 20))

# Print top results in mouse genes with |Log2FC| >= 2
print("Top 20 results ordered by p-values in mouse genes with |Log2FC| >= 2:")
print(head(metaOutputFDR_OrderbyPval_Log2FC_2$Mouse_Symbol, 20))

# Print top results in rat genes with |Log2FC| >= 2
print("Top 20 results ordered by p-values in rat genes with |Log2FC| >= 2:")
print(head(metaOutputFDR_OrderbyPval_Log2FC_2$Rat_Symbol, 20))

# Print top results in mouse genes with |Log2FC| >= 1
print("Top 20 results ordered by p-values in mouse genes with |Log2FC| >= 1:")
print(head(metaOutputFDR_OrderbyPval_Log2FC_1$Mouse_Symbol, 20))

# Print top results in rat genes with |Log2FC| >= 1
print("Top 20 results ordered by p-values in rat genes with |Log2FC| >= 1:")
print(head(metaOutputFDR_OrderbyPval_Log2FC_1$Rat_Symbol, 20))

# Print top results in mouse genes with |Log2FC| >= 0.5
print("Top 20 results ordered by p-values in mouse genes with |Log2FC| >= 0.5:")
print(head(metaOutputFDR_OrderbyPval_Log2FC_0.5$Mouse_Symbol, 20))

# Print top results in rat genes with |Log2FC| >= 0.5

```

```

print("Top 20 results ordered by p-values in rat genes with |Log2FC| >= 0.5:")
print(head(metaOutputFDR_OrderbyPval_Log2FC_0.5$Rat_Symbol, 20))

# Return the annotated output and ordered output with FDR
return(list(metaOutputFDR = metaOutputFDR,
            metaOutputFDR_annotated = metaOutputFDR_annotated,
            metaOutputFDR_OrderbyPval = metaOutputFDR_OrderbyPval,
            metaOutputFDR_OrderbyPval_Log2FC_2 = metaOutputFDR_OrderbyPval_Log2FC_2,
            metaOutputFDR_OrderbyPval_Log2FC_1 = metaOutputFDR_OrderbyPval_Log2FC_1,
            metaOutputFDR_OrderbyPval_Log2FC_0.5 = metaOutputFDR_OrderbyPval_Log2FC_0.5))

# Remove temporary objects
rm(tempPvalAdjMeta, metaPvalAdj, TempDF, TempDF2)
}

```

```

# Function use

```

```

# Meta-analysis with 0 NA
metaOutputFDR_all_ONA <- FalseDiscoveryCorrection(0,
                                                    metaOutput_ONA,
                                                    HOM_MouseVsRat,
                                                    MetaAnalysis_Annotation_ONA)

```

```

## [1] "Meta-analysis output with FDR:"
## 'data.frame': 9979 obs. of 7 variables:
## $ Log2FC_estimate : num -0.0108 0.0309 -0.1138 0.1782 0.9453 ...
## $ SE : num 0.0394 0.0761 0.0504 0.1373 0.4259 ...
## $ pval : num 0.7842 0.6848 0.024 0.1943 0.0264 ...
## $ CI_lb : num -0.088 -0.1182 -0.2126 -0.0909 0.1106 ...
## $ CI_ub : num 0.0664 0.18 -0.015 0.4473 1.78 ...
## $ Number_Of_Comparisons: num 8 8 8 8 8 8 8 8 8 ...
## $ FDR : num 0.866 0.79 0.118 0.356 0.123 ...
## NULL
## [1] "# of genes that are statistically significant following loose FDR correction (FDR < 0.10):"
## [1] 1665
## [1] "# of genes that are statistically significant following traditional FDR correction (FDR < 0.05)"
## [1] 718
## [1] "# of genes that are statistically significant following traditional FDR correction (FDR < 0.05)"
## [1] 61
## [1] "# of genes that are statistically significant following traditional FDR correction (FDR < 0.05)"
## [1] 123
## [1] "# of genes that are statistically significant following traditional FDR correction (FDR < 0.05)"
## [1] 139
## [1] "Top 20 results ordered by p-values in mouse genes:"
## [1] "Ppp2r5a" "Cdhr1" "Sema5b" "Sema7a"
## [5] "Thop1" "Cpd" "Col6a1" "Col16a1"
## [9] "Spcs2" "Ldaf1" "Hras" "Zfp108"
## [13] "Clec14a" "Smc4" "Caprin1" "1700001022Rik"
## [17] "Asap1" "Adamt15" "Utp3" "Mapk8ip3"
## [1] "Top 20 results ordered by p-values in rat genes:"
## [1] "Ppp2r5a" "Cdhr1" "Sema5b" "Sema7a" "Thop1" "Cpd"
## [7] "Col6a1" "Col16a1" "Spcs2" "Ldaf1" "Hras" NA

```

```

## [13] "Clec14a" "Smc4" "Caprin1" "C3h9orf50" "Asap1" "Adamts15"
## [19] "Utp3" "Mapk8ip3"
## [1] "Top 20 results ordered by p-values in mouse genes with |Log2FC| >= 2:"
## [1] "Gbp3" "Ifit1" "Usp18" "B2m" "Gbp2" "Oasl2" "Bst2"
## [8] "Iigp1" "Irgm1" "Stat1" "Gbp7" "Trim30a" "H2-K1" "Ifitm3"
## [15] "Isg15" "Cd52" "Plac8" "Ifi44" "Psmb9" "Cxc110"
## [1] "Top 20 results ordered by p-values in rat genes with |Log2FC| >= 2:"
## [1] "Gbp4" "Ifit1" "Usp18" "B2m" NA "Oasl2" "Bst2" NA
## [9] "Irgm" NA "Gbp7" NA NA NA "Isg15" "Cd52"
## [17] "Plac8" "Ifi44" "Psmb9" "Cxc110"
## [1] "Top 20 results ordered by p-values in mouse genes with |Log2FC| >= 1:"
## [1] "Gbp3" "Ifit1" "Usp18" "B2m" "Gbp2" "Oasl2" "Bst2"
## [8] "Iigp1" "Irgm1" "Stat1" "Gbp7" "Trim30a" "H2-K1" "Ifitm3"
## [15] "Isg15" "Cd52" "Plac8" "Ifi44" "Psmb9" "Cxc110"
## [1] "Top 20 results ordered by p-values in rat genes with |Log2FC| >= 1:"
## [1] "Gbp4" "Ifit1" "Usp18" "B2m" NA "Oasl2" "Bst2" NA
## [9] "Irgm" NA "Gbp7" NA NA NA "Isg15" "Cd52"
## [17] "Plac8" "Ifi44" "Psmb9" "Cxc110"
## [1] "Top 20 results ordered by p-values in mouse genes with |Log2FC| >= 0.5:"
## [1] "Gbp3" "Ly86" "Ifit1" "Usp18" "B2m" "Gbp2" "Oasl2"
## [8] "Bst2" "Iigp1" "Irgm1" "Stat1" "Gbp7" "Trim30a" "H2-K1"
## [15] "Ifitm3" "Isg15" "Cd52" "Plac8" "Ifi44" "Psmb9"
## [1] "Top 20 results ordered by p-values in rat genes with |Log2FC| >= 0.5:"
## [1] "Gbp4" "Ly86" "Ifit1" "Usp18" "B2m" NA "Oasl2" "Bst2" NA
## [10] "Irgm" NA "Gbp7" NA NA NA "Isg15" "Cd52" "Plac8"
## [19] "Ifi44" "Psmb9"

```

```

# Because all 6 datasets are from mouse models, we would focus more on mouse
# gene symbols

```

```

# Separate the FDR outputs into individual objects

```

```

# Meta-analysis with FDR output only

```

```

metaOutputFDR_ONA <- metaOutputFDR_all_ONA[[1]]

```

```

# Meta-analysis with FDR output with annotations

```

```

metaOutputFDR_Annotated_ONA <- metaOutputFDR_all_ONA[[2]]

```

```

# Meta-analysis with FDR output ordered by p-values

```

```

metaOutputFDR_OrderByPval_ONA <- metaOutputFDR_all_ONA[[3]]

```

```

# Meta-analysis with FDR output ordered by p-values filtered by Log2FC at 2

```

```

metaOutputFDR_OrderbyPval_Log2FC_2_ONA <- metaOutputFDR_all_ONA[[4]]

```

```

# Meta-analysis with FDR output ordered by p-values filtered by Log2FC at 1

```

```

metaOutputFDR_OrderbyPval_Log2FC_1_ONA <- metaOutputFDR_all_ONA[[5]]

```

```

# Meta-analysis with FDR output ordered by p-values filtered by Log2FC at 0.5

```


```

metaOutputFDR_OrderbyPval_Log2FC_0.5_ONA <- metaOutputFDR_all_ONA[[6]]

```

#### 14) Forest plots for statistically significant genes

```
# Check the range of Log2FC values  
hist(metaOutputFDR_0NA[, 1], breaks = 40)
```



```
# Create a function to generate forest plot  
MakeForestPlots <- function(metaOutputFDR_annotated,  
                             GeneSymbol,  
                             species,  
                             MetaAnalysis_FoldChanges_ForMeta,  
                             MetaAnalysis_SV_ForMeta){  
  
  # "gene_row" object always return a dataframe with a lot of NA row so only row  
  # with the least NA values across columns is extracted for "gene_row"  
  if (species == "Mouse"){  
    gene_row <- metaOutputFDR_annotated[metaOutputFDR_annotated$Mouse_Symbol == GeneSymbol, ]  
    gene_row <- gene_row[which.max(rowSums(!is.na(gene_row))), ]  
  } else if (species == "Rat"){  
    gene_row <- metaOutputFDR_annotated[metaOutputFDR_annotated$Rat_Symbol == GeneSymbol, ]  
    gene_row <- gene_row[which.max(rowSums(!is.na(gene_row))), ]  
  } else {  
    stop("Please use either 'Mouse' or 'Rat' to indicate whether you are using annotation for mouse or rat")  
  }  
}
```

```

# Check if the gene exists
if (nrow(gene_row) == 0){
  stop(paste("No gene found for symbol:", GeneSymbol))
}

# Extract gene symbols for specific species
MouseGeneSymbol <- gene_row$Mouse_Symbol
RatGeneSymbol <- gene_row$Rat_Symbol

# Extract Log2FC and SV
if (species == "Mouse"){
  fc <- as.numeric(MetaAnalysis_FoldChanges_ForMeta[MetaAnalysis_FoldChanges_ForMeta$Mouse_EntrezGene
  sv <- as.numeric(MetaAnalysis_SV_ForMeta[MetaAnalysis_FoldChanges_ForMeta$Mouse_EntrezGene.ID == gene
} else if (species == "Rat"){
  fc <- as.numeric(MetaAnalysis_FoldChanges_ForMeta[MetaAnalysis_FoldChanges_ForMeta$Rat_EntrezGene.ID
  sv <- as.numeric(MetaAnalysis_SV_ForMeta[MetaAnalysis_FoldChanges_ForMeta$Rat_EntrezGene.ID == gene
}

# Create the filename for the output plot
filename <- paste("ForestPlot_Mouse_", GeneSymbol, "_Rat_", RatGeneSymbol, ".png", sep = "")

# Open a PNG device with specified resolution
png(filename, height = 5, width = 8, units = "in", res = 300)

# Create the forest plot
forest.rma(rma(fc, sv),
           slab = colnames(MetaAnalysis_FoldChanges_ForMeta)[-c(1:3)],
           xlim = c(-10, 10),
           cex = 0.75)

# Add labels to the plot
mtext(paste("Mouse:", GeneSymbol, "_Rat:", RatGeneSymbol, sep = ""),
      line = -1.5,
      cex = 1.5)

# Close the PNG device
dev.off()
}

```

```

# Function use

# Top genes ordered by p-values

# Ppp2r5a
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Ppp2r5a",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)

```

```

## pdf
## 2

```



```
# Cdhr1
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Cdhr1",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Sema5b
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Sema5b",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Sema7a
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Sema7a",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Thop1
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Thop1",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Cpd
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Cpd",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Col6a1
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Col6a1",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Col16a1
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Col16a1",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Spcs2
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Spcs2",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Function use

# Top genes ordered by p-values with |Log2FC| >= 1
```

```
# Gbp3
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Gbp3",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Ifit1
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Ifit1",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Usp18
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Usp18",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# B2m
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "B2m",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Gbp2
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Gbp2",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Oasl2
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Oasl2",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Bst2
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Bst2",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Bst2
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Bst2",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Iigp1
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Iigp1",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Irgm1
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Irgm1",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Stat1
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Stat1",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Gbp7
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Gbp7",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Trim30a
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Trim30a",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# H2-K1
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "H2-K1",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Ifitm3
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Ifitm3",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Isg15
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Isg15",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Cd52
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Cd52",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Plac8
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Plac8",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Ifi44
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Ifi44",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Psmb9
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Psmb9",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

```
# Psmb9
MakeForestPlots(metaOutputFDR_Annotated_ONA,
                 "Cxcl10",
                 "Mouse",
                 MetaAnalysis_FoldChanges_ForMeta_ONA,
                 MetaAnalysis_SV_ForMeta_ONA)
```

```
## pdf
## 2
```

## Interpretation of Forest Plots

### 1. Study Labels (Left Side)

- The labels on the left side of the plot indicate the individual contrasts included in the meta-analysis.

### 2. Effect Sizes and Confidence Intervals (Right side)

- Each horizontal line represents the effect size (Log2FC) for a particular contrast along with its confidence interval. The squares represent the point of estimate of the effect size for each contrast. The horizontal lines extending from the squares are the confidence intervals for the effect size.

- The size of the squares represent the weight of each contrast in the meta-analysis, with larger square indicating more weight.

### 3. Overall Effect (Bottom)

- The diamond shape at the bottom of the plot represents the overall effect size calculated from the meta-analysis (random-effects model).
- The width of the diamond represents the confidence interval for the overall effect size.

### 4. X-axis (Observed Outcome)

- The x-axis shows the scale/range for the effect sizes (Log2FC).
- The vertical dash line at 0 indicate no effect. Effect sizes to the left of this line suggest a decrease, while those to the right suggest an increase.

## 15) Retrieval the function of statistically significant gene

```
# Create a function to get gene function from NCBI using Entrez Gene ID
GetGeneFunctionByID <- function(NumberOfNAs, Log2FCThreshold, EntrezGeneList) {

  # Create an empty list to store the result
  gene_info_list <- list()

  # Loop through each Entrez Gene ID
  for(i in EntrezGeneList){

    # Print the message indicating which gene is being processed
    print(paste("Processing Entrez Gene ID:", i, sep = ""))

    # Retrieve the gene summary using the Entrez Gene ID
    gene_summary <- tryCatch({
      entrez_summary(db = "gene", id = i)
    },

    # In case of error, print a warning and return NULL
    error = function(e){
      warning(paste("Error in retrieving data for Entrez Gene ID:", i, sep = "", e$message))
      return(NULL)
    })

    # Check if the gene summary was successfully retrieved
    if(!is.null(gene_summary)){
      # If the gene summary is not NULL, extract relevant info
      gene_info_list[[i]] <- list(
        # ID
        Entrez_ID = gene_summary$uid,
        # Gene symbol
        Gene_symbol = gene_summary$name,
        # Full name of gene
        Gene_description = gene_summary$description,
```

```

    # Location on chromosome
    Chromosome = gene_summary$chromosome,
    # Detailed location
    Map_location = gene_summary$maplocation,
    # Scientific name of model
    Model_scientific_name = gene_summary$organism$scientificname,
    # Common name of model
    Model_common_name = gene_summary$organism$commonname,
    # Function of the gene
    Gene_function = gene_summary$summary
  )
} else {
  # If the gene summary is NULL, return NA for all columns
  gene_info_list[[i]] <- list(
    Entrez_ID = i,
    Gene_symbol = NA,
    Gene_description = NA,
    Chromosome = NA,
    Map_location = NA,
    Model_scientific_name = NA,
    Model_common_name = NA,
    Gene_function = NA
  )
}
# Introduce a delay of 0.5 seconds between request to avoid hitting API rate limit
Sys.sleep(0.5)
}

# Convert the final list into a dataframe
gene_info_df <- do.call(rbind, lapply(gene_info_list, as.data.frame))
rownames(gene_info_df) <- NULL

# Export the dataframe of gene function into working directory
write.csv(gene_info_df,
          paste("Gene_function_Log2FC_", Log2FCThreshold, "_", NumberOfNAs, "NA.csv", sep = ""))

# Return the dataframe of gene function
return(gene_info_df)
}

```

```

# Extract gene entrez ID for genes with FDR < 0.05 & |Log2FC| > 1
EntrezGeneList_Log2FC_1_ONA <- metaOutputFDR_OrderbyPval_Log2FC_1_ONA %>%
  filter(FDR < 0.05) %>%
  pull(Mouse_EntrezGene.ID)

# Extract gene entrez ID for genes with FDR < 0.05 & |Log2FC| > 2
EntrezGeneList_Log2FC_2_ONA <- metaOutputFDR_OrderbyPval_Log2FC_2_ONA %>%
  filter(FDR < 0.05) %>%
  pull(Mouse_EntrezGene.ID)

# Function use
GeneFunction_Log2FC_1_ONA <- GetGeneFunctionByID(0,
  1,

```



```
## [1] "Processing Entrez Gene ID:55932"
## [1] "Processing Entrez Gene ID:15957"
## [1] "Processing Entrez Gene ID:24110"
## [1] "Processing Entrez Gene ID:12010"
## [1] "Processing Entrez Gene ID:14469"
## [1] "Processing Entrez Gene ID:23962"
## [1] "Processing Entrez Gene ID:69550"
## [1] "Processing Entrez Gene ID:60440"
## [1] "Processing Entrez Gene ID:15944"
## [1] "Processing Entrez Gene ID:20846"
## [1] "Processing Entrez Gene ID:229900"
## [1] "Processing Entrez Gene ID:20128"
## [1] "Processing Entrez Gene ID:14972"
## [1] "Processing Entrez Gene ID:66141"
## [1] "Processing Entrez Gene ID:100038882"
## [1] "Processing Entrez Gene ID:23833"
## [1] "Processing Entrez Gene ID:231507"
## [1] "Processing Entrez Gene ID:99899"
## [1] "Processing Entrez Gene ID:16912"
## [1] "Processing Entrez Gene ID:15945"
## [1] "Processing Entrez Gene ID:19039"
## [1] "Processing Entrez Gene ID:20293"
## [1] "Processing Entrez Gene ID:20304"
## [1] "Processing Entrez Gene ID:58185"
## [1] "Processing Entrez Gene ID:80285"
## [1] "Processing Entrez Gene ID:67775"
## [1] "Processing Entrez Gene ID:236312"
## [1] "Processing Entrez Gene ID:107350"
## [1] "Processing Entrez Gene ID:209387"
## [1] "Processing Entrez Gene ID:22436"
## [1] "Processing Entrez Gene ID:71586"
## [1] "Processing Entrez Gene ID:108670"
## [1] "Processing Entrez Gene ID:19264"
## [1] "Processing Entrez Gene ID:66607"
## [1] "Processing Entrez Gene ID:14938"
## [1] "Processing Entrez Gene ID:72310"
## [1] "Processing Entrez Gene ID:68774"
## [1] "Processing Entrez Gene ID:60533"
## [1] "Processing Entrez Gene ID:107526"
## [1] "Processing Entrez Gene ID:57444"
## [1] "Processing Entrez Gene ID:16391"
## [1] "Processing Entrez Gene ID:13058"
## [1] "Processing Entrez Gene ID:231655"
## [1] "Processing Entrez Gene ID:243771"
## [1] "Processing Entrez Gene ID:246256"
## [1] "Processing Entrez Gene ID:16859"
## [1] "Processing Entrez Gene ID:16819"
## [1] "Processing Entrez Gene ID:234311"
## [1] "Processing Entrez Gene ID:15958"
## [1] "Processing Entrez Gene ID:16913"
## [1] "Processing Entrez Gene ID:15042"
```

## [1] "Processing Entrez Gene ID:14939"  
## [1] "Processing Entrez Gene ID:54123"  
## [1] "Processing Entrez Gene ID:14960"  
## [1] "Processing Entrez Gene ID:70110"  
## [1] "Processing Entrez Gene ID:67742"  
## [1] "Processing Entrez Gene ID:14961"  
## [1] "Processing Entrez Gene ID:547253"  
## [1] "Processing Entrez Gene ID:17329"  
## [1] "Processing Entrez Gene ID:110454"  
## [1] "Processing Entrez Gene ID:217069"  
## [1] "Processing Entrez Gene ID:246728"  
## [1] "Processing Entrez Gene ID:68713"  
## [1] "Processing Entrez Gene ID:17857"  
## [1] "Processing Entrez Gene ID:12642"  
## [1] "Processing Entrez Gene ID:14190"  
## [1] "Processing Entrez Gene ID:16186"  
## [1] "Processing Entrez Gene ID:20558"  
## [1] "Processing Entrez Gene ID:15894"  
## [1] "Processing Entrez Gene ID:60361"  
## [1] "Processing Entrez Gene ID:19106"  
## [1] "Processing Entrez Gene ID:65221"  
## [1] "Processing Entrez Gene ID:13040"  
## [1] "Processing Entrez Gene ID:11810"  
## [1] "Processing Entrez Gene ID:12983"  
## [1] "Processing Entrez Gene ID:229003"  
## [1] "Processing Entrez Gene ID:671535"  
## [1] "Processing Entrez Gene ID:16362"  
## [1] "Processing Entrez Gene ID:15950"  
## [1] "Processing Entrez Gene ID:20684"  
## [1] "Processing Entrez Gene ID:80876"  
## [1] "Processing Entrez Gene ID:56045"  
## [1] "Processing Entrez Gene ID:17476"  
## [1] "Processing Entrez Gene ID:20821"  
## [1] "Processing Entrez Gene ID:58203"  
## [1] "Processing Entrez Gene ID:14580"  
## [1] "Processing Entrez Gene ID:76933"  
## [1] "Processing Entrez Gene ID:12258"  
## [1] "Processing Entrez Gene ID:14127"  
## [1] "Processing Entrez Gene ID:15900"  
## [1] "Processing Entrez Gene ID:13011"  
## [1] "Processing Entrez Gene ID:12266"  
## [1] "Processing Entrez Gene ID:21354"  
## [1] "Processing Entrez Gene ID:14129"  
## [1] "Processing Entrez Gene ID:12702"  
## [1] "Processing Entrez Gene ID:20555"  
## [1] "Processing Entrez Gene ID:16409"  
## [1] "Processing Entrez Gene ID:22035"  
## [1] "Processing Entrez Gene ID:21355"  
## [1] "Processing Entrez Gene ID:23880"  
## [1] "Processing Entrez Gene ID:30935"  
## [1] "Processing Entrez Gene ID:16149"  
## [1] "Processing Entrez Gene ID:12364"  
## [1] "Processing Entrez Gene ID:24088"  
## [1] "Processing Entrez Gene ID:19288"

```
## [1] "Processing Entrez Gene ID:12257"
## [1] "Processing Entrez Gene ID:12517"
## [1] "Processing Entrez Gene ID:20556"
## [1] "Processing Entrez Gene ID:15163"
## [1] "Processing Entrez Gene ID:73656"
## [1] "Processing Entrez Gene ID:21810"
## [1] "Processing Entrez Gene ID:67776"
## [1] "Processing Entrez Gene ID:12362"
## [1] "Processing Entrez Gene ID:20306"
## [1] "Processing Entrez Gene ID:80837"
## [1] "Processing Entrez Gene ID:12505"
## [1] "Processing Entrez Gene ID:12363"
## [1] "Processing Entrez Gene ID:68487"
## [1] "Processing Entrez Gene ID:21857"
## [1] "Processing Entrez Gene ID:12655"
## [1] "Processing Entrez Gene ID:20296"
## [1] "Processing Entrez Gene ID:16365"
## [1] "Processing Entrez Gene ID:20302"
```

```
GeneFunction_Log2FC_2_ONA <- GetGeneFunctionByID(0,
2,
EntrezGeneList_Log2FC_2_ONA)
```

```
## [1] "Processing Entrez Gene ID:55932"
## [1] "Processing Entrez Gene ID:15957"
## [1] "Processing Entrez Gene ID:24110"
## [1] "Processing Entrez Gene ID:12010"
## [1] "Processing Entrez Gene ID:14469"
## [1] "Processing Entrez Gene ID:23962"
## [1] "Processing Entrez Gene ID:69550"
## [1] "Processing Entrez Gene ID:60440"
## [1] "Processing Entrez Gene ID:15944"
## [1] "Processing Entrez Gene ID:20846"
## [1] "Processing Entrez Gene ID:229900"
## [1] "Processing Entrez Gene ID:20128"
## [1] "Processing Entrez Gene ID:14972"
## [1] "Processing Entrez Gene ID:66141"
## [1] "Processing Entrez Gene ID:100038882"
## [1] "Processing Entrez Gene ID:23833"
## [1] "Processing Entrez Gene ID:231507"
## [1] "Processing Entrez Gene ID:99899"
## [1] "Processing Entrez Gene ID:16912"
## [1] "Processing Entrez Gene ID:15945"
## [1] "Processing Entrez Gene ID:19039"
## [1] "Processing Entrez Gene ID:20293"
## [1] "Processing Entrez Gene ID:20304"
## [1] "Processing Entrez Gene ID:58185"
## [1] "Processing Entrez Gene ID:80285"
## [1] "Processing Entrez Gene ID:67775"
## [1] "Processing Entrez Gene ID:107350"
## [1] "Processing Entrez Gene ID:209387"
## [1] "Processing Entrez Gene ID:71586"
## [1] "Processing Entrez Gene ID:68774"
## [1] "Processing Entrez Gene ID:60533"
```

```
## [1] "Processing Entrez Gene ID:57444"
## [1] "Processing Entrez Gene ID:231655"
## [1] "Processing Entrez Gene ID:243771"
## [1] "Processing Entrez Gene ID:246256"
## [1] "Processing Entrez Gene ID:16859"
## [1] "Processing Entrez Gene ID:16819"
## [1] "Processing Entrez Gene ID:234311"
## [1] "Processing Entrez Gene ID:15958"
## [1] "Processing Entrez Gene ID:16913"
## [1] "Processing Entrez Gene ID:14939"
## [1] "Processing Entrez Gene ID:54123"
## [1] "Processing Entrez Gene ID:70110"
## [1] "Processing Entrez Gene ID:547253"
## [1] "Processing Entrez Gene ID:17329"
## [1] "Processing Entrez Gene ID:110454"
## [1] "Processing Entrez Gene ID:17857"
## [1] "Processing Entrez Gene ID:12642"
## [1] "Processing Entrez Gene ID:16186"
## [1] "Processing Entrez Gene ID:20558"
## [1] "Processing Entrez Gene ID:60361"
## [1] "Processing Entrez Gene ID:16362"
## [1] "Processing Entrez Gene ID:76933"
## [1] "Processing Entrez Gene ID:12258"
## [1] "Processing Entrez Gene ID:21354"
## [1] "Processing Entrez Gene ID:73656"
## [1] "Processing Entrez Gene ID:21810"
## [1] "Processing Entrez Gene ID:12363"
## [1] "Processing Entrez Gene ID:68487"
## [1] "Processing Entrez Gene ID:20296"
## [1] "Processing Entrez Gene ID:20302"
```

```
# Check the structure of the output
str(GeneFunction_Log2FC_1_ONA)
```

```
## 'data.frame': 123 obs. of 8 variables:
## $ Entrez_ID : chr "55932" "15957" "24110" "12010" ...
## $ Gene_symbol : chr "Gbp3" "Ifit1" "Usp18" "B2m" ...
## $ Gene_description : chr "guanylate binding protein 3" "interferon-induced protein with tetrat...
## $ Chromosome : chr "3" "19" "6" "2" ...
## $ Map_location : chr "3 66.69 cM" "19 29.78 cM" "6 57.17 cM" "2 60.55 cM" ...
## $ Model_scientific_name: chr "Mus musculus" "Mus musculus" "Mus musculus" "Mus musculus" ...
## $ Model_common_name : chr "house mouse" "house mouse" "house mouse" "house mouse" ...
## $ Gene_function : chr "Predicted to enable GTP binding activity; GTPase activity; and prote"
```

## 16) Gene Set Enrichment Analysis (GSEA) with KEGG/GO/Reactome databases

```
# Create a function to perform GSEA on common databases, including KEGG, GO, and
# Reactome
GSEAPerform_KEGG_GO_Reactome <- function(EntrezGeneList,
                                          pvalueCutoff,
                                          qvalueCutoff){
  # Load the mouse gene annotation database
```

```

OrgDb <- org.Mm.eg.db

# Perform GSEA with KEGG database
KEGG_GSEA_result <- enrichKEGG(gene = EntrezGeneList,
                                # Organism code for Mus musculus
                                organism = "mmu",
                                # p-value cut off
                                pvalueCutoff = pvalueCutOff,
                                # FDR cut off
                                qvalueCutoff = qvalueCutOff)

# Perform GSEA with GO database
GO_GSEA_result <- enrichGO(gene = EntrezGeneList,
                            # Select database for Mus musculus
                            OrgDb = OrgDb,
                            # Ontology for biological process
                            # Other ontologies include "MF" for Molecular Function
                            # and "CC" for Cellular Component
                            ont = "BP",
                            # p-value cut off
                            pvalueCutoff = pvalueCutOff,
                            # FDR cut off
                            qvalueCutoff = qvalueCutOff)

# Perform GSEA with Reactome database
Reactome_GSEA_result <- enrichPathway(gene = EntrezGeneList,
                                        # Organism code for Mus musculus
                                        organism = "mouse",
                                        # p-value cut off
                                        pvalueCutoff = pvalueCutOff,
                                        # FDR cut off
                                        qvalueCutoff = qvalueCutOff)

# Return the list of results
return(list(KEGG = KEGG_GSEA_result,
            GO = GO_GSEA_result,
            Reactome = Reactome_GSEA_result))
}

```

```

# Function use
GSEA_Log2FC_1_ONA <- GSEAPerform_KEGG_GO_Reactome(EntrezGeneList_Log2FC_1_ONA,
                                                    0.5,
                                                    0.5)

```

## Reading KEGG annotation online: "https://rest.kegg.jp/link/mmu/pathway"...


## Reading KEGG annotation online: "https://rest.kegg.jp/list/pathway/mmu"...

```

GSEA_Log2FC_2_ONA <- GSEAPerform_KEGG_GO_Reactome(EntrezGeneList_Log2FC_2_ONA,
                                                    0.5,
                                                    0.5)


```

```
# Visualize the GSEA results
# png("GSEA_Log2FC_1_ONA_KEGG.png", 8, 5, "in", res = 300)
dotplot(GSEA_Log2FC_1_ONA$KEGG, showCategory = 10, font.size = 7)
```




```
# dev.off()

# png("GSEA_Log2FC_2_ONA_KEGG.png", 8, 5, "in", res = 300)
dotplot(GSEA_Log2FC_2_ONA$KEGG, showCategory = 10, font.size = 7)
```



```
# dev.off()


# png("GSEA_Log2FC_1_ONA_GO.png", 8, 5, "in", res = 300)
barplot(GSEA_Log2FC_1_ONA$GO, showCategory = 10, font.size = 7)
```



```
# dev.off()


# png("GSEA_Log2FC_2_ONA_GO.png", 8, 5, "in", res = 300)
barplot(GSEA_Log2FC_2_ONA$GO, showCategory = 10, font.size = 7)
```






```
# dev.off()

# png("GSEA_Log2FC_1_ONA_Reactome.png", 8, 5, "in", res = 300)
barplot(GSEA_Log2FC_1_ONA$Reactome, showCategory = 10, font.size = 7)
```



```
# dev.off()

# png("GSEA_Log2FC_2_ONA_Reactome.png", 8, 5, "in", res = 300)
barplot(GSEA_Log2FC_2_ONA$Reactome, showCategory = 10, font.size = 7)
```



```
# dev.off()

# Transform the matched pathways results into dataframes and export into the working
# directory
GSEA_Log2FC_1_ONA_KEGG <- as.data.frame(GSEA_Log2FC_1_ONA$KEGG)
row.names(GSEA_Log2FC_1_ONA_KEGG) <- NULL
write.csv(GSEA_Log2FC_1_ONA_KEGG, "GSEA_Log2FC_1_ONA_KEGG.csv")

GSEA_Log2FC_2_ONA_KEGG <- as.data.frame(GSEA_Log2FC_2_ONA$KEGG)
row.names(GSEA_Log2FC_2_ONA_KEGG) <- NULL
write.csv(GSEA_Log2FC_2_ONA_KEGG, "GSEA_Log2FC_2_ONA_KEGG.csv")

GSEA_Log2FC_1_ONA_GO <- as.data.frame(GSEA_Log2FC_1_ONA$GO)
row.names(GSEA_Log2FC_1_ONA_GO) <- NULL
write.csv(GSEA_Log2FC_1_ONA_GO, "GSEA_Log2FC_1_ONA_GO.csv")

GSEA_Log2FC_2_ONA_GO <- as.data.frame(GSEA_Log2FC_2_ONA$GO)
row.names(GSEA_Log2FC_2_ONA_GO) <- NULL
write.csv(GSEA_Log2FC_2_ONA_GO, "GSEA_Log2FC_2_ONA_GO.csv")

GSEA_Log2FC_1_ONA_Reactome <- as.data.frame(GSEA_Log2FC_1_ONA$Reactome)
row.names(GSEA_Log2FC_1_ONA_Reactome) <- NULL
write.csv(GSEA_Log2FC_1_ONA_Reactome, "GSEA_Log2FC_1_ONA_Reactome.csv")

GSEA_Log2FC_2_ONA_Reactome <- as.data.frame(GSEA_Log2FC_2_ONA$Reactome)
row.names(GSEA_Log2FC_2_ONA_Reactome) <- NULL
```

```
write.csv(GSEA_Log2FC_2_ONA_Reactome, "GSEA_Log2FC_2_ONA_Reactome.csv")
```

## 17) Gene Set Enrichment Analysis (GSEA) with Brain.GMT database

The Brain.GMT database, developed by Hagenauer et al. (2024), is designed to improve the interpretation of brain-derived differential expression results, especially in studies focused on neuropsychiatric disorders. The Brain.GMT can be used within common pipelines (GSEA, limma, edgeR) to interpret results from 3 species of rat, mouse, human. The database includes 918 gene sets derived from various sources, each curated to be relevant to brain functions, brain celltypes, co-expression networks, and regional gene expression signatures.

Gene sets included in the Brain.GMT:

### 1. MSigDB Gene Sets

- Curated Gene Sets: 158 gene sets related to the nervous system.
- Cell Type Signature Gene Sets: 211 gene sets related to the nervous system and blood.

### 2. BrainInABlender

- 39 gene sets related to cell type-enriched expression, particularly in the cortex.

### 3. DropViz

- 13 gene sets focused on hippocampal expression, and 12 gene sets for the nucleus accumbens.

### 4. HippoSeq

- 14 gene sets related to regional enriched expression in the hippocampus.

### 5. Coexpression Analyses

- 55 gene sets derived from coexpression networks in the hippocampus.

### 6. Gene Weaver

- 33 gene sets for the hippocampus and 6 gene sets for the nucleus accumbens related to stress, environmental enrichment, affective behavior, and mood disorder.

### 7. Gemma

- 29 gene sets derived from reanalysis pipelines focusing on stress, environmental enrichment, affective behavior, and mood disorder in the nucleus accumbens.

Ref for Brain.GMT: <https://doi.org/10.1016/j.mex.2024.102788>

Ref for original GSEA: <https://doi.org/10.1073/pnas.0506580102>

Although the Brain.GMT focuses on brain-related genes, the impact of viral infection might involve specific pathways or immune responses that are not well-represented in this database.

```

# Create a named vector from meta-analysis output
# Names = Mouse gene symbol / Values = Log2FC estimate
# FDR < 0.05 / |Log2FC| > 1

BrainGMT_metaOutputFDR_1_ONA_FDR_0.05 <- metaOutputFDR_OrderbyPval_Log2FC_1_ONA %>%
  filter(FDR < 0.05)

BrainGMT_metaOutputFDR_1_ONA <- setNames(
  BrainGMT_metaOutputFDR_1_ONA_FDR_0.05$Log2FC_estimate,
  BrainGMT_metaOutputFDR_1_ONA_FDR_0.05$Mouse_Symbol
)

# Remove genes with NA or duplicated names
BrainGMT_metaOutputFDR_1_ONA_cleaned <- BrainGMT_metaOutputFDR_1_ONA %>%
  # Convert to dataframe for easier manipulation
  enframe(name = "gene_name", value = "Log2FC_estimate") %>%
  # Remove rows with NA names
  filter(!is.na(gene_name)) %>%
  # Remove duplicated names, keeping the first instance
  distinct(gene_name, .keep_all = TRUE) %>%
  # Convert back to named vector
  deframe()

# Order the vector by Log2FC in ascending order
BrainGMT_metaOutputFDR_OrderedByLog2FC_1_ONA <- BrainGMT_metaOutputFDR_1_ONA_cleaned[order(BrainGMT_metaOutputFDR_OrderedByLog2FC_1_ONA_cleaned)]

# Import the Brain.GMT for the specific species of interest
# Ignore the warning about incomplete line
BrainGMT_Mouse <- gmtPathways("BrainGMTv2_MouseOrthologs.gmt.txt")

```

```

## Warning in readLines(gmt.file): incomplete final line found on
## 'BrainGMTv2_MouseOrthologs.gmt.txt'

```

```

# Perform fast fGSEA with Brain.GMT
GSEA_Log2FC_1_ONA_BrainGMT <- fgseaSimple(BrainGMT_Mouse,
  BrainGMT_metaOutputFDR_OrderedByLog2FC_1_ONA,
  # Number of permutations for the GSEA
  nperm = 10000,
  # Minimum size of gene sets to consider
  minSize = 10,
  # Maximum size of gene sets to consider
  maxSize = 1000)

```

```

## Warning in preparePathwaysAndStats(pathways, stats, minSize, maxSize,
## gseaParam, : All values in the stats vector are greater than zero and scoreType
## is "std", maybe you should switch to scoreType = "pos".

```

```

# Converts the list of leading edge genes (genes contributing to enrichment) in
# the GSEA results to a comma-separated string
GSEA_Log2FC_1_ONA_BrainGMT$leadingEdge <- vapply(GSEA_Log2FC_1_ONA_BrainGMT$leadingEdge,
  paste,
  collapse= ",",

```

```

                                character(1L))

# Export the matched pathways into the working directory
write.csv(GSEA_Log2FC_1_ONA_BrainGMT, "GSEA_Log2FC_1_ONA_BrainGMT.csv")

# It is not sorted by p-value?
# padj: FDR corrected p-value (using familywise-error rate???)
# ES & NES: Enrichment Score and Normalized Enrichment Score for each gene set
# Positive ES & NES means that the gene set is enriched with upregulation in response
# to your variable of interest
# Negative ES & NES means that the gene set is enriched with downregulation in response
# to your variable of interest
# leadingEdge: The core of a gene set that accounts for the enrichment signal
# nMoreExtreme???
# Size???

# Create a named vector from meta-analysis output
# Names = Mouse gene symbol | Values = Log2FC estimate
# FDR < 0.05 | |Log2FC| > 2

BrainGMT_metaOutputFDR_2_ONA_FDR_0.05 <- metaOutputFDR_OrderbyPval_Log2FC_2_ONA %>%
  filter(FDR < 0.05)

BrainGMT_metaOutputFDR_2_ONA <- setNames(
  BrainGMT_metaOutputFDR_2_ONA_FDR_0.05$Log2FC_estimate,
  BrainGMT_metaOutputFDR_2_ONA_FDR_0.05$Mouse_Symbol
)

# Remove genes with NA or duplicated names
BrainGMT_metaOutputFDR_2_ONA_cleaned <- BrainGMT_metaOutputFDR_2_ONA %>%
  # Convert to dataframe for easier manipulation
  enframe(name = "gene_name", value = "Log2FC_estimate") %>%
  # Remove rows with NA names
  filter(!is.na(gene_name)) %>%
  # Remove duplicated names, keeping the first instance
  distinct(gene_name, .keep_all = TRUE) %>%
  # Convert back to named vector
  deframe()

# Order the vector by Log2FC in ascending order
BrainGMT_metaOutputFDR_OrderedByLog2FC_2_ONA <- BrainGMT_metaOutputFDR_2_ONA_cleaned[order(BrainGMT_met

# Perform fast fGSEA with Brain.GMT
GSEA_Log2FC_2_ONA_BrainGMT <- fgseaSimple(BrainGMT_Mouse,
  BrainGMT_metaOutputFDR_OrderedByLog2FC_2_ONA,
  # Number of permutations for the GSEA
  nperm = 10000,
  # Minimum size of gene sets to consider
  minSize = 10,
  # Maximum size of gene sets to consider
  maxSize = 1000)

## Warning in preparePathwaysAndStats(pathways, stats, minSize, maxSize,

```

```
## gseaParam, : All values in the stats vector are greater than zero and scoreType
## is "std", maybe you should switch to scoreType = "pos".
```

```
# Converts the list of leading edge genes (genes contributing to enrichment) in
# the GSEA results to a comma-separated string
GSEA_Log2FC_2_ONA_BrainGMT$leadingEdge <- vapply(GSEA_Log2FC_2_ONA_BrainGMT$leadingEdge,
                                                  paste,
                                                  collapse= ",",
                                                  character(1L))

# Export the matched pathways into the working directory
write.csv(GSEA_Log2FC_2_ONA_BrainGMT, "GSEA_Log2FC_2_ONA_BrainGMT.csv")
```