

Quantifying Chaos

Title

Murray Jones (520487532)

University of Sydney | PHYS1902 | Lab Class X

Contents

Introduction:	1
Aim:	1
Hypothesis:	1
Scientific basis:	1
Experimental Setup:	2
Equipment list:	2
Method:	3
Data and Results:	4
Tracking the nodes:	4
Analyzing the data:	4
Discussion and Interpretation:	4
Conclusion:	7
References	7

Introduction:

Aim:

The aim of this experiment is to determine a quantitative measure of the chaos in the motion of a triple pendulum, and use this to determine a relationship between the extent of chaos exhibited by the pendulum, and the the total energy of the pendulum arm.

Hypothesis:

The extent of chaos exhibited by the triple pendulum will be directly proportional to the total energy of the pendulum at that point in time.

As the impact of frictional effects on this pendulum is very minimal, it is valid to assume that the total energy of the pendulum will remain approximately constant throughout a run with duration of ~15 seconds. Hence, as the initial energy of the pendulum arm is entirely in the form of gravitational potential energy, we can adapt the hypothesis to suit this easier to measure parameter as follows:

The extent of chaos exhibited by the triple pendulum will be directly proportional to the initial energy of the pendulum.


Scientific basis:

Edward Lorenz defined chaos as:


When the present determines the future, but the approximate present does not approximately determine the future.

Based on this definition, we can conclude that the extent of chaos expressed by a system over time can be measured as the difference in paths taken by a system over multiple trials whose initial conditions are approximately the same.

Consider the first four frames of a pendulum run, taken at equal intervals:



We can the conduct a second run with approximate the same initial conditions, and measure the difference between the end node positions x at each frame x_n :



Hence, based of our above definition, it is valid to describe a measure of chaos for this system as:

$$Chaos = \Delta t \cdot \sum_{k=0}^n x_k$$


Where $\Delta t = \frac{1}{120}$ is the time between each frame.

Experimental Setup:

Equipment list:

The following equipment was used in this experiment:

- Weighted triple pendulum (*shown below*), with an arm length of 120mm, as measured between the centers of any two consecutive nodes.
- Four different brightly colored stickers.
- Sony A7C full-camera using a 24mm, f2.8 lens, at aperture f5.6. Capable of recording footage at 4K resolution, with 120 frames per second.
- Scales with 0.1g precision.
- Protractor with 0.5° precision, and a hanging bob to reference the vertical direction.
- Tape measure & meter ruler with 1mm precision.
- White paper and masking tape to cover reflective parts of pendulum (*see experimental setup diagram*).



Method:

The method used to collect data in this experiment was as follows:

1. Camera and pendulum were set up in front of blank white wall, with good lighting, such that the camera's field of view was centered on the origin node (to reduce parallax error), and the lens of the camera was placed 1.2m horizontally from the origin node, such that the whole range of motion of the pendulum was within the camera's field of view.
2. Blue, yellow, pink, and green markers were placed on nodes 0 to 3 respectively. These colors were chosen as they stood out easily from the other colors present on the pendulum apparatus, such as the red of the arms.
3. Pendulum arm was brought to the desired initial angle, as measure using protractor, and held until all nodes were motionless.
4. Recording was started and pendulum released after a brief countdown.
5. During recording, the initial conditions were verbally announced, so that they could be manually determined from the data.
6. Pendulum was allowed to run for 15 seconds (or 45 seconds for propagation trials), then recording was stopped.
7. The above process was repeated from step 3 with initial angle adjusted in 15° increments from 0°, a motionless control run, to 180°, where the arm was oriented vertically upward and the initial energy was a maximum. For each distinct initial angle, three runs were conducted.

8. Recordings of each run were saved, and the data analysed using the method described under *Data & Analysis*.



Data and Results:

Tracking the nodes:

Our data collection process produced approximately 10Gb of recordings. In order to extract the node position data from these

Analyzing the data:

Comment on the precision of your measurements. Indicate main sources of error, clearly explain how you estimated/calculated uncertainties.

Present the final form of the analysed data (e.g. final graphs, tables, bar graphs, LINEST results). It should align with your aim.

Include the method you used to analyse the data (e.g. I plotted these two variables against each other, I used Excel to fit this trend, and so on).

Don't forget to include units, uncertainties, and use correct number of significant figures.

Describe your results

Include tables of data and Excel plots where appropriate

Make sure all data has units and appropriate uncertainties

1-2 pages of text and diagrams

Discussion and Interpretation:

Interpret the analysed data to answer the aim

Comment on the validity, reliability and accuracy of the data

Discuss your uncertainty analysis and sources of error.

If there are discrepancies between predictions and measurements, discuss these and provide plausible explanations/justifications.

Any limitations of your experimental approach?

Connect your results to your experiment aims/hypotheses

~ 1 page of text


```
## 'data.frame':   148434 obs. of  24 variables:
## $ Recording   : int   223 223 223 223 223 223 223 223 ...
## $ Time        : num   0 0.00833 0.01667 0.025 0.03333 ...
```


```


## $ Type      : chr  "prop" "prop" "prop" "prop" ...
## $ InitAngle : num   45 45 45 45 45 45 45 45 45 45 ...
## $ AddedMass : int    0 0 0 0 0 0 0 0 0 0 ...
## $ LateStart  : int    0 0 0 0 0 0 0 0 0 0 ...
## $ BlueX      : num   -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 ...
## $ BlueY      : num   -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 ...
## $ BlueAngle  : num  -45 -45 -45 -45 -45 ...
## $ BlueDist   : num    1.41 1.41 1.41 1.41 1.41 ...
## $ YellowX    : num    0.0176 0.0174 0.0176 0.0176 0.0174 ...
## $ YellowY    : num   -0.359 -0.358 -0.359 -0.358 -0.358 ...
## $ YellowAngle: num    2.82 2.78 2.82 2.81 2.78 ...
## $ YellowDist : num    0.359 0.359 0.359 0.359 0.359 ...
## $ PinkX      : num    0.0417 0.0423 0.0412 0.0401 0.0395 ...
## $ PinkY      : num   -0.731 -0.731 -0.731 -0.731 -0.731 ...
## $ PinkAngle  : num    3.26 3.31 3.22 3.14 3.09 ...
## $ PinkDist   : num    0.732 0.733 0.732 0.732 0.732 ...
## $ GreenX     : num    0.338 0.338 0.338 0.337 0.337 ...
## $ GreenY     : num   -0.957 -0.956 -0.955 -0.954 -0.955 ...
## $ GreenAngle : num   19.4 19.5 19.5 19.5 19.5 ...
## $ GreenDist  : num    1.01 1.01 1.01 1.01 1.01 ...
## $ Timeshifts : num    0 0 0 0 0 0 0 0 0 0 ...
## $ AdjTime    : num    0 0.00833 0.01667 0.025 0.03333 ...

## [1] 45 90 135 180 15 30 40.5 60 150
## Levels: 15 < 30 < 40.5 < 45 < 60 < 90 < 135 < 150 < 180

```







```
##
## Call:
## lm(formula = difSet ~ 0 + energySet)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.68179 -0.22182 -0.02039  0.14636  0.19417
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## energySet  11.6724     0.1655   70.52 3.03e-11 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.3201 on 7 degrees of freedom
## Multiple R-squared:  0.9986, Adjusted R-squared:  0.9984
## F-statistic: 4973 on 1 and 7 DF, p-value: 3.031e-11
```

Conclusion:

Address the aim/question based on evidence from your results.
 Any limitations (with uncertainties) and future work
 A few sentences.

References