

No.	Time	Delta	Source	Destination	Protocol	Length	Info
35418	39.126947	34.906569	IntelCor_16:ac:10	Broadcast	ARP	42	Who has 192.168.0.1? Tell 192.168.0.14

Frame 35418: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface \Device\NPF_{929C1C35-CDC3-455E-A88B-6DEDC953D510}, id 0

Interface id: 0 (\Device\NPF_{929C1C35-CDC3-455E-A88B-6DEDC953D510})
Interface name: \Device\NPF_{929C1C35-CDC3-455E-A88B-6DEDC953D510}
Interface description: Wi-Fi
Encapsulation type: Ethernet (1)
Arrival Time: Nov 30, 2021 17:58:10.137952000 Eastern Standard Time
[Time shift for this packet: 0.000000000 seconds]
Epoch Time: 1638313090.137952000 seconds
[Time delta from previous captured frame: 0.005222000 seconds]
[Time delta from previous displayed frame: 34.906569000 seconds]
[Time since reference or first frame: 39.126947000 seconds]
Frame Number: 35418
Frame Length: 42 bytes (336 bits)
Capture Length: 42 bytes (336 bits)
[Frame is marked: False]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:arp]
[Coloring Rule Name: ARP]
[Coloring Rule String: arp]

Ethernet II, Src: IntelCor_16:ac:10 (f8:59:71:16:ac:10), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
Destination: Broadcast (ff:ff:ff:ff:ff:ff)
Address: Broadcast (ff:ff:ff:ff:ff:ff)
.... ..1. = LG bit: Locally administered address (this is NOT the factory default)
.... ...1 = IG bit: Group address (multicast/broadcast)

Source: IntelCor_16:ac:10 (f8:59:71:16:ac:10)
Address: IntelCor_16:ac:10 (f8:59:71:16:ac:10)
.... ..0. = LG bit: Globally unique address (factory default)
.... ...0 = IG bit: Individual address (unicast)

Type: ARP (0x0806)
Address Resolution Protocol (request)
Hardware type: Ethernet (1)
Protocol type: IPv4 (0x0800)
Hardware size: 6
Protocol size: 4
Opcode: request (1)
Sender MAC address: IntelCor_16:ac:10 (f8:59:71:16:ac:10)
Sender IP address: 192.168.0.14
Target MAC address: 00:00:00_00:00:00 (00:00:00:00:00:00)
Target IP address: 192.168.0.1

```

0000  ff ff ff ff ff ff f8 59 71 16 ac 10 08 06 00 01  ....Yq.....
0010  08 00 06 04 00 01 f8 59 71 16 ac 10 c0 a8 00 0e  ....Yq.....
0020  00 00 00 00 00 00 c0 a8 00 01  ....

```