

# LiveEngage Enterprise In-App Messenger SDK: Android Deployment Guide

Document Version: 1.1  
January 2016

Contents

Introduction .....3

Platform Support.....3

Deployment.....3

Security.....3

Deploying the App Messaging SDK .....3

    Download the SDK package .....4

    Set up the SDK package in Android Studio .....4

    Test the SDK .....6

LivePerson API Methods .....7

Configuring the SDK .....10

Permissions .....12

Dependencies.....12

## Introduction

This document describes the process for integrating the App Messaging SDK into mobile native apps based on Android OS. It provides a high-level overview, as well as a step-by-step guide on how to consume the SDK, build the app with it, and customize it for the needs of the app.

## Platform Support

- **Supported OS:** Android 4.0+
- **Certified devices:** Nexus 5, Samsung S5, LG G3, LG G4, Samsung S3, S4

## Deployment

- **Embeddable library for AAR:** Binary distribution of an Android Library Project
- **Installers:** Gradle

## Security

Security is a top priority and key for enabling trusted, meaningful engagements.

LivePerson's comprehensive security model and practices were developed based on years of experience in SaaS operations, close relationships with Enterprise customers' security teams, frequent assessments with independent auditors, and active involvement in the security community.

LivePerson has a comprehensive security compliance program to help ensure adherence to internationally recognized standards and exceed market expectations. Among the standards LivePerson complies with are: SSAE16 SOC2, ISO27001, PCI-DSS via Secure Widget, Japan's FISC, SafeHarbor, SOX, and more.

Our applications are developed under a strict and controlled Secure Development Life-Cycle: Developers undergo secure development training, and security architects are involved in all major projects and influence the design process. Static and Dynamic Code Analysis is an inherent part of the development process and, upon maturity, the application is tested for vulnerabilities by an independent penetration testing vendor. On average, LivePerson undergoes 30 penetration tests each year.

## Deploying the App Messaging SDK

To deploy the App Messaging SDK, you are required to complete the following steps:

- Download the SDK package
- Set up the SDK package in Android Studio
- Test the SDK

## To deploy the App Messaging SDK:

### Download the SDK package

Click [here](#) to download the SDK. Once downloaded, extract the ZIP file to a folder on your computer.

### Set up the SDK package in Android Studio

1. Create a new Android Studio Project.
  - a. Under Configure your new project, enter the Application name and Company Domain. Click **Next**.
  - b. Under Target Android Devices, select the checkbox next to Phone and tablet. From the dropdown list, select **API 14: Android 4.0.3**, or above. Click **Next**.
  - c. Under Add an activity to Mobile, select **Blank Activity**. Click **Next**.
  - d. Under Customize the Activity, click **Finish** to create the project.
2. In the Android Studio sidebar, select **Project view**. Navigate down the tree to MyApplication>app>libs.
3. Navigate to the folder where you extracted the SDK file. Navigate to the AAR file, and then copy it to the libs subfolder.
4. Using the project navigator, navigate to app>build.gradle, and open the app gradle file. Add repositories and dependencies as shown below.

```
apply plugin: 'com.android.application'
android {
    compileSdkVersion 23
    buildToolsVersion "23.0.0"

    repositories {
        flatDir {
            dirs 'libs'
        }
    }

    defaultConfig {
        applicationId "liveperson.com.livepersonsampleapp"
        minSdkVersion 14
        targetSdkVersion 23
        versionCode 1
        versionName "1.0"
    }
    buildTypes {
        release {
            minifyEnabled false
            proguardFiles getDefaultProguardFile('proguard-
rules.pro')
        }
    }
}

dependencies {
```

```

compile (name: '<aar fileName>', ext:'aar')
compile 'com.koushikdutta.async:androidasync:2.1.6'
compile 'com.android.support:appcompat-v7:23.1.0'
compile 'com.android.support:design:23.1.0'
compile 'com.facebook.fresco:fresco:0.8.0'
}

```

5. Create the Branding.xml file:

- Using the project navigator, navigate to app>src>main>res.
- Under the **values** folder, create a new resource file called branding.xml.
- Add your resources, for example icons, colors, and strings, to this file.

*Note: For more information on the branding.xml file, refer to [Configuring the SDK](#).*

### Example of using the SDK:

Add a button to trigger the LivePerson conversation UI:

- Navigate to the main layout file: activity\_main.xml.
- Edit the file to add the button.

```

<RelativeLayout xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:paddingLeft="@dimen/activity_horizontal_margin"
    android:paddingRight="@dimen/activity_horizontal_margin"
    android:paddingTop="@dimen/activity_vertical_margin"
    android:paddingBottom="@dimen/activity_vertical_margin"
    tools:context=".MainActivity">

    <Button
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Start Messaging"
        android:id="@+id/show_btn"/>

    <Button
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Hide Screen"
        android:id="@+id/hide_btn"/>

</RelativeLayout>

```

Add a button handler to open the LivePerson conversation UI:

- Open the main activity file: MainActivity.java.
- Edit the file to add the button handler.

```

import com.liveperson.messaging.sdk.bootstrap.LivePerson;

public class MainActivity extends AppCompatActivity {

    @Override

```

```
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.main_activity);

    String BrandID = "brandIdString";
    LivePerson.initialize(MainActivity.this, BrandID);

    LivePerson.setUserProfile("Default", "User", "11111");

    Button showBtn = (Button) findViewById(R.id.show_btn);
    showBtn.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            LivePerson.showConversation(MainActivity.this);
        }
    });

    Button hideBtn = (Button) findViewById(R.id.hide_btn);
    hideBtn.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            LivePerson.hideConversation(MainActivity.this);
        }
    });
}
```

## Test the SDK

That's it! You are ready to run the app and try it out. Hit the **Run** command and try tapping on the button in the main view.

## LivePerson API Methods

Detailed below are the LivePerson API methods that shall be called by the developer, and demonstrated on the sample app.

API Name	Purpose
initialize	To initialize the resources required by the SDK
showConversation	To display the messaging screen
hideConversation	To hide the conversation screen
setUserProfile	To take custom parameters about the consumer as an input, set them for the messaging agent, and attach them to the transcript
registerLPPusher	To register to LivePerson push services
handlePush	To receive all incoming push messages in a single function
getSDKVersion	To return the SDK version
setCallback	To gets events from SDK - need to implement ILivePersonCallback
removeCallBack	To stop getting events from the SDK
checkActiveConversation	To check whether there is an active conversation
checkAgentID	To return agent data such as, first name, last name, email, avatarURL, through callback
markConversationAsUrgent	To mark the current conversation as urgent
resolveConversation	To resolve the current conversation
shutDown	To shut down the SDK

### initialize

```
public static void initialize (Context context, String brandId)
```

To allow for user interaction, the Messaging Mobile SDK must be initiated. This API initializes the resources required by the SDK; all subsequent API calls assume that the SDK has been initialized.

When the conversation screen is displayed, the server connection for messaging will be established. If a user session is already active and an additional SDK init call is made, it will be ignored and will not start an additional session.

### showConversation

```
public static boolean showConversation(Activity activity)
```

The showConversation API displays the messaging screen. The consumer can then start or continue a conversation. The conversation screen is controlled entirely by the SDK.

This method returns a value to mark success opening the messaging screen, or an error code. Initiating the conversation screen opens the websocket to the LivePerson Messaging Server.

### hideConversation

```
public static void hideConversation(Activity activity)
```

The `hideConversation` API hides the conversation screen. The conversation screen is shown again by calling `Start Conversation`. Hiding the conversation closes the websocket after one minute.

*Note: The back button on the conversation screen completes the same function.*

## `setUserProfile`

```
public static void setUserProfile(String firstName, String lastName, String phone)
```

The `setUserProfile` API takes custom parameters about the consumer as an input and sets it for the messaging agent, and attaches it to the transcript. This can be set at any time either before, after, or during a messaging session.

## `registerLPPusher`

```
public static void registerLPPusher(String gcmToken)
```

The push notification service used by the application must be registered with LivePerson with the API passing the relevant token for iOS and Android push services.

## `handlePush`

```
public static void handlePush(Context ctx, String brandId, String message)
```

All incoming push messages are received in a single function in the host app. This allows the host app to:

- Receive non-messaging related push messages.
- Handle custom in-app alerts upon an incoming message.
- Use the SDK's in-app alert upon an incoming message by calling the `DisplayInAppAlert` API. This API will present the default in-app alert as an overlay on top of the host app's current screen.

*Note: In the situation that you want your own custom notification, do not call this method.*

## `getSDKVersion`

```
public static String getSDKVersion()
```

Returns the SDK version.

## `setCallback`

```
public static void setCallback(ILivePersonCallback listener)
```

See `ILivePersonCallback` Interface for more information.

## `removeCallback`

```
public static void removeCallback()
```

Removes the `ILivePersonCallback` callback.

## `checkActiveConversation`

```
public static boolean checkActiveConversation()
```

Checks whether there is an active (unresolved) conversation and returns a boolean accordingly.

## `checkAgentID`

```
public static void checkAgentID(ICallback<AgentData, Throwable> callback)
```

If there is an active conversation, this API returns agent data (first name, last name, email, avatarURL) through callback. If there is no active conversation, the API returns null.



## markConversationAsUrgent

```
public static boolean markConversationAsUrgent()
```

Marks the current conversation as urgent. Returns false if called before initializing the SDK (initialize). Otherwise, returns true.

## resolveConversation

```
public static boolean resolveConversation()
```

Resolves the current conversation. Returns false if called before initializing the SDK (initialize). Otherwise, returns true.

## shutDown

```
public static void shutDown()
```

Shutting down the SDK removes the footprint of the user session from local memory. After shutdown the SDK is unavailable until re-initiated. Message history is saved locally on the device and synced with the server upon reconnection. The server continues to send push notifications when the SDK is shut down. This does not end the messaging conversation.

*Note: This API is not currently available on SDK v0.1.*

## ILivePersonCallback Interface

```
public interface ILivePersonCallback {  
    void onCustomGuiTapped();  
    void onInAppMessageReceived(String agentName, String message);  
}
```

## Custom GUI on Toolbar

The API uses the custom GUI interaction API to determine if the consumer has interacted with a custom UI element in the messaging window. The callback is `ILivePersonCallback:CustomGUITapped`.

When this callback is triggered, the application can run the corresponding method.

- To configure the button, edit the proper values in `branding.xml`:  
`custom_button_icon_name`, `custom_button_icon_description`.
- To disable the button, leave an empty value.
- The `OnClick` button will call callback listener:  
`ILivePersonCallback:onCustomGuiTapped<toolbar screenshot>`

## Push Messages and Notifications

The GCM push receiver needs to be implemented by the host app. You must pass the GCM token to the SDK by calling the `LivePerson:registerLPPusher` method.

There are two scenarios for receiving messages when the conversation screen is not visible:

- A. The SDK is still connected to server: In this case, the SDK will pass it to the host app by calling the callback `ILivePersonCallback:onInAppMessageReceived`.
- B. The SDK is not connected, or the app stopped running: In this case the host app will receive the push messages on the GCM receiver.

In both scenarios, you can decide what to do with the messages. You can either implement your own behavior, or call `LivePerson:handlePush`, and the SDK will show it as a notification.

## Configuring the SDK

The SDK allows you to configure the look and feel of your app with your branding.xml file. This file MUST contain all the exact resource-names as listed below:

### Brand

Resource Name	Description
<code>&lt;string name="brand_name"&gt;</code>	The brand name will be shown as a title on toolbar when there is no active conversation.
<code>&lt;string name="language"&gt;</code>	The language is defined by a two-letter <a href="#">ISO 639-1</a> language code, for example, "en" for English. If no value is provided, the SDK will use the language according to the device's locale.
<code>&lt;string name="country"&gt;</code>	Country code. If no value is provided, the SDK will use the country according to the device's locale. For more information about language and country, click <a href="#">here</a> .
<code>&lt;integer name="message_receive_icons"&gt;</code>	For each message, there are three indicators available: Message sent, Message received, Message read. You can customize the indicators according to your needs, by using a number between 1 and 3: 0 - text (sent, delivered etc.) instead of icons 1 - Sent only 2 - Sent+received 3 - Sent+received+read
<code>&lt;string-array name="message_receive_text"&gt;</code>	If you set 0 in the resource message_receive_icons, you can specify what texts appears for each state. You must have 4 items, in the following order: 1 <sup>st</sup> item - message sent 2 <sup>nd</sup> item - message delivered 3 <sup>rd</sup> item - message read 4 <sup>th</sup> item - message not delivered
<code>&lt;string name="custom_button_icon_name"&gt;</code>	Custom button icon filename without extension. This will be displayed on the toolbar. onClick listener is available by implementing the callback listener using: <code>LivePerson.setCallback ( ILivePersonCallback:onCustomGuiTapped).</code>
<code>&lt;string name="custom_button_icon_description"&gt;</code>	Content description for custom button. It briefly describes the view and is primarily used for accessibility support. Set this property to enable better accessibility support for your application
<code>&lt;bool name="showTTRPopup"&gt;</code>	TRUE: Show TTR popup as the message is sent. FALSE: Show TTR popup when the conversation screen is hidden and then shown again.

### Styling

Resource Name	Description
<code>&lt;color name="conversation_background"&gt;</code>	Color code for the entire view background.

## Agent Message Bubble

Resource Name	Description
<code>&lt;dimen name="agent_bubble_stroke_width"&gt;</code>	Int number for the outline width.
<code>&lt;color name="agent_bubble_stroke_color"&gt;</code>	Color code for the outline color.
<code>&lt;color name="agent_bubble_message_text_color"&gt;</code>	Color code for the text of the agent bubble.
<code>&lt;color name="agent_bubble_message_link_text_color"&gt;</code>	Color code for links in the text of the agent bubble.
<code>&lt;color name="agent_bubble_timestamp_text_color"&gt;</code>	Color code for the timestamp of the agent bubble.
<code>&lt;color name="agent_bubble_background_color"&gt;</code>	Color code for the background of the agent bubble.

## Visitor Message Bubble

Resource Name	Description
<code>&lt;color name="visitor_bubble_message_text_color"&gt;</code>	Color code for the text of the visitor bubble.
<code>&lt;color name="visitor_bubble_message_link_text_color"&gt;</code>	Color code for links in the text of the visitor bubble.
<code>&lt;color name="visitor_bubble_timestamp_text_color"&gt;</code>	Color code for the timestamp of the visitor bubble.
<code>&lt;color name="visitor_bubble_background_color"&gt;</code>	Color code for the background of the visitor bubble.

## System messages

Resource Name	Description
<code>&lt;color name="system_bubble_text_color"&gt;</code>	Color code for the text of the system messages.

## Permissions

The SDK requires some permissions from your app's `AndroidManifest.xml` file.

These permissions allow the SDK to open network sockets and to access information about networks.

```
<uses-permission android:name="android.permission.INTERNET" />
<uses-permission android:name="android.permission.ACCESS_NETWORK_STATE" />
```

## Dependencies

**com.koushikdutta.async:androidasync:2.1.6**

Low level network protocol library.

**com.facebook.fresco:fresco:0.8.0**

An Android library for managing images and the memory they use.

This document, materials or presentation, whether offered online or presented in hard copy ("LivePerson Informational Tools") is for informational purposes only. LIVEPERSON, INC. PROVIDES THESE LIVEPERSON INFORMATIONAL TOOLS "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

The LivePerson Informational Tools contain LivePerson proprietary and confidential materials. No part of the LivePerson Informational Tools may be modified, altered, reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), without the prior written permission of LivePerson, Inc., except as otherwise permitted by law. Prior to publication, reasonable effort was made to validate this information. The LivePerson Information Tools may include technical inaccuracies or typographical errors. Actual savings or results achieved may be different from those outlined in the LivePerson Informational Tools. The recipient shall not alter or remove any part of this statement.

Trademarks or service marks of LivePerson may not be used in any manner without LivePerson's express written consent. All other company and product names mentioned are used only for identification purposes and may be trademarks or registered trademarks of their respective companies. LivePerson shall not be liable for any direct, indirect, incidental, special, consequential or exemplary damages, including but not limited to, damages for loss of profits, goodwill, use, data or other intangible losses resulting from the use or the inability to use the LivePerson Information Tools, including any information contained herein.

© 2016 LivePerson, Inc. All rights reserved.