

# User Guide to the OpenCalphad software package version 6.0

DRAFT

Bo Sundman, August 29, 2019

Updates of OC User Guide

- version 5, 2018-09-19 first use of hypertargets
- version 4, 2016-10-06
- version 3, 2016-01-01

Earlier versions of OC had no User Guide

This page intentionally blank

# Contents

<b>1</b>	<b>Introduction</b>	<b>12</b>
<b>2</b>	<b>Some general features</b>	<b>12</b>
2.1	Command line user interface . . . . .	12
2.1.1	Command line editing and history . . . . .	13
2.1.2	Popup window for read/save . . . . .	13
2.1.3	On-line help . . . . .	14
2.1.4	Environment and startup macro file . . . . .	14
2.1.5	Macro files . . . . .	14
2.1.6	User interface feedback . . . . .	15
2.2	Names and symbols . . . . .	15
2.3	Elements, species, components, constituents and system . . . . .	16
2.4	Phases, composition sets and phase tuples . . . . .	16
2.5	The use of wildcards for names . . . . .	17
2.6	State variables . . . . .	17
2.7	Thermodynamic databases . . . . .	17
2.8	Model parameters . . . . .	17
2.8.1	Model Parameter Identifiers . . . . .	18
2.8.2	Constituent array and degrees . . . . .	21
2.8.3	The TPFUN expression and bibliographic reference . . . . .	21
2.9	The reference state of a component . . . . .	22
2.10	Equilibrium calculations . . . . .	23
2.11	Property diagrams . . . . .	23
2.12	Phase diagrams . . . . .	23
2.13	Assessment of model parameters for databases . . . . .	23
2.13.1	Entering coefficients to be assessed . . . . .	24
2.13.2	Entering phases and model parameters . . . . .	24
2.13.3	Entering experimental data . . . . .	24
2.13.4	Saving the state of the assessment . . . . .	24
2.13.5	Performing the assessment . . . . .	25
2.14	Application software . . . . .	25

<b>3</b>	<b>All commands</b>	<b>26</b>
3.1	Options . . . . .	26
<b>4</b>	<b>About</b>	<b>27</b>
<b>5</b>	<b>Amend</b>	<b>27</b>
5.1	Amend assessment result . . . . .	27
5.2	<i>amend</i> Bibliography . . . . .	27
5.3	<i>amend</i> Components . . . . .	28
5.4	<i>amend</i> Constitution . . . . .	28
5.5	<i>amend</i> Element . . . . .	28
5.6	<i>amend</i> Equilirium . . . . .	28
5.7	<i>amend</i> General . . . . .	29
5.8	<i>amend</i> Line . . . . .	29
5.9	<i>amend</i> All optimizing coefficients . . . . .	29
5.10	<i>amend</i> Parameter . . . . .	29
5.11	<i>amend</i> for Phase <phase name> . . . . .	29
5.11.1	<i>amend</i> phase < ...> Addition . . . . .	30
5.11.1.1	<i>amend phase ... addition</i> Elastic_model_1 . . . . .	30
5.11.1.2	<i>amend phase ... addition</i> LowT_Cp_model . . . . .	30
5.11.1.3	<i>amend phase ... addition</i> Magnetic_contrib . . . . .	30
5.11.1.4	<i>amend phase ... addition</i> Quit . . . . .	31
5.11.1.5	<i>amend phase ... addition</i> Schottky_anomaly . . . . .	31
5.11.1.6	<i>amend phase ... addition</i> Smooth-Cp-step . . . . .	31
5.11.1.7	<i>amend phase ... addition</i> Twostate-liquid . . . . .	31
5.11.2	<i>amend phase ...</i> Aqueous-model . . . . .	31
5.11.3	<i>amend phase ...</i> BCC-permutations . . . . .	32
5.11.4	<i>amend phase ...</i> Composition set . . . . .	32
5.11.5	<i>amend phase ...</i> Default Constitution . . . . .	32
5.11.6	<i>amend phase ...</i> Diffusion . . . . .	33
5.11.7	<i>amend phase ...</i> Disordered fraction sets . . . . .	33
5.11.8	<i>amend phase ...</i> FCC_CVM_tetradrn . . . . .	33
5.11.9	<i>amend phase ...</i> FCC-permutations . . . . .	33
5.11.10	<i>amend phase ...</i> Flory_Huggins model . . . . .	34

5.11.11	<i>amend phase ... Gaddition</i> . . . . .	34
5.11.12	<i>amend phase ... Quasichemical</i> . . . . .	34
5.11.13	<i>amend phase ... Quit</i> . . . . .	34
5.11.14	<i>amend phase ... UNIQUAC</i> . . . . .	34
5.12	<i>amend Quit</i> . . . . .	34
5.13	<i>amend for Species</i> . . . . .	34
5.14	<i>amend Symbol</i> . . . . .	34
5.15	<i>amend Tpfunction</i> . . . . .	35
<b>6</b>	<b>Back</b>	<b>35</b>
<b>7</b>	<b>Calculate</b>	<b>35</b>
7.1	<i>calculate All equilibria</i> . . . . .	35
7.2	<i>calculate Equilibrium</i> . . . . .	36
7.3	<i>calculate Global-Gridmin</i> . . . . .	36
7.4	<i>calculate No-Global</i> . . . . .	36
7.5	<i>calculate Phase &lt;phase name&gt;</i> . . . . .	37
7.5.1	<i>calculate phase ... All-Derivatives</i> . . . . .	37
7.5.2	<i>calculate phase ... Constitution_Adjust</i> . . . . .	37
7.5.3	<i>calculate phase ... Diffusion_Coefficients</i> . . . . .	37
7.5.4	<i>calculate phase ... G_and_dGdy</i> . . . . .	38
7.5.5	<i>calculate phase ... Only-G</i> . . . . .	38
7.5.6	<i>calculate phase ... Quit</i> . . . . .	38
7.6	<i>calculate Quit</i> . . . . .	38
7.7	<i>calculate Symbol</i> . . . . .	38
7.8	<i>calculate Tpfun-Symbols</i> . . . . .	39
7.9	<i>calculate Transition</i> . . . . .	39
7.10	<i>calculate Tzero point</i> . . . . .	39
7.11	<i>calculate with check after</i> . . . . .	39
<b>8</b>	<b>Debug</b>	<b>39</b>
8.1	<i>debug Elasticity</i> . . . . .	39
8.2	<i>debug Free lists</i> . . . . .	40
8.3	<i>debug Stop_on_Error</i> . . . . .	40

<b>9</b>	<b>Delete</b>	<b>40</b>
9.1	<i>delete</i> Composition set . . . . .	40
9.2	<i>delete</i> Element . . . . .	40
9.3	<i>delete</i> Equilibrium . . . . .	40
9.4	<i>delete</i> Phase . . . . .	40
9.5	<i>delete</i> Quit . . . . .	40
9.6	<i>delete</i> Species . . . . .	41
9.7	<i>delete</i> Step_Map_Results . . . . .	41
<b>10</b>	<b>Enter</b>	<b>41</b>
10.1	<i>enter</i> Bibliography . . . . .	41
10.2	<i>enter</i> Comment . . . . .	42
10.3	<i>enter</i> Constitution . . . . .	42
10.4	<i>enter</i> Copy of equilibrium . . . . .	42
10.5	<i>enter</i> Element . . . . .	42
10.6	<i>enter</i> Equilibrium . . . . .	42
10.7	<i>enter</i> Experiment . . . . .	43
10.8	<i>enter</i> GNUPLOT Terminal . . . . .	43
10.9	<i>enter</i> Many Equilibria . . . . .	43
10.10	<i>enter</i> Material . . . . .	44
10.11	<i>enter</i> Optimizing coefficient . . . . .	45
10.12	<i>enter</i> Parameter . . . . .	45
10.13	<i>enter</i> Phase . . . . .	46
10.14	<i>enter</i> Plot_data . . . . .	47
10.15	<i>enter</i> Quit . . . . .	47
10.16	<i>enter</i> Species . . . . .	48
10.17	<i>enter</i> Symbol . . . . .	48
10.18	<i>enter</i> Tpfun_Symbol . . . . .	49
<b>11</b>	<b>Exit</b>	<b>49</b>
<b>12</b>	<b>Fin</b>	<b>49</b>
<b>13</b>	<b>Help and ?</b>	<b>49</b>

<b>14 HPcalc</b>	<b>50</b>
<b>15 Information</b>	<b>50</b>
<b>16 List</b>	<b>50</b>
16.1 <i>list</i> active-equilibria . . . . .	50
16.2 <i>list</i> Axis . . . . .	51
16.3 <i>list</i> Bibliography . . . . .	51
16.4 <i>list</i> Conditions . . . . .	51
16.5 <i>list</i> Data . . . . .	51
16.5.1 <i>list data</i> LaTeX . . . . .	51
16.5.2 <i>list data</i> Macro . . . . .	51
16.5.3 <i>list data</i> PDB . . . . .	51
16.5.4 <i>list data</i> TDB . . . . .	51
16.6 <i>list</i> Equilibria . . . . .	51
16.7 <i>list</i> Error message . . . . .	52
16.8 <i>list</i> Line equilibria . . . . .	52
16.9 <i>list</i> Model parameter identifiers . . . . .	52
16.10 <i>list</i> Model parameter value . . . . .	52
16.11 <i>list</i> optimization . . . . .	52
16.11.1 <i>list optimization</i> coefficients . . . . .	52
16.11.2 <i>list optimization</i> debug . . . . .	52
16.11.3 <i>list optimization</i> correlation_matrix . . . . .	52
16.11.4 <i>list optimization</i> experiments . . . . .	52
16.11.5 <i>list optimization</i> graphics . . . . .	53
16.11.6 <i>list optimization</i> long . . . . .	53
16.11.7 <i>list optimization</i> macro . . . . .	53
16.11.8 <i>list optimization</i> short . . . . .	53
16.12 <i>list</i> Parameter . . . . .	54
16.13 <i>list</i> Phase <phase name> . . . . .	54
16.13.1 <i>list phase</i> ... Constitution . . . . .	54
16.13.2 <i>list phase</i> ... Data . . . . .	54
16.13.3 <i>list phase</i> ... Model . . . . .	54
16.14 <i>list</i> Quit . . . . .	54

16.15	<i>list</i> Results . . . . .	55
16.16	<i>list</i> Short . . . . .	55
16.17	<i>list</i> State_Variables . . . . .	56
16.18	<i>list</i> Symbols . . . . .	56
16.19	<i>list</i> Tpfun Symbols . . . . .	56
<b>17</b>	<b>Macro</b>	<b>56</b>
<b>18</b>	<b>Map</b>	<b>57</b>
<b>19</b>	<b>New</b>	<b>57</b>
<b>20</b>	<b>Optimize</b>	<b>57</b>
<b>21</b>	<b>Plot</b>	<b>58</b>
21.1	<i>plot xaxis yaxis</i> Horizontal axis variable . . . . .	58
21.2	<i>plot xaxis yaxis</i> Vertical axis variable . . . . .	58
21.3	<i>plot xaxis yaxis</i> Options? . . . . .	58
21.4	<i>plot xaxis yaxis</i> Append . . . . .	59
21.5	<i>plot xaxis yaxis</i> Axis_Labels . . . . .	59
21.6	<i>plot xaxis yaxis</i> Graphics format . . . . .	60
21.7	<i>plot xaxis yaxis</i> Output file . . . . .	60
21.8	<i>plot xaxis yaxis</i> Position of keys . . . . .	60
21.9	<i>plot xaxis yaxis</i> Quit . . . . .	60
21.10	<i>plot xaxis yaxis</i> Render . . . . .	60
21.11	<i>plot xaxis yaxis</i> Scale_Range . . . . .	61
21.12	<i>plot xaxis yaxis</i> Text . . . . .	61
21.12.1	<i>plot xaxis yaxis text</i> Modify existing text?: . . . . .	61
21.12.2	<i>plot xaxis yaxis text</i> Which text index?: . . . . .	61
21.12.3	<i>plot xaxis yaxis text</i> X position . . . . .	61
21.12.4	<i>plot xaxis yaxis text</i> Y position . . . . .	61
21.12.5	<i>plot xaxis yaxis text</i> Fontscale . . . . .	61
21.12.6	<i>plot xaxis yaxis text</i> Angle (degrees) . . . . .	61
21.12.7	<i>plot xaxis yaxis text</i> Do you want to calculate the equilibrium? . . . . .	62
21.12.8	<i>plot xaxis yaxis text</i> Text: . . . . .	62



21.13	<i>plot xaxis yaxis</i> Title . . . . .	62
21.14	<i>plot xaxis yaxis</i> Extra . . . . .	62
21.14.1	<i>plot xaxis yaxis</i> extra font-and-color . . . . .	63
21.14.2	<i>plot xaxis yaxis</i> extra Gibbs-triangle . . . . .	63
21.14.3	<i>plot xaxis yaxis</i> extra line-with-symbols . . . . .	63
21.14.4	<i>plot xaxis yaxis</i> extra logscale . . . . .	63
21.14.5	<i>plot xaxis yaxis</i> extra manipulate lines . . . . .	63
21.14.6	<i>plot xaxis yaxis</i> extra lower left corner text . . . . .	63
21.14.7	<i>plot xaxis yaxis</i> extra spawn . . . . .	63
21.14.8	<i>plot xaxis yaxis</i> extra no heading . . . . .	63
21.14.9	<i>plot xaxis yaxis</i> extra pause option . . . . .	63
21.14.10	<i>plot xaxis yaxis</i> extra ratios XY . . . . .	64
21.14.11	<i>plot xaxis yaxis</i> extra tie-line . . . . .	64
<b>22</b>	<b>Quit</b>	<b>64</b>
<b>23</b>	<b>Read</b>	<b>64</b>
23.1	<i>read</i> Direct . . . . .	64
23.2	<i>read</i> Quit . . . . .	64
23.3	<i>read</i> PDB . . . . .	64
23.4	<i>read</i> TDB . . . . .	65
23.5	<i>read</i> Unformatted . . . . .	65
<b>24</b>	<b>Save</b>	<b>65</b>
24.1	<i>save</i> Direct . . . . .	65
24.2	<i>save</i> Quit . . . . .	66
24.3	<i>save</i> PDB . . . . .	66
24.4	<i>save</i> TDB . . . . .	66
24.5	<i>save</i> SOLGAS . . . . .	66
24.6	<i>save</i> Unformatted . . . . .	66
<b>25</b>	<b>Select</b>	<b>66</b>
25.1	<i>select</i> Equilibrium . . . . .	66
25.2	<i>select</i> Graphics . . . . .	66
25.3	<i>select</i> Language . . . . .	66

25.4	<i>select</i> Minimizer . . . . .	67
25.5	<i>select</i> Optimizer . . . . .	67
<b>26</b>	<b>Set</b>	<b>67</b>
26.1	<i>set</i> Advanced . . . . .	67
26.1.1	<i>set advanced</i> equilibrium transfer . . . . .	67
26.1.2	<i>set advanced</i> global-min-onoff . . . . .	67
26.1.3	<i>set advanced</i> grid_density . . . . .	67
26.1.4	<i>set advanced</i> help-popup-off . . . . .	67
26.1.5	<i>set advanced</i> map-special . . . . .	68
26.1.6	<i>set advanced</i> open-popup-off . . . . .	68
26.1.7	<i>set advanced</i> quit . . . . .	68
26.1.8	<i>set advanced</i> turn on equi-entropy extrapolation . . . . .	68
26.1.9	<i>set advanced</i> level . . . . .	68
26.1.10	<i>set advanced</i> small-grid-onoff . . . . .	68
26.1.11	<i>set advanced</i> working-directory . . . . .	68
26.2	<i>set</i> As start equilibrium . . . . .	68
26.3	<i>set</i> Axis . . . . .	69
26.4	<i>set</i> Bit . . . . .	69
26.5	<i>set</i> Condition . . . . .	70
26.6	<i>set</i> Echo . . . . .	71
26.7	<i>set</i> Fixed coefficient . . . . .	71
26.8	<i>set</i> Input-Amounts . . . . .	71
26.9	<i>set</i> Interactive . . . . .	73
26.10	<i>set</i> Log-File . . . . .	73
26.11	<i>set</i> Numeric-Options . . . . .	73
26.12	<i>set</i> Optimizing conditions . . . . .	73
26.13	<i>set</i> system variable . . . . .	73
26.14	<i>set</i> Phase <phase name> . . . . .	73
26.14.1	<i>set phase</i> ... Amount . . . . .	73
26.14.2	<i>set phase</i> ... Bits . . . . .	74
26.14.3	<i>set phase</i> ... Constitution . . . . .	74
26.14.4	<i>set phase</i> ... Default-constitution . . . . .	74
26.14.5	<i>set phase</i> ... Quit . . . . .	74

26.14.6 <i>set phase ... Status</i> . . . . .	74
26.15 <i>set Quit</i> . . . . .	74
26.16 <i>set Range of experimental equilibria</i> . . . . .	75
26.17 <i>set Reference-State</i> . . . . .	75
26.18 <i>set Scaled coefficient</i> . . . . .	75
26.19 <i>set Status</i> . . . . .	76
26.19.1 <i>set status Constituent</i> . . . . .	76
26.19.2 <i>set status Element</i> . . . . .	76
26.19.3 <i>set status Phases</i> . . . . .	76
26.19.4 <i>set status Species</i> . . . . .	77
26.20 <i>set initial_T_and_P</i> . . . . .	77
26.21 <i>set Units</i> . . . . .	77
26.22 <i>set Variable coefficient</i> . . . . .	77
26.23 <i>set Verbose</i> . . . . .	77
26.24 <i>set Weight</i> . . . . .	77
<b>27 Show</b>	<b>77</b>
27.1 <i>property:</i> . . . . .	78
<b>28 Step</b>	<b>78</b>
28.1 <i>step Conditional</i> . . . . .	78
28.2 <i>step Normal</i> . . . . .	78
28.3 <i>step Quit</i> . . . . .	78
28.4 <i>step Separate</i> . . . . .	78
<b>29 Summary</b>	<b>79</b>

# 1 Introduction

The development of the OpenCalphad (OC) software was started by a small group of dedicated scientists who wanted to provide an open source multicomponent thermodynamic software. It aims to provide a free high quality software for thermodynamic calculations, including property and phase diagrams, assessment of databases and a thermodynamic library for simulations for inorganic systems i.e. gases, liquids, alloys and other materials using many different kinds of models for the phases. There are three basic papers published about OC [1, 2, 3]. General information about thermodynamic models, calculations and assessments based on the Calphad technique can be found in the book by Lukas et al [4]. The software is provided free with a GNU GPL license.

In OC there is also a framework to store different kinds of materials properties that depend on temperature, pressure and composition when such properties are related to the phases of the system. The OC software can also be used to assess model parameters for such properties from experimental and theoretical values.

Complimentary (and maybe sometimes contradictory, I am not perfect) information about the OC software can be found in `getting-started.pdf`, `news-oc5.pdf` and the other parts of the OC documentation.

## 2 Some general features

The different parts of the OC software are documented separately for each module: thermodynamic models (GTP), equilibrium calculations (HMS), step/map/plot routines (SMP) and the application software interface (OCASI/TQ). With OC version 6 the old utility package `metlib`, originally written in F77, has been converted completely to the new Fortran standard and is included in the documentation. The documentation of the assessment module is not finished.

OC uses the free numerics packages LAPACK and BLAS and a free least square routine, LMDIF [5], developed at Argonne 1980, for assessments. For graphics OC generates a command file which can be plotted with the free GNUPLOT [6] software. If GNUPLOT is properly installed this is done automatically by OC.

### 2.1 Command line user interface

OC is operated by commands typed by the user or read from a macro file. The command monitor has a menu of command and each of these usually has sub-menus and finally some questions may be asked like phase names, a value or an expression. In most cases a default answer is provided which can be selected by just pressing the RETURN key or by typing a comma, “,”, on the same line as the command. At all levels the user should be able to type a ? and get some help, usually an extract from this manual, sometimes just a menu or examples of answers.

For the menu commands a single ? will just display the menu, in order to obtain the User Guide type two, ??.

If you prefer a graphical user interface (GUI) you are welcome to add this to the OC software.

### 2.1.1 Command line editing and history

On Windows the OS provides history and on-line editing of commands but on Linux and other OS this has to be provided by the software itself. Thus a C routine with an iso-C interface written by Urban S Jost (2009) copied from <http://www.urbanjost.altervista.org/LIBRARY/libCLI/Getkey/getkey.html> has been added and there is a separate documentation of this if you want to change anything.

The command history is saved inside OC and by typing “upparrow” (normally ctrl-P but it can be different on different terminals) earlier command can be retrieved and also edited.

### 2.1.2 Popup window for read/save

To open a file for reading or saving one needs a file browser and from OC version 5.018 I have included a routine “TINYFILEDIALOGS” developed by Guillaume Vareille (2014-2018) available at <http://tinyfiledialogs.sourceforge.net>. This will open a popup window to open a file (for a macro, a database or to save a calculation). In this window you can browse your directories to find the file.

This has some consequences for editing your macro files which you should be aware of and which are explained below.

You can turn off the open file popup window feature with the command **set advanced open\_popup\_off Y**. You can turn it on again with the same command finishing with anything but Y.

- The directory where you start the session with OC is called the “working directory”. On a linux system you can find this directory by typing “pwd” before starting OC (or if you type *@pwd* inside OC). On a Windows system you can see the working directory and its files if you type *@dir* inside OC.
- When the popup window is opened the directories and files matching the “filter” in the working directory should be listed. If not you can select a directory inside the popup window. The filter when open a macro file is “OCM” and when opening a database file it is “TDB” which means only files with these extensions are listed. You can change the directory in the popup window to select the file you want and you can read a file with another extension. OC will save internally the directory where you start the macro.
- Inside a macro file you normally read a TDB file and if you do not specify the name of the database on the same line as the command *read tdb* the popup window will open so you can specify the file in this window.
- But normally you know which database you want to use inside the macro and if you give the file name on the same line as the command: *read tdb filename* the popup window will not open and OC will search for the specified database file starting from the “working directory”. But if the database file is in the same directory as the macro file you MUST prefix “filename” with “./”, i.e. *read tdb ./filename*. You may include directories in “filename”, (including “./” to go to the directory above). OC will replace the “./” by the directory where you started the macro or prefix “./” by this directory.
- In the macro file you can give the full path to the file to be opened but that is rather clumsy.

- When you open a file for write inside a macro, like output from a plot, you can also specify the file name in the command prefixed by “./” if you want to save the file on the same directory as the macro file. Otherwise it will be saved at the working directory.
- If you use the switch “/output=” or “/append=” after a command to redirect output from the command you can also use the popup window to specify the file name or use a filename with or without the prefix “./”. The default extension in this case is “DAT”.

Opening files on different directories can be complicated inside OC. For example during assessments you may use many different files for generating graphics and unformatted save files. Preferably you keep all of these on the same directory.

You are welcome to provide feedback on this popup feature and other parts of the user interface.

### 2.1.3 On-line help

A recent feature added to OC is providing on-line help using a browser window where this user guide is available as a searchable HTML file.

Whenever the user wants an explanation of a question the OC software asks he can type a ? and the OC software will open a separate browser window positioned at the relevant text in the user guide. You can then search the whole user guide for related information.

Whenever the user types ? at a menu level just the menu will be displayed but if you type ?? the user guide will be opened at the relevant menu text with additional explanations.

This feature is new and is still under development. Feedback is helpful. It can be turned off (or on again) by the command **set advanced help\_popup\_off y** in section subsection26.1.4.

For installation of the help system please read the installation guide.

### 2.1.4 Environment and startup macro file

The OC program will look for an environment variable called OCHOME and if it finds this it will look for a file start.OCM which will be executed before the user gets control. This can typically be useful to set some variables like the plot terminals, see section subsection10.8. If there is no OCHOME environment variable the current “working directory” will be searched.

The ochelp.tex and ochelp.html file should be copied from the directory “manual” in the installation directory to this OCHOME directory.

### 2.1.5 Macro files

The macro command is very useful for preparing complex calculations and to remember how you did them. A macro file is simplest to create starting from a log file (created by the **SET LOG** command). See the macros directory for examples.

After a macro command the popup window will allow you to search for the file on all your directories unless you type the name of the file on the same line. In the latter case the macro file must be on your “working directory”, see section subsection2.1.2

When you open files, such as databases, inside a macro file and you type the file name on the same line as the command as “read tdb ./steel1”, you must prefix the file name, “steel1” with “./” if the tdb file is on the same directory as the macro file. If your command line is just “read tdb” the popup window will be activated and you can specify the file there.

If you open another macro file inside a macro (typically when you do assessments) you must also prefix the name of the macro with “./” unless you want to select the macro using the popup window.

You can insert stops in the macro file with “@&” at the beginning of a line. This can be useful to inspect the output. The macro continues after pressing the ENTER/RETURN key. Depending on the graphical driver you use the program will normally pause after each plot and you must use the mouse to click on the graphical window to continue.

You can insert comments in the macro file with “@\$” at the beginning of the comment line.

A macro file should be terminated with the command **SET INTERACTIVE** which gives back control to the keyboard (or the calling macro file) otherwise the program may terminate at the end of the macro.

Macro files can be nested 5 levels deep.

### 2.1.6 User interface feedback

OC has grown organically and although the basic concepts has been quite clear the implementations of several of these has become rather confusing. This will eventually require some cleaning up of the user interface.

A central part of any thermodynamic software is the modeling of the phases. A new PDB format for databases may help a little with the specification of the models. An attempt has been made in this version to clean up the way a model is specified and used. At present you must first ENTER the phase to give a name, basic model, sublattices and constituents. Then use the AMEND command to add magnetism, a disordered fraction set and/or use BCC/FCC permutations. Originally some of these things were set by the command SET PHASE ... BIT and that was not very clear.

Some computational options like for the grid minimizer are still set with several different commands. It is useful for the developers to have some feedback from users to organize this better.

## 2.2 Names and symbols

There are many symbols and names used in this package. A symbol or name **MUST** start with a letter A-Z. It usually can contain digits and the underscore character after the initial letter. All names are CASE INSENSITIVE, i.e. fe, FE, fE and Fe is the same. Some special symbols are used:

- $/-$  is used to denote the electron.  $/+$  or  $/-1$  can be used for a positive charge.
- $\#$  are used to identify composition sets after a phase name or sublattice after a constituent name.
- $\&$  are used in some parameter identifiers to specify the constituent for the parameter, like for mobilities, the mobility of Fe in the BCC phase is denoted MQ&FE(BCC).

A name of an element is one or two characters, a species maximum 24 characters (note that a species name does not have to be its stoichiometric formula). A phase name is 24 characters but can also have a pre- and suffix 4 characters long and possibly a composition set number after a hash symbol, #.

State variable symbols and TP-fun symbols can be 16 characters long. TP-funs are expressions used to describe the  $T$  and  $P$  dependence of model parameters.

For user input it is possible to use abbreviations of names but you must be careful with names that have the same abbreviation and avoid phase names that are abbreviations of another phase!

## 2.3 Elements, species, components, constituents and system

Much of the confusion using thermodynamics is due to the fact that the user has no clear idea of the terms in the title of this section. A strict definition used in OC is:

- An element is from the periodic chart. The user can also enter fictitious elements.
- A species is a molecularlike aggregate of elements with fixed ratios. It can also have a charge and be called an ion. The vacancy, representing an empty lattice site, is also a species.
- The constituents of a phase is a subset of the species.
- The set of components limits the composition of the system. By default the elements are the components but the user can enter any orthogonal set of species as components by a command, see section subsection5.3.

A system is defined by its components. Conditions on the amounts or chemical potentials can only be set for the components, not for any arbitrary species.

The models for phases can use many different models and sets of constituents to describe Long Range Ordering (LRO) and Short Range Ordering (SRO). Some phases can exist only for a specific composition, or for only a subset of the components of a system.

## 2.4 Phases, composition sets and phase tuples

Many come across thermodynamic calculations the first time in chemistry writing chemical reactions. In such reactions the solid and liquid phases are usually treated as stoichiometric and only the gas can have several constituents. In the Calphad approach most phases are treated as solutions with variable composition but with different models for their Gibbs energy functions. But some phases can exist only for a specific or very restricted composition.

Each phase in a system has a name and a thermodynamic model and set of constituents, see section subsection2.3. The models are explained in a separate documentation. The phases can be entered interactively or read from a database or a saved file together with the last calculation.

In some cases a phase can be stable with two or more different compositions for example inside miscibility gaps or when the phase has order/disorder transitions. In such a case you use a composition set index to separate these. The composition set index is appended to the phase name preceded by a hash “#” character, like liquid#2.



Composition sets can be created manually, see the command **AMEND PHASE** in section subsection5.11.4 or automatically by the grid minimizer or application software.

The phase tuple has been introduced to have a single index for both phases and composition sets in application software. The tuple index thus contain both the phase number and the composition set index. The array of tuple indices is updated internally whenever a new composition set is created or deleted.

## 2.5 The use of wildcards for names

In many cases you can use an asterix “\*” as a name and this normally means “all”. For setting status of phases you can use the special “\*S” for all suspended phase, “\*D” for all dormant phases.

## 2.6 State variables

A state variable in a thermodynamic system has a value which at equilibrium is independent of the way the system has reach its current state. All state variables available in OC are listed in Table table1. They are used to set conditions and to obtain results from an equilibrium calculation. It is possible to use state variables also when close to the equilibrium state for example when simulating a phase transformation.

The value of a state variable depend on the reference states of the elements. The user may define this for each element with a command, see section subsection2.9. The default reference state is the stable state of the elements at 298.15 K and 1 bar, called SER. Whenever necessary this can be indicated by an final suffix “S”, for example ACS(C) indicate the activity of C using the reference state SER whereas AC(C) is always the activity relative the current reference state, either the default or that set by the user.

## 2.7 Thermodynamic databases

The use of thermodynamic software depend on assessed model parameters for phases and elements. With the OC software one can make assessments of such model parameters using experimental and theoretical data, see section subsection2.13.5. However, this user guide does not describe the construction of such databases or how one can obtain them.

## 2.8 Model parameters

All data is organized relative to a phase and the phase is identified by a name. Each phase can have a different model for the composition dependence but the way to enter model parameters is the same for all models. However, the meaning of a model parameter will depend on the model of the phase.

Many types of data can be stored as explained in the section on parameter identifiers. The parameter also has a constituent specification explained in the constituent array section and possibly a degree, the meaning of which is model dependent and a bibliographic reference.

The basic syntax of a parameter is

“identifier” ( “phase name” , “constituent array” ; “degree” ) “expression” “bibl.ref.”

Table 1: A preliminary table with the state variables and their internal representation. Some model parameter properties are also included. The "z" used in some symbols like Sz means the optional normalizing symbol M, W, V or F.

Symbol	Id	Index		Normalizing	Meaning
		1	2	suffix	
Intensive properties					
T	1	-	-	-	Temperature
P	2	-	-	-	Pressure
MU	3	component	-/phase	-	Chemical potential
AC	4	component	-/phase	-	Activity
LNAC	5	component	-/phase	-	LN(activity)
Extensive and normalized properties					
U	10	-/phase#set	-	-	Internal energy for system
UM	11	-/phase#set	-	M	Internal energy per mole
UW	12	-/phase#set	-	W	Internal energy per mass
UV	13	-/phase#set	-	V	Internal energy per m <sup>3</sup>
UF	14	phase#set	-	F	Internal energy per formula unit
Sz	2z	-/phase#set	-	-	entropy
Vz	3z	-/phase#set	-	-	volume
Hz	4z	-/phase#set	-	-	enthalpy
Az	5z	-/phase#set	-	-	Helmholtz energy
Gz	6z	-/phase#set	-	-	Gibbs energy
NPz	7z	phase#set	-	-	Moles of phase
BPz	8z	phase#set	-	-	Mass of phase
Qz	9z	phase#set	-	-	Stability of phase
DGz	10z	phase#set	-	-	Driving force of phase
Nz	11z	-/phase#set/comp	-/comp	-	Moles of component
X	111	phase#set/comp	-/comp	0	Mole fraction
X%	111	phase#set/comp	-/comp	100	Mole per cent
Bz	12z	-/phase#set/comp	-/comp	-	Mass of component
W	122	phase#set/comp	-/comp	0	Mass fraction
W%	122	phase#set/comp	-/comp	100	Mass per cent
Y	130	phase#set	const#subl	-	Constituent fraction
Some model parameter identifiers					
TC	-	phase#set	-	-	Curie temperature
B MAG	-	phase#set	-	-	Aver. Bohr magneton number
MQ&X	-	phase#set	constituent	-	Mobility of X
THET	-	phase#set	-	-	Debye temperature

These parts are explained in more detail below.

### 2.8.1 Model Parameter Identifiers

The OC thermodynamic package can handle any phase property that depend on  $T, P$  and the constitution of the phase using the models implemented. It is easy to extend the number of properties by declaring property identifiers in the source code. If the parameters should have an influence on the Gibbs energy (like the Curie temperature) or a diffusion coefficient (like the mobility) the necessary code to calculate this must be added.

A list of the model parameter identifiers as shown in Table table2 can be obtained by the command

## LIST MODEL-PARAM-ID

Table 2: Current set of model parameter identifiers

Indx	Ident	T	P	Specification	Status	Note
1	G	T	P		0	Energy
2	TC	-	P		2	Combined Curie/Neel T
3	BMAG	-	-		1	Average Bohr magneton numb
4	CTA	-	P		2	Curie temperature
5	NTA	-	P		2	Neel temperature
6	IBM	-	P	&<constituent#sublattice>;	12	Individual Bohr magneton num
7	THET	-	P		2	Debye or Einstein temp
8	VO	-	-		1	Volume at T0, P0
9	VA	T	-		4	Thermal expansion
10	VB	T	P		0	Bulk modulus
11	G2	T	P		0	Liquid two state parameter
12	LAMB	T	P		0	Thermal conductivity
13	MQ	T	P	&<constituent#sublattice>;	10	Mobility activation energy
14	MF	T	P	&<constituent#sublattice>;	10	RT*ln(mobility freq.fact.)
15	MG	T	P	&<constituent#sublattice>;	10	Magnetic mobility factor
16	THT2	-	P		2	Smooth step function T
17	DCP2	-	P		2	Smooth step function value
18	VISC	T	P		0	Viscosity
19	LPX	T	P		0	Lattice param X axis
20	LPY	T	P		0	Lattice param Y axis
21	LPZ	T	P		0	Lattice param Z axis
22	LPTH	T	P		0	Lattice angle TH
23	EC11	T	P		0	Elastic const C11
24	EC12	T	P		0	Elastic const C12
25	EC44	T	P		0	Elastic const C44
26	UQT	T	P	&<constituent#sublattice>;	10	UNIQUAC residual parameter
27	RHO	T	P		0	Electric resistivity
28	HMVA	T	P		0	Enthalpy of vacancy form.
29	TSCH	-	P		2	Schottky anomaly T
30	CSCH	-	P		2	Schottky anomaly Cp/R.

Several of these identifiers have no supporting software implemented, this is an ongoing project. The columns T P indicate if the parameter may depend on  $T$  or  $P$ . Some identifiers require additional specification of the constituent and sublattice, like the mobility of a constituent. Currently it is not yet clear if mobilities should depend on the sublattice or not but the notation allows that.

A slightly more detailed explanation of the identifiers are:

- G, the Gibbs energy parameter for an endmember or an interaction. G(LIQUID,FE;0) is the Gibbs energy for pure liquid Fe. Note that the parameter will be used also below the melting temperature of Fe for a liquid phase containing Fe. G(LIQUID,CR,FE;0) is the regular parameter for Cr and Fe in the liquid.
- TC, a parameter for the critical temperature for ferro or antiferro magnetic ordering using the Inden model.

- BMAG, a parameter for the average Bohr magneton number using the Inden model.
- CTA, a parameter for the Curie temperature for ferromagnetic ordering using a modified Inden model.
- NTA, a parameter for the Neel temperature for antiferromagnetic ordering using a modified Inden model.
- IBM&C, a parameter for the individual Bohr magneton number for constituent C using a modified Inden model. For example IBM&FE(BCC,FE) is the Bohr magneton number for BCC Fe. The identifier IBM&FE(BCC,CR) means the Bohr magneton number of a single Fe atom in BCC Cr. An identifier IBM&FE(BCC,CR,FE) can be used to describe the composition dependence of the Bohr magneton number for Fe in BCC.
- THET, a parameter for the Debye or Einstein temperature.
- V0, a parameter for the volume at 298.15 K and 1 bar.
- VA, a parameter for the integrated thermal expansion.
- VB, a parameter for the Bulk modulus.
- G2, a parameter for the two-state liquid model.
- LAMB, a parameter for the thermal conductivity.
- MQ&C, a parameter for the logarithm of the frequency factor of the mobility of constituent C.
- MF&C, a parameter for the activation energy of the mobility of constituent C.
- MG&C, a parameter for the magnetic factor of the mobility of constituent C.
- THT2, The T for a smooth change of  $C_P$
- DCP2, The value of the smooth change in J/mol
- VISC, a parameter for the viscosity.
- LPX, a parameter the lattice parameter in X direction.
- LPY, a parameter the lattice parameter in Y direction.
- LPZ, a parameter the lattice parameter in Z direction.
- LPTH, a parameter the angle between lattice directions.
- EC11, a parameter for the elastic constant C11.
- EC12, a parameter for the elastic constant C12.
- EC44, a parameter for the elastic constant C44.
- UQT&C, a parameter for the UNIQUAC residual energy for species C
- RHO, a parameter for the electrical resistivity.

- HMVA, a parameter for the enthalpy of vacancy formation.
- TSCH, the T for a Schottky anomaly
- CSCH, the Schottky anomaly  $\Delta C_P$ .

The current value of any of these parameter identifiers can be obtained by the command **LIST STATE\_VARIABLE** using the identifier and appropriate phase and component specifiers, see section subsection16.17.

For details of the meaning of the model identifier refer to the model documentation. As already mentioned many of the identifiers, like the mobility, does not influence the Gibbs energy but as they depend on the  $T$ ,  $P$  and constitution of the phase it is convenient to model them in the same way as the thermodynamic data.

### 2.8.2 Constituent array and degrees

A constituent array specifies one or more constituent in each sublattice. A constituent must be entered as a species with fixed stoichiometry. Between constituents in different sublattices you must give a colon, ":", between interacting constituents in the same sublattice you must give a comma, ",", or a space. A constituent array with exactly one constituent in each sublattice is also called an "endmember" as it give the value for a "compound" with fixed stoichiometry. Constituent arrays with one or more interaction constituents describe the composition dependence of the property. Without such parameters the property will vary linearly between the endmembers.

If there are no sublattices, like in the gas, you just give the phase and the constituent

G(GAS,C1O2)

If no degree is specified it is assumed to be zero. For endmembers the degree must be zero but it may sometimes be useful to specify the zero in order to distinguish the parameter from the expression for the calculated value of the property, like the chemical potential of a component. In the gas phase you normally assumes there are no interactions but it is possible to add such parameters. For an fcc phase with 4 sublattice for ordering and one for interstitials an endmember parameter is

G(FCC,AL:NI:NI:NI:VA;0)

This would be the Gibbs energy of an fcc AL1NI3 ordered compound.

An interaction between vacancies and carbon in the austenite is

G(FCC,FE:C,VA;0)

For an interaction parameter you should always specify a degree but also in this case an omitted degree is interpreted as zero.

### 2.8.3 The TPFUN expression and bibliographic reference

The expression for a parameter can be a single value or a function of  $T$  and  $P$ . It must start with a low temperature limit, usually 298.15 K and must finish with a high temperature limit. These expressions as well as their first and second derivatives will be calculated by the TP-fun package. To simplify that there is a strict syntax for the expression. A term in the expression is

“numeric value” \* “name of TP function” \*T\*\* “power” \*P\*\* “power”

You can construct very complex expression by referring to other functions. If “power” is zero the corresponding \*T\*\* or \*P\*\* can be omitted. If it is negative it must be surrounded by parenthesis like (-1). If it is unity the \*\*1 can be skipped.

Several terms, separated by signs, forms an expression and it must be terminated by a semicolon, “;”. After the semicolon there must be a high temperature limit or a breakpoint in temperature. A breakpoint must be followed by the letter “Y” and then a new expression for temperatures above the breakpoint.

**It is the responsibility of the database manager to ensure the expression is continuous at the breakpoint. If there are jumps in the value at a breakpoint strange things will happen when calculating equilibria.**

After the high temperature limit the letter “N” must be given followed by a bibliographic reference for the parameter. Use the commands AMEND or ENTER BIBLIOGRAPHIC to give the reference.

**The database manager should always add a bibliographic reference even if it is just his or her name and a date. This avoids people to mistake a value inspired by your experience for a carefully validated parameter.**

A term can be used inside a natural logarithm, LN, or exponential, EXP. And the LN or EXP can be multiplied with a term. On the other hand you are not allowed to have any parenthesis, except around powers or arguments to LN and EXP. A valid expression is

```
298.15 -8856.94+157.48*T-26.908*T*LN(T)+.00189435*T**2
-1.47721E-06*T**3+139250*T**(-1); 2180 Y
-34869.344+344.18*T-50*T*LN(T)-2.88526E+32*T**(-9); 6000 N 91Din
```

where 91Din is the bibliographic reference to the SGTE unary database.

## 2.9 The reference state of a component

The values of most thermodynamic data must have a defined reference state. By default the reference state for the components is SER (Stable Element Reference) which is the stable state of the element at 298.15 K and 1 bar. (NOTE: the default reference state is defined by the database but today almost all databases have SER as reference state.)

For each component (also for other components than the elements) you can specify a phase at a given temperature and pressure as reference state, see section subsection26.17. The phase must exist for the component as pure.

A state variable like the chemical potential, MU(O), will refer to the user defined reference state if set. To obtain the value for the SER state you can use a suffix S, i.e. MUS(O) to obtain the chemical potential referred to SER. All state variables are listed in Table table1.

Note that the value of integral properties like Gibbs energy,  $G$ , enthalpy,  $H$ , etc. may have mixed reference states unless all components have the same phase as reference state. In order to have the enthalpy of mixing of a phase all components must have that phase as reference state. For the volume,  $V$ , SER is always used as reference state unless all components have the same reference state.

## 2.10 Equilibrium calculations

The basic application of OC is to calculate the equilibrium of a system as described in section subsection7.2. The user can specifying the external conditions like  $T, P$  and the composition, see section subsection7.2.. The minimizing algorithm [2] use Lagrangian multiplier so many different sets of state variables can be used for specifying the external conditions. Each condition is set separately and it is possible to extract phase amounts and compositions after the calculation. By changing the status of the phases it is possible to calculate metastable state.

In order to do any calculation the user must provide a database with the model parameters for his system or enter these manually.

The conditions can also be set using the command *set\_input\_amount*, see section subsection26.8.

## 2.11 Property diagrams

A property diagram is calculate with the STEP command. First you must set conditions to calculate a single equilibrium and then set set one of the conditions as an axis. After the STEP command, see section section28 you can plot how any state variable varies with the selected axis variable. See the section section21 and the OC macros guide.

## 2.12 Phase diagrams

A phase diagram show the regions of different sets of stable phases in a system. It can have two or more axis variables, in OC the maximum number of axis is two at present. As for property diagrams you must first calculate a single equilibrium and then select two conditions as axis variables. The command MAP, see section section18, will then trace the lines in your systems where the set of stable phases changes. There is no limit on the number of components for a phase diagram calculation.

After calculating a diagram you can plot it with many different types of axis, see section section21 and the OC macros guide.

## 2.13 Assessment of model parameters for databases

One of the important uses of the OC software is to assess model parameters in the phases of a system using experimental and theoretical data. This is done by recalculating the experimental data from the model and by varying the model parameters a least square routine, LMDIF developed at Argonne National Lab in 1981, is used to find the best set.

Assessments are a very difficult procedure as you must also take into account the extrapolations of the model outside the range of experimental data. So called “First Principles Calculations” or the somewhat simpler “Density Functional Theory” (DFT) which are based on the electronic structure of the elements can provide information for metastable as well as for the stable state. But you must be careful that the result from such calculations does not represent a mechanically unstable state with imaginary phonon frequencies.

Experimental data can be direct measurements of thermodynamic data like enthalpies, chemical potentials, heat capacities, activities, etc but very important are also measurements of phase diagrams,

solubilities etc because they are also related to the equilibrium state.

There are several commands related to the assessment procedure in OC but during the assessment you will also use the basic facilities to calculate equilibria for different kinds of conditions as well as many different kinds of diagrams to verify the results.

### 2.13.1 Entering coefficients to be assessed

The command “enter optimizing coefficients”, see section subsection10.11 creates symbols A00 up to A99 that can be used as coefficients in the thermodynamic model parameters. Maximum number of coefficients are 100.

### 2.13.2 Entering phases and model parameters

The elements, species and phases with their appropriate models are entered using the appropriate commands. Normally this is on a macro file in order to have proper documentation. Keep also in mind that an assessment is often revised after a few years when new data become available or you find that the extrapolations of an assessment to a higher order system is not reasonable.

The model parameters are entered using “enter parameter”, see section subsection10.12 or “enter tpfun”, see section subsection10.18 as many parameters may share some properties and a TP-function can be used in several parameters. The optimizing coefficients A00 to A99 with different T and P dependence can be used instead of numerical values as their values should be assessed.

### 2.13.3 Entering experimental data

This is done either by entering single equilibria with conditions and in addition using the command “enter experiment”, see section subsection10.7 where the experimental data is given with an uncertainty. Each equilibrium with an experiment is given a unique name.

Often there are tables with values and instead of entering each of them there is a command “enter many\_equilibria”, see section subsection10.9 with a simplified syntax.

When all equilibria with experiential data has been entered you have to give the command “set range”, see section subsection26.16 to give the first and last equilibrium number that should be used in the assessment. If necessary this range can be extended during the assessment.

All the experimental data should also be entered as a macro file to keep a documentation.

### 2.13.4 Saving the state of the assessment

Any time during an assessment it is possible to save the values of all assessed parameters and the calculated experimental equilibria by the command “save uniform *filename*”, see section subsection24.6. With this command the data inside OC will be written as an unformatted Fortran file and this can be saved and later read back into the OC software by the command “read unfomatted *filename*”, see section subsection23.5. If these commands are inside a macro file prefix the filename with “./” to read and write on the same directory as the macro file.



These unformatted files are very convenient but beware that they may not be portable to other operating systems or even other versions of OC compiled with different Fortran compilers. It may change in future releases of the OC software. Thus keep printouts and macro files also if you later want to make modifications.

### 2.13.5 Performing the assessment

There are many decisions to make during the assessment and a general description how to perform an assessment can be found in the book by Lukas et al [4]. It is never possible to try to assess all parameters using all experiments in a single step. Normally the user selects different sets of experimental data by the “set weight” command, see section subsection26.24 and fits a few model parameters to these using the command “set variable-coeff”, see section subsection26.22. This can typically an enthalpy of mixing or a heat capacity function for a compound.

The command to run the least square fit is “optimize” followed by the maximum number of iterations, see section section20. If zero is given a single loop is made through all equilibria with nonzero weights within the specified range is made. It is also possible to use the command “calculate all”, see section subsection7.1, to calculate all non-zero weight equilibria. With the latter command you can turn on the grid minimizer, in the optimize command the grid minimizer is always turned off.

When the optimize command is given with nonzero maximum there will be output on the screen at regular intervals giving the current values of the optimizing coefficients and the value of the sum of squares. When the oprimization is finished there will also be a listing of the errors for all experiments.

With the command “list opt short”, see section subsubsection16.11.8, the current values of the optimizing coefficients and all equiliria with the experimental data is listed together with the sum of squares. New selection of equilibria or weights can be made and the values obtained for the optimizing coefficients must also be reasonable but to know what is reasonable is not always easy. These steps are repeated until the user is satisfied or exhausted.

Macro files to calculate and plot of the calculated properties overlayed with the experimental data should be preoared and run regularly as just looking at numbers is not sufficient.

At a later stage solubilities and phase diagram data are used but in many cases reasonable guesses of the start values of model parameters must be made to be able to calculate the equilibrium with the experiment. Great care must be taken that the calculated equilibria for the inital model parameters are reasonably close to the experimental. Parts of the experimental phase diagram may have to be assessed separately and the metastable extrapolations of the different phases checked.

Sometimes a phase appears in a region where it should not be stable and additional fictitious experimental data may have to be added to prevent this to happen.

At the end the assessment should be written up and published.

## 2.14 Application software

There is a separate guide for using OpenCalphad Application Interface (OCASI) in application software. For such cases it is convenient to have the source code which can be compiled together with the applications software. A special feature is also the possibility to use OpenMP to calculate in parallel.

### 3 All commands

The commands in alphabetical order as listed with the ?. The commands with an \* has subcommands.

ABOUT	EXIT	MAP	SELECT *
AMEND *	FIN	NEW	SET *
BACK	HELP	OPTIMIZE	SHOW *
CALCULATE *	HPCALC	PLOT *	STEP *
DEBUG *	INFORMATION *	QUIT	
DELETE *	LIST *	READ *	
ENTER *	MACRO	SAVE *	

Many of the commands have “subcommands” and usually there is a default (listed within slashes /default/) which is selected by pressing return. You can type commands and subcommands and other parameters (separated by a space) on the same line if you know the order.

To select a default when typing several commands and answers to questions (command arguments) on the same line, you can use a comma, “,” to select the default answer. For example “l,,,,” will list on the screen with the current list options.

Many commands will ask additional questions, all of them are not included in this guide but those which are will be **shown in bold**. Examples and references to other commands are sometimes in **bold**, sometimes in *italics*.

Whenever the program asks a question you do not understand you can type a question mark, “?”, to obtain help. If the online help system is correctly installed, see section subsection2.1.3, this will open a browser window with this manual and hopefully position the manual at the relevant part. You can browse the whole manual in this window if you need additional help.

#### 3.1 Options

There are some options that can be set for the whole session or for just a single command. The options are identified by a / in front like /output=myfile.dat.

An option must be specified directly after a command for example:

**list /out=equil5 result 2**

Only a few options are implemented.

- /OUTPUT=*file name* open a file and write on it. Note that if you have popup windows enabled this will open unless you type the file name (with path) on the same line as the command. In a macro file must prefix the file name with “./” to have the output (or append) on the same directory as the macro file. See also section subsection2.1.2 and subsection2.1.5.
- /APPEND=*file name* append output to a file, any previous content is kept.
- /ALL apply for all.
- /FORCE override normal restrictions.
- /VERBOSE write information while executing.

- /SILENT do not write anything except fatal error messages.

## 4 About

This is OpenCalphad (OC), a free software for thermodynamic calculations as described in B Sundman, U R Kattner, M Palumbo and S G Fries, Integrating Materials and Manuf. Innov. (2015) 4:1; B Sundman, X-G Lu and H Ohtani, Comp Mat Sci, Vol 101 (2015) 127-137 and B Sundman et al., Comp Mat Sci, Vol 125 (2016) 188-196

It is available for download at <http://www.opencalphad.org> or the sundmanbo/opencalphad repository at <http://www.github.com>

This software is protected by the GNU General Public License You may freely distribute copies as long as you also provide the source code and use the GNU GPL license also for your own additions and modifications.

The software is provided "as is" without any warranty of any kind, either expressed or implied. The full license text is provided with the software or can be obtained from the Free Software Foundation <http://www.fsf.org>

Copyright 2011-2019, Bo Sundman, Gif sur Yvette, France. Contact person Bo Sundman, [bo.sundman@gmail.com](mailto:bo.sundman@gmail.com)

## 5 Amend

Intended to allow changes of already entered data. Only some of the subcommands are implemented.

ASSESSMENT_RESULT	ELEMENT	OPTIMIZING-COEFS	SPECIES
BIBLIOGRAPHY	EQUILBRIUM	PARAMETER	SYMBOL
COMPONENTS	GENERAL	PHASE *	TPFUN-SYMBOL
CONSTITUTION	LINE	QUIT	

The default selection is PHASE.

### 5.1 Amend assessment result

After assessing a set of parameters for a system each of these has a Relative Standard Deviation (RSD) listed in the result. Using this RSD it is possible to modify one parameter and recalculate how much all the other parameters should change due to this modification without rerunning the actual assessment.

This command allows to calculate such a change and it can be tested by reassessing the parameters using the experiments.

### 5.2 *amend* Bibliography

**Reference identifier:**

The text for bibliographic reference identifier can be amended. The reference identifier is CASE INsensitive.

**Reference text, end with “;”:**

The text for this reference will be set to the text supplied. It can be several lines terminated with a “,”  
;

### 5.3 *amend* Components

**Give all new components:**

By default the elements are the components. This command can set any orthogonal set of species as components. The number of components cannot be changed by this command. The new components must exist as species and be orthogonal. For example in the system Ca-O-Si one can define CaO SiO<sub>2</sub> and O as components.

The components are important as you can only use components to specify compositions, such as  $x(\text{cao})=.3$  is possibly only if CaO is a component. See also **set input-amount** subsection 26.8.

Note that when you have other components than the elements you may have negative mole fractions and phase amounts (but never negative mass).

### 5.4 *amend* Constitution

**Phase name:**

The program will ask for a phase name and you can set the amount and constitution of the phase. This will be used as initial constitution for a calculation unless the grid minimizer is used.

**Amount of phase:**

**Current (Y), default (D) or new (N) constitution:**

Answer Y to keep current constitution, D to set a default constitution (if you have set such a constitution) or N to provide a new constitution.

**Fraction of component:**

You can specify a value between 0.0 and 1.0. The sum of all constituents must be unity, values below 0.0 or 1.0 are not allowed. If you want the fraction of a constituent to be 1.0-(all the other fractions) you can set its value to REST. Otherwise the last constituent is set to the “rest”.

### 5.5 *amend* Element

The data for the element can be amended, not implemented yet.

### 5.6 *amend* Equilibrium

Not sure what could be amended and anyway not implemented.

## 5.7 *amend* General

A number of general settings can be amended by the user:

- The name of the system.
- The level of the user (beginner, frequent user, expert). This may affect the behavior of the program (not implemented yet).
- If global minimization is allowed or not.
- If the grid minimizer is allowed to merge gridpoints in the same phase after global minimization.
- If the grid minimizer can automatic create composition sets is allowed or not.
- If redundant composition sets can be deleted automatically after an equilibrium calculaion.

Note that these and some other general feautres can also be changed by the command **SET BIT GLOBAL**

## 5.8 *amend* Line

After a STEP or MAP command it is possible to give the command LIST LINE to list all calculated equilibria or AMEND LINE which allows you to EXCLUDE lines or INCLUDE lines from the plotting.

## 5.9 *amend* All optimizing coefficients

The values of each optimizing coefficients, see section subsection26.16 can be rescaled (start values set to current values) or recovered (current values set to previous start values).

## 5.10 *amend* Parameter

The possible parameters that can be amended depend on the model of the phase. By specifying a parameter you can change its expression. This is not yet implemented you must use the command **ENTER PARAMETER** to change the parameter expression.

## 5.11 *amend* for Phase <phase name>

You must first specify the phase name and then you can amend some of the properties of the phase:

If you want to amend something for a composition set you must specify the composition set number together with the phase name after a hash character (#) (like liquid#2).

### Phase name:

You must specify the name of the phase you want to amend.

ADDITION *	DEFAULT-CONSTIT	FCC-PERMUTATIONS	QUIT
AQUEUS-MODEL	DIFFUSION	FLORY-HUGG-MODEL	UNIQUAC-MODEL
BCC-PERMUTATIONS	DISORDERED-FRACS	GADDITION	
COMPOSITION-SET	FCC-CVM-TETRAHDR	QUASICHEM-MODEL	

### 5.11.1 *amend phase < ...> Addition*

Additions are used to give a contribution to the Gibbs energy of a phase using more or less physically based model. Usually they require additional model parameters, see section `refsc:paramid`. The difference between addition and other things that can be amended may not always be very clear. The possible additions are

ELASTIC-MODEL-1	MAGNETIC-CONTRIB	SCHOTTKY-ANOMATY	TWOSTATE-LIQUID
LOW-CP-MODEL	QUIT	SMOOTH-CP-STEP	

BEWHERE! The OC software allows you to mix many types of additions for a phase but it is up to you as user to defend the physical reasons for this!

#### **Per formula unit?**

The theoretical equation for most additions usually gives the value per mole of atoms. As the Gibbs energy is calculated per mole formula unit of the phase in OC (as well as most thermodynamic software) the addition must be multiplied with the number of atoms per formula unit of the phase.

Some of the additions, for example mobilities, are for properties that does not contribute to the thermodynamics but which depend on the phase,  $T$ ,  $P$  and phase constitution in the same way as the Gibbs energy and it is thus convenient to model and store the data together with the thermodynamic data.

#### 5.11.1.1 *amend phase ... addition Elastic\_model\_1*

A contribution to the Gibbs energy due to elastic strain can be added. This also requires values of the elastic constants and lattice parameters, see section `subsubsection2.8.1`.

There is no code to calculate the elastic energy implemented yet.

#### 5.11.1.2 *amend phase ... addition LowT\_Cp\_model*

The Einstein model for heat capacities from 0 K has been implemented. It requires a value of the property Einstein T as listed in section `subsubsection2.8.1`.

#### 5.11.1.3 *amend phase ... addition Magnetic\_contrib*

The Inden-Hillert and the modified Inden-Qing-Xiong model for the magnetic contribution to the Gibbs energy can be set by this command This depends on model parameters describing the Curie and Neel temperatures and the Bohr magneton number, as listed in model parameters identifiers `subsubsection2.8.1`, for the phase.

You also must also enter model parameters for the constituents of the phase, see the documentation of the model or Lukas [4].

#### **Antiferromagnetic factor:**

The Qing-Xiong model is selected by giving zero (0) for the question about the anti-ferromagnetic factor. For the original Inden-Hillert model -3 is used for FCC and HCP whereas -1 is used for BCC.

The Inden-Hillert model is described in Lukas et al [4]. The Inden-Qing-Xiong modified model requires separate values of the Curie and Neel Temperatures and either an “effective” Bohr magneton number or individual Bohr magneton numbers for the constituents of the phase.

#### **5.11.1.4 *amend phase ... addition* Quit**

You did not really wanted to add any addition.

#### **5.11.1.5 *amend phase ... addition* Schottky\_anomaly**

Some physical phenomena can create a “bump” in the heat capacity for a phase at a certain  $T$  and this addition can describe this. It uses two model parameter identifiers, TSCH and CSCH that may depend on the composition. TSCH specify the  $T$  for the anomaly and CSCH the maximum contribution to the heat capacity (J/mol/formula unit) divided by  $R$ , i.e. as a factor of the gas constant,  $R$ .

#### **5.11.1.6 *amend phase ... addition* Smooth-Cp-step**

The 3rd generation thermodynamic databases extrapolate to 0 K and require that the heat capacity is zero at 0 K. This means it is impossible to use  $T \cdot \ln(T)$  terms (and also negative powers of  $T^{-n}$ ) but there may be some physical phenomena that causes an incremental increase of the heat capacity at some temperature. Ignoring the physical reason for such an increase this “smooth\_ $C_P$ \_step” addition will provide such this using two parameters, THT2 to specify  $T$  and DCP2 to specify the increment in heat capacity. DCP2 is a factor of  $R$ . It uses the same mathematical expression as the Einstein heat capacity function but has no enthalpy contribution.

#### **5.11.1.7 *amend phase ... addition* Twostate-liquid**

The two-state model for the hear capacity for the undercooled liquids can be added. It assumes a low  $T$  amorphous state modeled as an Einstein solid and requires an Einstein  $T$ . For the liquid transition it uses the model\_parameter\_ident bf G2, both of which are listed in section subsection2.8.1.

You must specify parameters for THET and G2 for all constituents of the phase and possibly also interaction parameters to specify the composition dependence.

The implementation of this addition is not finished.

#### **5.11.2 *amend phase ...* Aqueous-model**

A model with dilute configurational entropy. Not implemented yet.

### 5.11.3 *amend phase ... BCC-permutations*

This is intended for the 4 sublattice CEF model for BCC ordering. Due to crystallographic symmetry several model parameters must be identical such as

$$G(\text{BCC}, \text{AL:FE:FE:FE}) = G(\text{BCC}, \text{FE:AL:FE:FE}) = G(\text{BCC}, \text{FE:FE:AL:FE}) = G(\text{BCC}, \text{FE:FE:FE:AL})$$

and this command means these parameters need to be entered only once. This affects the data storage and the calculation of the Gibbs energy is slightly more efficient. The same applies for the FCC-permutations but the BCC tetrahedron is slightly asymmetric which makes it a bit more complicated than the FCC. There can be a 5th sublattice with interstitials.

### 5.11.4 *amend phase ... Composition set*

Each phase has by default a single composition set. If the same phase can exist as stable (or metastable) with two or more compositions (miscibility gaps or order/disorder transformations) you may have to amend the phase by creating additional composition sets.

Composition sets can also be created automatically by the grid minimizer during an equilibrium calculation. In such a case the composition set will have the suffix `_AUTO`,

Composition sets of a phase can be created and deleted. Phases with miscibility gaps or which can exist with different chemical ordering like A2 and B2 must be treated as different composition sets. You can specify a prefix and suffix for the composition set. Extra composition sets will always have a suffix `#digit` where digit is a number between 2 and 9. You cannot have more than 9 composition sets.

The composition set number is given after the phase name and preceded by a hash character `#`. In the OCASI interface and some more cases phase tuples are used to identify a phase and a composition set by a single number. As composition sets can be created and deleted a phase tuple index for the 2nd or higher composition set may change between calculations.

In some cases it may be interesting to calculate metastable states inside miscibility gaps and you can prevent the automatic creation of composition sets by turning off the global minimization using **AMEND GENERAL** or for an individual phase by **SET PHASE ... BIT NO\_AUTO\_COMP\_SET**

### 5.11.5 *amend phase ... Default Constitution*

The default constitution of a phase can be set. Unless the grid minimizer is used this will be used for the first calculation with the phase and sometimes if there are convergence problems. NOTE that if you want to specify a default constitution for the second or higher composition set of a phase you must specify the composition set with the phase name!

Depending on the minimizing software used the initial constitution can be important to find the correct equilibrium if the phase has ordering or a miscibility gap.

For each constituent you can specify a minimum `>` or maximum `<` fraction or give `NONE` if there are no default.

If a phase has miscibility gaps and you have created composition sets with default constitutions the grid minimizer will try to select the composition set with a composition closest to the default for a



stable phase.

To temporarily set a new constitution of a phase use the command **AMEND CONSTITUTION** <phase> or **CALCULATE PHASE ...** .

#### 5.11.6 *amend phase ... Diffusion*

This is to specify how the diffusion coefficient matrix should be calculated when simulating a phase transformation. Normally the mobilities for the constituents of the phase are read from the database but you may use different “depended” and “independent” constituents in the diffusion model and also some other factors. This command is intended for such use. It is not implemented yet.

There is no intention that OC itself should simulate diffusion but as the diffusion coefficients are strongly dependent on the thermodynamic factor (the Darken stability matrix) which represent the second derivatives of the Gibbs energy it is convenient to include some properties used in a simulation in the thermodynamic software.

#### 5.11.7 *amend phase ... Disordered fraction sets*

For phases with several sublattices the Gibbs energy of the phase can be divided into two sets of fractions where the second or “disordered” set have only one or two sublattices and the fractions on these represent the sum of fraction on some or all of the first or “ordered” set of sublattices.

There are two different ways to handle the disordered fraction set depending on the fact if the phase can be totally disordered. The latter is the case for phases like B2, L1<sub>2</sub> etc which can be totally disordered as BCC/A2 or FCC/A1. The calculation of the Gibbs energy in the latter case will subtract the contribution from the ordered part when the phase is disordered, see for example Lukas et al [4].

This is particularly important to model the Gibbs energy for phases with ordering like FCC, BCC and HCP and for intermediate phases like SIGMA, MU etc.

#### 5.11.8 *amend phase ... FCC\_CVM\_tetradrn*

This model is intended for the CVM tetrahedron model for FCC and HCP. Not implemented yet.

#### 5.11.9 *amend phase ... FCC\_permutations*

This is intended for the 4 sublattice CEF model for FCC ordering. Due to crystallographic symmetry several model parameters must be identical such as

$$G(\text{FCC}, \text{AL:FE:FE:FE}) = G(\text{FCC}, \text{FE:AL:FE:FE}) = G(\text{FCC}, \text{FE:FE:AL:FE}) = G(\text{FCC}, \text{FE:FE:FE:AL})$$

Setting this means that unique model parameters need to be entered only once, the software will take care of all permutations. HCP permutations are also handled with this command as the HCP tetrahedron model is identical to the FCC. There can be a 5th interstitial sublattice.

#### **5.11.10 *amend phase ... Flory\_Huggins model***

A model when the configurational entropy takes into account that the constituents have very different size. Not implemented yet.

#### **5.11.11 *amend phase ... Gaddition***

You can add a constant value of the Gibbs energy to a phase in Joule per formula unit. This is a simple way to implement a for example a nucleation barrier.

#### **5.11.12 *amend phase ... Quasichemical***

There are several quasichemical models for the liquid that only describes the short range ordering (SRO). None of them are yet implemented.

#### **5.11.13 *amend phase ... Quit***

Do not amend anything for the phase.

#### **5.11.14 *amend phase ... UNIQUAC***

The UNIQUAC model for polymers has been implemented and the documentation is on its way.

### **5.12 *amend Quit***

Do not amend anything (more).

### **5.13 *amend for Species***

This is implemented for UNIQUAC species which has a specific volume and area used in the configurational entropy.

The user is expected to enter the surface and volume of the species.

### **5.14 *amend Symbol***

For a symbol that is a constant this command means changing the value of symbol.

For other symbols it is very special. It is intended for use in assessments to specify that a particular symbol must not be evaluated except when specified explicitly, or when calculating a specific equilibrium.

The main problem is that a symbol can have an expression using another symbols and thus all symbols are normally evaluated whenever the value of a specific symbol is requested. This is to ensure that all symbol values are consistent and refer to the same calculated equilibrium. But in certain

cases you may want to enter a symbol that is only evaluated when referenced explicitly or at a specific equilibrium and this can be set with this command.

When you want to compare the value of a thermodynamic property, like the enthalpy, in two equilibria you must be able to store the calculated enthalpy from one equilibrium in a symbol. For example if you have experimental data on the heat difference for a compound at various  $T$ . In such a case the enthalpy at the reference  $T$  can be stored in a symbol, which has been amended with this command to specify at which equilibrium it should be evaluated. In all other equilibria the value of this symbol will have the value at the specified equilibrium. See also the documentation on the assessment procedure, section subsection2.13.5.

### Should the symbol be evaluated explicitly only?

You will be asked if the symbol should be evaluated only when explicitly referenced. As already stated all symbols are normally evaluated whenever the value of any symbol is requested because a symbol may depend on other symbols and they must all be evaluated at the same time.

The exception is symbols representing “dot derivatives” which automatically are set to be evaluated only when referenced explicitly.

### Should the symbol be evaluated at a specific equilibrium?

You can select if the symbol should be evaluated only at a specific equilibrium. This is useful for symbols used as reference values in assessments when a property in other equilibria is a difference with a value, for example an enthalpy, calculated at a specific  $T$  in a specific equilibrium.

## 5.15 *amend* Tpfuction

You can replace a TP function with a new expression. If it is a constant you can give a new value.

## 6 Back

Return back from the command monitor to the application program. In the OC software itself it means terminate the program.

## 7 Calculate

Many different things can be calculated. The normal thing to calculate is **equilibrium**, the other things are special.

ALL-EQUILIBRIA	NO-GLOBAL	SYMBOL	TZERO-POINT
EQUILIBRIUM	PHASE *	TPFUN-SYMBOLS	WITH-CHECK-AFTER
GLOBAL-GRIDMIN	QUIT	TRANSITION	

### 7.1 *calculate* All equilibria

Intended for the assessment procedure. Calculates all equilibria with non-zero weight as set by the command **SET RANGE**. It can also be used for other purposes, for example testing the paralleliza-

tion. The equilibria can be entered by the command **ENTER MANY EQUILIB**.

This command can be looped to measure calculation times.

## 7.2 *calculate* Equilibrium

The normal command to calculate the equilibrium of a system for the current set of conditions and phase status. You can calculate a metastable equilibrium if some phases that should be stable have been set dormant or suspended or if automatic creation of composition sets is not allowed. If the conditions allow, the grid minimizer will be used to find start values unless the grid minimizer is explicitly turned off.

Before this command you must have entered thermodynamic data from a database or interactively and used the command **set condition**, section subsection26.5, to set as many conditions as you have components plus two. The commands **set status phase**, section subsection26.19.3, and **set input-amount**, section subsection26.8 can also be used to set conditions.

For the first equilibrium calculation it is recommended to set conditions on  $T, P$  and the overall composition. Those conditions allow the grid minimizer to be used to find the best set of stable phases and their constitutions that should give the global minimum. However, the density of the grid may in some cases have to be increased to ensure that.

For later equilibria you can use a very flexible set of conditions, see section subsection26.5 and the gridminimizer may not be able to use the grid minimizer. In such a case OC will use the current set of stable phases and their constitution as start values. If you want to check that such a calculation is the global you can use the command *calculate with* which will call the grid minimizer called AFTER the equilibrium calculation (if it has converged) to check that it is indeed a global equilibrium.

## 7.3 *calculate* Global-Gridmin

Calculate with the global grid minimizer without using this result as a start point for the general minimizer. Used to debug the grid minimizer.

## 7.4 *calculate* No-Global

Calculate the equilibrium without using a global grid minimizer to generate start constitutions. The current equilibrium is used as start point. Can be quicker when only small changes of conditions made since previous calculation and this is how equilibria is calculated during STEP and MAP. It means no check of new miscibility gaps.

## 7.5 *calculate* Phase <phase name>

This is to calculate properties for a single phase independent of the current conditions except the values of  $T$  and  $P$ .

**Phase name:**

**Amount of phase:**

**Current (Y), default (D) or new (N) constitution?**

You must provide a phase name, the amount of the phase and if you should use the current constitution or enter a new.

The Gibbs energy of a phase and possible derivatives and some other things can be calculated. Mainly for debugging the implementation of models and testing the software.

ALL-DERIVATIVES	DIFFUSION-COEFF	ONLY-G
CONSTITUTION-ADJ	G-AND-DGDY	

### 7.5.1 *calculate phase ... All-Derivatives*

The Gibbs energy, all  $T$  and  $P$  derivatives and all first and second derivatives with respect to constituents for the specified phase for current  $T, P$  are calculated and listed.

It is possible to loop this calculation to measure calculation times.

### 7.5.2 *calculate phase ... Constitution\_Adjust*

You will be asked to enter a new composition of the phase (the current constitution but the current is the default) and this command will then calculate the Gibbs energy and all chemical potentials for the given composition.

For a phase with sublattices the constitution of the phase will be adjusted to have the minimum Gibbs energy for the given composition.

It is useful when one or more components are parts of several constituents, for example in a gas and for phases with order/disorder transitions, in particular when the corresponding subroutine is used in simulations.

### 7.5.3 *calculate phase ... Diffusion\_Coefficients*

You will be asked to enter a new composition (default is current) of the phase and this command will then calculate the Darken stability matrix

$$\frac{\partial^2 G}{\partial N_A \partial N_B}$$

for all components (see the documentation of the minimiser) and also all mobility values (if there are any).

#### 7.5.4 *calculate phase ... G\_and\_dGdy*

The Gibbs energy, all  $T$  and  $P$  derivatives and all first derivatives with respect to constituents for the specified phase for current  $T, P$  are calculated and listed.

IMPORTANT NOTE: The value of  $\frac{\partial G_m}{\partial y_i}$  is NOT the chemical potential,  $\mu_i$  of component  $i$ . The understanding of thermodynamics is often poor and the user is reminded that the chemical potential of a component  $i$  is defined as:

$$\mu_i = \left( \frac{\partial G}{\partial N_i} \right)_{T, P, N_{j \neq i}}$$

where  $G$  is the integral Gibbs energy and all  $N_i$  are independent variables. When we model the molar Gibbs energy,  $G_m$  as a function of the constituent fractions,  $y_i$ , these fractions are not independent and for a substitutional model, where  $y_i = x_i$  i.e. the mole fractions, the chemical potential is calculated from  $G_m$  using:

$$\mu_i = G_m + \left( \frac{\partial G_m}{\partial x_i} \right)_{T, P, x_{j \neq i}} - \sum_j x_j \left( \frac{\partial G_m}{\partial x_j} \right)_{T, P, N_{k \neq j}}$$

because the mole fractions,  $x_i$  are not independent.

#### 7.5.5 *calculate phase ... Only-G*

The Gibbs energy and all  $T$  and  $P$  derivatives calculated and listed for the specified phase for the current values of  $T, P$ .

If the phase has additions the Gibbs energy and its first derivatives and its second derivative of  $T$  of each addition are also listed

#### 7.5.6 *calculate phase ... Quit*

Do not calculate anything for the phase.

#### 7.6 *calculate Quit*

Do not calculate anything at all.

#### 7.7 *calculate Symbol*

A state variable symbol or function is calculated using the results from the last equilibrium or grid minimizer calculation. It is used in particular for calculation of “dot derivatives” like  $H.T$  for the heat capacity.

If a wildcard, “\*”, is given as name all symbols, except dot derivatives and symbols that must be specified explicitly and those that should be calculated for another specified equilibria. See section sub-section5.14.

## 7.8 *calculate* Tpfun-Symbols

All or a specific TPFUN symbol are calculated for current values of  $T$  and  $P$ .

## 7.9 *calculate* Transition

After calculating an equilibrium you can calculate directly when a phase will appear or disappear by releasing one of the conditions you have specified. Typically this is used to calculate the melting temperature of an alloy or a solubility limit.

You specify the phase name and the condition to be released. The program will set this phase as FIXED with zero amount and remove the condition you specified and calculate the equilibrium. The calculation may fail if the phase cannot be set stable with zero amount. If successful the removed condition will be set to the value calculated and the phase set stable with zero amount.

## 7.10 *calculate* Tzero point

The T0 (or T zero) point is where two phases have the same Gibbs energy. It is a limit of diffusionless transformation between these phases. This can be calculated by varying T (or a composition) calculating the Gibbs energy for the two phases separately using the same overall composition. NOTE in many cases there are no such point!

It is particularly interesting in steels to predict the martensite transformation which is normally some 100 K below the T0 point.

## 7.11 *calculate* with check after

When the conditions does not allow for the gridminimizer to be used to find an initial set of phases this command can be used to call the gridminimizer after the iterative calculation. If the gridminimizer finds a phase that should be stable the equilibrium will be automatically recalculated.

This type of calculations is regularly done during STEP and MAP commands as such calculations normally have a phase as FIX which prevents use of the gridminimizer.

# 8 Debug

Several possibilities to trace calculations will be implemented in order to find errors but very little is working yet.

BROWSER	FREE LISTS	TEST1	TRACE
ELASTICITY	STOP-ON-ERROR	TPFUN	

## 8.1 *debug* Elasticity

Intended to test the model for strain and stress. Not implemented.

## 8.2 *debug* Free lists

Only for experts.

## 8.3 *debug* Stop\_on\_Error

The program will stop at the command level after printing the error message if an error has occurred when using macro file. This should make it easier to find errors occurring when running macro files.

However, it is not implemented.

# 9 Delete

It is quite difficult to delete anything when the data structure is so involved. In many cases it may be better to enter the data again without the data that should be deleted. But there are a few things that must occasionally be deleted.

COMPOSITION_SET	EQUILIBRIUM	QUIT	STEP_MAP_RESULTS
ELEMENTS	PHASE	SPECIES	

## 9.1 *delete* Composition set

The first composition set of a phase cannot be deleted. Otherwise there is usually no problem unless several equilibria are entered because the composition set must be deleted in all equilibria. Composition sets are created and deleted during normal equilibrium calculations to detect miscibility gaps.

## 9.2 *delete* Element

Dangerous and will probably never be implemented.

## 9.3 *delete* Equilibrium

Dangerous but sometimes necessary. Done automatically at a second STEP or MAP command if you specifies to delete previous results.

## 9.4 *delete* Phase

Dangerous and will probably never be implemented.

## 9.5 *delete* Quit

Do not delete anything.



## 9.6 *delete* Species

Not implemented yet and will probably never be.

## 9.7 *delete* Step\_Map\_Results

This removes all equilibria and saved equilibria associated with STEP and MAP commands. It also deletes the axis.

# 10 Enter

In most cases data will be read from a database file. But it is possible to enter all thermodynamic data interactively. This should normally start by entering all elements, then all species (the elements will automatically also be species) and then the phases.

A species have a fixed stoichiometry and possibly a charge. The species are the constituents of the phases.

A phase can have sublattices and constituents and also various additions like magnetic, low T heat capacity etc. which are specified by the **AMEND** command after entering the phase (but normally before any model parameters for the phase are entered).

TPFUN symbols can be used to describe common parts of model parameters. See section subsection2.8.3 for an explanation.

Each model parameter of a phase is entered separately. You may use TPFUN symbols which are already entered.

At present the multicomponent CEF model and the ionic 2-sublattice liquid model are the only basic models implemented. The CEF model includes as special cases the gas phase, regular solutions with Redlich-Kister Muggianu model and phases with up to 9 sublattices and ionic constituents. These models describe the basic configurational entropy contribution to the phase, models such as the magnetic contribution and low T heat capacity can be added to a phase with the **AMEND** command.

The enter command is also used to enter bibliographic data, equilibria for assessments and many other things.

The subcommands are:

BIBLIOGRAPHY	EQUILIBRIUM	OPTIMIZE-COEFF	SPECIES
COMMENT	EXPERIMENT	PARAMETER	SYMBOL
CONSTITUTION	GNUPLOT-TERMINAL	PHASE	TPFUN-SYMBOL
COPY-OF-EQUILIB	MANY-EQUILIBRIA	PLOT-DATA	
ELEMENT	MATERIAL	QUIT	

## 10.1 *enter* Bibliography

Each model parameter must have a bibliographic reference to ensure everyone can find the origin of its value. When entering a parameter a bibliographic reference symbol must be given and with this command you can give a full reference text for that, for example a published paper, a report or simply

a reason for the value together with the date and your name so the origin of the parameter can be traced.

#### **Reference identifier:**

The text for bibliographic reference identifier can be amended. The reference identifier is case insensitive.

#### **Reference text, end with “;”:**

The text for this reference will be set to the text supplied. It can be several lines terminated with a “;”

### **10.2 *enter* Comment**

A line of comment text can be added to an equilibrium. It is particularly important when entering experimental data to give the reference to the data.

### **10.3 *enter* Constitution**

The constitution (fraction of all constituents) of a phase can be entered. This is a way to provide start values for an equilibrium calculation (when not using grid minimizer). To calculate the Gibbs energy for a specific phase at a specific constitution use the command **CALCULATE PHASE**.

### **10.4 *enter* Copy of equilibrium**

This command creates a copy of the current equilibrium with the same set of conditions and related data.

### **10.5 *enter* Element**

The data for an element is entered. It consists of its symbol, name, reference phase, mass, H298-H0 and S298.

The element symbol must be one or two letters, they will be converted to UPPER case automatically. The element name and reference phase is never used anywhere but included for completeness. The reference phase SER means the Stable Element Reference phase, the phase stable at 298.15 K and 1 bar. The mass is needed for input of amount (using state variable B), mass fractions or mass percent of the element.

The values of H298-H0 and S298 are never used for any calculation but included for completeness.

### **10.6 *enter* Equilibrium**

You can have several equilibria each with a unique set of conditions including phase status (dormant, suspended, fix or entered) but all with the same components and thermodynamic data. This is useful for compare different states, to simulate transformations and to assess model parameters as each experimental or theoretical information represented as an equilibrium.

All equilibria use the same thermodynamic data but they have an independent set of conditions and result data structure, also for TP functions and symbols, and they can be calculated in parallel.

After entering the equilibrium you can select if your following commands, such as *enter condition* etc. will apply to the new equilibrium.

## 10.7 *enter* Experiment

This is used for assessments, experimental data can be specified for an equilibrium. The experiment is a state variable or symbol which can be set equal to the experimental value followed by a colon, “:” and its uncertainty.

In some cases an experimental value can be an upper or lower limit. In such cases the “>” or “<” can be used. The value of the uncertainty will then be interpreted as a penalty factor if the calculated value is outside the specified limit.

## 10.8 *enter* GNUPLOT Terminal

For plotting OC generates a command file for the GNUPLOT [6] software. GNUPLOT can be downloaded free for most OS but depending on your screen and other hardware you may prefer to specify your preferred set of terminals. On Windows the defaults are:

Name	=	GNUPLOT definition
1 SCREEN		set terminal wxt size 940,700 font "arial,16"
2 PS		set terminal postscript color solid fontsize 1.2
3 PDF		set terminal pdf color solid size 6,5 enhanced font "arial,16"
4 GIF		set terminal gif enhanced fontsize 0.7
5 PNG		set terminal png enhanced fontsize 0.7

The text after the > is written on the GNU command file. You can change these or add additional terminals. You can also change these in the source code (userif/pmon6.F90 file) or use a macro file OCHOME/start.OCM file to set them.

## 10.9 *enter* Many Equilibria

This command is intended for adding tables of experimental data of the same type. It can also be used for calculation of many equilibria using the **calculate all** command. The user first enters a TABLE HEAD giving the necessary phase status, conditions, experiments etc. In this “head” some values of text can be referred to columns in the following table using the “@” character followed by a digit 1 to 9, where the digit is the column number.

The prompt for input to the table head is “table head::”

In the examples below, taken from the parallel2.OCM macro file, user input is **in bold** and explanations *in italics*.

- By default all phases are suspended so the user must first specify the phases with dormant, entered or fixed status (including amount) like  
Table head: **entered 0** \* *all phases should be entered*

Table head: **fix 0 liquid** *liquid should be fix with 0 moles*

Table head: **fix 1 @2** *the phase in column 2 should be fix with 1 moles*

- The conditions can be given using the @ character to indicate vaules that are given in the specified column in table to follow.

Table head: **condition t=@1 p=1e5 n=1 w(cr)=@3 w(mo)=@4**

- Optional calculations of entered symbols

Table head: **calculate cp**

- Optional listing of state variables

Table head: **list HM tc(bcc)**

- Optional experimental data

Table head: **experiment x(liquid,cr)=@5:.01, x(bcc,cr)=@6:.02**

- Optional reference state

The reference state for a component can be set.

Table head: **reference O gas \* 1e5**

The reference state for the component O will be gas at the current  $T$  and 1 bar.

- Optional plot\_data specifying a dataset number and coordinates to be plotted and a symbol. The coordinates can be table columns. Use the dataset numbers to have data of the same type together like enthalpies, phase diagram data etc.

Table head: **plot 1 @1 @2 5**

- Optional comment

Table head: **comment experimental data from Kubaschewski 1955**

- The table head is finished by an empty line or “table\_start”

For the rows in the table the user must first provide a unique name for each equilibrium (that is counted as column 0 (zero)) and values for all columns referenced in the table head like:

Table row: **EQ1 1573 BCC 0.3 0.05 0.12 0.28**

Table row: **EQ2 1623 BCC 0.3 0.10 0.18 0.24**

The table is finished by an empty line or

Table row: **table\_end**

## 10.10 *enter* Material

The user will be asked for a name of the material and possibly a database. Then he can give elements and their amount in mass percent or mole fraction. Finish with an empty line.

Finally he can specify the temperature and the program will automatically make a calculation at 1 bar with the given composition. For example:

OC4:enter mat

Database:steel7

```

Elements: C , MO, V , CR, FE, SI,
Major element or material:fe
Input in mass percent? /Y/:
Input expected in mass percent

First alloying element:c
Mass percent: /1/:
Second alloying element:cr
Mass percent: /1/: 5
Third alloying element:mo
Mass percent: /1/: 8
Next alloying element:v
Mass percent: /1/:
Next alloying element:
  3E reading a TDB file
  3D em:  W%(C)=1  W%(CR)=5  W%(MO)=8  W%(V)=1  N=1
Temperature /1000/:
  3Y Constitution of metastable phases set
  3Y Composition set(s) created:          1
Gridmin: 18846 points  6.25E-02 s and      78 clockcycles, T= 1000.00
Phase change: its/add/remove:      5      0      21
Equilibrium calculation 19 its,  6.2500E-02 s and      94 clockcycles

```

The user can use the same command to specify another composition of the alloy or use other commands such as **SET CONDITION** and **CALCULATE** or calculate diagrams using **SET AXIS** and then **STEP** or **MAP**.

### 10.11 *enter* Optimizing coefficient

The number of TP symbols for the coefficients to be optimized are entered. They have the names A00 to A99. They are used in model parameters and can be varied by the optimization procedure to minimize the difference between the experimental data and the same property calculated from the models of the phases.

You can also specify the size of the workspace needed for the optimization. The default value, 2500, is usually sufficient.

### 10.12 *enter* Parameter

A model parameter is defined by its identifier, the phase and constituent array and the degree. A parameter can be a constant or depend on T and P. The parameter will be multiplied with the fractions of the constituents given by its constituent array. See the documentation of the GTP model package or the book by Lukas et al[4] for more information about thermodynamic models.

For example G(LIQUID,CR) is the Gibbs energy of liquid Cr relative to its reference state, normally the stable state of Cr at 298.15 K and 1 bar, and called an endmember.

For a gas molecule the parameter  $G(\text{GAS}, \text{C1O2})$  is also an endmember and represent the Gibbs energy of the C1O2 molecule relative to the reference states of C (carbon) and O (oxygen).

For interaction parameters the components are separated by a comma “,” as in  $G(\text{LIQUID}, \text{CR}, \text{FE})$ .

For phases with sublattices the constituents in each sublattice are separated by a colon, “:” and interacting constituents in the same sublattice by a comma, “,”. For example:  $G(\text{FCC}, \text{FE}:\text{C}, \text{VA})$  is the interaction between C (carbon) and VA (vacant interstitial sites) in the FCC phase.

The only binary excess model implemented in OC is the Redlich-Kister with the Muggianu ternary extrapolation method.

$$L_{A,B} = \sum_{\nu=0}^n {}^{\nu}L_{A,B}(y_A - y_B)^{\nu}$$

where the degree,  $\nu$ , of the interaction parameter is specified after a semicolon,  $L(\text{phase}, A, B; \nu)$ .

For ternary parameters and for reciprocal parameters the Hillert model for composition dependence is implemented, see [4].

You can store many different types of data in OC with different parameter identifier. Some of the parameters are not related to the thermodynamic properties but as they depend on the phase, T, P and composition it is convenient to store them together with the thermodynamic data. For example the mobility of Fe in BCC (including an empty interstitial sublattice) is specified as:  $\text{MQ\&FE}(\text{BCC}, \text{FE}:\text{VA})$ .

An explanation of the identifiers implemented in OC can be found in section subsection2.8.1. The current list can be obtained by the command **LIST MODEL\_PARAM.ID**. All of them can be composition dependent. Some cannot depend on  $T$  or  $P$  or neither. Many kinds of the parameters are available but in some cases the software for the models to handle them are not implemented. The value of a model parameter can be obtained using **LIST MODEL\_PARAM.VAL** or simply **SHOW**. You must specify phase and endmember for the parameter.

### 10.13 *enter* Phase

The user must specify a unique phase name:

#### **Phase name:**

All thermodynamic data are connected to a phase as defined by its parameters, see **enter parameter**. A phase has a name with can contain letters, digits and the underscore character. It must start with a letter.

#### **Phase model:**

After the phase name you must specify a model. The model specification is implemented in a rather rudimentary way. The only recognized models are

- IDEAL for a single lattice phase without interactions (like GAS)
- RKM for a substitutional phase with interactions (like metallic liquid)
- I2SL for the ionic liquid phase (2 sublattices with variable site ratios). If the phase name is IONIC\_LIQUID this prompted as the default model.

- CQC means the “Corrected Quasichemical model” for liquids.
- CEF for any other phase with two or more sublattices

This list may be extended in a future version of OC. Many other model features like magnetism, quasichemical etc are specified with the **AMEND PHASE** command, see section subsection5.11. The AMEND PHASE command is also used to specify disordered fraction set, low temperature CP model and many other things.

#### **Number of sublattices:**

For a phase with Long Range Ordering (LRO) you must specify the number of sublattices. After that you have for each sublattice specify the number of sites and constituents. Even if you have just one lattice you must specify the number of atoms on that lattice per formula unit.

For most models OC will ask for the number of sublattices and a phase can have 1 to 9 sublattices and you must specify the number of sites on each. Preferably use small integer values, if fractions are used at least 6 digits should be provided.

#### **Number of sites on a sublattice**

For some models, like the ionic liquid model, the number of sites may change with the composition of the phase so the number specified is irrelevant. See the book by Lukas et al [4] for more details on models.

#### **Models with bonds**

Some models depend on the number of bonds between atoms, such as the quasichemical model. The modified quasichemical model have a single sublattice and include additional species to describe the Short Range Ordering (SRO).

For each sublattice you must specify the constituents on the sublattice. A constituent that is not an element must already have been entered as a species, see section subsection10.16.

You may have to use the **AMEND PHASE** command, see section subsection5.11, for some additional model features like magnetism, low  $T$  heat capacity or permutations.

### **10.14 *enter Plot\_data***

This is when entering experimental data for assessments when combining experimental data in single equilibria with those entered in tables using the command “MANY\_EQUILIBRIA”.

You can add points to a dataset 1 to 9 to be plotted the current equilibrium. The dataset must already have created by a PLOT command inside a **ENTER MANY\_EQUILIB** command, see section subsection10.9.

### **10.15 *enter Quit***

Quit entering things.

## 10.16 *enter* Species

A species consists of a name and a stoichiometric formula. It can have a valence or charge. The name is often the stoichiometric formula but it does not have to be that. Examples:

- enter species water h2o
- enter species c2h2cl2\_trans c2h2cl2
- enter species c2h2cl2\_cis c2h2cl2
- enter species h+ h1/- -1

Single letter element names must be followed by a stoichiometric factor unless it is the last element when 1 is assumed. Two-letter element names have by default the stoichiometric factor 1.

There can be a problem with ambiguity with a species name like h2o if there is also a species h2o2. In such cases use a final unity, i.e. h2o1.

- enter species carbonmonoxide c1o1
- enter species cobaltoxide coo
- enter species carbondioxide c1o2
- DO NOT USE enter species co c1o1

The species name is important as it is the name, not the stoichiometry, that is used when referring to the species elsewhere like as a phase constituent. It is of course convenient to choose a species name similar to its stoichiometric formula but as shown above, that is not always sufficient.

### **Species symbol:**

The symbol must start with a letter a A-Z and contain just letter, digits and the special characters “\_” (underscore), “-” (minus) and “+” (plus).

### **Species stoichiometry:**

The stoichiometry must contain element symbols followed by a stoichiometry factor. The stoichiometry factor 1 can be omitted for two-letter element symbols. The charge is given as “/-” or “/+” followed by a stoichiometry factor.

## 10.17 *enter* Symbol

The OC package has both “symbols” and “tpfun.symbols”, the latter has a very special syntax and can be used when entering parameters.

The symbols are designed to handle relations between state variables, you can define expressions like **enter symbol KLBCR = X(LIQUID,CR)/X(BCC,CR);** where KLBCR is set to the partition of the Cr mole fractions between liquid and bcc.



The symbols also include “dot derivatives” like  $H.T$  which is the second derivative of the Gibbs energy with respect to the for the current system at the given set of conditions.

**enter symbol CP = H.T;**

If  $T$  and  $P$  are conditions and all other conditions are mass balance conditions CP is the heat capacity. It also takes account of the change of configurational entropy.

Currently  $H.T$  is the only dot derivatives allowed but more will be added as soon as possible.

## 10.18 *enter Tpfun\_Symbol*

This symbol is a special type of expression depending on  $T$  and  $P$  that can be used when entering parameters. A Tpfun can refer to another Tpfun but not any other state variable or symbol.

The program requests a name and if the symbol should be a FUNCTION, CONSTANT or a TABLE (tables not implemented).

If it is a FUNCTION you must specify a low  $T$  limit, and expression consisting of simple terms (signed coefficients multiplied with  $T$  and  $P$  possibly raised to powers).

A term may also be multiplied with another TP function or with LN(FX) for the natural logarithm of “FX” or EXP(FX) for the exponential of the expression of function “FX”.

The “FX” inside the parenthesis of an LN or EXP may refer to another TP function or it can be a coefficient multiplied with powers of T or P.

It is not allowed to use parenthesis except around arguments of LN and EXP or around negative powers such as  $T * (-1)$ .

The expression must be terminated by a semicolon followed by an upper  $T$  limit. After the upper  $T$  limit you must specify either N or Y. If you give Y it means there is another expression above this T limit. The last T-range limit must be followed by N and a bibliographic reference, see section subsection10.1.

TPFUNs have a strict syntax because the software must be able calculate not only its value but also its first and second derivatives with respect to  $T$  and  $P$  millions of times during a phase diagram calculations, see section subsection2.8.3.

## 11 Exit

Terminate the OC software in Swedish, Ha en bra dag.

## 12 Fin

Terminate the OC software in French, Au revoir.

## 13 Help and ?

### Which command:

Can give a list of commands or subcommands or parts of this help text. The user guide is also available as a searchable HTML file.

For a submenu question a single ? will give the menu and two ?? will give an extract of this user guide. Then the question will be asked again.

## 14 HPcalc

Start the reverse polish calculator.

## 15 Information

on the following topics:

CHANGES	DATABASES	HELP-SYSTEM	PROPERTY-DIAGRAM
COMPOSITION-SET	ELEMENTS	PHASE	QUIT-INFO
CONDITIONS	EQUILIBRIUM	PHASE-DIAGRAM	SPECIES

This command is still not fully implemented.

The intention is to provide the on-line help to users who does not like to read manuals. But it is not yet implemented.

### Topic? /CHANGES/:

Will list the most recent changes in the OC software from the changes.txt file (if it can be found). Stop listing by a q.

You can explore different parts of this User Guide online by selecting other topics.

Give QUIT or press return to go back to top level.

## 16 List

Many things can be listed. Output is normally on the screen unless it is redirected by the /output=*file name* or /append=*file name* option, see subsection 3.1.

ACTIVE_EQUILIBR	ELEMENTS	MODEL_PARAM_ID	RESULTS
AXIS	EQUILIBRIA	OPTIMIZATION *	SHORT
BIBLIOGRAPHY	ERROR_MESSAGE	PARAMETER	STATE_VARIABLES
CONDITIONS	LINE_EQUILIBRIA	PHASE	SYMBOLS
DATA	MODEL_PARAM_VAL	QUIT	TPFUN_SYMBOLS

## 16.1 *list* active-equilibria

This is used during assessment to list equilibria with non-zero weights.

## 16.2 *list* Axis

Lists the axis set by you.

## 16.3 *list* Bibliography

List the bibliographic references for the data.

## 16.4 *list* Conditions

Lists the current set of conditions set by you. If the degrees of freedoms are zero you can calculate an equilibrium.

## 16.5 *list* Data

Lists all thermodynamic data. The default is on SCREEN but you can also choose among the formats: LaTeX, MACRO, PDB and TDB.

The only formats implemented at present are SCREEN, PDB and TDB.

### 16.5.1 *list data* LaTeX

The thermodynamic data will be formatted according to LaTeX for later inclusion in publications. Not implemented.

### 16.5.2 *list data* Macro

The thermodynamic data will be written as a macro file that can later be read back into the OC software. Not implemented.

### 16.5.3 *list data* PDB

A “Portable phase related Data Format” similar to the TDB file format adapted for OC.

### 16.5.4 *list data* TDB

A variant of the TDB file format with Thermo-Calc flavor.

## 16.6 *list* Equilibria

Lists the equilibria entered. To list the results of the calculation of an equilibrium use **list result**.

## 16.7 *list* Error message

The message associated with an error code generated by OC can be listed

## 16.8 *list* Line equilibria

Lists the equilibria calculated during STEP or MAP commands. See also the command **AMEND LINE-EQUILIBRIA**.

## 16.9 *list* Model parameter identifiers

Lists the model parameter identifiers available in the current version of OC, see section subsection2.8.1.

## 16.10 *list* Model parameter value

The current value of a model parameter identifier can be listed. Note that the value is always phase dependent and may also depend on the composition set.

## 16.11 *list* optimization

Lists results of an optimization, several sub-options will be implemented but currently there is a short version only. To save this on a file use the option /output= or /append=, see subsection3.1.

COEFFICIENTS	DEBUG	GRAPHICS	MACRO
CORRELATION_MTRX	EXPERIMENTS	LONG	SHORT

### 16.11.1 *list optimization* coefficients

This gives a list of the coefficients and their values.

### 16.11.2 *list optimization* debug

Not implemented yet.

### 16.11.3 *list optimization* correlation\_matrix

Not implemented yet.

#### 16.11.4 *list optimization* experiments

List of experiments in the equilibria with non-zero weights.

#### 16.11.5 *list optimization* graphics

A figure with the experimental values on the X axis and calculated values on the Y axis for all experiments. Not implemented yet.

#### 16.11.6 *list optimization* long

Not implemented yet

#### 16.11.7 *list optimization* macro

A listing of all thermodynamic data and current values of model parameter and experimental data with current weight. This can be read back as a start of a re-assessment and an important documentation of the current state of the assessment. But not yet implemented.

#### 16.11.8 *list optimization* short

This specifies the data and hour of the listing and first a table with the optimizing coefficients with name, current value, start value, scaling factor and its relative standard deviation.

In the first table all the optimizing coefficients with non-zero values are listed together with the current values, the start values and their scaling factor (usually the same as the start value). In the column "RSD" the Relative Standard Deviation" should appear but it is not yet calculated correctly. Last column is the name of the TP symbol(s) where the coefficient is used.

After that all equilibria with non-zero weights are listed together with their experimental data, both the prescribed value, the uncertainty and the currently calculated one. In the last column the error is listed.

Listing of optimization results: date 2018.08.20 : 12h47

List of coefficients with non-zero values

Name	Current value	Start value	Scaling factor	RSD	Used in
A11	3.46818E+02	4.00095E+02	4.00095E+02	1.25070E-06	_GFCCAB0
A12	-5.66234E+01	-6.52871E+01	-6.52871E+01	1.33802E-06	
A13	-2.10028E-02	-1.30393E-02	-1.30393E-02	8.97167E-06	_GFCCAB0

List of 4 equilibria with 8 experimental data values

No	Equil name	Weight	Experiment	\$ calculated	Error
2	FCC1_ZA	1.00	SM=17:1	\$ 17	9.8995E-09
2		1.00	CP1=18:1	\$ 17.28685	7.1315E-01
3	FCC2_ZB	1.00	HDIFF=9000:500	\$ 9997.813	-1.9956E+00

3	1.00	CP1=20:DCP \$ 22.55698	-2.5570E-02
4 FCC3_ZC	1.00	HDIFF=15000:500 \$ 14719.24	5.6152E-01
4	1.00	CP1=22:DCP \$ 24.65726	-2.6573E-02
5 FCC4_ZD	1.00	HDIFF=20000:500 \$ 19860.72	2.7856E-01
5	1.00	CP1=24:DCP \$ 26.75754	-2.7575E-02

Final sum of squared errors: 4.88614E+00 using 8 experiments and  
 3 coefficient(s). Degrees of freedom: 5, normalized error: 9.7723E-01

In the list of equilibria with non-zero weight the first column is a sequential equilibrium number assigned by the software. Then the name of the equilibrium assigned by the user. The third column is the weight, only equilibria with nonzero weight are listed. Then comes a column with the experimental property and value and after the dollar sign its calculated value with the present set of coefficients. The rightmost column gives the difference for each experiment  $i$ ,  $q_i$  that should be as close to zero as possible:

$$q_i = \frac{z_i^{\text{exp}} - z_i^{\text{calc}}}{\sigma_i} w_i \quad (1)$$

where  $i$ ,  $z_i^{\text{exp}}$  is the experimental property,  $z_i^{\text{calc}}$  is the same property calculated from the model and  $\sigma_i$  is the experimental uncertainty and  $w_i$  is the weight assigned to equilibria with the experiment. If  $w_i = 1$  and  $q_i$  is between -1 and 1 the experiment has been fitted within the experimental uncertainty.

The least square routine tries to determine coefficients to make the sum of all  $q_i^2$  as small as possible.

At the end of the listing  $\sum_i q_i^2$  is listed. The degrees of freedom is the number of experiments minus the number of coefficients.

## 16.12 *list* Parameter

List a specific parameter.

## 16.13 *list* Phase *<phase name>*

You must first specify the phase name. Then you can specify if you want the phase CONSTITUTION, DATA or some MODEL information. To write on a file use the options /output= or /append=, see subsection3.1.

### 16.13.1 *list phase ... Constitution*

List the constitution of the phase.

### 16.13.2 *list phase ... Data*

List the model and model parameter expressions.

### 16.13.3 *list phase ... Model*

List some model data for example if there is a disordered fraction set.

### 16.14 *list Quit*

You did not really want to list anything.

### 16.15 *list Results*

List the results of an equilibrium calculation. This is the most frequent list command. The listing will contain the current set of conditions, a table with global data, a table with component specific data and then a list of stable phases with amounts, compositions and possibly constitutions. It is possible to list also unstable phases.

There are 9 options for the formatting:

- 1 Output in mole fractions, phase constituents in value order (constituent with highest fraction first).
- 2 as 1 but include also the phase constitution (sublattices and their fractions) in value order.
- 3 as 1 with the phase composition in alphabetical order
- 4 Output in mass fractions, phase composition in value order.
- 5 as 4 with the phase composition in alphabetical order.
- 6 as 4 and also include the phase constitutions in value order.
- 7 Output all phases with composition in mass fractions and in value order. Unstable phases will have a negative driving force.
- 8 Output all phases with composition in mole fraction and constitution in alphabetic order. Unstable phases will have a negative driving force.
- 9 as 8 but in value order.

For each phase the name, its status (S=suspended/D=dormant/E=entered/F=fix), moles (or mass), volume, number of formula units, atoms per formula units and driving force (in dimensionless units) is given on one line.

The moles of a phase is the number of formula unit multiplied with atoms per formula units. The gas phase and phases with interstitials and vacancies have a varying amount of moles of atoms per formula units. The composition of the phase can be in value order or alphabetical order.

To write the output on a file use /output= or /append=, see subsection 3.1.

## 16.16 *list* Short

There are 4 options: A/C/M/P

The A option lists a single line for each element, species and phases with some essential data.

The C option lists one line for each component.

The M option lists the models and constitution for all phases.

The P option lists one line for each stable phase and then one line for some of the remaining phases in decreasing order of stability.

## 16.17 *list* State\_Variables

Values of individual state variables like G, HM(LIQUID), X(LIQUID,CR) etc. can be listed. Terminate the command by an empty line. Note that the values of symbols and TP functions cannot be listed here, they are calculated by the CALCULATE SYMBOL or CALCULATE TP command.

The current values of parameter identifiers, see section subsection2.8.1 can be listed with the command, like TC(BCC) will give the calculated Curie temperature for BCC. A symbol like MQ&FE(FCC) will give the logarithm of the mobility of Fe in the FCC phase.

This command is the same as the SHOW command, section section27.

## 16.18 *list* Symbols

All state variable symbols listed but not their values, they are calculated by the CALCULATE SYMBOL command.

List of all state variable symbols

No Special Name= expression ;

1		R= 8.31451;
2		RT= R*T;
3		T_C= T-273.15;
4	D	CP= HM.T;
5	C	DCP= 1
6	7X	H298= HM;

In the “special” column the “D” means the symbol that is a “dot derivative” which is calculated only when explicitly specified, “C” means a numeric value that can be amended. The special 7X means a symbol that is evaluated only at equilibrium 7 which means you can refer to the value of this symbol calculated at the specified equilibrium in other equilibria. See also section subsection5.14.

## 16.19 *list* Tpfun Symbols

All or some TPFUN expressions listed. By giving \* all are listed, bu giving the g\* all TP functions starting with G are listed.



Note that all parameters are also TP functions, they can be listed by giving “\_\*” as name. The abbreviation “\_g\*” will list the function for all parameters with identifiers starting with G.

To obtain the values of TP functions use the **calculate TP** command.

## 17 Macro

By specifying a file name commands will be read from that file. The default extension is OCM. A macro file can open another macro file (max 5 levels). When a macro file finish with SET INTERACTIVE the calling macro file will continue or the user can continue interactively. See section subsection2.1.5.

When you start OC you can give a macro file name on the same line and the program will drictly start reading from this file.

With the popup window facility there are some special things. If you open the macro file with the popup window OC will save the directory where the macro file was found. If there are references to other files such as databases or other macro files inside the macro and these file names are on the same line as the command **read tdb ./steel1** the file name must be preceeded by a “./”, otherwise OC will try to open the file on its “working directory”, see section subsection2.1.2.

## 18 Map

For phase diagram calculations. You must first set two axis with state variables which are already set as conditions.

### Reinitiate?

If you give several MAP commands you can choose to erase or keep the previous results at each command.

During mapping each calculated equilibria is saved and for plotting any state variable can be used.

## 19 New

To remove all data and calculated results to enter a new system. It is fragile.

The user must confirm with UPPER CASE Y.

## 20 Optimize

The command is part of the facility to assess model parameters for thermodynamic databases. You have already entered elements, phases and model parameters with coefficients to be assessed and all the experimental data yu can find. Estimated and theoretical data calculated by DFT can also be entered as experimental data.

The model parameters to optimized are selected by SET VARIABLE\_COEFF and there is a least square routine LMDIF which will vary these to obtain the best least fit the experimental data provided.

As already state you must have entered the thermodynamic descriptions of the phases with model parameters depending on optimizing coefficients and the experimental data before this command. You must also set the weights of the experiments and which coefficients to be variable.

You provide a maximum number of iterations allowed. If you give zero a “dry run” will be made with the current values of the optimizing coefficients. This is useful to check that there are no problems calculating the equilibria. Usually you have to change the set of model parameters, weights of the experimental data and other criteria many times before you get a satisfactory result.

Developing better assessment software is one of the main aspects of the OC software. There will be more options to this and related commands.

## 21 Plot

Plot the result from a STEP or MAP calculation. A simple interface to GNUPLOT [6] has been implemented in OC. This generates a command file which is automatically plotted using GNUPLOT after the “render” command.

In OC you must first specify the state variable on the horizontal (x-axis) and vertical (y-axis) axis. Then you can give several of the options below, finish with RENDER or QUIT.

### 21.1 *plot xaxis yaxis* Horizontal axis variable

Specify the state variable or symbol to be plotted on the horizontal axis.

Note that if you plot a phase diagram with “tie-lines in the plane” you should specify a fraction variable as X(\*,C) and not X(C) because you want the carbon content in all stable phases.

### 21.2 *plot xaxis yaxis* Vertical axis variable

Specify the state variable or symbol to be plotted on the vertical axis.

Note that if you plot a phase diagram with “tie-lines in the plane” you should specify a fraction variable as X(\*,C) and not X(C) because you want the carbon content in all stable phases.

### 21.3 *plot xaxis yaxis* Options?

You can choose various options before plotting. Typing a ? gives a menu, typing ?? will give this text of the online help is correctly installed. The menu here is not very clear and will be reorganized.

The simplest way to generate a complex plot to be saved as PDF or PNG format is to first select the appropriate axis and then set a few options like scaling, axis texts and text labels and plot on the screen. If you are not satisfied you can plot again (without changing the axis variables, if you change these all options you have set will be cleared) and add or modify the options. When you are satisfied with the plot on the screen you plot a final time and set the GRAPHICS-FORMAT option and plot in the desired format on a file. Or you can select to plot on a file in the GNUPLOT window. Note that some texts and formats may not be exactly identical to those you see on the screen.

Default plotfile is “ocgnu.plt”. On this file all the GNUPLOT commands and data will be written to be executed by GNUPLOT. If GNUPLOT is correctly installed then OC will start GNUPLOT and generate the graphics output when you RENDER the plot.

You can change the name of the plotfile before plotting with the command “output file”. Whenever you set a new terminal you can also set the output file name. Or you can rename the file after the RENDER command and before you generate a new plot.

GNUPLOT is a very powerful graphics software, only a few of its facilities are available within OC. The gnuplot command file generated by OC can be edited to exploit additional facilities in GNUPLOT.

APPEND	GRAPHICS_FORMAT	QUIT	TEXT
AXIS_LABELS	OUTPUT_FILE	RENDER	TITLE
EXTRA	POSITION_OF_KEYS	SCALE_RANGES	

A short summary:

- APPEND means overlay the current plot with another GNUPLOT file
- AXIS-LABELS you can specify the label on X or Y axis
- EXTRA provides less frequent options
- GRAPHICS-FORMAT to select the GNUPLOT output device (PS, PDF, PNG etc)
- OUTPUT-FILE the GNUPLOT file is saved on this file (default ocgnu.plt)
- POSITION of the identification labels for the curves
- QUIT no plot generated
- RENDER finally plot
- SCALE-RANGES for X and Y axis you can specify min and max value plotted
- TEXT you can place a text inside the plot
- TITLE the heading of the plot

The EXTRA command provides less used options:

FONT_AND_COLOR	LOGSCALE	NO_HEADING	RATIOS_XY
GIBBS_TRIANGLE	LOWER_LEFT_TEXT	PAUSE_OPTION	SPAWN
LINE_WITH_SYMBLS	MANIPULATE_LINES	QUIT	TIE_LINES

## 21.4 *plot xaxis yaxis Append*

A GNUPLOT file previously generated by OC or edited manually can be specified to be overlayed on the current plot.

## 21.5 *plot xaxis yaxis* Axis\_Labels

You specify for the X or Y axis the axis labels. By default the state variable or symbol plotted will be used as label.

### For X or Y axis?

Specify the axis for which you want to enter the label

### Axis label:

The default label is given in the question.

## 21.6 *plot xaxis yaxis* Graphics format

The GNUPLOT terminals entered in section subsection10.8 can be used. For other formats than SCREEN you can also specify an output file which will be written for the specified format.

Graphics format index:

The default terminal indices are:

	Name	=	GNUPLOT definition
1	SCREEN		set terminal wxt size 940,700 font "arial,16"
2	PS		set terminal postscript color solid fontscale 1.2
3	PDF		set terminal pdf color solid size 6,5 enhanced font "arial,16"
4	GIF		set terminal gif enhanced fontscale 0.7
5	PNG		set terminal png enhanced fontscale 0.7

You can change these or enter more graphics formats with the **enter gnuplot** command. subsection10.8. The SCREEN driver is usually "wxt" for Windows and "Qt" for Linux but can be selected in the Makefile for the pmon6.F90 file.

If SCREEN is not selected the you can specify the name of the file where OC will save the command-file for GNUPLOT as well as the final graphics file created by GNUPLOT. It will have the appropriate extention depending on the format. By default OC saves the GNUPLOT command file on the file "ocgnu.plt". This can be renamed and edited if you want to keep it for later processing.

Plot file:

In addition to the GNUPLOT command file the graphics a file with the specified format will be generated.

## 21.7 *plot xaxis yaxis* Output file

By default plotting will generate a ocgnu.plt file for GNUPLOT. You can specify other name here. If you plot on other terminals than SCREEN there will be an additional file with extension ".ps" for Postscript, ".pdf" for Adobe PDF or ".gif" for GIF format.

If the file already exists the user must confirm it it should be overwritten.

## 21.8 *plot xaxis yaxis* Position of keys

The identification (labels) of the curves in the plot can be positioned with this command. See the GNUPLOT manual [6] for information.

## 21.9 *plot xaxis yaxis* Quit

No plot generated.

## 21.10 *plot xaxis yaxis* Render

Press return to plot using all the option set. Otherwise you can select any of these commands:

APPEND	GRAPHICS_FORMAT	QUIT	TEXT
AXIS_LABELS	OUTPUT_FILE	RENDER	TITLE
EXTRA	POSITION_OF_KEYS	SCALE_RANGES	

## 21.11 *plot xaxis yaxis* Scale\_Range

You specify for the X or Y axis the minimum and maximum range. The automatic (default) scaling range can always be restored.

## 21.12 *plot xaxis yaxis* Text

This is a facility to add a text to a plot at an arbitrary position.

### 21.12.1 *plot xaxis yaxis text* Modify existing text?:

If there is already some text items you must first answer if you wants modify an already existing one. If so all the texts are listed and you can select which one you wants to modify.

### 21.12.2 *plot xaxis yaxis text* Which text index?:

You must provide the index of the text to change.

For a new or changed text you must give:

### 21.12.3 *plot xaxis yaxis text* X position

The X coordinate of the text (in the plot scale)

### 21.12.4 *plot xaxis yaxis text* Y position

The Y coordinate of the text (in the plot scale)

#### 21.12.5 *plot xaxis yaxis text* Fontscale

A relative size factor, default is 1. The size of the text will be scaled accordingly.

#### 21.12.6 *plot xaxis yaxis text* Angle (degrees)

The text will be written with the specified angle. Zero means horizontally, negative values slopes downward, positive upwards. An angle of 180 means the text will be upside down.

#### 21.12.7 *plot xaxis yaxis text* Do you want to calculate the equilibrium?

If it is a phase diagram that is plotted you can select to calculate an equilibrium at the specified coordinates. The names of the stable phases will be proposed as text.

#### 21.12.8 *plot xaxis yaxis text* Text:

The text to be added to the plot. The text will start at the coordinates given. On Postscript and PDF a greek character can be given as “/Symbol m” for  $\mu$ .

#### 21.13 *plot xaxis yaxis* Title

The default is the date and the conditions. You can add a text of your own here. You can remove the title altogether with EXTRA NO\_HEADING. That will make the figure slightly larger.

#### 21.14 *plot xaxis yaxis* Extra

Less common options for the plotting is available here. For really nice plotting it is recommended to edit the output file from OC as GNUPLOT has too many facilities to be made available here.

The EXTRA commands provides more obscure options:

FONT-AND-COLOR	LOGSCALE	NO-HEADING	RATIOS_XY
GIBBS-TRIANGLE	LOWER-LEFT-TEXT	PAUSE-OPTION	SPAWN
LINE-WITH-SYMBOLS	MANIPULATE-LINES	QUIT	TIE-LINES

- FONT-AND-COLOR you can select font and color of text
- GIBBS-TRIANGLE means an equilateral triangular diagram
- LINE-WITH-SYMBOLS means a symbol at every calculated equilibrium
- LOGSCALE you can specify that X or Y axis is logarithmic
- LOWER-LEFT-TEXT you can set a text in the lower left corner
- MANIPULATE-LINES is to select line identification
- NO-HEADING means remove title and text above the plot

- PAUSE-OPTION to select how GNUPLOT should behave after plotting
- QUIT no plot generated
- RATIOS-XY will change the relative length of X and Y axis
- SPAWN will allow you to continue calculating with the plot window open
- TIE-LINES if you have tie-lines in the plane you can plot some of them

#### **21.14.1 *plot xaxis yaxis* extra font-and-color**

Not fully implemented. Intended to select font and color of all text. Some GNUPLOT terminals may not support certain fonts.

The user can select color of monovariant equilibria in isothermal sections and tie-line colors.

#### **21.14.2 *plot xaxis yaxis* extra Gibbs-triangle**

Gibbs triangle plots should only be used for isothermal sections. A trial implementation is available which can generate equiaxial triangular isothermal diagrams.

If you already set this option you can set it again to plot on a square.

#### **21.14.3 *plot xaxis yaxis* extra line-with-symbols**

Not implemented yet

#### **21.14.4 *plot xaxis yaxis* extra logscale**

You can set logarithmic scale on X or Y axis (or both).

#### **21.14.5 *plot xaxis yaxis* extra manipulate lines**

This is not implemented. It is intended to allow specification of the color of the curves in the plot.

#### **21.14.6 *plot xaxis yaxis* extra lower left corner text**

You can set a short text in the lower left corner of the plot

#### **21.14.7 *plot xaxis yaxis* extra spawn**

You can spawn the plot window and continue working looking at it.

#### **21.14.8 *plot xaxis yaxis* extra no heading**

Remove the text above the plot with date and title. The plot is larger this way.

#### **21.14.9 *plot xaxis yaxis* extra pause option**

When you plot on the screen the last command on the file to GNUPLOT is “pause mouse”. You can change this with this command.

#### **21.14.10 *plot xaxis yaxis* extra ratios XY**

The relative ratios of the X and Y axis can be specied.

#### **21.14.11 *plot xaxis yaxis* extra tie-line**

Tie-lines in isothermal ternary phase diagram can be plotted. You can specify the density of the tie-lines by

Tie-line plot increment?

The increment is related to the actual equilibria calculated. 0 means no tie-lines plotted, 3 means to plot a tie-line at every 3rd calculated equilibria and so on.

## **22 Quit**

Terminate the OC software in English, have a nice day.

## **23 Read**

It is possible to read a (non-encrypted) TDB file but it should be not too different from what is normally generated by the LIST\_DATA command in TC.

DIRECT	PDB	UNFORMATTED
QUIT	TDB	

### **23.1 *read* Direct**

#### **File name:**

In the future it will be possible to save results on a random access (DIRECT) file.

### **23.2 *read* Quit**

You did not really want to read anything.



### 23.3 *read* PDB

**File name:**

A PDB file (with extension PDB) should be specified. The file should be in the Portable phase dependent Data Base format.

The user can select to read the whole file or select elements.

### 23.4 *read* TDB

A TDB file (with extension TDB) should be specified. The TDB file must not deviate very much from the standard output from Thermo-Calc.

**File name:**

If you do not use the popup window for opening files you must specify the database file name. The file must be on the working directory (where you started the OC program, see section subsection2.1.2) or you must provide the path.

After opening the file the program will list the elements and ask:

**Select elements /all/:**

If you give RETURN the data for all elements will be read. If you answer q or quit nothing will be read. If you specify one or more elements the data for those will be read and if you selected a subset you will have the question:

**Select elements /no more/:**

And you can select some more or just give RETURN (or type quit). All phases that can be formed by the elements selected will be read, you cannot select the phases here but inside OC you can suspend those phases you are not interested in.

**Error reading TDB file**

In some cases there are non-fatal errors or warnings reading TDB files created by different groups because the TDB format varies a lot. The user should carefully check if there are any data missing but can continue using the data he read if he is confident it is correct. The TDB file should be corrected manually.

### 23.5 *read* Unformatted

**File name:**

For use to read a file created with a SAVE UNFORMATTED command. It may not always work as the data structure is still changing.

## 24 Save

There are several forms of save, three forms write a text file that can be read and modified with a normal editor. Two forms are unformatted, either on a sequential file or a direct (random access) file.

DIRECT	SOLGAS	UNFORMATTED
QUIT	TDB	PDB

### 24.1 *save* Direct

It will eventually be possible to save the result of STEP and MAP commands on a random access file for later processing.

### 24.2 *save* Quit

You did not want to save anything.

### 24.3 *save* PDB

Saves current set of model parameters and functions on a file in the Portable phase dependant Data Base format.

### 24.4 *save* TDB

Saves current set of model parameters and functions on a file in TDB format. Same as the command **list data tdb**.

### 24.5 *save* SOLGAS

Saves current set of model parameters and functions on a file in a format that (hopefully) can be read by the FactSage software.

### 24.6 *save* Unformatted

With this command you can save the current status of the calculations on a file and then resume the calculations by reading this file. Note that the Fortran unformatted files may not be portable, they depend on the compiler, the operating system and the hardware.

## 25 Select

There are a few things that can be selected, most important which equilibrium the following commands will operate on.

### 25.1 *select* Equilibrium

As you can enter several equilibria with different conditions this command allows him to select the current equilibria.

## 25.2 *select* Graphics

Only GNUPLOT citegnuplot available.

## 25.3 *select* Language

Only English implemented (except a few French exclamations).

## 25.4 *select* Minimizer

Only Hillert's algorithm implemented in matsmin [2] available.

## 25.5 *select* Optimizer

The LMDIF [5] least square fitting software is the only one implemented.

# 26 Set

Many things can be set. Things to be “set” and “amended” sometimes overlap.

ADVANCED	FIXED_COEFF	OPTIMIZING_COND	STATUS
AS_START_EQUILIB	INITIAL_T_AND_P	PHASE	SYSTEM_VARIABLE
AXIS	INPUT_AMOUNTS	QUIT	UNITS
BIT	INTERACTIVE	RANGE_EXP_EQUIL	VARIABLE_COEFF
CONDITION	LOG_FILE	REFERENCE_STATE	VERBOSE
ECHO	NUMERIC_OPTIONS	SCALED_COEFF	WEIGHT

## 26.1 *set* Advanced

A few options implemented

EET_EXTRAPOL	GRID-DENSITY	MAP-SPECIAL	SMALL-GRID-ONOFF
EQUILIB-TRANSF	HELP-POPUP-OFF	OPEN-POPUP-OFF	WORKING-DIRECTRY
GLOBAL-MIN-ONOFF	LEVEL	QUIT	

### 26.1.1 *set advanced* equilibrium transfer

This is only for experts who know what they are doing.

### 26.1.2 *set advanced* global-min-onoff

Turn on or off the use of the global gridminimizer.

### **26.1.3    *set advanced* grid\_density**

At present the grid density cannot be fine tuned. For some phases it is fixed for others you can select a more or less dense grid.

### **26.1.4    *set advanced* help-popup-off**

The user can turn off or on the HTML popup help feature. He can also change the browser and help file.

**Turn off popup help? /Y/:**

If the user answers N he will be asked for the browser and HTML file. These are normally set when compiling the OC software and their current values are proposed as default within slashes `../`.

**Browser including full path `//usr/local/firefox/`:**

**HTML help file including full path `//home/user/.ochelp/ochelp.html/`:**

### **26.1.5    *set advanced* map-special**

Not implemented yet.

### **26.1.6    *set advanced* open-popup-off**

Any other answer than Y will turn off popup windows for opening files. By answering Y you turn on popup windows for opening files (the default) provided the program is linked with this facility.

### **26.1.7    *set advanced* quit**

You did not want to set anything advanced.

### **26.1.8    *set advanced* turn on equi-entropy extrapolation**

This command turns on or off the use of the EET criterion to prevent solid phases with higher entropy than the liquid to become stable.

### **26.1.9    *set advanced* level**

You can specify if you are a beginner, regular user or expert. The intention is that a beginner should have more help and an expert more privileges but nothing of that is implemented.

### **26.1.10    *set advanced* small-grid-onoff**

A particularly small grid for the global minimization is selected or not. Replaced by setting GRID-DENSITY to zero.

### 26.1.11 *set advanced working-directory*

The name of the working directory (where OC was started) is listed. It cannot be changed at present. It is related to the popup windows for opening files, see section subsection2.1.2.

### 26.2 *set As start equilibrium*

The current equilibrium will be copied to the list of start equilibria for STEP and MAP commands.

### 26.3 *set Axis*

To set an axis you must first has set the conditions necessary to calculate an equilibrium and also calculated this.

#### **Axis number:**

The axis are numbered 1, 2 etc and you must set them in sequential order. To change an axis variable just give the number of the axis to change.

#### **Condition to vary along the axis:**

You can set select one of the condition to vary between a min and max value along the axis. If you has just one axis you can use STEP to calculate a property diagram, i.e. how the system properties varies with a single variable. Typically a phase fraction plot or how the heat capacity varies with the independent axis variable.

#### **Minimal/maximal value of the axis:**

The calculation will start with the current value and calculate in both directions.

#### **Increment:**

By default the increment is 1/40 of the difference beteen max and min.

If you set two or more axis (current limit is 2) the OC software will map the phase diagram, i.e. follow the lines where the set of phases changes. This means OC will replace one axis condition with a condition that a phase should be stable with zero amount.

To calculate a diagram you must then give a STEP command (if you have one axis) or a MAP command (if you have 2 or more axis). For the STEP command section28, there are several options.

### 26.4 *set Bit*

Many records have status words where the bits are used to signify different things. An advanced user can set these bits for the global, equilibrium and phase records, but only if you know what it means.

- The GLOBAL record bits are listed below. Most of them are set or reset automatically by the software or by other commands.
  - 0 you are a beginner
  - 1 you are experienced (default)

- 2 you are an expert
  - 3 gridminimizer must not be used
  - 4 gridminimizer must not merge comp.sets.
  - 5 there are no data (cleread automatically)
  - 6 there are no phases (cleared automatically)
  - 7 comp.sets must not be created automatically
  - 8 comp.sets must not be deleted automatically
  - 9 data has changed since last save (set automatically)
  - 10 means verbose is on (not implemented)
  - 11 means verbose is permanently on (not implemented)
  - 12 means be silent (supress warnings)
  - 13 no cleanup after an equilibrium calculation
  - 14 use denser grid in grid minimizer (see also SET ADVANCED)
  - 15 calculations in parallel is not allowed
  - 16 no global test at node point during STEP/MAP
  - 17 the components are not the elements
  - 18 global test of equilibrium AFTER calculation
  - 19 use old (less dense) grid minimizer
  - 20 do not recalculate if global test AFTER fails
  - 21 use old MAP algorithm
  - 22-31 not yet used
- The EQUILIBRIUM record bits are listed below
    - 0 No threads allowed (no parallel calculation)
    - 1 No global minimization allowed for this equilibrium
    - 2 No equilibrium has been calculated (there are no results)
    - 3 Conditions and results not consistent
    - 4 Last equilibrium calculation failed
    - 5 No automatic generation of composition sets
    - 6 Equilibrium tested by grid minimizer
    - 7 Current results are from a grid minimization
  - To change the phase status word use SET PHASE ... bit

## 26.5 *set* Condition

Most of the text here also applies to **enter experiment**.

### State variable:

A condition is a value assigned to a state variable or an expression of state variables. All state variables are listed in Table table1 in section refsc:statevar

By setting the status of a phase to fix you have also set a condition. For example

```
set cond t=1273 p=1e5 n=1 x(cr)=0.1 w%(c)=1
```

Three cases of expressions can be used as conditions, for example a relation between mole fraction like

```
set condition x(liq,o)-x(c1_mo2,o)=0
```

means that the oxygen content in liquid and c1\_mo2 phases should be the same. That is useful to calculate the congruent melting of c1\_mo2.

Another case is if the total amount of some components has a relation, for example:

```
set condition n(u)+n(zr)=1
```

means that the total number of moles of the components U and Zr should be unity.

A third case is  $y(\text{B2,Al})-y(\text{B2,Al}\#2)=0.01$  to calculate a second order transition line when the B2 ordered phase is on the limit of disorder as the fractions of Al on the two sublattices are almost equal.

### Value:

A numeric value or a symbol representing a constant value is expected.

## 26.6 *set* Echo

This is useful command in macro files or when demonstrating the program.

## 26.7 *set* Fixed coefficient

One or more optimizing coefficients are assigned a fixed value. The index 0 to 99 is used to indicate the coefficients A00 to A99. One can use a range as 15-19 to set all variable coefficients in the range to their current values.

## 26.8 *set* Input-Amounts

This command allows you to specify a system by giving a redundant amount of various species in the system. The software will transform this to conditions on the amounts of the components.

Species and amount as  $N(..)=$  or  $B(...)=$  :

An example:

```
--->OC5:read tdb cho-gas
--->OC5:set input
Species and amount as N(..)= or B(...)= : n(c1o2)
```

```

Amount: 10
--->OC5:set input n(c1h4)=5
--->OC5:l c
Conditions for equilibrium: 1, DEFAULT_EQUILIBRIUM
1:N(C)=45, 2:N(O)=80, 3:N(H)=30
Degrees of freedom are 2

```

The amounts of the species has been split on the components. Setting input amounts is just another way to set these directly. If we set a  $T$  and  $P$  we can calculate the equilibrium fraction of all the species.

```

--->OC5:set c t=1000 p=1e5
--->OC5:l c
Conditions for equilibrium: 1, DEFAULT_EQUILIBRIUM
1:N(C)=45, 2:N(O)=80, 3:N(H)=30, 4:T=1000, 5:P=100000
Degrees of freedom are 0
--->OC5:c e
3Y Constitution of metastable phases set
Gridmin: 85 points 1.56E-02 s and 0 clockcycles, T= 1000.00
Phase change: its/add/remove: 5 11 0
Phase change: its/add/remove: 12 12 0
Phase change: its/add/remove: 17 0 12
Phase change: its/add/remove: 53 0 11
Equilibrium calculation 79 its, 7.8125E-02 s and 93 clockcycles
--->OC5:l
LIST what? /RESULTS/:
Results output mode: /1/:

```

```

Output for equilibrium: 1, DEFAULT_EQUILIBRIUM 2018.08.21
Conditions .....:
1:N(C)=45, 2:N(O)=80, 3:N(H)=30, 4:T=1000, 5:P=100000
Degrees of freedom are 0

```

```

Some global data, reference state SER .....:
T= 1000.00 K ( 726.85 C), P= 1.0000E+05 Pa, V= 4.9872E+00 m3
N= 1.5500E+02 moles, B= 1.8507E+03 g, RT= 8.3145E+03 J/mol
GS= -2.80411E+07 J, GS/N=-1.8091E+05 J/mol, HS=-1.2914E+07 J, SS= 1.513E+04 J/K

```

```

Some data for components .....:
Component name      Moles      Mole-fr  Chem.pot/RT  Activities  Ref.state
C                    4.5000E+01  0.29032 -3.7354E+00  2.3863E-02  SER (default)
H                    3.0000E+01  0.19355 -9.8098E+00  5.4910E-05  SER (default)
O                    8.0000E+01  0.51613 -3.6377E+01  1.5911E-16  SER (default)

```

```

Some data for phases .....:
Name                Status Moles      Volume      Form.Units Cmp/FU dGm/RT  Comp:
GAS..... E 1.550E+02  4.99E+00  6.00E+01  2.58  0.00E+00  X:
O 5.16129E-01 C 2.90323E-01 H 1.93548E-01
Constitution: There are 73 constituents:
C102 4.54395E-01 C2H3 8.67456E-17 C4H10_1 2.73242E-23
C101 2.95682E-01 C3H4_2 3.04922E-17 C4H10_2 1.38822E-23
H201 1.29270E-01 C3H8 2.73523E-17 C4H2 8.16657E-24

```



H2	1.20501E-01	C3H601	1.94895E-17	H102	4.37267E-24
C1H4	1.52786E-04	C3H4_1	8.18695E-18	C4H6_5	1.44915E-24
C1H202_CIS	4.04887E-08	C1H301_CH3O	3.87833E-18	C4H8	1.04297E-25
C1H201	2.01368E-08	C2H401_OXIRA	1.64221E-19	C2H1	7.79712E-26
C1H202_TRANS	5.82767E-09	C1H2	3.98656E-20	C4H8_4	6.39692E-26
H	7.88542E-10	H202	3.27068E-20	C6H601	3.00598E-26
C1H401	1.27636E-10	O	1.46838E-20	C1H1	1.81712E-27
C2H4	1.05140E-10	C2H602	1.19305E-20	C3H1	1.68523E-28
C2H6	3.44726E-11	O2	8.71930E-21	C4H4_1_3	7.73762E-29
C1H3	1.83302E-11	C4H6_2	5.73533E-21	C1H202_DIOXI	4.04963E-30
C1H101	7.24719E-12	C201	1.72590E-21	C4H1	1.00000E-30
C2H401_ACETA	2.00054E-12	C4H8_5	9.38081E-22	C2H402_DIOXE	1.00000E-30
H101	1.86354E-12	C4H8_3	5.91323E-22	C4	1.00000E-30
C2H2	1.82837E-12	C4H8_1	4.75317E-22	C2H403_123TR	1.00000E-30
C1H102	1.57298E-12	C4H8_2	4.17043E-22	C2H403_124TR	1.00000E-30
C2H402_ACETI	7.65642E-13	C2H201	1.47405E-22	C2	1.00000E-30
C1H301_CH2OH	1.64978E-15	C4H6_4	8.47392E-23	C6O	1.00000E-30
C302	1.11079E-15	C6H6	8.21607E-23	C3	1.00000E-30
C3H6_2	7.21243E-16	C4H4	5.46648E-23	C5	1.00000E-30
C3H6	7.13743E-16	C4H6_1	5.05773E-23	O3	1.00000E-30
C2H601	6.22811E-16	C4H6_3	2.87604E-23		
C2H5	4.72671E-16	C4H10_1	2.73242E-23		

--->OC5:

The calculation shows that mixing 10 moles of CO<sub>2</sub> with 5 moles of CH<sub>4</sub> at 1000 K and 1 bar gives a gas with 45% CO<sub>2</sub>, 30% CO, 13% H<sub>2</sub>O and the rest H<sub>2</sub>

## 26.9 *set* Interactive

The last command on a macro file. Gives command back to the keyboard of the user, or to the calling macro file. Without this the program will just terminate when the macro is finished.

## 26.10 *set* Log-File

A useful command to save all interactive input while running OC. The log file can easily be transformed to a macro file. All bug reports should be accompanied by a log file which reproduces the bug.

## 26.11 *set* Numeric-Options

The default number of iterations and accuracy can be specified. Default values are 500 and 10<sup>-6</sup>.

Some more obscure values may also be asked for, they should never be changed.

## 26.12 *set* Optimizing conditions

A few variables used to guide the optimization of model parameters can be set.

### 26.13 *set* system variable

This is a new idea to have global variables. No idea how to use it yet.

### 26.14 *set* Phase <phase name>

You must specify a phase name. Some phase specific things can be set, also for the model. Some subcommands allow wildcard “\*” as name.

#### 26.14.1 *set phase ... Amount*

You can specify the amount of the phase which is used as initial value for an equilibrium calculation.

#### 26.14.2 *set phase ... Bits*

Some of the models and use of data storage depend on the bits of the phase. Most of them are set automatically by the software and other commands like AMEND PHASE. Changing them with this command will not have the expected effect and may cause the program to fail.

The bits that can be changed are:

- EXTRA\_DENSE\_GRID makes it possible to have a larger number of gridpoints calculated by the gridminimizer for the specified phase.
- NO\_AUTO\_COMP\_SET. This makes it possible to prevent that the specific phase has automatic composition set created during calculations.
- QUIT, do not set any more bits.

#### 26.14.3 *set phase ... Constitution*

This is the same as **amend phase constitution**. The amount of the phase can also be set. You can specify the constituent fraction of each constituent. A fraction must be larger than zero and less than unity.

As the sum of fractions must be unity the last constituent in each sublattice will not be asked for unless you specify the fraction for one of the constituents as “rest”. The fraction of that will then be set as “the rest” i.e. one minus the sum of the other fractions.

This is also be used for the command **calculate phase** to calculate properties for a single phase.

#### 26.14.4 *set phase ... Default-constitution*

Same as **amend phase default\_constit**.

#### 26.14.5 *set phase ... Quit*

You did not want to set anything for the phase.

#### 26.14.6 *set phase ... Status*

Use the SET STATUS PHASE command to set the status of one or several phases. The different status are explained for that command, section subsection26.19.3.

A phase with the status FIX must also have an amount specified. For a phase with the status ENTERED the amount is also requested but normally it should be set to zero. A nonzero value means the user assumes the phase should be stable.

#### 26.15 *set Quit*

You did not really want to set anything.

#### 26.16 *set Range of experimental equilibria*

For an assessment several consecutive equilibria with experimental data must be entered. This command specifies the first and last of those equilibria. It possible to add more equilibria later one by one (not yet though).

**First equilibrium number:** /2/:

**Last equilibrium number:**

The equilibria are assigned the weight one by default. The weight can be changed with the SET WEIGHT command. The weight zero means the equilibrium is not calculated.

#### 26.17 *set Reference-State*

By default the reference state for the components is SER (Stable Element Reference) which is the stable state of the element at 298.15 K and 1 bar. (NOTE: in principle SER is defined by the database but today almost all databases have SER as reference state.)

**Component name:**

**Reference phase:**

For each component (also for other components than the elements) you can specify a phase at a given temperature and pressure as reference state. The phase must exist for the component as pure.

**Temperature:**

Instead of a fixed  $T$  you can give a \*, indicating current  $T$ , if you calculates at different values of  $T$ .

**Pressure:**

Example:

*set reference O gas \* 1e5*

Note that state variables like the chemical potential,  $\text{MU}(\text{O})$ , will refer to the user defined reference state. To obtain the value for the SER state you can use the suffix S, i.e.  $\text{MUS}(\text{O})$  will give the chemical potential referred to SER.

IMPORTANT NOTE: the value of integral properties like Gibbs energy,  $G$ , enthalpy,  $H$ , etc. will also be affected by the change of the reference state of an element. If all elements have the same phase as reference state the value of the enthalpy obtained by  $H$  for that phase will be the enthalpy of mixing. If not it is only confusing.

In order to have use SER as reference state use a suffix S. The enthalpy relative to SER is  $HS$  independent of any reference state set for the elements by the user.

## 26.18 *set* Scaled coefficient

A coefficient for optimization can be specified with a start value, scaling factor and a minimum and maximum value. The *set* VARIABLE command sets the scaling factor equal to the start value and have no min or max values.

## 26.19 *set* Status

The status of elements, constituents, species or phases can be changed. Only phases are implemented.

### 26.19.1 *set status* Constituent

A constituent of a phase can be suspended. Not yet implemented.

### 26.19.2 *set status* Element

An element can be ENTERED or SUSPENDED. If an element is suspended all species with this element is automatically suspended. If such a species is the single constituent of a phase that phase is also suspended.

Not yet implemented.

### 26.19.3 *set status* Phases

#### Phase name(s):

A phase can have one of 4 different status

- ENTERED, this is the default. The phase will be stable if that would give the most stable state for the current conditions. The user can give a tentative amount.
- SUSPENDED, the phase will not be included in any calculations.
- DORMANT, the phase will be included in the calculations but will not be allowed to become stable even if that would give the most stable equilibrium. In such a case the phase will have a positive driving force.

- **FIXED** means that it is a condition that the phase is stable with the specified amount. Note that for solution phases the composition is not known.

You can use a list of phase names or a wildcard for the phase name and the must give an equal sign, “=”, before the new status. You can also use the special “\*S” for all suspended phase, “\*D” for all dormant phases.

Changing the phase status does not affect anything except the phase itself. For a single phase you can use `SET PHASE ... STATUS <status>`.

Setting a stable phase as dormant or suspended and calculate the equilibrium will give you a metastable equilibrium.

Setting a phase status as **FIXED** means it is a condition that this phase should be stable. Setting the liquid fix with the amount zero is a quick way to calculate the melting temperature of a system if there is no condition on the T. For entered phases the amount is used as a start value.

**Amount:** /0/:

#### **26.19.4    *set status Species***

A species can be **ENTERED** or **SUSPENDED**. If a species is suspended all phases that have this as single constituent in a sublattice will be automatically suspended. Not yet implemented.

#### **26.20    *set initial\_T\_and\_P***

Local values of T and P can be set. These are not conditions but are used for commands like **CALCULATE PHASE ...**

#### **26.21    *set Units***

For each property the unit can be specified like Kelvin, Farenheit or Celsius for temperature. Not implemented yet.

#### **26.22    *set Variable coefficient***

One or more coefficients for optimization, A00 to A99, can be set as variable to be optimized against the selected experimental data.

A single variable index, 0 to 99, can be used with a start value provided. Or a range such as 15-19 which will set all nonzero variables A15 to A19 as variable.

#### **26.23    *set Verbose***

Not implemented yet.

## 26.24 *set* Weight

Intended for assessments. A weight is zero or a positive value. Equilibria with weight zero will be ignored in an optimization.

You can specify the current equilibrium or give an abbreviation that will set the weight of all equilibria with a name for which the abbreviation fits. Or you can give a range of equilibria by giving two numbers separated by a hyphen like 63-106.

If an abbreviation or a range is given the software will list how many equilibria that had the weight set to the new value.

## 27 Show

This command shows a value of a property, the property can be a state variable like T, G etc or a user defined symbol containing several state variable or a model parameter identifier (which must always have a phase specification) like the Curie temperature. The state variables can contain wildcards like X(FCC,\*) means all mole fractions of the FCC phase. Several properties can be specified on the same line, separated by a space character.

It is the same as the command *LIST state-variables*, see section subsection16.17

### 27.1 property:

The value of one or more properties or symbols can be shown:

```
--->OC5:show t g tc(bcc) mu(cr) cp
T= 1.2000000E+03
G= -5.9565761E+04
TC(BCC_A2)= 1.0272646E+03
MU(CR)= -7.2489667E+04
CP= 4.08487869E+01
```

## 28 Step

Requires that a single axis is set. If a second step command is given you have the choice of deleting or keeping the previous results.

There are 3 variants of the STEP command:

CONDITIONAL    NORMAL    QUIT    SEPARATE

### 28.1 *step* Conditional

A specified symbol is evaluated at each step. Can be used for Scheil-Gulliver solidification simulation when implemented.

## 28.2 *step* Normal

Calculates equilibria from the low axis limit to the high at each increment. The exact axis value for any phase changes is calculated.

## 28.3 *step* Quit

You did not want to *step*.

## 28.4 *step* Separate

This command calculates equilibria for each phase separately along the axis. It is typically used to separately calculate and plot together the Gibbs energy curves for a number of phases across a composition range.

### Delete previous results?

Any previous results from the STEP or MAP commands can be deleted or kept. If kept the previous results can be plotted together with the results from the new STEP command.

## 29 Summary

That's all and I hope enough (when all is implemented). Have fun and report all errors or problems providing a macro file and the necessary data.

## References

- [1] B Sundman, U R Kattner, M Palumbo and S G Fries, *OpenCalphad - a free thermodynamic software*, in Integrating Materials and Manufacturing Innovation, **4:1** (2015), open access
- [2] B Sundman, X-L Liu and H Ohtani, *The implementation of an algorithm to calculate thermodynamic equilibria for multi-component systems with non-ideal phases in a free software*, Computational Materials Science, **101** (2015) 127–137
- [3] B Sundman, U R Kattner, C Sigli, M Stratmann, R Le Tellier, M Palumbo and S G Fries, *The OpenCalphad thermodynamic software interface*, Comp Mat Sci, **125** (2016) 188–196
- [4] H L Lukas, S G Fries and B Sundman, *Computational Thermodynamics, the CALPHAD method*, Cambridge Univ Press 2007.
- [5] <https://www.math.utah.edu/software/minpack/minpack/lmdif.html>
- [6] <http://www.gnuplot.info/documentation.html>