

Module Interface Specification for Software Engineering

Team #1, Sanskrit Ciphers

Omar El Aref

Dylan Garner

Muhammad Umar Khan

Aswin Kuganesan

Yousef Shahin

January 21, 2026

1 Revision History

Date	Version	Notes
Nov. 13, 2025	1.0	Added Section 2: Symbols, Abbreviations and Acronyms.
Nov. 13, 2025	1.1	Added Section 3: Introduction.
Nov. 13, 2025	1.2	Added Section 4: Notation.
Nov. 13, 2025	1.3	Added Section 5: Module Decomposition.
Nov. 13, 2025	1.4	Added Sections 6–29: Module Interface Specifications for all modules.
Nov. 13, 2025	1.5	Added Reflection and References

2 Symbols, Abbreviations and Acronyms

The following symbols, abbreviations, and acronyms are used throughout this Module Interface Specification (MIS):

Project-Specific

- **SMFRP** — Sanskrit Manuscript Fragment Reconstruction Platform
- **SRS** — System Requirements Specification
- **MG** — Module Guide
- **MIS** — Module Interface Specification

Layer & Module Prefixes

- **HW** — Hardware-Hiding Level
- **UI** — User Interface Layer
- **Svc** — Service Layer
- **ML** — Machine Learning Layer
- **Data** — Data Management Layer
- **Util** — Utility / Software Decision Level

UI / Web Terms

- **DOM** — Document Object Model
- **UI** — User Interface
- **HTML** — HyperText Markup Language
- **API** — Application Programming Interface
- **URL** — Uniform Resource Locator

Data Types & Structures

- **ID** — Identifier (e.g., ImageID, FragmentID)
- **MB** — Megabyte
- **JSON** — JavaScript Object Notation
- **HTTP** — Hypertext Transfer Protocol
- **REST** — Representational State Transfer

Exceptions / Errors

- **UIRenderError** — User Interface Rendering Error
- **NetworkError** — Network Communication Error
- **ValidationError** — Input Validation Error
- **UploadError** — File Upload Failure
- **AuthError** — Authentication Error
- **NotFoundError** — Missing Resource
- **StorageWriteError** / **StorageReadError** — File I/O Problems

Machine Learning Terms

- **OCR** — Optical Character Recognition
- **ML** — Machine Learning

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Introduction	1
4	Notation	1
4.1	Primitive Data Types	2
4.2	Derived Data Types	2
4.3	Interface and Parameter Conventions	2
5	Module Decomposition	3
5.1	Module Hierarchy	3
5.2	Description of Levels	4
5.2.1	Hardware-Hiding Level	4
5.2.2	Behaviour-Hiding Level	4
5.2.3	Software Decision Level	4
6	MIS of HW.ImageStorage	5
6.1	Module	5
6.2	Uses	5
6.3	Syntax	5
6.3.1	Exported Constants	5
6.3.2	Exported Access Programs	5
6.4	Semantics	6
6.4.1	State Variables	6
6.4.2	Environment Variables	6
6.4.3	Assumptions	6
6.4.4	Access Routine Semantics	6
6.4.5	Local Functions	7
7	MIS of UI.Auth	7
7.1	Module	7
7.2	Uses	7
7.3	Syntax	7
7.3.1	Exported Constants	7
7.3.2	Exported Access Programs	7
7.4	Semantics	7
7.4.1	State Variables	7
7.4.2	Environment Variables	8
7.4.3	Assumptions	8
7.4.4	Access Routine Semantics	8

7.4.5	Local Functions	8
8	MIS of UI.Upload	8
8.1	Module	8
8.2	Uses	9
8.3	Syntax	9
8.3.1	Exported Constants	9
8.3.2	Exported Access Programs	9
8.4	Semantics	9
8.4.1	State Variables	9
8.4.2	Environment Variables	9
8.4.3	Assumptions	9
8.4.4	Access Routine Semantics	9
8.4.5	Local Functions	10
9	MIS of UI.Canvas	10
9.1	Module	10
9.2	Uses	10
9.3	Syntax	10
9.3.1	Exported Constants	10
9.3.2	Exported Access Programs	11
9.4	Semantics	11
9.4.1	State Variables	11
9.4.2	Environment Variables	11
9.4.3	Assumptions	11
9.4.4	Access Routine Semantics	11
9.4.5	Local Functions	12
10	MIS of UI.Search	12
10.1	Module	12
10.2	Uses	12
10.3	Syntax	13
10.3.1	Exported Constants	13
10.3.2	Exported Access Programs	13
10.4	Semantics	13
10.4.1	State Variables	13
10.4.2	Environment Variables	13
10.4.3	Assumptions	13
10.4.4	Access Routine Semantics	13
10.4.5	Local Functions	14

11 MIS of UI.SaveSession	14
11.1 Module	14
11.2 Uses	14
11.3 Syntax	15
11.3.1 Exported Constants	15
11.3.2 Exported Access Programs	15
11.4 Semantics	15
11.4.1 State Variables	15
11.4.2 Environment Variables	15
11.4.3 Assumptions	15
11.4.4 Access Routine Semantics	15
11.4.5 Local Functions	16
12 MIS of UI.LoadSession	16
12.1 Module	16
12.2 Uses	16
12.3 Syntax	16
12.3.1 Exported Constants	16
12.3.2 Exported Access Programs	17
12.4 Semantics	17
12.4.1 State Variables	17
12.4.2 Environment Variables	17
12.4.3 Assumptions	17
12.4.4 Access Routine Semantics	17
12.4.5 Local Functions	18
13 MIS of Svc.API	18
13.1 Module	18
13.2 Uses	18
13.3 Syntax	19
13.3.1 Exported Constants	19
13.3.2 Exported Access Programs	19
13.4 Semantics	19
13.4.1 State Variables	19
13.4.2 Environment Variables	19
13.4.3 Assumptions	19
13.4.4 Access Routine Semantics	20
13.4.5 Local Functions	20
14 MIS of Svc.AuthZ	21
14.1 Module	21
14.2 Uses	21
14.3 Syntax	21

14.3.1	Exported Constants	21
14.3.2	Exported Access Programs	21
14.4	Semantics	21
14.4.1	State Variables	21
14.4.2	Environment Variables	21
14.4.3	Assumptions	22
14.4.4	Access Routine Semantics	22
14.4.5	Local Functions	22
15	MIS of Svc.Session	22
15.1	Module	22
15.2	Uses	22
15.3	Syntax	23
15.3.1	Exported Constants	23
15.3.2	Exported Access Programs	23
15.4	Semantics	23
15.4.1	State Variables	23
15.4.2	Environment Variables	23
15.4.3	Assumptions	23
15.4.4	Access Routine Semantics	23
15.4.5	Local Functions	24
16	MIS of Svc.ProcOrch	24
16.1	Module	24
16.2	Uses	24
16.3	Syntax	24
16.3.1	Exported Constants	24
16.3.2	Exported Access Programs	24
16.4	Semantics	25
16.4.1	State Variables	25
16.4.2	Environment Variables	25
16.4.3	Assumptions	25
16.4.4	Access Routine Semantics	25
16.4.5	Local Functions	25
17	MIS of Svc.MatchOrch	25
17.1	Module	25
17.2	Uses	26
17.3	Syntax	26
17.3.1	Exported Constants	26
17.3.2	Exported Access Programs	26
17.4	Semantics	26
17.4.1	State Variables	26

17.4.2	Environment Variables	26
17.4.3	Assumptions	26
17.4.4	Access Routine Semantics	26
17.4.5	Local Functions	27
18	MIS of Svc.Search	27
18.1	Module	27
18.2	Uses	27
18.3	Syntax	27
18.3.1	Exported Constants	27
18.3.2	Exported Access Programs	27
18.4	Semantics	28
18.4.1	State Variables	28
18.4.2	Environment Variables	28
18.4.3	Assumptions	28
18.4.4	Access Routine Semantics	28
18.4.5	Local Functions	28
19	MIS of Data.FragmentStore	28
19.1	Module	28
19.2	Uses	28
19.3	Syntax	29
19.3.1	Exported Constants	29
19.3.2	Exported Access Programs	29
19.4	Semantics	29
19.4.1	State Variables	29
19.4.2	Environment Variables	29
19.4.3	Assumptions	29
19.4.4	Access Routine Semantics	29
19.4.5	Local Functions	30
20	MIS of Data.Catalog	30
20.1	Module	30
20.2	Uses	30
20.3	Syntax	30
20.3.1	Exported Constants	30
20.3.2	Exported Access Programs	31
20.4	Semantics	31
20.4.1	State Variables	31
20.4.2	Environment Variables	31
20.4.3	Assumptions	31
20.4.4	Access Routine Semantics	31
20.4.5	Local Functions	32

21 MIS of Data.User	32
21.1 Module	32
21.2 Uses	32
21.3 Syntax	32
21.3.1 Exported Constants	32
21.3.2 Exported Access Programs	32
21.4 Semantics	32
21.4.1 State Variables	32
21.4.2 Environment Variables	32
21.4.3 Assumptions	33
21.4.4 Access Routine Semantics	33
21.4.5 Local Functions	33
22 MIS of Data.Project	33
22.1 Module	33
22.2 Uses	34
22.3 Syntax	34
22.3.1 Exported Constants	34
22.3.2 Exported Access Programs	34
22.4 Semantics	34
22.4.1 State Variables	34
22.4.2 Environment Variables	34
22.4.3 Assumptions	34
22.4.4 Access Routine Semantics	34
22.4.5 Local Functions	35
23 MIS of ML.EdgeMatch	35
23.1 Module	35
23.2 Uses	35
23.3 Syntax	35
23.3.1 Exported Constants	35
23.3.2 Exported Access Programs	36
23.4 Semantics	36
23.4.1 State Variables	36
23.4.2 Environment Variables	36
23.4.3 Assumptions	36
23.4.4 Access Routine Semantics	36
23.4.5 Local Functions	36
24 MIS of ML.ScriptClass	37
24.1 Module	37
24.2 Uses	37
24.3 Syntax	37

24.3.1	Exported Constants	37
24.3.2	Exported Access Programs	37
24.4	Semantics	37
24.4.1	State Variables	37
24.4.2	Environment Variables	37
24.4.3	Assumptions	37
24.4.4	Access Routine Semantics	37
24.4.5	Local Functions	38
25	MIS of ML.TextSim	38
25.1	Module	38
25.2	Uses	38
25.3	Syntax	38
25.3.1	Exported Constants	38
25.3.2	Exported Access Programs	38
25.4	Semantics	38
25.4.1	State Variables	38
25.4.2	Environment Variables	38
25.4.3	Assumptions	38
25.4.4	Access Routine Semantics	39
25.4.5	Local Functions	39
26	MIS of ML.Segmentation	39
26.1	Module	39
26.2	Uses	39
26.3	Syntax	39
26.3.1	Exported Constants	39
26.3.2	Exported Access Programs	40
26.4	Semantics	40
26.4.1	State Variables	40
26.4.2	Environment Variables	40
26.4.3	Assumptions	40
26.4.4	Access Routine Semantics	40
26.4.5	Local Functions	41
27	MIS of ML.CircleRecognition	41
27.1	Module	41
27.2	Uses	41
27.3	Syntax	41
27.3.1	Exported Constants	41
27.3.2	Exported Access Programs	41
27.4	Semantics	41
27.4.1	State Variables	41

27.4.2	Environment Variables	41
27.4.3	Assumptions	42
27.4.4	Access Routine Semantics	42
27.4.5	Local Functions	42
28	MIS of ML.LineCount	42
28.1	Module	42
28.2	Uses	42
28.3	Syntax	42
28.3.1	Exported Constants	42
28.3.2	Exported Access Programs	43
28.4	Semantics	43
28.4.1	State Variables	43
28.4.2	Environment Variables	43
28.4.3	Assumptions	43
28.4.4	Access Routine Semantics	43
28.4.5	Local Functions	43
29	MIS of ML.EdgeClassification	44
29.1	Module	44
29.2	Uses	44
29.3	Syntax	44
29.3.1	Exported Constants	44
29.3.2	Exported Access Programs	44
29.4	Semantics	44
29.4.1	State Variables	44
29.4.2	Environment Variables	44
29.4.3	Assumptions	45
29.4.4	Access Routine Semantics	45
29.4.5	Local Functions	45
30	MIS of Util.Error	45
30.1	Module	45
30.2	Uses	45
30.3	Syntax	45
30.3.1	Exported Constants	45
30.3.2	Exported Access Programs	46
30.4	Semantics	46
30.4.1	State Variables	46
30.4.2	Environment Variables	46
30.4.3	Assumptions	46
30.4.4	Access Routine Semantics	46

31 MIS of Util.Logging	46
31.1 Module	46
31.2 Uses	47
31.3 Syntax	47
31.3.1 Exported Constants	47
31.3.2 Exported Access Programs	47
31.4 Semantics	47
31.4.1 State Variables	47
31.4.2 Environment Variables	47
31.4.3 Assumptions	47
31.4.4 Access Routine Semantics	47
32 MIS of Util.Config	48
32.1 Module	48
32.2 Uses	48
32.3 Syntax	48
32.3.1 Exported Constants	48
32.3.2 Exported Access Programs	48
32.4 Semantics	48
32.4.1 State Variables	48
32.4.2 Environment Variables	48
32.4.3 Assumptions	49
32.4.4 Access Routine Semantics	49
33 MIS of Util.TestStub	49
33.1 Module	49
33.2 Uses	49
33.3 Syntax	49
33.3.1 Exported Constants	49
33.3.2 Exported Access Programs	49
33.4 Semantics	50
33.4.1 State Variables	50
33.4.2 Environment Variables	50
33.4.3 Assumptions	50
33.4.4 Access Routine Semantics	50
33.4.5 Local Functions	50

List of Tables

1	Primitive Data Types	2
2	Module Hierarchy	4
3	HW.ImageStorage - Exported Access Programs	5
4	UI.Auth - Exported Access Programs	7
5	UI.Upload - Exported Access Programs	9
6	UI.Canvas - Exported Access Programs	11
7	UI.Search - Exported Access Programs	13
8	UI.SaveSession - Exported Access Programs	15
9	UI.LoadSession - Exported Access Programs	17
10	Svc.API - Exported Access Programs	19
11	Svc.AuthZ - Exported Access Programs	21
12	Svc.Session - Exported Access Programs	23
13	Svc.ProcOrch - Exported Access Programs	24
14	Svc.MatchOrch - Exported Access Programs	26
15	Svc.Search - Exported Access Programs	27
16	Data.FragmentStore - Exported Access Programs	29
17	Data.Catalog - Exported Access Programs	31
18	Data.User - Exported Access Programs	32
19	Data.Project - Exported Access Programs	34
20	ML.EdgeMatch - Exported Access Programs	36
21	ML.ScriptClass - Exported Access Programs	37
22	ML.TextSim - Exported Access Programs	38
23	ML.Segmentation - Exported Access Programs	40
24	ML.CircleRecognition - Exported Access Programs	41
25	ML.LineCount - Exported Access Programs	43
26	ML.EdgeClassification - Exported Access Programs	44
27	Util.Error - Exported Access Programs	46
28	Util.Logging - Exported Access Programs	47
29	Util.Config - Exported Access Programs	48
30	Util.TestStub - Exported Access Programs	49

3 Introduction

The following document details the Module Interface Specifications (MIS) for the Sanskrit Manuscript Fragment Reconstruction Platform (SMFRP). This system supports researchers and scholars in reconstructing fragmented Sanskrit manuscripts by providing a unified digital workspace that integrates fragment management, intelligent matching, and image-based reconstruction tools.

The MIS defines the external behavior and interfaces for each software module in the system. Each module is specified in terms of its responsibilities, provided services, hidden state (secrets), environment variables, and exported access programs. These specifications are written at the right level of abstraction, focusing on logical interfaces and responsibilities rather than low-level implementation details such as programming language syntax or data structures.

This document ensures that the system achieves consistency, and minimal coupling across modules. The defined interfaces promote high cohesion, and generality, enabling independent development, verification, and maintenance of each module.

Complementary Documents

- **System Requirements Specification (SRS)** – Defines the system’s functional and non-functional requirements. The SRS ([Ciphers, 2025b](#)) can be accessed at: [SRS](#)
- **Module Guide (MG)** – Outlines the overall software architecture, module decomposition, and dependency hierarchy.

Repository

The full project documentation and implementation can be found in the team’s [GitHub repository](#)

4 Notation

In this section, we define the notation used throughout the Module Interface Specification. The purpose of this notation is to describe, in a clear and consistent manner, what each module provides and requires, without referencing any specific programming language or implementation detail.

Each module in this MIS is described in terms of:

- **State Variables** – The module’s internal data that is not visible externally.
- **Environment Variables** – Data received from or affecting the external environment (e.g., databases, file storage, APIs).

- **Exported Constants and Access Programs** – The operations, services, or functions the module provides to other modules.

This approach focuses on interface behavior, not implementation syntax (such as JSON or Python code), ensuring that the interfaces remain consistent.

4.1 Primitive Data Types

Table 1: Primitive Data Types

Data Type	Notation	Description
Character	<code>char</code>	A single symbol or letter.
Integer	<code>int</code>	Whole numbers with no fractional part.
Real	<code>float</code>	Numbers with decimal or fractional parts.
Boolean	<code>bool</code>	Represents logical truth values (true or false).

4.2 Derived Data Types

In addition to the primitive types above, the system specification also makes use of the following derived or composite types:

- **Sequence:** An ordered collection of elements of the same data type. Example: A list of fragment identifiers or saved user sessions.
- **String:** A sequence of characters, typically used for textual input, labels, or metadata fields.
- **Tuple:** An ordered collection of values that may be of different data types. Commonly used to represent grouped entities such as (`FragmentId`, `ConfidenceScore`) or (`x`, `y`, `width`, `height`).
- **Record / Object:** A structured type that groups named fields with defined data types, such as `{id: FragmentId, script: String, confidence: Float}`.
- **Function:** A mapping defined by the types of its inputs and outputs. Functions are specified by their type signatures (inputs/outputs) and behavior (preconditions, postconditions, and effects).

4.3 Interface and Parameter Conventions

This section explains how interfaces and operations are written in the MIS. The goal is to make them easy to read and understand while staying general enough to apply to any implementation.

- **Inputs and Outputs:** Labeled as `in:` and `out:` in operation definitions. Example: `search(in: SearchQuery, out: SearchResult)`
- **Operation Format:** `functionName(in: InputType, out: OutputType) → may throw ErrorType`
- **Module Naming Convention:** Each module name follows the format `Layer.Module`, for example: `UI.Canvas`, `Svc.MatchOrch`, or `Data.FragmentStore`.
- **Boolean Conditions:** Represented using logical symbols such as \wedge (and), \vee (or), \neg (not), and \implies (implies).

5 Module Decomposition

The following section summarizes the module hierarchy for the *Sanskrit Manuscript Fragment Reconstruction Platform*. It is consistent with the **Module Guide (MG)** for this project and represents how the system has been decomposed into modules at different abstraction levels.

Each level in the hierarchy captures a different design concern:

- **Hardware-Hiding Level:** Interfaces directly with the system's physical or platform-dependent resources.
- **Behaviour-Hiding Level:** Encapsulates the main functional behavior of the system, implementing the use cases described in the SRS.
- **Software Decision Level:** Contains lower-level utility modules and software decisions that simplify implementation but are not visible to the user.

5.1 Module Hierarchy

Table 2: Module Hierarchy

Level 1	Level 2 Modules
Hardware-Hiding (HW)	Image Storage Interface
Behaviour-Hiding	User Interface (UI): <code>UI.Canvas</code> , <code>UI.Search</code> , <code>UI.Auth</code> , <code>UI.Upload</code> , <code>UI.SaveSession</code> , <code>UI.LoadSession</code> Service Layer (Svc): <code>Svc.API</code> , <code>Svc.Search</code> , <code>Svc.AuthZ</code> , <code>Svc.Session</code> , <code>Svc.ProcOrch</code> , <code>Svc.MatchOrch</code> Data Management (Data): <code>Data.FragmentStore</code> , <code>Data.Catalog</code> , <code>Data.User</code> , <code>Data.Project</code> Machine Learning Modules (ML): <code>ML.EdgeMatch</code> , <code>ML.ScriptClass</code> , <code>ML.TextSim</code> , <code>ML.Segmentation</code> , <code>ML.CircleRecognition</code> , <code>ML.LineCount</code> , <code>ML.EdgeClassification</code>
Software Decision	Utility and Support Modules (Error Handling, Logging, Configuration Management, Test Stubs)

5.2 Description of Levels

5.2.1 Hardware-Hiding Level

This level hides all hardware and platform dependencies from the rest of the system. It includes interfaces that communicate with the file storage system, image repositories, and cloud infrastructure. These components provide a uniform interface for accessing images and metadata regardless of the underlying storage medium.

5.2.2 Behaviour-Hiding Level

This level defines the functional behavior of the system, implementing the requirements outlined in the SRS. It includes the user-facing modules (UI), the application logic (Service Layer), data persistence (Data Layer), and intelligent processing (ML Layer). These modules interact through clearly defined service interfaces, promoting modularity and separation of concerns.

5.2.3 Software Decision Level

This level includes supporting components that are primarily design decisions rather than functional necessities. These modules include configuration handlers, utility libraries, and testing or logging frameworks that support development, debugging, and maintenance.

6 MIS of HW.ImageStorage

6.1 Module

HW.ImageStorage (Image Storage Interface)

This module provides a uniform interface for reading, writing, and managing manuscript fragment image files and related metadata in the underlying file system or cloud storage. It hides all platform-specific file operations from higher-level modules and ensures consistent access and naming conventions.

6.2 Uses

- `Data.FragmentStore` – for linking stored image references to fragment metadata records.
- `Svc.ProcOrch` – for initiating preprocessing or orientation correction workflows once an image is stored.
- External file system or object storage API.

6.3 Syntax

6.3.1 Exported Constants

- `MAX_FILE_SIZE` = 50MB
- `SUPPORTED_FORMATS` = `{.jpg, .png, .tiff}`
- `STORAGE_PATH` = `"/images/"`

6.3.2 Exported Access Programs

Table 3: HW.ImageStorage - Exported Access Programs

Name	In	Out	Exceptions
<code>storeImage</code>	<code>file: ImageFile,</code> <code>metadata: Record</code>	<code>ImageID</code>	<code>InvalidFormatError,</code> <code>StorageWriteError</code>
<code>retrieveImage</code>	<code>id: ImageID</code>	<code>ImageFile</code>	<code>NotFoundError,</code> <code>StorageReadError</code>
<code>deleteImage</code>	<code>id: ImageID</code>	<code>bool</code>	<code>NotFoundError,</code> <code>StorageWriteError</code>
<code>getMetadata</code>	<code>id: ImageID</code>	<code>Record</code>	<code>NotFoundError</code>

6.4 Semantics

6.4.1 State Variables

- `storageIndex`: `Map[ImageID, FilePath]`
- `metadataCache`: `Map[ImageID, Record]`

6.4.2 Environment Variables

- `FileSystem` / `CloudStorage` – external persistence for image binaries

6.4.3 Assumptions

- The underlying storage service guarantees atomic read/write operations.
- ImageIDs are globally unique.

6.4.4 Access Routine Semantics

`storeImage(file, metadata)`:

- transition: file is written to storage; `storageIndex` and `metadataCache` updated with new entry.
- output: a newly generated `ImageID`.
- exception: `InvalidFormatError` if file type not in `SUPPORTED_FORMATS`; `StorageWriteError` if write fails.

`retrieveImage(id)`:

- output: image file associated with `id`.
- exception: `NotFoundError` if `id` absent from `storageIndex`; `StorageReadError` if read fails.

`deleteImage(id)`:

- transition: remove image file from storage; delete entries from `storageIndex` and `metadataCache`.
- output: `true` if deletion successful.
- exception: `NotFoundError` if `id` not present; `StorageWriteError` if deletion fails.

`getMetadata(id)`:

- output: metadata record associated with `id`.
- exception: `NotFoundError` if no record exists.

6.4.5 Local Functions

- `generateImageID(file: ImageFile): ImageID`
- `validateFormat(file: ImageFile): bool`

7 MIS of UI.Auth

7.1 Module

UI.Auth (Authentication Interface)

This module provides the browser-facing login and logout experience. It collects user credentials, displays relevant error messages, and forwards authentication requests to the backend service. It does not perform authentication logic itself.

7.2 Uses

- `Svc.AuthZ` – for validating credentials and issuing session tokens.
- `Svc.Session` – for managing client-side session lifecycle.

7.3 Syntax

7.3.1 Exported Constants

- `MAX_LOGIN_ATTEMPTS = 5`

7.3.2 Exported Access Programs

Table 4: UI.Auth - Exported Access Programs

Name	In	Out	Exceptions
<code>renderLoginForm</code>	<code>none</code>	<code>none</code>	<code>UIRenderError</code>
<code>submitCredentials</code>	<code>creds: UserCredentials</code>	<code>AuthResult</code>	<code>AuthError</code> , <code>NetworkError</code> , <code>InboxOverflowError</code>
<code>logoutUser</code>	<code>none</code>	<code>bool</code>	<code>NetworkError</code>

7.4 Semantics

7.4.1 State Variables

- `loginAttempts: int` – count of consecutive failed attempts in current session.
- `authErrorMessage: String` – message shown on failed login.

7.4.2 Environment Variables

- Browser window and Document Object Model(DOM).

7.4.3 Assumptions

- Network connectivity is available for requests to `Svc.AuthZ`.
- Password input is masked and handled securely by the browser.

7.4.4 Access Routine Semantics

`renderLoginForm()`:

- transition: updates DOM to show login form, clears previous error message.
- output: none.
- exception: `UIRenderError` if DOM cannot be updated.

`submitCredentials(creds)`:

- transition: sends credentials to `Svc.AuthZ`; updates `loginAttempts` and `authErrorMessage` based on response.
- output: `AuthResult` indicating success or failure.
- exception: `AuthError` if credentials rejected; `NetworkError` if backend unreachable.

`logoutUser()`:

- transition: clears client-side session state and redirects to login view.
- output: `true` if logout succeeds.
- exception: `NetworkError` if logout call to backend fails.

7.4.5 Local Functions

- `displayError(msg: String)` – updates UI error region.
- `resetForm()` – clears form fields.

8 MIS of UI.Upload

8.1 Module

UI.Upload (Fragment Upload Interface)

This module allows users to select, preview, and submit manuscript fragment images for processing. It performs basic client-side validation and delegates storage and preprocessing to backend services.

8.2 Uses

- `Svc.API` – for upload endpoints.
- `HW.ImageStorage` – indirectly, via backend, for persistent image storage.

8.3 Syntax

8.3.1 Exported Constants

- `MAX_FILES_PER_UPLOAD = 20`

8.3.2 Exported Access Programs

Table 5: `UI.Upload` - Exported Access Programs

Name	In	Out	Exceptions
<code>renderUploadPanel</code>	<code>none</code>	<code>none</code>	<code>UIRenderError</code>
<code>selectFiles</code>	<code>files:</code> <code>Sequence[ImageFile]</code>	<code>none</code>	<code>ValidationError</code>
<code>submitUpload</code>	<code>none</code>	<code>UploadResult</code>	<code>NetworkError</code> , <code>UploadError</code>

8.4 Semantics

8.4.1 State Variables

- `pendingFiles:` `Sequence[ImageFile]`
- `uploadErrorMessage:` `String`

8.4.2 Environment Variables

- Browser file picker and local file system access (sandboxed).

8.4.3 Assumptions

- The browser enforces configured file size constraints on selection when possible.

8.4.4 Access Routine Semantics

`renderUploadPanel()`:

- `transition`: renders the upload panel, including file input control and status indicators.
- `output`: `none`.

- exception: `UIRenderError` if DOM cannot be updated.

`selectFiles(files):`

- transition: validates file count and basic properties; if valid, stores them in `pendingFiles`.
- output: none.
- exception: `ValidationError` if any file exceeds size or format constraints.

`submitUpload():`

- transition: sends `pendingFiles` to backend via `Svc.API`; clears `pendingFiles` on success.
- output: `UploadResult` containing list of created fragment IDs.
- exception: `NetworkError` if request fails; `UploadError` if backend rejects the upload.

8.4.5 Local Functions

- `validateFiles(files)` – checks count, format, and size bounds.
- `previewThumbnails()` – generates and displays thumbnails for selected files.

9 MIS of UI.Canvas

9.1 Module

UI.Canvas (Interactive Fragment Workspace)

This module provides the interactive canvas where scholars can view, move, rotate, and arrange multiple fragments simultaneously. It displays match suggestions and visual overlays for edges, damage patterns, or text regions.

9.2 Uses

- `Svc.MatchOrch` – for requesting match suggestions.
- `Svc.Session` – for loading and saving canvas layouts.
- `Svc.API` – for fetching fragment images and overlays.

9.3 Syntax

9.3.1 Exported Constants

- `MAX_FRAGMENTS_ON_CANVAS = 50`

9.3.2 Exported Access Programs

Table 6: UI.Canvas - Exported Access Programs

Name	In	Out	Exceptions
renderCanvas	state: CanvasState	none	UIRenderError
placeFragment	id: FragmentID, position: Tuple	none	LayoutError
rotateFragment	id: FragmentID, angle: float	none	LayoutError
requestMatches	id: FragmentID	none	NetworkError
saveLayout	none	LayoutID	NetworkError

9.4 Semantics

9.4.1 State Variables

- `currentState`: CanvasState – positions, rotations, and visibility for fragments.
- `selectedFragment`: FragmentID or null
- `activeMatchOverlay`: MatchResultList

9.4.2 Environment Variables

- Browser rendering surface (HTML canvas or equivalent).

9.4.3 Assumptions

- Device supports required rendering capabilities for zoom and pan.

9.4.4 Access Routine Semantics

`renderCanvas(state)`:

- transition: updates the visual layout to match `state`.
- output: none.
- exception: `UIRenderError` if rendering fails.

`placeFragment(id, position)`:

- transition: updates `currentState` with new position for `id`.
- output: none.

- exception: `LayoutError` if fragment exceeds bounds or limit exceeded.

`rotateFragment(id, angle):`

- transition: updates rotation of `id` in `currentState`.
- output: none.
- exception: `LayoutError` if rotation cannot be applied.

`requestMatches(id):`

- transition: sends match request to `Svc.MatchOrch`; updates `activeMatchOverlay` when response is received.
- output: none.
- exception: `NetworkError` if request fails.

`saveLayout():`

- transition: persists `currentState` via `Svc.Session`.
- output: a `LayoutID` for later retrieval.
- exception: `NetworkError` if persistence fails.

9.4.5 Local Functions

- `snapToEdges(id)` – adjusts position so nearby edges align visually.
- `highlightMatches(id)` – visually emphasizes suggested neighbors.

10 MIS of UI.Search

10.1 Module

UI.Search (Database Search and Exploration Interface)

This module provides the interface for querying the fragment database, filtering results, and viewing metadata. It supports search by script type, line count, fragment size, and other criteria.

10.2 Uses

- `Svc.Search` – for executing search queries.
- `Svc.API` – for retrieving fragment summaries and export payloads.

10.3 Syntax

10.3.1 Exported Constants

- `RESULTS_PAGE_SIZE = 25`

10.3.2 Exported Access Programs

Table 7: UI.Search - Exported Access Programs

Name	In	Out	Exceptions
<code>renderSearchPanel</code>	<code>none</code>	<code>none</code>	<code>UIRenderError</code>
<code>submitQuery</code>	<code>q: SearchQuery</code>	<code>none</code>	<code>ValidationError</code> , <code>NetworkError</code>
<code>nextPage</code>	<code>none</code>	<code>none</code>	<code>NetworkError</code>
<code>exportResults</code>	<code>format: ExportFormat</code>	<code>none</code>	<code>NetworkError</code> , <code>ExportError</code>

10.4 Semantics

10.4.1 State Variables

- `currentQuery: SearchQuery`
- `currentPage: int`
- `results: SearchResultPage`

10.4.2 Environment Variables

- Browser viewport for displaying tables and filters.

10.4.3 Assumptions

- Backend search service responds within acceptable time bounds defined in the SRS.

10.4.4 Access Routine Semantics

`renderSearchPanel()`:

- `transition`: displays search form, filters, and an empty or last-used results view.
- `output`: `none`.
- `exception`: `UIRenderError` if rendering fails.

`submitQuery(q):`

- transition: validates query parameters; if valid, sends query to `Svc.Search` and updates `results` and `currentPage`.
- output: none.
- exception: `ValidationError` if query malformed; `NetworkError` if backend unreachable.

`nextPage():`

- transition: increments `currentPage` and requests next result page.
- output: none.
- exception: `NetworkError` if request fails.

`exportResults(format):`

- transition: sends export request for current query to backend.
- output: none at UI level; triggers file download in browser.
- exception: `NetworkError` if backend unreachable; `ExportError` if export fails.

10.4.5 Local Functions

- `renderResultsTable(results)` – updates DOM table from latest `SearchResultPage`.
- `validateSearchQuery(q)` – checks filter ranges and required fields.

11 MIS of UI.SaveSession

11.1 Module

UI.SaveSession (Session Save Interface)

This module provides the user interface for saving the current workspace state, including fragment arrangements, annotations, and reconstruction progress. It allows users to name and persist their work for later retrieval.

11.2 Uses

- `Svc.Session` – for persisting session data to backend storage.
- `UI.Canvas` – for retrieving current canvas state.

11.3 Syntax

11.3.1 Exported Constants

- `MAX_SESSION_NAME_LENGTH = 100`

11.3.2 Exported Access Programs

Table 8: UI.SaveSession - Exported Access Programs

Name	In	Out	Exceptions
<code>renderSaveDialog</code>	<code>none</code>	<code>none</code>	<code>UIRenderError</code>
<code>saveCurrentSession</code>	<code>name: String</code>	<code>SessionID</code>	<code>ValidationError</code> , <code>NetworkError</code>
<code>validateSessionName</code>	<code>name: String</code>	<code>bool</code>	<code>ValidationError</code>

11.4 Semantics

11.4.1 State Variables

- `sessionName: String`
- `saveInProgress: bool`
- `lastSavedID: SessionID or null`

11.4.2 Environment Variables

- Browser DOM for dialog rendering.

11.4.3 Assumptions

- User is authenticated and has valid session context.
- Canvas state is available and valid at time of save.

11.4.4 Access Routine Semantics

`renderSaveDialog()`:

- transition: displays modal dialog with input field for session name and save button.
- output: none.
- exception: `UIRenderError` if dialog cannot be rendered.

`saveCurrentSession(name)`:

- transition: validates session name; captures current canvas state from `UI.Canvas`; sends save request to `Svc.Session`; updates `lastSavedID` on success.
- output: `SessionID` assigned by backend.
- exception: `ValidationError` if name invalid; `NetworkError` if save fails.

`validateSessionName(name):`

- output: `true` if name meets length and character requirements.
- exception: `ValidationError` if name invalid.

11.4.5 Local Functions

- `showSuccessMessage(id)` – displays confirmation with session ID.
- `closeDialog()` – closes save dialog and clears state.

12 MIS of `UI.LoadSession`

12.1 Module

`UI.LoadSession` (Session Load Interface)

This module provides the user interface for browsing, selecting, and loading previously saved workspace sessions. It displays session metadata and allows users to restore their reconstruction work.

12.2 Uses

- `Svc.Session` – for retrieving available sessions and loading session data.
- `UI.Canvas` – for applying loaded state to the canvas.

12.3 Syntax

12.3.1 Exported Constants

- `SESSIONS_PAGE_SIZE = 10`

12.3.2 Exported Access Programs

Table 9: UI.LoadSession - Exported Access Programs

Name	In	Out	Exceptions
renderLoadDialog	none	none	UIRenderError
fetchSessionList	none	SessionList	NetworkError
loadSession	id: SessionID	none	NotFoundError, NetworkError
deleteSession	id: SessionID	bool	NetworkError

12.4 Semantics

12.4.1 State Variables

- `availableSessions`: SessionList
- `selectedSessionID`: SessionID or null
- `loadInProgress`: bool

12.4.2 Environment Variables

- Browser DOM for dialog rendering and session list display.

12.4.3 Assumptions

- User is authenticated and has valid session context.
- Session data retrieved from backend is valid and compatible with current system version.

12.4.4 Access Routine Semantics

`renderLoadDialog()`:

- transition: displays modal dialog with list of saved sessions and load button.
- output: none.
- exception: `UIRenderError` if dialog cannot be rendered.

`fetchSessionList()`:

- transition: requests list of available sessions from `Svc.Session`; updates `availableSessions`.
- output: `SessionList` containing session metadata (ID, name, date, preview).

- exception: `NetworkError` if request fails.

`loadSession(id):`

- transition: retrieves session data from `Svc.Session`; applies state to `UI.Canvas`; closes load dialog.
- output: none.
- exception: `NotFoundError` if session does not exist; `NetworkError` if retrieval fails.

`deleteSession(id):`

- transition: sends delete request to `Svc.Session`; removes session from `availableSessions` on success.
- output: `true` if deletion successful.
- exception: `NetworkError` if deletion fails.

12.4.5 Local Functions

- `renderSessionList()` – updates DOM with session list.
- `confirmDelete(id)` – shows confirmation dialog before deletion.
- `closeDialog()` – closes load dialog and clears state.

13 MIS of Svc.API

13.1 Module

Svc.API (Backend API Gateway)

This module exposes the backend functionality of the Sanskrit Manuscript Fragment Reconstruction Platform as a REST-style service layer. It routes incoming HTTP requests from the UI to the corresponding internal services, enforces basic request validation, and standardizes API responses.

13.2 Uses

- `Svc.AuthZ` – for authentication and authorization checks.
- `Svc.Session` – for resolving current user/session context.
- `Svc.ProcOrch` – for preprocessing and normalization requests.
- `Svc.MatchOrch` – for fragment match discovery.
- `Svc.Search` – for database search and exploration.
- `Data.FragmentStore`, `Data.User`, `Data.Project`.

13.3 Syntax

13.3.1 Exported Constants

- `API_VERSION` = "v1"
- `MAX_REQUEST_SIZE` – logical upper bound on payload size (aligned with SRS).

13.3.2 Exported Access Programs

Table 10: Svc.API - Exported Access Programs

Name	In	Out	Exceptions
<code>handleAuthRequest</code>	<code>req:</code> <code>HttpRequest</code>	<code>HttpResponse</code>	<code>AuthError</code>
<code>handleUploadRequest</code>	<code>req:</code> <code>HttpRequest</code>	<code>HttpResponse</code>	<code>ValidationError</code> , <code>ServiceError</code>
<code>handleMatchRequest</code>	<code>req:</code> <code>HttpRequest</code>	<code>HttpResponse</code>	<code>ServiceError</code>
<code>handleSearchRequest</code>	<code>req:</code> <code>HttpRequest</code>	<code>HttpResponse</code>	<code>ValidationError</code> , <code>ServiceError</code>
<code>handleSessionRequest</code>	<code>req:</code> <code>HttpRequest</code>	<code>HttpResponse</code>	<code>ServiceError</code>

13.4 Semantics

13.4.1 State Variables

- `routeTable`: `Map[Endpoint, Handler]` – mapping between URL paths and internal handlers.

13.4.2 Environment Variables

- HTTP server environment providing incoming requests and outgoing responses.

13.4.3 Assumptions

- All requests include sufficient information to resolve user/session context when required.
- Lower-level services enforce their own invariants in addition to basic checks at this layer.

13.4.4 Access Routine Semantics

`handleAuthRequest(req):`

- transition: forwards credentials/token to `Svc.AuthZ`; logs outcome.
- output: `HttpResponse` with status code and (if successful) session token or user info.
- exception: `AuthError` if authentication fails or token invalid.

`handleUploadRequest(req):`

- transition: validates payload size and type; forwards work to `Svc.ProcOrch` for ingestion.
- output: `HttpResponse` including created fragment IDs or error details.
- exception: `ValidationError` if request violates constraints; `ServiceError` if downstream failure occurs.

`handleMatchRequest(req):`

- transition: parses fragment identifier and forwards to `Svc.MatchOrch`.
- output: `HttpResponse` containing ranked match suggestions.
- exception: `ServiceError` if orchestrator fails or times out.

`handleSearchRequest(req):`

- transition: validates search query parameters; forwards to `Svc.Search`.
- output: `HttpResponse` containing search results page.
- exception: `ValidationError` for malformed queries; `ServiceError` on backend failures.

`handleSessionRequest(req):`

- transition: routes session save/load actions to `Svc.Session`.
- output: `HttpResponse` with session payload or confirmation.
- exception: `ServiceError` if the session operation fails.

13.4.5 Local Functions

- `parseJSONBody(req)` – extracts and validates JSON payload.
- `buildErrorResponse(code, msg)` – standardizes error responses.

14 MIS of Svc.AuthZ

14.1 Module

Svc.AuthZ (Authentication and Authorization Service)

This module validates user credentials, issues and verifies session tokens, and enforces access control for protected operations.

14.2 Uses

- `Data.User` – for user credentials and role lookup.
- Cryptographic utilities (hashing, token signing).

14.3 Syntax

14.3.1 Exported Constants

- `TOKEN_TTL_MINUTES` – session token lifetime.
- `MAX_FAILED_ATTEMPTS` – lockout threshold.

14.3.2 Exported Access Programs

Table 11: Svc.AuthZ - Exported Access Programs

Name	In	Out	Exceptions
<code>authenticate</code>	<code>creds: UserCredentials</code>	<code>AuthResult</code>	<code>AuthError</code>
<code>validateToken</code>	<code>token: String</code>	<code>UserContext</code>	<code>AuthError</code>
<code>checkAccess</code>	<code>ctx: UserContext,</code> <code>action: String</code>	<code>bool</code>	<code>AuthError</code>

14.4 Semantics

14.4.1 State Variables

- `failedAttempts: Map[UserID, int]`

14.4.2 Environment Variables

- Secure storage for password hashes and secret keys.

14.4.3 Assumptions

- Passwords are stored as salted hashes only.
- Time and randomness sources are trustworthy for token generation.

14.4.4 Access Routine Semantics

`authenticate(creds):`

- `transition`: verifies credentials against stored hash; updates `failedAttempts`.
- `output`: `AuthResult` containing success flag and token on success.
- `exception`: `AuthError` if user locked out or credentials invalid.

`validateToken(token):`

- `output`: `UserContext` if token valid and not expired.
- `exception`: `AuthError` if token invalid or expired.

`checkAccess(ctx, action):`

- `output`: `true` if user role in `ctx` is allowed to perform `action`.
- `exception`: `AuthError` if context invalid.

14.4.5 Local Functions

- `hashPassword(pw)` – hashes password for comparison.
- `generateToken(user)` – constructs signed token.

15 MIS of Svc.Session

15.1 Module

Svc.Session (Session and Workspace Management Service)

This module manages user sessions, saved canvas layouts, and ongoing reconstruction projects. It provides persistent storage and retrieval of user workspace state.

15.2 Uses

- `Data.Project` – for project-level data and references.
- `Data.User` – for associating sessions with users.

15.3 Syntax

15.3.1 Exported Constants

- `MAX_SAVED_LAYOUTS_PER_USER`

15.3.2 Exported Access Programs

Table 12: `Svc.Session` - Exported Access Programs

Name	In	Out	Exceptions
<code>saveCanvasState</code>	<code>ctx:</code> <code>UserContext</code> , <code>state:</code> <code>CanvasState</code>	<code>LayoutID</code>	<code>SessionError</code>
<code>loadCanvasState</code>	<code>ctx:</code> <code>UserContext</code> , <code>id:</code> <code>LayoutID</code>	<code>CanvasState</code>	<code>NotFoundError</code> , <code>SessionError</code>
<code>listLayouts</code>	<code>ctx:</code> <code>UserContext</code>	<code>Sequence[LayoutSummary]</code>	<code>SessionError</code>

15.4 Semantics

15.4.1 State Variables

- `layoutStore`: `Map[LayoutID, (UserID, CanvasState)]`

15.4.2 Environment Variables

- Persistent database for layouts and project metadata.

15.4.3 Assumptions

- `UserContext` is valid and has been authenticated by `Svc.AuthZ`.

15.4.4 Access Routine Semantics

`saveCanvasState(ctx, state):`

- `transition`: creates or updates an entry in `layoutStore` for the user.
- `output`: generated `LayoutID`.
- `exception`: `SessionError` if write fails or limit exceeded.

`loadCanvasState(ctx, id):`

- output: `CanvasState` associated with user and layout ID.
- exception: `NotFoundError` if layout does not exist or not owned by user; `SessionError` on read failure.

`listLayouts(ctx)`:

- output: summaries of layouts owned by the user.
- exception: `SessionError` if retrieval fails.

15.4.5 Local Functions

- `generateLayoutID()` – creates unique identifier for layouts.

16 MIS of Svc.ProcOrch

16.1 Module

Svc.ProcOrch (Preprocessing and Normalization Orchestrator)

This module coordinates image preprocessing workflows such as orientation correction, denoising, and resolution standardization before downstream analysis.

16.2 Uses

- `HW.ImageStorage` – for reading and writing image files.
- `ML.EdgeMatch`, `ML.Damage` – where preprocessing parameters are shared.
- External image processing library (for example, OpenCV).

16.3 Syntax

16.3.1 Exported Constants

- `TARGET_RESOLUTION` – canonical resolution for normalized images.
- `MAX_ORIENTATION_ERROR` – tolerated post-correction skew.

16.3.2 Exported Access Programs

Table 13: Svc.ProcOrch - Exported Access Programs

Name	In	Out	Exceptions
<code>enqueuePreprocessing</code>	<code>id: ImageID</code>	<code>JobID</code>	<code>PreprocError</code>
<code>runPreprocessing</code>	<code>job: JobID</code>	<code>PreprocResult</code>	<code>PreprocError</code>

16.4 Semantics

16.4.1 State Variables

- `jobQueue`: `Sequence[JobID]`

16.4.2 Environment Variables

- Execution environment for batch or async jobs.

16.4.3 Assumptions

- Input image already stored by `HW.ImageStorage`.

16.4.4 Access Routine Semantics

`enqueuePreprocessing(id)`:

- `transition`: creates a preprocessing job for `id` and appends it to `jobQueue`.
- `output`: `JobID` for tracking.
- `exception`: `PreprocError` if job cannot be created.

`runPreprocessing(job)`:

- `transition`: retrieves image by `ImageID`, applies normalization steps, and writes results back to storage.
- `output`: `PreprocResult` containing normalized image reference and metrics (for example, estimated orientation error).
- `exception`: `PreprocError` if any step fails.

16.4.5 Local Functions

- `correctOrientation(img)` – aligns text horizontally.
- `normalizeResolution(img)` – resamples to `TARGET_RESOLUTION`.

17 MIS of Svc.MatchOrch

17.1 Module

Svc.MatchOrch (Fragment Matching Orchestrator)

This module coordinates AI models for fragment matching, aggregates model outputs, and produces ranked match suggestions for a given fragment.

17.2 Uses

- `ML.EdgeMatch`, `ML.Damage`, `ML.TextSim`.
- `Data.FragmentStore` – for retrieving fragment metadata.

17.3 Syntax

17.3.1 Exported Constants

- `MAX_TOP_MATCHES = 10`
- `MATCH_CONFIDENCE_THRESHOLD = 0.6`

17.3.2 Exported Access Programs

Table 14: `Svc.MatchOrch` - Exported Access Programs

Name	In	Out	Exceptions
<code>generateMatches</code>	<code>frag: FragmentID</code>	<code>MatchResultList</code>	<code>MatchError</code>
<code>aggregateScores</code>	<code>scores: Sequence[ModelScore]</code>	<code>float</code>	<code>AggregationError</code>

17.4 Semantics

17.4.1 State Variables

- `recentResults: Map[FragmentID, MatchResultList]`

17.4.2 Environment Variables

- ML model serving endpoints.

17.4.3 Assumptions

- Each model returns normalized scores in $[0, 1]$.

17.4.4 Access Routine Semantics

`generateMatches(frag):`

- `transition`: queries all relevant ML models; aggregates and sorts candidate matches; updates `recentResults`.
- `output`: `MatchResultList` of top candidates above threshold.

- exception: `MatchError` if models unavailable or response invalid.

`aggregateScores(scores):`

- output: combined score (for example, weighted mean) over model scores.
- exception: `AggregationError` if sequence empty or weights invalid.

17.4.5 Local Functions

- `filterByThreshold(results)` – drops candidates below `MATCH_CONFIDENCE_THRESHOLD`.
- `sortByScore(results)` – orders candidates descending by final score.

18 MIS of Svc.Search

18.1 Module

Svc.Search (Search and Exploration Service)

This module executes queries over stored fragments and metadata, providing paginated and filterable search results to the UI.

18.2 Uses

- `Data.FragmentStore`, `Data.Catalog`.

18.3 Syntax

18.3.1 Exported Constants

- `DEFAULT_PAGE_SIZE = 25`

18.3.2 Exported Access Programs

Table 15: Svc.Search - Exported Access Programs

Name	In	Out	Exceptions
<code>executeQuery</code>	<code>q: SearchQuery,</code> <code>page: int</code>	<code>SearchResultPage</code>	<code>SearchError</code>
<code>exportResults</code>	<code>q: SearchQuery,</code> <code>format:</code> <code>ExportFormat</code>	<code>ExportPayload</code>	<code>SearchError,</code> <code>ExportError</code>

18.4 Semantics

18.4.1 State Variables

- none

18.4.2 Environment Variables

- Database engine for indexing and querying fragment records.

18.4.3 Assumptions

- All searchable fields are indexed appropriately for performance.

18.4.4 Access Routine Semantics

`executeQuery(q, page):`

- output: `SearchResultPage` containing fragment summaries for the requested page.
- exception: `SearchError` if query invalid or backend failure occurs.

`exportResults(q, format):`

- output: `ExportPayload` that can be streamed to client as CSV or PDF.
- exception: `SearchError` on query failure; `ExportError` if export generation fails.

18.4.5 Local Functions

- `buildQueryPlan(q)` – compiles filter and sort options into database query.
- `formatExport(results, format)` – converts results into specified output format.

19 MIS of `Data.FragmentStore`

19.1 Module

`Data.FragmentStore` (Fragment Metadata Store)

This module is responsible for storing and retrieving logical fragment entities. It maintains metadata such as fragment IDs, associated image IDs, script labels, line counts, and status flags, and acts as the core record of fragments used throughout the system.

19.2 Uses

- `HW.ImageStorage` – via stored `ImageID` references.
- `Data.Catalog` – for linking to external catalogue identifiers when available.

19.3 Syntax

19.3.1 Exported Constants

- MAX_LABEL_LENGTH

19.3.2 Exported Access Programs

Table 16: Data.FragmentStore - Exported Access Programs

Name	In	Out	Exceptions
createFragment	rec: FragmentRecord	FragmentID	FragmentError
getFragment	id: FragmentID	FragmentRecord	NotFoundError
updateFragment	id: FragmentID, rec: FragmentRecord	bool	FragmentError, NotFoundError
deleteFragment	id: FragmentID	bool	FragmentError, NotFoundError

19.4 Semantics

19.4.1 State Variables

- fragmentTable: Map[FragmentID, FragmentRecord]

19.4.2 Environment Variables

- Relational database or equivalent persistent storage.

19.4.3 Assumptions

- Fragment IDs are globally unique and stable over time.

19.4.4 Access Routine Semantics

createFragment(rec):

- transition: inserts a new record into fragmentTable.
- output: new FragmentID.
- exception: FragmentError if insert fails or constraints violated.

getFragment(id):

- output: record associated with `id`.
- exception: `NotFoundError` if no record exists.

`updateFragment(id, rec):`

- transition: replaces existing record for `id` with `rec`.
- output: `true` if update successful.
- exception: `NotFoundError` if `id` unknown; `FragmentError` on write failure.

`deleteFragment(id):`

- transition: removes record associated with `id`.
- output: `true` if deletion successful.
- exception: `NotFoundError` if `id` unknown; `FragmentError` on delete failure.

19.4.5 Local Functions

- `validateFragment(rec)` – checks required fields and constraints.

20 MIS of Data.Catalog

20.1 Module

Data.Catalog (External Catalogue Link Store)

This module maintains mappings between internal fragments and external catalogue identifiers from libraries, collections, or previous editions.

20.2 Uses

- `Data.FragmentStore` – for core fragment records.

20.3 Syntax

20.3.1 Exported Constants

- `MAX_CATALOG_ID_LENGTH`

20.3.2 Exported Access Programs

Table 17: Data.Catalog - Exported Access Programs

Name	In	Out	Exceptions
linkFragmentToCatalog	frag: FragmentID, catID: String	bool	CatalogError
getCatalogIDs	frag: FragmentID	Sequence[String]	CatalogError
findByCatalogID	catID: String	Sequence[FragmentID]	CatalogError

20.4 Semantics

20.4.1 State Variables

- `catalogMap`: Map[FragmentID, Sequence[String]]

20.4.2 Environment Variables

- Same underlying database as the fragment store or a logically related schema.

20.4.3 Assumptions

- External catalogue identifiers are opaque strings; uniqueness is handled externally.

20.4.4 Access Routine Semantics

`linkFragmentToCatalog(frag, catID)`:

- transition: appends `catID` to the list of identifiers for `frag`.
- output: `true` on success.
- exception: `CatalogError` on write failure.

`getCatalogIDs(frag)`:

- output: all catalogue IDs associated with `frag`.
- exception: `CatalogError` if retrieval fails.

`findByCatalogID(catID)`:

- output: all `FragmentID` values linked to `catID`.
- exception: `CatalogError` if query fails.

20.4.5 Local Functions

- `normalizeCatalogID(catID)` – optional normalization (trim, case).

21 MIS of Data.User

21.1 Module

Data.User (User Account Store)

This module stores user accounts, credentials (hashed), roles, and profile information required for authentication and access control.

21.2 Uses

- Cryptographic utilities for password hashing.

21.3 Syntax

21.3.1 Exported Constants

- `MAX_USERNAME_LENGTH`
- `MAX_EMAIL_LENGTH`

21.3.2 Exported Access Programs

Table 18: Data.User - Exported Access Programs

Name	In	Out	Exceptions
<code>createUser</code>	<code>rec: UserRecord</code>	<code>UserID</code>	<code>UserError</code>
<code>getUserByID</code>	<code>id: UserID</code>	<code>UserRecord</code>	<code>NotFoundError</code>
<code>getUserByEmail</code>	<code>email: String</code>	<code>UserRecord</code>	<code>NotFoundError</code>
<code>updateUser</code>	<code>id: UserID, rec: UserRecord</code>	<code>bool</code>	<code>UserError,</code> <code>NotFoundError</code>

21.4 Semantics

21.4.1 State Variables

- `userTable: Map[UserID, UserRecord]`

21.4.2 Environment Variables

- Persistent user database with appropriate access controls.

21.4.3 Assumptions

- Email addresses are unique per user.

21.4.4 Access Routine Semantics

`createUser(rec):`

- transition: inserts new user record; hashes password fields before storage.
- output: generated `UserID`.
- exception: `UserError` if constraints violated or write fails.

`getUserByID(id):`

- output: user record with `id`.
- exception: `NotFoundError` if no such user.

`getUserByEmail(email):`

- output: user record whose email matches `email`.
- exception: `NotFoundError` if not found.

`updateUser(id, rec):`

- transition: updates record for `id`.
- output: `true` on success.
- exception: `NotFoundError` if `id` unknown; `UserError` on failure.

21.4.5 Local Functions

- `validateUser(rec)` – checks email format, password policy etc.

22 MIS of Data.Project

22.1 Module

Data.Project (Project and Reconstruction Session Store)

This module records reconstruction projects, including project metadata, associated fragments, and saved reconstruction sessions.

22.2 Uses

- `Data.User` – to associate projects with owners or collaborators.
- `Data.FragmentStore`.

22.3 Syntax

22.3.1 Exported Constants

- `MAX_PROJECT_NAME_LENGTH`

22.3.2 Exported Access Programs

Table 19: `Data.Project` - Exported Access Programs

Name	In	Out	Exceptions
<code>createProject</code>	<code>rec: ProjectRecord</code>	<code>ProjectID</code>	<code>ProjectError</code>
<code>getProject</code>	<code>id: ProjectID</code>	<code>ProjectRecord</code>	<code>NotFoundError</code>
<code>updateProject</code>	<code>id: ProjectID,</code> <code>rec: ProjectRecord</code>	<code>bool</code>	<code>ProjectError,</code> <code>NotFoundError</code>
<code>listProjectsForUser</code>	<code>user: UserID</code>	<code>Sequence[ProjectSummary]</code>	<code>ProjectError</code>

22.4 Semantics

22.4.1 State Variables

- `projectTable: Map[ProjectID, ProjectRecord]`

22.4.2 Environment Variables

- Persistent project database.

22.4.3 Assumptions

- Each project belongs to at least one user.

22.4.4 Access Routine Semantics

`createProject(rec):`

- `transition`: inserts new row in `projectTable`.
- `output`: created `ProjectID`.

- exception: `ProjectError` on constraint violation or failure.

`getProject(id):`

- output: project record matching `id`.
- exception: `NotFoundError` if none exists.

`updateProject(id, rec):`

- transition: updates stored record.
- output: `true` on success.
- exception: `NotFoundError` or `ProjectError`.

`listProjectsForUser(user):`

- output: summaries of all projects owned by or shared with `user`.
- exception: `ProjectError` if query fails.

22.4.5 Local Functions

- `validateProject(rec)` – checks required fields and name length.

23 MIS of ML.EdgeMatch

23.1 Module

ML.EdgeMatch (Edge Pattern Matching Model)

This module provides model-based similarity estimates based on fragment edge contours and shapes.

23.2 Uses

- `HW.ImageStorage` – to retrieve normalized images.

23.3 Syntax

23.3.1 Exported Constants

- `EDGE_SIGNATURE_DIM`

23.3.2 Exported Access Programs

Table 20: ML.EdgeMatch - Exported Access Programs

Name	In	Out	Exceptions
computeEdgeSignature	id: ImageID	EdgeSignature	ModelError
scoreEdgeSimilarity	a: EdgeSignature, b: EdgeSignature	float	ModelError

23.4 Semantics

23.4.1 State Variables

- Optional cached model weights and configuration.

23.4.2 Environment Variables

- Model runtime (for example, PyTorch or TensorFlow backend).

23.4.3 Assumptions

- Input images have been preprocessed and normalized by `Svc.ProcOrch`.

23.4.4 Access Routine Semantics

`computeEdgeSignature(id)`:

- output: fixed-length vector representing edge features for the image.
- exception: `ModelError` if image cannot be processed.

`scoreEdgeSimilarity(a, b)`:

- output: similarity score in $[0, 1]$ reflecting how well edges match.
- exception: `ModelError` if signatures invalid or incompatible.

23.4.5 Local Functions

- `extractContours(img)` – local function to compute edge features.

24 MIS of ML.ScriptClass

24.1 Module

ML.ScriptClass (Script Classification Model)

This module classifies the script type of a fragment (for example, Gupta Brāhmī, Tibetan Uchen, Chinese) and returns confidence scores.

24.2 Uses

- `HW.ImageStorage`.

24.3 Syntax

24.3.1 Exported Constants

- `SUPPORTED_SCRIPTS`: `Sequence[String]`

24.3.2 Exported Access Programs

Table 21: ML.ScriptClass - Exported Access Programs

Name	In	Out	Exceptions
<code>classifyScript</code>	<code>id</code> : <code>ImageID</code>	<code>ScriptPrediction</code>	<code>ModelError</code>

24.4 Semantics

24.4.1 State Variables

- Model weights for script classification.

24.4.2 Environment Variables

- Model runtime and hardware accelerators (if available).

24.4.3 Assumptions

- Input image includes at least some legible text.

24.4.4 Access Routine Semantics

`classifyScript(id)`:

- output: `ScriptPrediction` containing predicted script label and confidence.
- exception: `ModelError` if classification fails or confidence undefined.

24.4.5 Local Functions

- `preprocessForScript(img)` – applies script-specific preprocessing pipeline.

25 MIS of ML.TextSim

25.1 Module

ML.TextSim (Textual Content Similarity Model)

This module computes semantic similarity between text segments derived from transcribed text or manual annotations.

25.2 Uses

- `Data.FragmentStore` – for accessing fragment text content.

25.3 Syntax

25.3.1 Exported Constants

- `EMBEDDING_DIM`

25.3.2 Exported Access Programs

Table 22: ML.TextSim - Exported Access Programs

Name	In	Out	Exceptions
<code>embedText</code>	<code>text: String</code>	<code>TextEmbedding</code>	<code>ModelError</code>
<code>scoreTextSimilarity</code>	<code>a: TextEmbedding, b: TextEmbedding</code>	<code>float</code>	<code>ModelError</code>

25.4 Semantics

25.4.1 State Variables

- Embedding model weights.

25.4.2 Environment Variables

- Model runtime.

25.4.3 Assumptions

- Input text is normalized (script, encoding).

25.4.4 Access Routine Semantics

`embedText(text):`

- output: fixed-length embedding vector.
- exception: `ModelError` if model fails.

`scoreTextSimilarity(a, b):`

- output: similarity score in $[0, 1]$.
- exception: `ModelError` if inputs invalid.

25.4.5 Local Functions

- `cosineSimilarity(a, b)` – core similarity computation.

26 MIS of ML.Segmentation

26.1 Module

ML.Segmentation (Fragment Segmentation Model)

This module performs image segmentation to identify and isolate individual fragment regions from manuscript images. It detects fragment boundaries and separates multiple fragments that may appear in a single scanned image.

26.2 Uses

- `HW.ImageStorage` – for retrieving images to segment.

26.3 Syntax

26.3.1 Exported Constants

- `MIN_FRAGMENT_SIZE` – minimum area threshold for valid fragments.
- `SEGMENTATION_CONFIDENCE_THRESHOLD = 0.7`

26.3.2 Exported Access Programs

Table 23: ML.Segmentation - Exported Access Programs

Name	In	Out	Exceptions
segmentImage	id: ImageID	SegmentationResult	ModelError
extractFragments	id: ImageID, masks: SegmentMaskList	Sequence[ImageID]	ModelError

26.4 Semantics

26.4.1 State Variables

- Segmentation model weights and configuration.

26.4.2 Environment Variables

- Model runtime environment for deep learning inference.

26.4.3 Assumptions

- Input images have been preprocessed (orientation correction, resolution normalization).
- Fragments in the image have sufficient contrast with the background.

26.4.4 Access Routine Semantics

`segmentImage(id):`

- output: `SegmentationResult` containing binary masks and bounding boxes for detected fragments.
- exception: `ModelError` if segmentation fails or image cannot be processed.

`extractFragments(id, masks):`

- transition: creates separate image files for each detected fragment region; stores them via `HW.ImageStorage`.
- output: sequence of new `ImageID` values for extracted fragments.
- exception: `ModelError` if extraction or storage fails.

26.4.5 Local Functions

- `applyMorphology(mask)` – cleans segmentation masks using morphological operations.
- `filterSmallRegions(masks)` – removes regions below `MIN_FRAGMENT_SIZE`.

27 MIS of ML.CircleRecognition

27.1 Module

ML.CircleRecognition (Circle Detection and Recognition Model)

This module detects circular marks, holes, or decorative elements in manuscript fragments. These features can serve as additional matching criteria when aligning fragments.

27.2 Uses

- `HW.ImageStorage` – for accessing fragment images.

27.3 Syntax

27.3.1 Exported Constants

- `MIN_CIRCLE_RADIUS` – minimum detectable circle size in pixels.
- `MAX_CIRCLE_RADIUS` – maximum detectable circle size in pixels.

27.3.2 Exported Access Programs

Table 24: ML.CircleRecognition - Exported Access Programs

Name	In	Out	Exceptions
<code>detectCircles</code>	<code>id: ImageID</code>	<code>CircleList</code>	<code>ModelError</code>
<code>matchCirclePatterns</code>	<code>a: CircleList,</code> <code>b: CircleList</code>	<code>float</code>	<code>ModelError</code>

27.4 Semantics

27.4.1 State Variables

- Detection parameters and thresholds.

27.4.2 Environment Variables

- Image processing library (e.g., OpenCV).

27.4.3 Assumptions

- Circles are sufficiently distinct from background texture.
- Images are preprocessed and normalized.

27.4.4 Access Routine Semantics

`detectCircles(id):`

- output: `CircleList` containing center coordinates, radii, and confidence scores for detected circles.
- exception: `ModelError` if detection fails.

`matchCirclePatterns(a, b):`

- output: similarity score in $[0, 1]$ based on spatial arrangement and properties of circles.
- exception: `ModelError` if matching algorithm fails.

27.4.5 Local Functions

- `computeSpatialHash(circles)` – creates geometric hash for circle arrangement.
- `filterOverlappingCircles(circles)` – removes duplicate detections.

28 MIS of ML.LineCount

28.1 Module

ML.LineCount (Text Line Counting Model)

This module analyzes manuscript fragments to count the number of text lines present. Line count serves as a useful filtering and matching criterion during fragment search and reconstruction.

28.2 Uses

- `HW.ImageStorage` – for accessing fragment images.

28.3 Syntax

28.3.1 Exported Constants

- `MIN_LINE_SPACING` – minimum expected spacing between lines in pixels.

28.3.2 Exported Access Programs

Table 25: ML.LineCount - Exported Access Programs

Name	In	Out	Exceptions
countLines	id: ImageID	LineCountResult	ModelError
detectLineRegions	id: ImageID	Sequence[BoundingBox]	ModelError

28.4 Semantics

28.4.1 State Variables

- Line detection model parameters.

28.4.2 Environment Variables

- Image processing and model inference environment.

28.4.3 Assumptions

- Text lines are approximately horizontal after preprocessing.
- Sufficient contrast exists between text and background.

28.4.4 Access Routine Semantics

`countLines(id):`

- output: `LineCountResult` containing the number of detected lines and confidence score.
- exception: `ModelError` if counting fails or image quality insufficient.

`detectLineRegions(id):`

- output: sequence of `BoundingBox` objects defining the spatial extent of each text line.
- exception: `ModelError` if line detection fails.

28.4.5 Local Functions

- `projectHorizontally(img)` – creates horizontal projection histogram for line detection.
- `findLineBoundaries(projection)` – identifies line separation points in projection.

29 MIS of ML.EdgeClassification

29.1 Module

ML.EdgeClassification (Edge Type Classification Model)

This module classifies fragment edges into categories such as torn, cut, original (manuscript boundary), or burned. Edge type classification helps improve matching accuracy by ensuring compatible edge pairs are compared.

29.2 Uses

- `HW.ImageStorage` – for accessing fragment images.
- `ML.EdgeMatch` – edge signatures may be shared for classification.

29.3 Syntax

29.3.1 Exported Constants

- `EDGE_TYPES =`
`torn, cut, original, burned, unknown`
- `MIN_CLASSIFICATION_CONFIDENCE = 0.6`

29.3.2 Exported Access Programs

Table 26: ML.EdgeClassification - Exported Access Programs

Name	In	Out	Exceptions
<code>classifyEdges</code>	<code>id: ImageID</code>	<code>EdgeClassificationResult</code>	<code>ModelError</code>
<code>getEdgeType</code>	<code>id: ImageID,</code> <code>edge: EdgeRegion</code>	<code>EdgeTypePrediction</code>	<code>ModelError</code>

29.4 Semantics

29.4.1 State Variables

- Edge classification model weights.

29.4.2 Environment Variables

- Model runtime for deep learning inference.

29.4.3 Assumptions

- Fragment edges are clearly visible in preprocessed images.
- Training data covers representative examples of each edge type.

29.4.4 Access Routine Semantics

`classifyEdges(id):`

- output: `EdgeClassificationResult` containing edge type predictions for all detected edges with confidence scores.
- exception: `ModelError` if classification fails.

`getEdgeType(id, edge):`

- output: `EdgeTypePrediction` for a specific edge region containing predicted type and confidence.
- exception: `ModelError` if edge region invalid or classification fails.

29.4.5 Local Functions

- `extractEdgeFeatures(img, region)` – computes texture and shape features for edge region.
- `normalizeConfidences(predictions)` – adjusts confidence scores to sum to 1.0.

30 MIS of Util.Error

30.1 Module

Util.Error (Error Type and Exception Utilities)

This module defines standard error types and helpers for constructing and handling errors in a consistent way across modules.

30.2 Uses

- None at the architectural level; referenced by many other modules.

30.3 Syntax

30.3.1 Exported Constants

- Standard error codes or identifiers (for example, `ERR_NOT_FOUND`, `ERR_VALIDATION`).

30.3.2 Exported Access Programs

Table 27: Util.Error - Exported Access Programs

Name	In	Out	Exceptions
buildError	code: String, msg: String	ErrorObject	None
toClientMessage	err: ErrorObject	String	None

30.4 Semantics

30.4.1 State Variables

- None.

30.4.2 Environment Variables

- None.

30.4.3 Assumptions

- All modules reference the same canonical error types.

30.4.4 Access Routine Semantics

`buildError(code, msg):`

- output: structured error object capturing code and message.
- exception: none.

`toClientMessage(err):`

- output: safe message for display at UI or API boundary.
- exception: none.

31 MIS of Util.Logging

31.1 Module

Util.Logging (Logging Utility)

This module provides structured logging for events, errors, and performance metrics.

31.2 Uses

- Underlying logging framework or standard output.

31.3 Syntax

31.3.1 Exported Constants

- Log levels such as `INFO`, `WARN`, `ERROR`.

31.3.2 Exported Access Programs

Table 28: Util.Logging - Exported Access Programs

Name	In	Out	Exceptions
<code>logInfo</code>	<code>msg: String</code>	<code>none</code>	<code>None</code>
<code>logWarn</code>	<code>msg: String</code>	<code>none</code>	<code>None</code>
<code>logError</code>	<code>msg: String,</code> <code>err: ErrorObject</code>	<code>none</code>	<code>None</code>

31.4 Semantics

31.4.1 State Variables

- Optional runtime configuration (log level, sinks).

31.4.2 Environment Variables

- File system, console, or external logging service.

31.4.3 Assumptions

- Logging operations are non-fatal and do not throw.

31.4.4 Access Routine Semantics

`logInfo(msg):`

- output: none; writes informational log entry.
- exception: none.

`logWarn(msg):`

- output: none; writes warning log entry.

- exception: none.

`logError(msg, err):`

- output: none; writes error entry including details from `err`.
- exception: none.

32 MIS of Util.Config

32.1 Module

Util.Config (Configuration Management)

This module provides read-only access to configuration values such as database connection strings, model paths, and feature flags.

32.2 Uses

- Environment variables or configuration files.

32.3 Syntax

32.3.1 Exported Constants

- None fixed; keys are used to look up values.

32.3.2 Exported Access Programs

Table 29: Util.Config - Exported Access Programs

Name	In	Out	Exceptions
<code>getValue</code>	<code>key: String</code>	<code>String</code>	<code>ConfigError</code>
<code>getBool</code>	<code>key: String</code>	<code>bool</code>	<code>ConfigError</code>

32.4 Semantics

32.4.1 State Variables

- `configCache: Map[String, String]`

32.4.2 Environment Variables

- Config file or environment variable store.

32.4.3 Assumptions

- Configuration is loaded at startup and remains static during runtime.

32.4.4 Access Routine Semantics

`getValue(key):`

- output: configuration value associated with `key`.
- exception: `ConfigError` if key missing.

`getBool(key):`

- output: parsed boolean value.
- exception: `ConfigError` if key missing or value not parseable.

33 MIS of Util.TestStub

33.1 Module

Util.TestStub (Testing Stubs and Fakes)

This module provides stub implementations of selected services and ML components for use in automated tests.

33.2 Uses

- Core service and ML interfaces for type compatibility.

33.3 Syntax

33.3.1 Exported Constants

- None.

33.3.2 Exported Access Programs

Table 30: Util.TestStub - Exported Access Programs

Name	In	Out	Exceptions
<code>getFixedOCRStub</code>	none	ML.OCR-like object	None
<code>getFixedMatchStub</code>	none	Svc.MatchOrch-like object	None

33.4 Semantics

33.4.1 State Variables

- Predefined responses used for deterministic tests.

33.4.2 Environment Variables

- None.

33.4.3 Assumptions

- Stubs are only used in test environments.

33.4.4 Access Routine Semantics

`getFixedOCRStub()`:

- output: object implementing `runOCR` that returns predictable results for known inputs.
- exception: none.

`getFixedMatchStub()`:

- output: object implementing `generateMatches` with fixed candidate lists.
- exception: none.

33.4.5 Local Functions

- `loadStubFixtures()` – loads predefined responses from static files.

References

- Team Sanskrit Ciphers. Hazard analysis document. <https://github.com/DylanG5/sanskrit-cipher/blob/43484da11e4fb0f879f7bbf2377c21900e5b9838/docs/HazardAnalysis/HazardAnalysis.pdf>, 2025a. Identifies potential hazards, risks, and mitigation strategies.
- Team Sanskrit Ciphers. Software requirements specification (srs). <https://github.com/DylanG5/sanskrit-ciphers-requirements/blob/9938018b682709551d0a6248a0a9f6e5794112ee/index.pdf>, 2025b. Specifies functional and non-functional requirements for the system.

Appendix — Reflection

The information in this section will be used to evaluate the team members on the graduate attribute of Problem Analysis and Design.

1. What went well while writing this deliverable?

One aspect that went particularly well was identifying the appropriate notation and determining which modules needed to be included in the design. Our team communicated effectively throughout this process, which helped us maintain a shared understanding of the system and its structure. Because we already had a strong grasp of the project vision, it was relatively easy to map our ideas into a formal design representation. As a result, we were able to present a clear and coherent picture of the system architecture that reflects both the requirements and the intended functionality.

2. What pain points did you experience during this deliverable, and how did you resolve them?

The main challenge we encountered was thinking through the lower-level implementation details. At this stage, we have not yet progressed far into the actual coding, so some of the design decisions, especially those related to specific algorithms, data structures, and system interactions required educated assumptions rather than concrete experience. We addressed this by focusing on higher-level abstractions and deferring detailed implementation decisions until we gain more clarity during development. This allowed us to complete the deliverable while still leaving room for necessary adjustments later.

3. Which of your design decisions stemmed from speaking to your client(s) or a proxy (e.g. your peers, stakeholders, potential users)? For those that were not, why, and where did they come from?

Many of our design decisions, especially those involving the user interface, were directly influenced by conversations with our supervisor, Dr. Shayne. Since he does not come from a technical background, he primarily expressed his needs in terms of how he wanted to interact with the system. This naturally shaped the UI and the workflow we designed for scholars. Additionally, the inclusion of segmentation-based machine learning came from his explicit request; he emphasized that automated assistance in identifying and matching fragments would significantly improve his research workflow. These inputs helped anchor our design choices in real user needs.

4. While creating the design doc, what parts of your other documents (e.g. requirements, hazard analysis, etc), it any, needed to be changed, and why?

Very few changes were needed to our previous documents. Because this is a pre-approved project with a well-defined problem and scope, many of the requirements and expectations were already laid out for us in the project description. As a result, our earlier documents, such as the SRS ([Ciphers, 2025b](#)) and Hazard Analysis ([Ciphers](#),

2025a), aligned naturally with the design work we did here. We did not need to revisit or adjust them significantly, beyond minor wording refinements and consistency updates.

5. What are the limitations of your solution? Put another way, given unlimited resources, what could you do to make the project better? (LO_ProbSolutions)

With unlimited resources, one of the most impactful improvements would be investing in more powerful AI infrastructure, such as GPUs dedicated to training and evaluating models. This would allow us to train new segmentation or matching models more frequently and at a much larger scale. We would also aim to build a more advanced fragment-matching pipeline with higher accuracy and more robust behaviour across different manuscript types. Additionally, we would elevate the quality of the UI significantly, improving performance, adding more interactive tools, and making the interface cleaner and more intuitive. Overall, the entire system could operate at a higher level of precision, speed, and sophistication.

6. Give a brief overview of other design solutions you considered. What are the benefits and tradeoffs of those other designs compared with the chosen design? From all the potential options, why did you select the documented design? (LO_Explores)

We did not explore many alternative designs because, from early discussions, the entire team already shared a clear mental model of how the system should operate. Our frequent conversations kept us aligned on the major components and workflow, so we naturally converged on a single coherent design. Although this meant we did not formally evaluate multiple competing solutions, the advantage was that we were able to focus our efforts on developing one strong, detailed design rather than splitting time considering options that did not align with the client's expectations. Given the clarity of the problem and the constraints provided, the chosen design was the most straightforward and appropriate path forward.