

COT 2000

# Foundations of Computing

Spring 2024

Lecture 21 – part 1

Lab 10 (Optional)

Homework 7 – 07/29/24

Exam 4 – 08/02/24

# Lecture 21 – part 2

## Review

# Review

- Graph Isomorphisms
- Degree of a vertex, outdegree, indegree
- Isomorphic Invariants
- Graphic Sequence
- Data structures
  - Adjacency Matrix
  - Edge dictionary
  - Edge list





# Graph Isomorphisms

## • Definition

Let  $G$  and  $G'$  be graphs with vertex sets  $V(G)$  and  $V(G')$  and edge sets  $E(G)$  and  $E(G')$ , respectively.  $G$  is **isomorphic to  $G'$**  if, and only if, there exist one-to-one correspondences  $g: V(G) \rightarrow V(G')$  and  $h: E(G) \rightarrow E(G')$  that preserve the edge-endpoint functions of  $G$  and  $G'$  in the sense that for all  $v \in V(G)$  and  $e \in E(G)$ ,



$$v \text{ is an endpoint of } e \iff g(v) \text{ is an endpoint of } h(e).$$

10.4.1





Note that these relabeling functions are one-to-one and onto.

**Exercise:** Show that the following two graphs are isomorphic.



**Solution:**

To solve this problem, you must find functions  $\mathbf{g}: V(G) \rightarrow V(G')$  and  $\mathbf{h}: E(G) \rightarrow E(G')$  such that for all  $\mathbf{v} \in V(G)$  and  $\mathbf{e} \in E(G)$ ,  $\mathbf{v}$  is an endpoint of  $\mathbf{e}$  if, and only if,  $\mathbf{g(v)}$  is an endpoint of  $\mathbf{h(e)}$ .



**Conclusion:**

There is isomorphism between  $G$  and  $G'$ .

# Degree of a vertex

(a) Let  $v$  be a vertex of an **undirected graph**.

- The **degree** of  $v$ , denoted  $\deg(v)$ , is the number of edges that connect  $v$  to the other vertices in the graph.

(b) If  $v$  is a vertex of a **directed graph**:

- Then the **outdegree** of  $v$ , denoted  $\text{outdeg}(v)$ , is the number of edges of the graph that initiate at  $v$ .
- The **indegree** of  $v$ , denoted  $\text{indeg}(v)$ , is the number of edges that terminate at  $v$ .

**Degree Sequence of a Graph:** The degree sequence of a simple undirected graph is the non-increasing sequence of its vertex degrees

# Isomorphic Invariant

A property that is preserved by graph isomorphism is called an **isomorphic invariant**.

## Example:

- if you are given two graphs, one with 16 vertices and the other with 17, you can immediately conclude that the two are not isomorphic.

### • Definition

A property  $P$  is called an **invariant for graph isomorphism** if, and only if, given any graphs  $G$  and  $G'$ , if  $G$  has property  $P$  and  $G'$  is isomorphic to  $G$ , then  $G'$  has property  $P$ .

### Theorem 10.4.2

Each of the following properties is an invariant for graph isomorphism, where  $n$ ,  $m$ , and  $k$  are all nonnegative integers:

- |                                     |  |
|-------------------------------------|--|
| 1. has $n$ vertices;                | 6. has a simple circuit of length $k$ ;    |
| 2. has $m$ edges;                   | 7. has $m$ simple circuits of length $k$ ; |
| 3. has a vertex of degree $k$ ;     | 8. is connected;                           |
| 4. has $m$ vertices of degree $k$ ; | 9. has an Euler circuit;                   |
| 5. has a circuit of length $k$ ;    | 10. has a Hamiltonian circuit.             |


Traversals



# Graphic Sequence


- A finite nonincreasing sequence of integers  $d_1, d_2, \dots, d_n$  is **graphic** if there exists a simple undirected graph with  $n$  vertices having the sequence as its degree sequence.

**Example:** Is this sequence 4, 2, 1, 1, 1, 1 a graphic sequence ?



The sequence 4, 2, 1, 1, 1, 1 is **graphic** because the degrees of the graph in the figure match these numbers.  
Note: There is no connection between the vertex number and its degree in this graph.

Example:



Adjacency Matrix

$$G = \begin{pmatrix} 0 & 1 & 0 & 1 \\ 0 & 0 & 1 & 1 \\ 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 0 \end{pmatrix}$$

Edge Dictionary

$G = \{ 1:[2,4], 2:[3,4], 3:[3], 4:[1] \}$

Edge List

$G = [(1,2),(1,4),(2,3),(2,4),(3,3),(4,1)]$

**Exercise:**

Directed graphs  $G_1, \dots, G_6$ , each with vertex set  $\{1, 2, 3, 4, 5\}$  are represented by the matrices below. Which graphs are isomorphic to one another?

$$G_1 : \begin{pmatrix} 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 1 \\ 1 & 0 & 0 & 0 & 0 \end{pmatrix}$$


$$G_2 : \begin{pmatrix} 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 0 & 1 \\ 0 & 0 & 0 & 0 & 0 \end{pmatrix}$$

$$G_3 : \begin{pmatrix} 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \end{pmatrix}$$

$$G_4 : \begin{pmatrix} 0 & 1 & 1 & 1 & 1 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \end{pmatrix}$$


$$G_5 : \begin{pmatrix} 0 & 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 & 0 \end{pmatrix}$$

$$G_6 : \begin{pmatrix} 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 \end{pmatrix}$$




**G1**

	v0	v1	v2	v3	v4
v0	0	1	0	0	0
v1	0	0	1	0	0
v2	0	0	0	1	0
v3	0	0	0	0	1
v4	1	0	0	0	0



**G2**


	v0	v1	v2	v3	v4
v0	0	0	0	0	0
v1	0	0	1	0	0
v2	0	0	0	0	0
v3	1	1	1	0	1
v4	0	0	0	0	0



**G3**

	v0	v1	v2	v3	v4
v0	0	0	0	0	0
v1	1	0	0	0	1
v2	0	1	0	0	0
v3	0	0	1	0	0
v4	0	0	1	0	0


G4



G4

	v0	v1	v2	v3	v4
v0	0	1	1	1	1
v1	0	0	0	0	0
v2	0	0	0	0	0
v3	0	0	1	0	0
v4	0	0	0	0	0


G5



G5

	v0	v1	v2	v3	v4
v0	0	0	0	0	1
v1	0	0	0	0	0
v2	0	1	0	1	0
v3	0	0	0	0	1
v4	0	0	1	0	0

G6





G6

	v0	v1	v2	v3	v4
v0	0	0	0	1	0
v1	0	0	0	0	0
v2	1	1	0	0	0
v3	0	0	1	0	0
v4	0	0	0	1	0

## Python code

```
{'G1 and G2': False,  
 'G1 and G3': False,  
 'G1 and G4': False,  
 'G1 and G5': False,  
 'G1 and G6': False,  
 'G2 and G3': False,  
 'G2 and G4': True, ✓  
 'G2 and G5': False,  
 'G2 and G6': False,  
 'G3 and G4': False,  
 'G3 and G5': True,  
 'G3 and G6': True,  
 'G4 and G5': False,  
 'G4 and G6': False,  
 'G5 and G6': True}
```



# Lecture 21 – part 3

## Special Topic (\*)

### The Power of Tsetlin Machines

\*Note: This topic is not included on exam.

## Traditional Neural Network

### Deep Neural Network




Figure 12.2 Deep network architecture with multiple layers.



# What are Tsetlin Machines

Tsetlin Automata

+

Propositional Logic





Image reproduced from <https://arxiv.org/pdf/1804.01508.pdf>

If condition then class

=

Tsetlin Machine



# Advantages

- **Scalability:** The parallel nature of TMs allows them to be effectively scaled for large datasets and complex problems.
- **Transparency and Interpretability:** The learned rules are highly interpretable. Each clause in the model can be understood as a human-readable rule, making it easier to analyze and trust the decisions made by the model.
- **Highly efficient**, both in terms of computational resources and power consumption, making them suitable for edge computing devices.

Tsetlin Machines have been applied for classification, regression, and even image recognition, demonstrating their versatility and potential as a complement or alternative to traditional machine learning models.

Michael Lvovitch Tsetli (1924 – 1966)  
Invented the Tsetlin automaton (1961)



M. L. Tsetlin, "On behaviour of finite automata in random medium," Avtomat. i Telemekh, vol. 22, no. 10, pp. 1345–1354, 1961

Professor Ole-Christoffer Granmo  
Created the Tsetlin machine (2018)



University of Agder, Norway

Granmo, Ole-Christoffer. "The Tsetlin Machine--A Game Theoretic Bandit Driven Approach to Optimal Pattern Recognition with Propositional Logic." arXiv preprint arXiv:1804.01508 (2018).

# Extremely simple dataset

**Input Features**

The diagram illustrates a classification task. A table titled 'Vehicles dataset' contains six data points with features: Four Wheels, Transport People, Wings, Yellow, and Blue. The output class is 'Vehicle'. Blue arrows point from the feature names to their respective columns in the table. An orange arrow points from the 'Vehicle' column to the 'Output Classes' label.

<b>Vehicles dataset</b>						
<b>Datapoint</b>	<b>Four Wheels</b>	<b>Transport People</b>	<b>Wings</b>	<b>Yellow</b>	<b>Blue</b>	<b>Vehicle</b>
1	Yes	Yes	No	No	Yes	Car
2	Yes	Yes	No	Yes	No	Car
3	Yes	Yes	No	Yes	No	Car
4	Yes	Yes	Yes	No	Yes	Plane
5	Yes	No	Yes	Yes	No	Plane
6	No	Yes	Yes	No	Yes	Plane

**Output Classes**

# Rule Examples

**If** condition **then** class

The **condition** part is a placeholder for a Boolean expression that describes a **pattern** in the data, to be learnt by the Tsetlin machine.

Rule 1:      **If** (four wheels **and** Transport People) **then** car

Rule 2:      **If** (wings) **then** plane

Rule n:

# Binarization

**Literals:** Input features and their negations

Dataset											
#	Four W	T.People	Wings	Yellow	Blue	<b>not</b> Four W	<b>not</b> T. People	<b>not</b> wings	<b>not</b> yellow	<b>not</b> blue	Class
1	1	1	0	0	1	0	0	1	1	0	car
2	1	1	0	1	0	0	0	1	0	1	car
3	1	1	0	1	0	0	0	1	0	1	car
4	1	1	1	0	1	0	0	0	1	0	plane
5	1	0	1	1	0	0	1	0	0	1	plane
6	0	1	1	0	1	1	0	0	1	0	plane

# Rule Memory

A Tsetlin machine simulates forgetting and memorization.

Literals under position five(5) **do not participate** on the rule condition.

Maximally Memorized	10									
	9									
	8									
	7	Four W								
Memorized	6		T. People					not wings		
Forgotten	5			Yellow						
	4				Blue					not blue
	3					not Four W	not T. People		not yellow	
	2		Wings							
Maximally Forgotten	1									



Tsetlin Automata (columns)

**Updated rule: If** (Four W and T. People and not wings) **then** car

# Rule Learning Algorithm

## Initialization:

Set all literals to position 5

## Step 1: Rule Evaluation:

Observe object and evaluate condition by assessing object literals.

## Step 2: Recognize Feedback (Type 1a)

If rule condition is true:

Memorize the object true literals by incrementing position for  $p < \text{Memorization\_value}$ .

Forget the object false literals by decrementing position for  $p < \text{Forget\_value}$ .

## Step 3: Erase Feedback (Type 1b)

If rule condition is false

Forget all literals (True or False) by decrementing position for  $p < \text{Forget\_value}$ .

## Step 4: Reject Feedback (Type 2) – (For a different class)

If rule condition is true:

Increment all forgotten literals ( $\text{pos} \leq 5$ ) that are false for the object (no randomization).

Else: do nothing



# Initialization

All literals initialized at memory position 5

Maximally Memorized	10										
	9										
	8										
	7										
Memorized	6										
Forgotten	5	Four W	T. People	Wings	Yellow	Blue	not Four W	not T. People	not wings	not yellow	not blue
	4										
	3										
	2										
Maximally Forgotten	1										

Updated rule

Condition

: If () then car

: (<empty>) = True (By default)

# Datapoint 1:

Step 1. Rule evaluation:

Condition: (empty) = True

Before

Maximally Memorized	10										
	9										
	8										
	7										
	6										
Memorized											
Forgotten	5	Four W	T. People	Wings	Yellow	Blue	not Four W	not T. People	not wings	not yellow	not blue
	4										
	3										
	2										
	1										
Maximally Forgotten											

## Step 2: Recognize feedback (Type 1a)

Car										
#	Four W	T.People	Wings	Yellow	Blue	not Four W	not T. People	not wings	not yellow	not blue
1	1	1	0	0	1	0	0	1	1	0
Prob.	0.03	0.02	0.50	0.60	0.01	0.80	0.70	0.30	0.20	0.50
Skip Increment if p>0.1	+1	+1			+1			skip	skip	
Skip decrement if p>0.9			-1	-1		-1	-1			-1

# Datapoint 1:

After

Maximally Memorized	10									
	9									
	8									
	7									
Memorized	6	Four W	T. People		Blue					
Forgotten	5							not wings	not yellow	
	4			Wings	Yellow		not Four W	not T. People		not blue
	3									
	2									
Maximally Forgotten	1									

Updated rule : If (Four W and T.People and Blue) then car

## Datapoint 2:

**Step 1. Rule evaluation:** (Four W and T.People and Blue) = (1 and 1 and 0) = **False**

## Before

Maximally Memorized	10										
	9										
	8										
	7										
Memorized	6	Four W	T. People			Blue					
Forgotten	5								not wings	not yellow	
	4			Wings	Yellow		not Four W	not T. People			not blue
	3										
	2										
Maximally Forgotten	1										

### Step 3: Erase feedback (Type 1b)

[illegible]

# Datapoint 2:

After

Maximally Memorized	10									
	9									
	8									
	7									
Memorized	6	Four W								
Forgotten	5		T. People			Blue			not wings	
	4								not yellow	
	3			Wings	Yellow		not Four W	not T. People		not blue
	2									
Maximally Forgotten	1									

Updated rule : If (Four W) then car

# Datapoint 3:

Step 1. Rule evaluation:

(Four W) = (1) = True

Before

Maximally Memorized	10									
	9									
	8									
	7									
Memorized	6	Four W								
Forgotten	5		T. People			Blue			not wings	
	4								not yellow	
	3			Wings	Yellow		not Four W	not T. People		not blue
	2									
Maximally Forgotten	1									

## Step 3: Recognize feedback (Type 1a)

Car										
#	Four W	T.People	Wings	Yellow	Blue	not Four W	not T. People	not wings	not yellow	not blue
1	1	1	0	1	0	0	0	1	0	1
Prob.	0.05	0.01	0.5	0.03	0.6	0.7	0.8	0.95	0.85	0.95
Skip Increment if p>0.1	+1	+1		+1				skip		skip
Skip decrement if p>0.9			-1		-1	-1	-1		-1	

# Datapoint 3:

After

Maximally Memorized	10									
	9									
	8									
	7	Four W								
Memorized	6		T.People							
Forgotten	5							not wings		
	4			Yellow	Blue					
	3								not yellow	not blue
	2			Wings			not Four W	not T. People		
Maximally Forgotten	1									

Updated rule : If (Four W and T.People) then car

## Datapoint 4:

**Step 1. Rule evaluation:** (Four W and T.People) = (1 and 1) = **True**

## Before

Maximally Memorized	10									
	9									
	8									
	7	Four W								
Memorized	6	T.People								
Forgotten	5							not wings		
	4				Yellow	Blue				
	3								not yellow	not blue
	2			Wings			not Four W	not T. People		
Maximally Forgotten	1									

### Step 3: Reject feedback (Type 2)

[illegible]



# Datapoint 4:

After

Maximally Memorized	10									
	9									
	8									
	7	Four W								
Memorized	6		T.People					not wings		
Forgotten	5			Yellow						
	4				Blue					not blue
	3					not Four W	not T. People		not yellow	
	2			Wings						
Maximally Forgotten	1									

Updated rule : If (Four W and T.People and not wings) then car

## Datapoint 5:

**Step 1. Rule evaluation:** (Four W and T.People and not wings) = (1 and 0 and 0) = **False** **Before**

Maximally Memorized	10									
	9									
	8									
	7	Four W								
Memorized	6		T.People					not wings		
Forgotten	5				Yellow					
	4					Blue				not blue
	3						not Four W	not T. People		not yellow
	2			Wings						
Maximally Forgotten	1									

### Step 3: Reject feedback (Type 2)

[illegible]

# Datapoint 5:

After

Maximally Memorized	10									
	9									
	8									
	7	Four W								
Memorized	6		T.People					not wings		
Forgotten	5			Yellow						
	4				Blue					not blue
	3					not Four W	not T. People		not yellow	
	2			Wings						
Maximally Forgotten	1									

Updated rule : If (Four W and T.People and not wings) then car

## Datapoint 6:

**Step 1. Rule evaluation:** (Four W and T.People and not wings) = (0 and 1 and 0) = **False** **Before**

Maximally Memorized	10									
	9									
	8									
	7	Four W								
Memorized	6		T.People					not wings		
Forgotten	5				Yellow					
	4					Blue				not blue
	3						not Four W	not T. People		not yellow
	2			Wings						
Maximally Forgotten	1									

### Step 3: Reject feedback (Type 2)

[illegible]

# Datapoint 6:


After

Maximally Memorized	10									
	9									
	8									
	7	Four W								
Memorized	6		T.People					not wings		
Forgotten	5			Yellow						
	4				Blue					not blue
	3					not Four W	not T. People		not yellow	
	2			Wings						
Maximally Forgotten	1									

Updated rule : If (Four W and T.People and not wings) then car

End of epoch

# Rule coordination



# Resources

- Professor Ole-Christoffer Granmo publications: [Google Scholar Page](#)
- Book (WIP): <https://tsetlinmachine.org/>
- Code and Datasets on GitHub: <https://github.com/cair/TsetlinMachine>
- International Symposium on the Tsetlin Machine (ISTM): <https://istm.no/>
- Python Package: <https://pypi.org/project/pyTsetlinMachine/>