

# PROCESS

1

1

## PROCESS CONCEPT

---

- Program is ***passive*** entity stored on disk (executable file), process is ***active***
  - Program becomes process when executable file loaded into memory

2

2

## PROCESS CONCEPT

---

- Program is **passive** entity stored on disk (executable file), process is **active**
  - Program becomes process when executable file loaded into memory
- Process Control Block (PCB)
  - A data structure created by the OS for each process

3

3

## PROCESS CONCEPT

---

- Program is **passive** entity stored on disk (executable file), process is **active**
  - Program becomes process when executable file loaded into memory
- Process Control Block (PCB)
  - A data structure created by the OS for each process
- One program can be several processes

4

4

## Process Control Block (PCB)

### Process state –

- running, waiting, etc

### Program counter –

- location of instruction to next execute

### CPU registers –

- contents of all process-centric registers

### CPU scheduling information –

- priorities, scheduling queue pointers

### Memory-management information –


- memory allocated to the process

### Accounting information –

- CPU used, clock time elapsed since start, time limits

### I/O status information –

- I/O devices allocated to process, list of open files



5

## Process States

### • As a process executes, it changes **state**

- **new**: The process is being created
- **ready**: The process is waiting to be assigned to a processor
- **running**: Instructions are being executed
- **waiting**: The process is waiting for some event to occur (Waiting = blocked)
- **terminated**: The process has finished execution

6

6

## Events causing a state transition

---

- A new process is created
- The process makes a resource request
- Resource is released
- The process requests an I/O device
- An I/O device is released after access
- The allocated time slice for a process is over. In this case, system timer sends a timer interrupt
- A higher-priority process appears in the ready queue. In this case, the running lower-priority job is pre-empted by a newly arrived higher-priority process
- The process reaches its end of execution or is aborted
- Any hardware interrupt is generated
- An error or exception condition is generated in the current running process

7

7

## Process States


---



8

8


## Process States



9

9


## Process States



10

10


## Process States



11

11


## Process States



12

12


## Process States



13

13

## Process States



14

14

## Process Scheduling

---

- Maximize CPU use, quickly switch processes onto CPU for time sharing
- System queues:
  - **Job queue** – set of all processes in the system

15

15

## Process Scheduling

---

- Maximize CPU use, quickly switch processes onto CPU for time sharing
- System queues:
  - **Job queue** – set of all processes in the system
  - **Ready queue** – set of all processes residing in main memory, ready and waiting to execute

16

16



## Process Scheduling

---

- Maximize CPU use, quickly switch processes onto CPU for time sharing
- System queues:
  - **Job queue** – set of all processes in the system
  - **Ready queue** – set of all processes residing in main memory, ready and waiting to execute
  - **Device queues** – set of processes waiting for an I/O device

17

17

## Process Scheduling

---

- Maximize CPU use, quickly switch processes onto CPU for time sharing
- System queues:
  - **Job queue** – set of all processes in the system
  - **Ready queue** – set of all processes residing in main memory, ready and waiting to execute
  - **Device queues** – set of processes waiting for an I/O device
- Processes migrate among the various queues

18

18

## Schedulers

---

- **Long-term scheduler** (or **job scheduler**)
- **Short-term scheduler** (or **CPU scheduler**)
- **Medium-term scheduler** can be added

19

19

## Schedulers

---

- **Long-term scheduler** (or **job scheduler**)
  - Selects which processes should be brought into the ready queue - invoked infrequently

20

20

## Schedulers

---

- **Long-term scheduler (or job scheduler)**
  - Selects which processes should be brought into the ready queue - invoked infrequently
- **Short-term scheduler (or CPU scheduler)**
  - Selects which process should be executed next and allocates CPU- invoked very frequently  $\Rightarrow$  (must be fast)
  - Sometimes the only scheduler in a system

21

21

## Schedulers


---

- **Long-term scheduler (or job scheduler)**
  - Selects which processes should be brought into the ready queue - invoked infrequently
- **Short-term scheduler (or CPU scheduler)**
  - Selects which process should be executed next and allocates CPU- invoked very frequently  $\Rightarrow$  (must be fast)
  - Sometimes the only scheduler in a system
- **Medium-term scheduler** can be added
  - Remove process from memory, store on disk, bring back in from disk to continue execution: **swapping**

22

22


## Medium Term Scheduling (Swapping)



23

23


## Medium Term Scheduling (Swapping)



24

24

## Medium Term Scheduling (Swapping)



25

25

## Process Definition

- Processes can be described as either type:
  - **I/O-bound process** – spends more time doing I/O than computations, many short CPU bursts

26

26

## Process Definition

---

- Processes can be described as either type:
  - **I/O-bound process** – spends more time doing I/O than computations, many short CPU bursts
  - **CPU-bound process** – spends more time doing computations; few very long CPU bursts

27

27

## Process Definition

---

- Processes can be described as either type:
  - **I/O-bound process** – spends more time doing I/O than computations, many short CPU bursts
  - **CPU-bound process** – spends more time doing computations; few very long CPU bursts
- Long-term scheduler strives for good **process mix**

28

28

## Process Definition

---

- Processes can be described as either type:
  - **I/O-bound process** – spends more time doing I/O than computations, many short CPU bursts
  - **CPU-bound process** – spends more time doing computations; few very long CPU bursts
- Long-term scheduler strives for good **process mix**
- The long-term and medium term scheduler control the **degree of multiprogramming** (number and type of active programs)

29

29

---

## CONTEXT SWITCH

- When CPU switches to another process
  - save the state of the old process and
  - load the saved state for the new process via a context switch

30

30

## Context Switch

---

- When CPU switches to another process
  - save the state of the old process and
  - load the saved state for the new process via a context switch
- **Context** of a process represented in the PCB

31

31

## Context Switch

---

- When CPU switches to another process
  - save the state of the old process and
  - load the saved state for the new process via a context switch
- **Context** of a process represented in the PCB
- Context-switch time is overhead
  - The system does no useful work while switching
  - The more complex the OS and the PCB
    - Longer the context switch

32

32



## Context Switch

---

- When CPU switches to another process
  - save the state of the old process and
  - load the saved state for the new process via a context switch
- **Context** of a process represented in the PCB
- Context-switch time is overhead
  - The system does no useful work while switching
  - The more complex the OS and the PCB
    - Longer the context switch
- Time dependent on hardware support
  - Some hardware provides multiple sets of registers per CPU -> multiple contexts loaded at once

33

33

## Operations on Processes

---

- Creation
- Termination
- Block
- Wake up
- Change priority
- Dispatch

34

34

## Process Creation

---

- **Parent** process creates **children** processes, which, in turn create other processes, forming a **tree of processes**
- Generally, process identified and managed via a **process identifier (pid)**
- Resource sharing options
- Execution options

35

35

## Process Creation

---

- **Parent** process creates **children** processes, which, in turn create other processes, forming a **tree of processes**
- Generally, process identified and managed via a **process identifier (pid)**
- Resource sharing options
  - Parent and children share all resources
  - Children share subset of parent's resources
  - Parent and child share no resources
- Execution options

36

36

## Process Creation

---

- **Parent** process creates **children** processes, which, in turn create other processes, forming a **tree** of processes
- Generally, process identified and managed via a **process identifier (pid)**
- Resource sharing options
  - Parent and children share all resources
  - Children share subset of parent's resources
  - Parent and child share no resources
- Execution options
  - Parent and children execute concurrently
  - Parent waits until children terminate

37

37

## Process Termination

---

- **Voluntary**

- **Involuntary**

38

38

## Process Termination

---

- **Voluntary**
  - Normal exit
  - Internal error or exception
    - Example: exit if no input file is found
- **Involuntary**

39

39

## Process Termination

---

- **Voluntary**
  - Normal exit
  - Internal error or exception
    - Example: exit if no input file is found
- **Involuntary**
  - Fatal error
    - Example: divide by zero/ illegal memory access
  - Explicitly killed by another process
    - Example: task manager

40

40

## Process Termination

---

- Process executes last statement and asks the operating system to delete it
- Output data from child to parent
- Process' resources are deallocated by operating system
- Parent may terminate execution of children processes
  - Child has exceeded allocated resources
  - Task assigned to child is no longer required
  - If parent is exiting
    - Some operating systems do not allow child to continue if its parent terminates
    - All children terminated - **cascading termination**
- If no parent waiting, then terminated process is a **zombie**
- If parent terminated, processes are **orphans**

41

41

## Implicit/System and Non-implicit/User processes

---

There are two types of processes depending on how they are defined and initialized.

If the OS defines a process, it is called an implicit or system process.

If the process is defined by the programmer, then it is an **explicit** or **user process**.

42

42

## Process Relationship

---

Concurrent processes

Independent processes

Interacting/cooperating processes

Parent processes

Child processes

43

43

## Inter-Process Communication (IPC)

---

- Processes within a system may be **independent** or **cooperating**
- Cooperating process can affect or be affected by other processes, including sharing data
- Reasons for cooperating processes:
  - Information sharing
  - Computation speedup
  - Modularity
  - Convenience
- Cooperating processes need **interprocess communication (IPC)**
- Two models of IPC
  - **Shared memory**
  - **Message passing**

44

44