


2D Dynamic Programming

2D because we use two-dimensional array to store solutions

The 0/1 Knapsack Problem



Input: A set of n items,
where item i has weight w_i and value v_i ,
and a knapsack with capacity W .

Goal: Find $x_1, \dots, x_n \in \{0,1\}$ satisfying $\sum_{i=1}^n x_i w_i \leq W$
that maximizes $\sum_{i=1}^n x_i v_i$.

Recall: Greedy doesn't provide optimal solution.

The Recurrence

First Attempt Definition: Let $V[w]$ be the largest obtainable value for a knapsack with capacity w .

First Attempt Recurrence:

If Optimal Solution for knapsack of size w chooses item i , remainder of optimal solution is optimal solution for subproblem of filling knapsack of size $w - w_i$
(1D solution coin denominations)

$$V[w] = \max(0, v_1 + V[w - w_1], v_2 + V[w - w_2], \dots, v_n + V[w - w_n])$$
$$V[j] = 0, j \leq 0$$

WRONG: This may pick the same item more than once! Non-legal Solution!

New 2D definition: Let $V[i, w]$ be the largest obtained value for a knapsack with capacity w , choosing ONLY from the first i items.

Recurrence:

$$V[i, w] = \max(V[i - 1, w], v_i + V[i - 1, w - w_i])$$

$$V[i, w] = 0, i = 0 \text{ or } w = 0$$

Doesn't choose i

Chooses i

So Far

Input: **A set of n items**; item i has weight w_i and value v_i ; **a knapsack with capacity W** .
Goal: Find $x_1, \dots, x_n \in \{0,1\}$ such that $\sum_{i=1}^n x_i w_i \leq W$ and $\sum_{i=1}^n x_i v_i$ is maximized.

Subproblem:

$V[i, w]$ is the largest obtained value for
knapsack with capacity w , choosing ONLY from **items $1, \dots, i$**

Recurrence: $V[i, w] = \max(V[i-1, w], v_i + V[i-1, w - w_i])$

With initial condition, $\forall i, V[i, 0] = 0$

Find Order for filling in table: For $i = 1$ to n
For $w = 1$ to W

Required Solution: $V[n, W]$

DP is 2-Dimensional (2 variables) and not 1-D.

The Algorithm

```

let  $V[0..n, 0..W]$  be a new 2D array of all 0
for  $i \leftarrow 1$  to  $n$  do
    for  $w \leftarrow 1$  to  $W$  do
        if  $w[i] \leq w$  and  $v[i] + V[i-1, w-w[i]] > V[i-1, w]$  then
             $V[i, w] \leftarrow v[i] + V[i-1, w-w[i]]$ 
        else
             $V[i, w] \leftarrow V[i-1, w]$ 
return  $V[n, W]$ 

```

Running time: $\Theta(nW)$

Space: $\Theta(nW)$, but can be improved to $\Theta(n + W)$

i	1	2	3	4
v_i	10	40	30	50
w_i	5	4	6	3

$V[i, w]$	0	1	2	3	4	5	6	7	8	9	10
$i = 0$	0	0	0	0	0	0	0	0	0	0	0
1	0	0	0	0	0	10	10	10	10	10	10
2	0	0	0	0	40	40	40	40	40	50	50
3	0	0	0	0	40	40	40	40	40	50	70
4	0	0	0	50	50	50	50	90	90	90	90

Reconstructing the Solution

Idea: Remember the optimal decision for each subproblem in $keep[i, w]$

```
let  $V[0..n, 0..W]$  and  $keep[0..n, 0..W]$  be a new array of all 0
for  $i \leftarrow 1$  to  $n$  do
    for  $w \leftarrow 1$  to  $W$  do
        if  $w[i] \leq w$  and  $v[i] + V[i - 1, w - w[i]] > V[i - 1, w]$  then
             $V[i, w] \leftarrow v[i] + V[i - 1, w - w[i]]$ 
             $keep[i, w] \leftarrow 1$ 
        else
             $V[i, w] \leftarrow V[i - 1, w]$ 
             $keep[i, w] \leftarrow 0$ 
 $K \leftarrow W$ 
for  $i \leftarrow n$  downto 1 do
    if  $keep[i, K] = 1$  then
        print  $i$ 
         $K \leftarrow K - w[i]$ 
```

Running time: $\Theta(nW)$

Space: $\Theta(nW)$, cannot be improved to $\Theta(n + W)$ due to the $keep$ array.

Longest Common Subsequence

Problem: Given two sequences $X = (x_1, x_2, \dots, x_m)$ and $Y = (y_1, y_2, \dots, y_n)$, we say that $Z = (z_1, z_2, \dots, z_k)$ is a **common subsequence** of X and Y if $x_{i_p} = y_{j_p} = z_p$ for all $p = 1, 2, \dots, k$

where $i_1 < i_2 < \dots < i_k$ and $j_1 < j_2 < \dots < j_k$.

The goal is to find the **longest common subsequence** of X and Y .

Example:


X : A B A C B D A B

Y : B D C A B A

Z : B C B A

The Recurrence


Observation: The problem is equivalent to finding the maximum matching between X and Y such that matched pairs don't cross.



Z : **B C B A** is a solution

The Recurrence

Observation: The problem is equivalent to finding the maximum matching between X and Y such that matched pairs don't cross.




Z : B C B A is a solution

Z' : B A B A is another legal solution

The Recurrence

Def: $c[i, j]$ is length of the longest common subsequence of $X[1..i]$ and $Y[1..j]$.

Observations: The problem is equivalent to finding the maximum matching between X and Y such that matched pairs don't cross.



The recurrence:

- Case 1: If $x_i = y_j$, then we match x_i and y_j .
- Case 2: If $x_i \neq y_j$, then either x_i or y_j is not matched.
Optimal solution reduces to either $c[i - 1, j]$ or $c[i, j - 1]$.

$$c[i, j] = \begin{cases} 0 & \text{if } i = 0 \text{ or } j = 0 \\ c[i - 1, j - 1] + 1 & \text{if } i, j > 0 \text{ and } x_i = y_j \\ \max\{c[i, j - 1], c[i - 1, j]\} & \text{if } i, j > 0 \text{ and } x_i \neq y_j \end{cases}$$

The Recurrence and Algorithm

$$c[i,j] = \begin{cases} 0 & \text{if } i = 0 \text{ or } j = 0 \\ c[i-1,j-1] + 1 & \text{if } i,j > 0 \text{ and } x_i = y_j \\ \max\{c[i,j-1], c[i-1,j]\} & \text{if } i,j > 0 \text{ and } x_i \neq y_j \end{cases}$$

```
let c[0..m,0..n] and b[0..m,0..n] be new arrays of all 0
for i ← 1 to m
  for j ← 1 to n
    if xi = yj then
      c[i,j] ← c[i-1,j-1] + 1
      b[i,j] ← "↖"                                     MATCH xi,yj
    else if c[i-1,j] ≥ c[i,j-1] then
      c[i,j] ← c[i-1,j]
      b[i,j] ← "↑"                                     xi not matched
    else
      c[i,j] ← c[i,j-1]
      b[i,j] ← "←"                                     yj not matched
Print-LCS(b,m,n)
```

Running time: $\Theta(mn)$

Space: $\Theta(mn)$, can be improved to $\Theta(\min(m,n))$ if we only need to return the optimal length.

Reconstruct the Optimal Solution

Print-LCS(b, i, j):

```

    if  $i = 0$  or  $j = 0$  then return
    if  $b[i, j] = "\nwarrow"$  then
        Print-LCS( $b, i - 1, j - 1$ )
        print  $x_i$ 
    else if  $b[i, j] = "\uparrow"$ 
        Print-LCS( $b, i - 1, j$ )
    else Print-LCS( $b, i, j - 1$ )

```

Value of $b[i, j]$ indicates whether

\nwarrow : x_i, y_j matched:

then write x_i and return LCS($i - 1, j - 1$)

\uparrow : x_i not matched

skip x_i and return LCS($i - 1, j$)

\leftarrow : y_j not matched

skip y_j and return LCS($i, j - 1$)

		j	0	1	2	3	4	5	6
		y_j		B	D	C	A	B	A
i	x_i								
0			0	0	0	0	0	0	0
1	A		0	\uparrow 0	\uparrow 0	\uparrow 0	\nwarrow 1	\leftarrow 1	\nwarrow 1
2	B		0	\nwarrow 1	\leftarrow 1	\leftarrow 1	\uparrow 1	\nwarrow 2	\leftarrow 2
3	C		0	\uparrow 1	\uparrow 1	\nwarrow 2	\leftarrow 2	\uparrow 2	\uparrow 2
4	B		0	\nwarrow 1	\uparrow 1	\uparrow 2	\uparrow 2	\nwarrow 3	\leftarrow 3
5	D		0	\uparrow 1	\nwarrow 2	\uparrow 2	\uparrow 2	\nwarrow 3	\uparrow 3
6	A		0	\uparrow 1	\uparrow 2	\uparrow 2	\nwarrow 3	\uparrow 3	\nwarrow 4
7	B		0	\nwarrow 1	\uparrow 2	\uparrow 2	\uparrow 3	\nwarrow 4	\uparrow 4

Longest Common Substring

Problem: Given two strings $X = x_1x_2 \dots x_m$ and $Y = y_1y_2 \dots y_n$, we wish to find their longest common substring Z , that is, the largest k for which there are indices i and j with $x_ix_{i+1} \dots x_{i+k-1} = y_jy_{j+1} \dots y_{j+k-1}$.

Ex:

X : DEADBEEF

Y : EATBEEF

Z : BEEF //pick the longest contiguous substring

Note: Brute-force algorithm takes $O(n^4)$ time.

Different from LCS problem because, in this problem, letters have to be together.

The Recurrence

Def: $d[i, j]$ = the length of the longest common substring of $X[1..i]$ and $Y[1..j]$. (Does this work?)

Def: $d[i, j]$ = the length of the longest common substring of $X[1..i]$ and $Y[1..j]$ **that ends at x_i and y_j .**

Q: Wait, are we changing the problem?

A: Yes, but it's OK. Optimal solution to the original is just $\max_{i,j} \{d[i, j]\}$

Recurrence:

- If $x_i = y_j$, then the LCS of $X[1..i]$ and $Y[1..j]$ is just the LCS of $X[1..i - 1]$ and $Y[1..j - 1]$, plus $x_i = y_j$
- If $x_i \neq y_j$, then there can't be a common substring ending at x_i and y_j !

$$d[i, j] = \begin{cases} d[i - 1, j - 1] + 1 & \text{if } x_i = y_j \\ 0 & \text{if } x_i \neq y_j \end{cases}$$

The Algorithm

```
let  $d[0..m, 0..n]$  be a new array of all 0
 $l_m \leftarrow 0, p_m \leftarrow 0$ 
for  $i \leftarrow 1$  to  $m$ 
    for  $j \leftarrow 1$  to  $n$ 
        if  $x_i = y_j$  then
             $d[i, j] \leftarrow d[i - 1, j - 1] + 1$ 
            if  $d[i, j] > l_m$  then
                 $l_m \leftarrow d[i, j]$ 
                 $p_m \leftarrow i$ 
for  $i \leftarrow p_m - l_m + 1$  to  $p_m$ 
    print  $x_i$ 
```

Note: For this problem, reconstructing the optimal solution just needs the location of the LCS.

Running time: $\Theta(mn)$

Space: $\Theta(mn)$ but can be improved to $\Theta(\min(m, n))$.

Exercise on Edit Distance

Given two strings s and t , the edit distance $edit(s, t)$ is the smallest number of following edit operations to turn s into t :

Insertion: add a letter

Deletion: remove a letter

Substitution: replace a character with another one.

Example: $s = \text{abode}$ and $t = \text{blog}$.

Then, $edit(s, t) = 4$ operations

Start from **abode**

1 delete a \Rightarrow **bode**

2 insert l after b \Rightarrow **blode**

3 delete d \Rightarrow **blo**e

4 substitute e with g \Rightarrow **blog**

Impossible to do so with at most 3 operations.

Exercise on Edit Distance (cont)

Let s and t be two strings with lengths m and n , respectively.

Case 1 If $m = 0$, then $\text{edit}(s, t) = n$.

Case 2 If $n = 0$, then $\text{edit}(s, t) = m$.

Case 3 If $m > 0, n > 0$, and $s[m] = t[n]$, then

$$\text{edit}(s, t) = \min \begin{cases} 1 + \text{edit}(s[1..m], t[1..n-1]) \\ 1 + \text{edit}(s[1..m-1], t[1..n]) \\ \text{edit}(s[1..m-1], t[1..n-1]) \end{cases}$$

Explanation of Case 3

- Delete $t[n]$, and use the least number of edit operations to change $s[1..m]$ into $t[1..n-1]$. The total number of edit operations is therefore $1 + \text{edit}(s[1..m], t[1..n-1])$. (example: $s = abc, t = abcc$)
- Delete $s[m]$, and use the least number of edit operations to change $s[1..m-1]$ into $t[1..n]$. The total number of edit operations is therefore $1 + \text{edit}(s[1..m-1], t[1..n])$. (example: $s = abcc, t = abc$)
- Simply change $s[1..m-1]$ into $t[1..n-1]$. The total number of edit operations is therefore $\text{edit}(s[1..m-1], t[1..n-1])$. (example: $s = abcc, t = abcc$)

Exercise on Edit Distance (cont2)

Case 4 If $m > 0, n > 0$, and $s[m] \neq t[n]$, then

$$\text{edit}(s, t) = \min \begin{cases} 1 + \text{edit}(s[1..m], t[1..n-1]) \\ 1 + \text{edit}(s[1..m-1], t[1..n]) \\ 1 + \text{edit}(s[1..m-1], t[1..n-1]) \end{cases}$$

Lets store $\text{edit}(i, j)$ in an array $E[i, j]$. Then

$$E[i, j] = \min \begin{cases} 1 + E[i, j-1] \\ 1 + E[i-1, j] \\ \begin{cases} E[i-1, j-1], & \text{if } s[i] = t[j] \\ 1 + E[i-1, j-1], & \text{if } s[i] \neq t[j] \end{cases} \end{cases}$$

DP Algorithm for filling array E

1 Fill in row 0 and column 0.

2 Fill in the cells of row 1 from left to right.

3 Fill in the cells of row 2 from left to right.

4 ...

5 Fill in the cells of row m from left to right.