

# **Autonomous Energy Optimization Platform for Smart Grids**

**Submitted by:** Aditi Mehta

**Celebal ID:** CT\_CSI\_DS\_20

Celebal Excellence Internship Program (Data Science) 2026

**Institution:** Amity University, Noida

## **ABSTRACT**

The rapid evolution of smart grid technology necessitates advanced analytical tools to ensure reliability and efficiency. This project introduces an autonomous energy optimization platform designed to forecast household energy consumption with high precision and provide real-time decision-making support for grid operators. By leveraging an XGBoost Regressor trained on the London Smart Meter dataset, the model captures complex temporal dependencies in energy usage. Furthermore, the implementation of SHAP (SHapley Additive exPlanations) provides a transparent, explainable layer to the decision-making process, replacing opaque "black-box" models. This report outlines the development of the MLOps pipeline, the technical architecture, and the impact of predictive analytics on modern grid stability.

## **INTRODUCTION**

Energy consumption globally is shifting toward decentralization, driven by the integration of renewable sources and IoT-enabled smart meters. Traditional power grids, however, often rely on reactive management systems that struggle to anticipate sudden load fluctuations. This limitation results in significant energy waste and increased risk of grid failure during peak hours.

This project addresses these challenges by developing an intelligent system that predicts energy demand and autonomously triggers grid-balancing protocols. The core focus is to create a system that is not only accurate but also interpretable, allowing human operators to understand the reasoning behind every machine-driven decision.

## **LITERATURE REVIEW**

Historically, energy load forecasting relied on basic statistical models such as ARIMA or Exponential Smoothing. While effective for stable conditions, these models fail to account for the non-linear variables present in modern household consumption, such as weather volatility and changing social habits.

The emergence of Machine Learning, particularly ensemble methods like Gradient Boosting, has revolutionized this domain. By modeling energy as a time-series problem with exogenous environmental variables, we can achieve error rates significantly lower than traditional methods. Additionally, recent research highlights the necessity of Explainable AI (XAI) in critical infrastructure, emphasizing that predictive accuracy alone is insufficient without the ability to audit the AI's decision-making logic.

## **METHODOLOGY**

### **1. Dataset Description**

The model utilized the London Smart Meter dataset, which includes high-resolution consumption data from thousands of households. The features included temporal data (time of day, day of week) and environmental data (temperature).


### **2. Feature Engineering**

Feature engineering was the primary driver of model performance.

- **Rolling Means:** 24-hour rolling averages were calculated to smooth out short-term noise.
- **Lag Features:** 1-hour and 24-hour lags were created to account for historical momentum.
- **Normalization:** All inputs were scaled to a range of 0–1 to ensure stable gradient descent during training.

### **3. Model Selection: XGBoost**

XGBoost was chosen for its ability to handle large-scale structured data through decision tree ensembling. Unlike neural networks, XGBoost provides highly interpretable feature importance scores, which were vital for the explainability component of this project.



*Figure 1: SHAP analysis showing feature contribution to energy forecast.*

This visual demonstrates that historical usage patterns and temporal factors are the primary predictors for load forecasting. The transparency provided by SHAP allows grid operators to trust the model, as they can verify that the AI is prioritizing logical variables rather than finding spurious correlations in the data.

## IMPLEMENTATION & ARCHITECTURE

The system employs an MLOps-inspired architecture to decouple heavy model training from real-time usage:

1. **Training Phase:** Performed in a cloud environment (Kaggle), allowing for hyperparameter tuning and massive data processing.
2. **Inference Phase:** The trained model was serialized into a lightweight `.json` format, which is then loaded into a local dashboard developed in Streamlit.
3. **Communication Layer:** A Flask-based API serves as the middleware, receiving sensor input and returning real-time predictions.




Figure 2: Snapshot of the Dashboard

RESULTS & DISCUSSION

Table 1: The system's performance was evaluated using standard regression metrics.

| Metric                         | Value      |
|--------------------------------|------------|
| Root Mean Squared Error (RMSE) | 0.3319 kWh |
| Mean Absolute Error (MAE)      | 0.1669 kWh |

These results indicate that the model is highly robust. Furthermore, the dashboard includes a safety trigger logic: if the predicted load exceeds 1.5 kWh, the system automatically transitions the status to "CRITICAL," recommending load-shedding actions.

## **FUTURE SCOPE & CONCLUSION**

### **Future Scope**

- **Integration with Renewable Energy:** Incorporating solar irradiance data to predict supply vs. demand.
- **City-Level Scalability:** Applying the current model to decentralized micro-grids.
- **Digital Twin Development:** Creating a fully simulated environment of a local city grid.

### **Conclusion**

This project successfully demonstrated that AI can be integrated into critical energy infrastructure to provide real-time optimization. By prioritizing both accuracy and explainability, this platform provides a blueprint for future smart energy systems.

## **REFERENCES**

1. Dataset: <https://www.kaggle.com/datasets/jeanmidev/smart-meters-in-london>
2. Documentation, Streamlit & Flask Frameworks (2026).