

12. Playwright MCP Setup and Testing

Goal

Use OpenCode to automate browser interactions, including:

AI Agent

↓

Open website

↓

Enter username/password

↓

Login

↓

Navigate pages

↓

Extract information

Step 1: Verify Playwright MCP Is Available

Open Command Prompt:

Verify Playwright MCP:

```
npx -y @playwright/mcp --help
```

Expected:

Usage: Playwright MCP [options]

If this command works, Playwright MCP is installed and available.

Step 2: Install Playwright Browsers

Playwright requires browser binaries.

Run:

```
npx playwright install
```

This downloads:

- Chromium

- Firefox
- WebKit

Expected output:

Downloading Chromium...

Downloading Firefox...

Downloading WebKit...

Done

Step 3: Backup Current OpenCode Configuration

Create a backup:

copy opencode.json opencode-browsermcp.json

Verify:

dir *.json

Expected:

opencode.json

opencode-browsermcp.json

Step 4: Create Playwright Configuration

Open Notepad:

notepad opencode-playwright.json

Paste:

```
{
"$schema": "https://opencode.ai/config.json",
"mcp": {
  "playwright": {
    "type": "local",
    "command": [
      "npx",
      "-y",
      "@playwright/mcp"
    ]
  }
}
```

```
],  
  "enabled": true  
}  
}  
}
```

Save and close Notepad.

Step 5: Start OpenCode with Playwright Configuration

Open Command Prompt:

```
set OPENCODE_CONFIG=opencode-playwright.json  
opencode
```

Step 6: Verify MCP Connection

Inside OpenCode:

```
/mcp
```

Expected:

```
playwright  
connected
```

Step 7: First Playwright Test

Prompt:

Using Playwright,

open <https://example.com>

tell me:

1. page title
2. main heading

Expected:

Title: Example Domain

Heading: Example Domain

Step 8: Login Automation Test

Prompt:

Using Playwright,

go to

<https://quotes.toscrape.com/login>

login using:

username: admin

password: admin

tell me whether login succeeded

Expected:

Login successful

Step 9: Form Inspection Test

Prompt:

Using Playwright,

go to

<https://quotes.toscrape.com/login>

identify all form fields

Expected:

Username field

Password field

Login button

Step 10: Research Extraction Example

Prompt:

Using Playwright,

go to <https://arxiv.org>

search for:

quantum machine learning

open the first 3 papers

create a table containing:

- title
- authors
- summary

BrowserMCP vs Playwright

Use BrowserMCP when:

You are already logged into Chrome.

Examples:

- Google Scholar
- ASU systems
- Canvas
- Microsoft 365
- GitHub

Workflow:

Human logs in

↓

Browser stores session

↓

AI reuses session

Use Playwright when:

AI should perform login automatically.

Workflow:

AI opens login page

↓

AI enters credentials

↓

AI logs in

↓

AI extracts information

Common Playwright Issues

Issue:

playwright not listed in /mcp

Fix:

```
npx -y @playwright/mcp --help
```

Issue:

Browser fails to start

Fix:

```
npx playwright install
```

Issue:

MFA-protected site fails

Examples:

- Duo
- Microsoft Authenticator
- Google Prompt
- Passkeys

Recommendation:

Use BrowserMCP instead because BrowserMCP can reuse an already authenticated Chrome session.

