

BrowserMCP + OpenCode Setup Summary (Windows 11)

Goal

Use OpenCode to access and extract information from websites where you are already logged in through Chrome.

```
You login to website
      ↓
Chrome stores cookies/session
      ↓
Browser MCP Extension
      ↓
OpenCode
      ↓
AI reads authenticated content
```

1. Install Node.js

Download

Official site:

<https://nodejs.org>

If you do not have administrator rights, download the **Windows ZIP (x64)** version:

<https://nodejs.org/en/download>

Look for:

Windows Binary (.zip)

Extract to:

C:\Users\<username>\Tools\node

Add to PATH temporarily:

```
set PATH=C:\Users\<username>\Tools\node;%PATH%
```

Verify:

```
node --version
npm --version
npx --version
```

2. Install OpenCode

Install:

```
npm install -g opencode-ai
```

Verify:

```
opencode --version
```

Example:

```
1.17.7
```

3. Install OpenCode Browser Integration

Run:

```
npx opencode-browser init
```

What is `opencode-browser`?

`opencode-browser` is an OpenCode plugin that automatically configures OpenCode to use BrowserMCP.

Repository:

```
https://github.com/michaljach/opencode-browser
```

It is **not** BrowserMCP itself.

Think of it as:

```
OpenCode
  ↓
opencode-browser plugin
  ↓
Browser MCP
  ↓
Chrome
```

The command:

```
npx opencode-browser init
```

creates:

```
opencode.json
```

and configures BrowserMCP automatically.

Expected output:

```
Created opencode.json
```

```
Applied changes:
```

- added OpenCode schema
 - enabled opencode-browser plugin
 - set Browser MCP type
 - set Browser MCP command
 - enabled Browser MCP server
-

4. Install Browser MCP Extension

Browser MCP website:

```
https://browsermcp.io
```

Chrome extension:

```
Browser MCP
```

Verify:

```
chrome://extensions
```

You should see:

```
Browser MCP  
Enabled
```

5. Pin Browser MCP to Toolbar

Chrome:

```
Puzzle Piece (Extensions)  
    ↓  
Browser MCP  
    ↓  
Pin
```

The Browser MCP icon should appear near the address bar.

6. Connect Browser MCP

Click:

Browser MCP icon



Connect

This establishes the connection between Chrome and OpenCode.

7. Start OpenCode

opencode

8. Verify MCP Connection

Inside OpenCode:

/mcp

Expected:

browsermcp
connected

9. Test Browser Control

Prompt:

Open `https://example.com` and tell me the page title.

Expected:

Example Domain

10. Test Logged-In Session

Login to GitHub in Chrome.

Prompt:

```
Go to github.com and tell me which account is logged in.
```

Expected:

```
GitHub username detected
```

11. Real Research Example

Login to Google Scholar.

Prompt:

```
Open my Google Scholar profile.
```

```
Create a table containing:
```

- title
- year
- citation count

or

```
Summarize my publication record.
```

Important Concept

BrowserMCP is **not designed to replace login**.

The intended workflow is:

```
You login manually
```

```
↓
```

```
Chrome stores authentication
```

```
↓
```

```
Browser MCP reuses session
```

```
↓
```

```
OpenCode extracts information
```

This works particularly well for:

- Google Scholar
- Microsoft 365
- Canvas
- GitHub
- Research portals
- MFA-protected websites

because the AI can leverage the authenticated browser session that already exists.

Common Issues and Fixes

Issue 1: npm ping returns ETIMEDOUT

Symptoms

npm ping

returns:

npm ERR! code ETIMEDOUT

npm ERR! network request to <https://registry.npmjs.org/>

Possible Causes

- VPN blocking npm traffic
- Corporate/university firewall
- Node.js cannot reach the npm registry

Diagnosis

curl -I <https://registry.npmjs.org/>

If curl works but npm ping fails, the issue is usually VPN or Node-specific network restrictions.

Fix

- Disconnect VPN and test again.
- Try a different network (home Wi-Fi or hotspot).
- Verify:

npm ping

should return:

npm notice PONG

Issue 2: npx opencode-browser init fails

Symptoms

npx opencode-browser init

fails with download or timeout errors.

Possible Causes

- npm registry access problem
- VPN/firewall restrictions

Fix

First verify:

npm ping

works.

Then rerun:

npx opencode-browser init

Issue 3: Browser MCP Extension Installed but OpenCode Says "No Connection"

Symptoms

OpenCode reports:

Still no connection.

Please click the Browser MCP extension icon and select Connect.

Cause

The Browser MCP extension is installed but not connected.

Fix

1. Open Chrome.
2. Click the Browser MCP icon.
3. Click:

Connect

4. Retry in OpenCode.

Issue 4: Browser MCP Icon Not Visible

Symptoms

Browser MCP is installed but there is no icon in the toolbar.

Fix

Open:

chrome://extensions

Verify:

Browser MCP

Enabled

Then:

Puzzle Piece (Extensions)



Browser MCP



Pin

The icon should appear next to the address bar.

Issue 5: Browser MCP Installed but Not Listed in Extensions Menu

Symptoms

You cannot find Browser MCP in the toolbar.

Fix

Open:

`chrome://extensions`

Check:

Browser MCP

Enabled

If disabled, enable it.

If missing, reinstall the extension.

Issue 6: OpenCode Cannot Find Browser MCP

Symptoms

Inside OpenCode:

`/mcp`

does not show:

`browsermcp`

Possible Causes

- `opencode-browser` plugin not configured
- `opencode.json` missing or corrupted

Fix

Re-run:

`npx opencode-browser init`

Verify that `opencode.json` contains a `BrowserMCP` section.

Issue 7: Browser Opens but AI Cannot Read the Page

Symptoms

Chrome opens the page but OpenCode cannot extract information.

Possible Causes

- Browser MCP not connected
- Site blocks access
- Page not fully loaded

Fix

1. Verify Browser MCP status:

/mcp

2. Retry after page loads.
3. Test with:

Open <https://example.com> and tell me the page title.

If this works, Browser MCP is functioning.

Issue 8: Authenticated Site Asks for Login Again

Symptoms

A site previously worked but now asks for credentials.

Cause

The website session expired.

Fix

Log in again manually in Chrome.

Browser MCP reuses existing authenticated sessions but does not bypass authentication or MFA.

Issue 9: Chrome Login Works but OpenCode Cannot See Logged-In State

Symptoms

You are logged into GitHub/Google Scholar, but OpenCode reports no user logged in.

Possible Causes

- Browser MCP not connected
- Multiple Chrome profiles
- OpenCode attached to a different browser session

Fix

1. Ensure Browser MCP is connected.
 2. Use the same Chrome profile where you logged in.
 3. Close unused Chrome profiles and retry.
-

Issue 10: University VPN Causes Browser MCP or npm Problems

Symptoms

- npm timeouts
- Browser MCP connection failures
- OpenCode cannot reach MCP servers

Cause

VPN routing or filtering.

Fix

Temporarily disconnect VPN and test:

npm ping

If connectivity returns, the VPN is the source of the issue.

Quick Health Check

When everything is working:

node --version

npm --version

opencode --version

npm ping

should succeed, and inside OpenCode:

/mcp

should show Browser MCP connected.

Then:

Open <https://example.com> and tell me the page title.

should return:

Example Domain

At that point, you are ready to use Browser MCP with authenticated websites such as Google Scholar, ASU systems, GitHub, Microsoft 365, Canvas, and research portals.