

DSLVSZPDI / FIELD BOOK

Rev 3.5 Install and User Guide

Phone-ready campaign record for
GrapheneOS on a Pixel 9 Pro XL

INSTALL ADDRESS

<https://dslv-vac-probe.grok.me>

FIELD DOCTRINE

The handset keeps the campaign record. The SDR, GPS-disciplined oscillator, and prompt correlator remain on the DSLVSZPDI nodes.

PURPOSE AND LIMITS

Read this first

This is the campaign record beside the array, not a second simulator.

The field book does not make a measurement

It does not synthesize IQ, residuals, magnitude-squared coherence, or a detection. It records what the node reduction produced and enforces the Rev 3.5 gates.

- **No Play Store package.** Install the published web app directly from its HTTPS address.
- **No account.** The campaign book lives in on-device site storage in the browser profile where you install it.
- **No cloud copy.** Export at every frozen milestone and before clearing site data, changing origins, or removing a campaign.
- **A local hash is not a pre-registration.** The SHA-256 must also be externally anchored and the anchor transaction ID recorded.
- **A null is a valid result.** Chain S and Chain C produce separate bounds under separate hypotheses.

FIELD REFERENCE

Contents

Install	04	Permissions	05
Screens	06	Open a campaign	07
Walk and gates	08	Steps 1-3	09-11
Registry	12-14	Calibration & injection	15-17
Baselines & freeze	18-19	Science logs	20-23
Publish	24	Bench	25
Book	26-27	Kill switches	28-29
Reading labels	30	Record care	31
Troubleshooting	32-33		

VANADIUM / NORMAL TAB

Install on GrapheneOS

Install from the published HTTPS origin. A chat preview or another hostname is a different site and a different book.

- 1 On the Pixel, open **Vanadium**. It is GrapheneOS's browser and does not require Play Services.
- 2 Use a **normal tab**, not Incognito. Open <https://dslv-vac-probe.grok.me>.
- 3 Confirm the padlock and the exact host **dslv-vac-probe.grok.me**.
- 4 Tap the three-dot menu at top right.
- 5 Tap **Install app** if offered. If the menu instead says **Add to home screen**, use that.
- 6 Confirm the name, place the icon, then open the field book from the home screen.

If Add to home screen seems to do nothing

Press and hold the shortcut icon in the placement sheet and drag it onto the home screen. This works around a Vanadium quirk seen on some builds.

Stock Android / Chrome

Chrome on a stock Pixel uses the same menu choices: **Install app** or **Add to Home screen**. The book remains local to that Chrome profile. Do not install it in Incognito.

GRAPHENEOS CONTROLS

Permissions worth setting once

Control	Set it this way
Network	Allow Vanadium network access. Without it, the site cannot load.
Location	Optional. Needed only for Capture a device fix. You may deny it and enter surveyed coordinates.
JIT	Leave off unless a loaded screen stays blank; then allow JIT for this origin only in Vanadium site settings.
Storage	Do not clear site data for this origin until you have exported. There is no cloud copy.
Updates	Open the published address again. The home-screen icon continues to point to that origin.

Location is not carrier phase

A handset fix is a GNSS position with an accuracy estimate and timestamp. It is not a monument, a residual, or a carrier-phase measurement. The fix is not uploaded by this app.

Two layers of location permission

- 1 Grant or deny Location under the Pixel app permission for Vanadium.
- 2 If granted, answer the site prompt for this origin.
- 3 Read the fix, accuracy, time, and source label before saving. A surveyed coordinate can be entered instead.

NAVIGATION

Five screens, one campaign book

Screen	Address	Job
Deck	https://dslv-vac-probe.grok.me/	Open a campaign; review freeze, roster, and formula identity.
Walk	https://dslv-vac-probe.grok.me/walk	Run the thirteen gated steps.
Bench	https://dslv-vac-probe.grok.me/bench	Use closed-form calculators; no automatic log writes.
Book	https://dslv-vac-probe.grok.me/book	Notes, log, export, import, and delete.
Switches	https://dslv-vac-probe.grok.me/doctrine	Kill switches, epistemic labels, and handset limits.

Navigation rule

The five tabs sit at the bottom of the screen. After a record exists, the campaign picker appears in the header.

The address links above are the production origin supplied for this release. A different hostname uses different site storage and therefore opens a different local book.

DECK

Open a campaign

- 1 **Name the campaign.** Campaign name is required. Operator and site may be blank, but they belong in the registry.
- 2 Tap **Create the record.** The record is stored only on this handset.
- 3 Replace catalog budget rows with measured values when available. Catalog rows remain explicitly labeled until replaced.
- 4 Use the header menu to switch campaigns. One handset can hold several, but they do not sync.
- 5 Read the deck status: node count, log count, completed pre-registration fields, and whether a common-clock floor is present.
- 6 Use **Continue the walk** to return to the step you left.

Formula identity is an app self-check

The deck compares closed forms with the registered Rev 3.5 identities. A miss is an app bug, not a residual or measurement. Do not interpret it as physics.

THIRTEEN STEPS

The Walk is gated

The top bar can jump between steps, but Next remains disabled until the current gate is satisfied. Back is always allowed.

Step	Gate to leave it
1, 2, 7	Tick “I have read this step against the paper.”
3	At least two fully identified nodes for Phase 0; four nodes for detection-grade disjoint-pair analysis.
4	All pre-registration fields except calibration floor and bias hash.
5	Calibration results, transferability record, and bias-file hash; export prompted after append.
6	At least one injection log: recovered, missed, or sealed.
8	SHA-256 frozen, externally anchored, anchor ID recorded, and JSON exported.
9-12	Frozen and externally anchored registry plus acknowledgement. Empty science log is allowed.
13	Campaign-close export is required from Book.

Operator rule

Read the plate and paragraphs, then enter only what you actually did. A silent skip is not allowed; “no measurement this session” is an honest record.

WALK / STEP 1

1. Name the hypotheses

H_S Sky gradient / Chain S

The estimator input is a between-node double difference of between-satellite single differences. It is blind to isotropic site phase. A null on Chain S does not constrain H_C.

H_C Correlated site-common differential / Chain C

The estimator input is a same-satellite inter-node difference. A phase literally identical at every antenna cancels and is unobservable; H_C is the correlated site-common term that differs between sites and survives the difference.

Expected outcome

A null is expected. The bound is the product; no amplitude or coupling model is assumed.

WALK / TRACKING PATH

2. From carrier to estimator

The field book records the reduction; carrier reconstruction and differencing occur on the node pipeline.

- **Raw IQ stays on nodes.** The phone does not hold the wideband ring buffer.
- **Tracking records the full carrier observable.** Use NCO carrier phase plus prompt-discriminator residual at the registered dump rate f_d . $\text{atan2}(Q, I)$ alone omits in-band phase absorbed by the loop.
- **Wipe bits and handle slips.** Apply L1 data-bit wipeoff and the frozen cycle-slip detection, repair, and exclusion procedure.
- **Chain S uses the double difference.** It cancels receiver clocks and the shared satellite-clock product error exactly. Per-node post-IGS single differences are diagnostics, not detection inputs.
- **Chain C keeps receiver clock.** Below the GPSDO steering bandwidth, nodes are one clock; exclude those frequencies on both chains.

Named inputs

Analyses A and B consume two disjoint node-pair series. The chain, satellite or satellite pair, band, and pair-of-pairs identifiers belong in the archive.

WALK / NODE ROSTER

3. Put the array on the page

Add at least two nodes for Phase 0. Detection-grade Analysis A requires four nodes so each statistic can use two disjoint node pairs. Every node needs a stable identity and measured clock behavior.

Field	Record
Name	Stable node identifier.
GPSDO identity	Installed unit and serial, not a catalog class.
Measured sigma_y at 1 s	Unitless Allan deviation of this installed unit.
f_loop	Measured steering-loop bandwidth in hertz.
Antenna	Installed antenna identity.
Latitude / longitude	Surveyed coordinate or labeled device fix.

Clock readout

The page computes sigma_phi at L1 and $\tau = 1\text{ s}$ as $2\pi f \tau$ sigma_y. Chain S cancels this clock term. Chain C does not.

- **Capture a device fix** records the phone solution, accuracy, time, and source label.
- **Surveyed coordinates** may be typed directly and are labeled surveyed.
- **No coordinate** means no baseline and no later lag claim.
- **Two identified nodes** form one pair for Phase-0 validation; **four** are the detection-grade minimum for two disjoint pairs.

WALK / PRE-REGISTRATION I

4. Write the registry

Enter the real plan before the run. Nothing is seeded, and nothing should be tuned after freeze.

Field	What belongs there
Science band	L1 + L5. Another band needs its own ionospheric row and spectrum-survey hash.
Spectrum hash	The real SHA-256; the app does not invent one.
Dump rate f_d	Hertz; nominally 1-10 kHz; fixed before freeze.
Elevation mask	Degrees; excluded satellites never enter a chain.
Analysis A window	Seconds; non-overlapped.
Block length	Frozen Politis-White value from pilot data, reconciled with Allan turnover.
Allan cross-check	Measured sigma_y(tau) turnover of installed units.
FDR procedure	Benjamini-Hochberg under PRDS; S and C are separate families.
Catalog / G_km	Transmitter catalog version and site multipath-model version.
Named inputs	For each chain, record the two disjoint node-pair series used by Analyses A and B.

WALK / PRE-REGISTRATION II

4. Finish the registry

Field	What belongs there
Analysis B grid	Half-width M in units of tau_c; include 0, +/-tau_c, +/-tau_iono, +/-tau_trop, and +/-M tau_c.
Slides and FAR	Time-slide count and joint false-alarm rate on post-subtraction residual streams.
Hold-out	Post-window data excluded from detection statistic; must confirm morphology independently.
IQ buffer	Depth in seconds; example 300 s. Trigger dumps coordinate across nodes; IQ stays on nodes.
Time transfer	Method and sigma_sync per baseline class.
Open injections	Amplitudes, lags, and chain class: correlated site-common differential for C, direction-differential for S.

Time-transfer shorthand

At 10 km, common-view GNSS may be suitable. At sub-kilometre scale, register White Rabbit or two-way optical transfer. In every case, state the achieved sigma_sync.

WALK / PRE-REGISTRATION III

4. Validation fields

Field	What belongs there
Blind injections	Count and distributions; register mechanism, never the seed.
Injection holder	Identity of a non-analyst.
Switch 2 tolerance	Relative tolerance and multi-component mixture policy for ϕ_1 / ϕ_2 ; example tolerance 0.05.
Phase-0 validation	Residual floor, measured L_{eff} , injection recovery, empirical false-positive rate, and bound coverage before any search claim.
Calibration transfer	Repeat schedule, interleaved spot checks, drift tolerance, and per-baseline atmospheric treatment.

Leave calibration values for Step 5

The measured calibration floors and L1/L5 inter-channel bias hash belong to the common-clock run, not this step.

Phase 0 comes first

A two- or three-node campaign validates the instrument and null. Detection-grade Analysis A begins only after four ready nodes and two disjoint node-pair inputs are frozen.

WALK / COMMON-CLOCK CALIBRATION

5. Split one clock

One GPSDO output drives two complete front ends at one site, with independent RF paths and antennas about a metre apart.

- 1 Record the **common-clock residual RMS** in radians. It measures the co-located non-clock floor for that hardware and site.
- 2 Record the **independent-clock co-located RMS**. When the independent value is larger, isolate the relative-clock term as the square root of ($\sigma_{\text{indep}}^2 - \sigma_{\text{common}}^2$).
- 3 Record the **L1/L5 inter-channel bias file hash**, thermal conditions, and the scheduled interleaved spot checks.
- 4 Describe what the run actually did, then tap **Append the calibration** and immediately export the campaign JSON.

A failed decomposition stops the campaign

If the common-clock run is noisier than the independent-clock run, the decomposition failed and Switch 3 fires. No science claim is permitted.

WALK / CHAIN C FLOOR

5. Bound calibration transfer

What the run measures

Front-end and splitter phase, inter-channel bias, thermal drift in the calibration environment, and co-located multipath, RFI, and supply effects.

What it does not reproduce

Far-site tropospheric differential, decorrelated far-site multipath, or independent GPSDO drift at separated sites.

- Add measured drift variance between repeat runs in quadrature.
- Retain the atmospheric and per-site multipath rows for every distributed baseline.
- Repeat the calibration per campaign and run the registered interleaved spot checks.
- If a spot check exceeds the frozen tolerance, Switch 3 stops the campaign until repair.

Per-baseline maximum

The Chain C bound is the maximum of the co-located non-clock floor, isolated relative-clock contribution, and baseline atmospheric differential RSS. Never quote a tighter number.

WALK / INJECTION AND RECOVERY

6. Prove the pipeline

Open injections test the pipeline. Blind injections test the analysts.

Injection class	Required signature
Isotropic site-common	Appears on Chain C and vanishes on Chain S.
Direction-differential	Appears on Chain S in the registered form.
Injection off	Returns to the null floor.

- **Recovered:** amplitude, lag, and chain pattern land inside the registered tolerance.
- **Not recovered:** Switch 3 is live; the campaign cannot support a science claim.
- **Still sealed:** tick the sealed state and do not enter an amplitude.
- **End-to-end null trials:** inject into realistic residuals with nonstationarity, shared satellite errors, steering, geometry changes, and gaps; record empirical false-positive rate and bound coverage.

Gate

At least one injection line - recovered, missed, or still sealed - must be in the book before leaving this step.

A chain that fails its distinctive injection, empirical false-alarm target, or coverage target has no standing to report an excess.

WALK / BASELINES

7. Mark resolution limits

For each surveyed pair, the app combines baseline distance with f_d . Light time is $\tau_c = d / c$; native lag resolution is one dump sample.

- **No coordinates:** no baseline and no lag claim.
- **Resolution-limited:** the pair may still enter Analysis A, but it does not get a spacelike-morphology sentence.
- **Morphology requirement:** the claim $|\tau|$ much less than τ_c requires τ_c much larger than $1/f_d$.
- **Synchronization still matters:** even a long-enough baseline needs σ_{sync} much less than τ_c .

Regional baseline caution

At nominal prompt-dump rates, many regional baselines remain resolution-limited. Raising the dump rate after freeze is not a valid repair.

WALK / REGISTRY COMMITMENT

8. Freeze and anchor

The app can compute a digest; only an independent timestamp turns that digest into an externally verifiable pre-registration.

- 1 Freeze only when the registry, required nodes, calibration fields, and bias hash are present.
- 2 Let the app hash the canonical registry with SHA-256 and stamp the handset time. Treat this local stamp as **self-attested**.
- 3 Anchor the hash through an OSF preregistration, a signed git tag in the public DSLV-ZPDI repository, or an OpenTimestamps / RFC-3161 timestamp.
- 4 Record the external anchor transaction ID in the registry, then export the campaign JSON immediately.
- 5 After freeze, science logs are append-only; node and registry edits lock.

Amendments create a new commitment

Give the reason, preserve the prior digest, re-freeze, create a fresh external anchor, record its transaction ID, and export again before new science entries.

WALK / STATIONARY COHERENCE

9. Enter Analysis A

You may draft the arithmetic before freeze. Logging stays disabled until the registry is frozen.

Input	Meaning
Chain and named inputs	S: two disjoint double-difference series. C: two disjoint same-satellite inter-node difference series. The bounds remain separate.
Measured gamma-hat	From the node reduction, not generated on the phone.
Duration T	Analyzed duration.
tau_corr	Measured residual correlation time.

The page computes $L_{eff} = T / \tau_{corr}$, the Beta-null expectation $E[\gamma\text{-hat}] = 1 / L_{eff}$, and the ratio $\gamma\text{-hat} / E[\gamma\text{-hat}]$. The ratio is not a detection threshold.

Calendar seconds are not independent

The large-L floor using $L = 86,400$ is the paper’s trap, not the program floor. Use the measured effective count or the registered bootstrap.

- Call the entry **consistent with the null, excess held for switches, or no measurement this session**.
- Append Analysis A. The app records the result; it does not generate the residual.
- If no recovered injection is in the book, Switch 3 remains live for any claim.

WALK / ANALYSIS B

10. Classify a measured lag

Choose the registered pair-of-pairs and enter a peak only when the reduction of those two named input series actually produced one.

- **Required:** pair, chain, peak lag tau, and sigma_sync.
- **Set only true flags:** seen on co-located pair; seen on separated pair; catalogued multipath match; vanishes with IGS or ionosphere correction; common-clock run excluded hardware; Switch 2 delay class passed.
- **Append only after freeze** and only when the classifier is actually on screen.

The classifier quotes rules; it does not invent a peak

A peak at about zero lag, even if every switch is passed, is common-mode noise. It is not superluminal signaling, and no information transfer follows from common mode.

Interpretation guardrails

- Ordinary direct propagation obeys $|\tau|$ less than or equal to τ_c .
- A peak beyond τ_c without a catalogued multipath explanation routes to a pipeline investigation under Switch 3.
- A $|\tau|$ much less than τ_c morphology is available only on baselines that clear both dump-rate and synchronization requirements.

WALK / UNCOMBINED L1 AND L5

11. Run Switch 2

Enter phi_1 for L1 and phi_2 for L5 in radians or cycles from the uncombined carriers. The ionosphere-free combination destroys the diagnostic ratio.

Class	phi_1 / phi_2	Reading
Delay	about 1.339	Equal time or path delay; the only class allowed to proceed.
Ionosphere	about 0.747	Carrier-phase ionosphere; return to the null.
Phase offset	1.000	Digital or processing artifact.
None	outside tolerance	Does not pass.

- The registered relative tolerance controls the classification; an example is 0.05.
- Switch 2 cannot fire on a null.
- A “candidate passed” call in Step 12 is refused until this chromatic entry exists.

WALK / CLASSIFICATION LIMITS

11. Interpret Switch 2

The frequency ratio is a discriminator, not a unique signal identifier.

Necessary, not sufficient

Passing the delay class rejects only ionospheric and digital-artifact explanations. Troposphere, multipath, and clock error are also delay-class.

- Classify real residuals with the frozen multi-component mixture model and uncertainty intervals.
- Apply the per-campaign common-clock calibration of frequency-dependent hardware terms.
- A candidate that matches no class is not promoted on chromaticity.
- Passing Switch 2 permits further investigation; it is not evidence specific to anomalous coherence.

Use phase units consistently

Both carrier entries must be in radians or both in cycles. Do not substitute metres into the ratio.

WALK / RECORD THE ACTUAL CALL

12. Adjudicate the switches

The book does not mark a switch passed because a field was left at its default.

Null holds	Candidate passed
Fired	Not applicable on a null

- **Switch 2 fired** requires an Analysis A or Analysis B entry.
- **Candidate passed** requires the uncombined chromatic entry.
- **Details and blast radii** remain visible on the Switches screen.
- **Record the call you are making**, not the call you hope to make later.

13. Close and publish the campaign

- Open [Book](#) and use the campaign-close export prompt to download JSON.
- Export Markdown for a human-readable campaign note and move both files off the handset.
- Raw IQ remains on the nodes.
- Report three distinct values for each chain: **predicted budget | measured residual floor | reported bound**.
- Chain S uses the measured double-difference floor. Chain C uses the per-baseline maximum from Step 5.

Null included

Publish a null campaign. The absence of an excess does not make the record disposable.

CLOSED FORMS / NO AUTOMATIC LOG WRITES

Bench is a calculator

Tool	Use
Phase stability	$\sigma_{\phi} = 2 \pi f \tau \sigma_y$ for the installed GPSDO.
Light time	Baseline, τ_c , and dump-rate lag resolution.
Stationary floor	Beta null and the $L = 86,400$ trap.
Weak common phase	Approximate $\phi = \sigma \sqrt{r}$, beside exact inversion.
Chromatic class	ϕ_1 / ϕ_2 against delay, ionosphere, and offset.
Ionospheric phase	0.1 TECU example; not a forecast.
Per-dump phase	σ about $1 / \sqrt{2 C/N_0 T}$, with $T = 1/f_d$.
Guard band	Below f_{loop} , disciplined oscillators are one clock.
Sphere baseline	Mean-Earth haversine; not a geodetic reduction.
Campaign RSS	Included budget rows; Chain S floor. Chain C uses the larger calibrated/atmospheric floor.
Rev 3.5 identity	Self-check; a failed row means the app is wrong.

Copy deliberately

Copy a Bench result into Walk only when it is the measured value or exact closed form you intend to record. Bench never appends the campaign log for you.

EXPORT / IMPORT / DELETE

Book is the handset archive

- **Export the book** downloads **dslv-zpdi-vacuum-book.json** with every local campaign, tagged for Rev 3.5.
- **Export this campaign** downloads one campaign as JSON, named from the campaign.
- **Markdown** downloads the same campaign as a human-readable note.
- **Import JSON** appends records. It does not overwrite a campaign already on the phone. Invalid files are refused.
- **Field note** appends a new log entry. Older entries are not edited.
- **Remove this campaign** deletes one local record after a second confirmation. Export first.

Local means fragile

Deleting browser site data or removing the campaign can destroy the only copy held by this app.

BOOK / EXPORT DISCIPLINE

Preserve every frozen milestone

Mandatory JSON prompts

- **Registry freeze** - after the external anchor ID is recorded.
- **Amendment re-freeze** - after the new anchor ID is recorded.
- **Calibration append** - immediately after the calibration line is written.
- **Campaign close** - before publication or removal from the handset.

Complete each export, move it off the handset, and note where the external freeze anchor can be verified.

What the log contains

Calibrations, injections, Analysis A and B entries, chromatic calls, switch decisions, freeze hashes, external anchor transaction IDs, amendments, exports, and field notes.

Move the archive off the phone

Use USB, a storage share you trust, or a manual copy. Treat JSON as the registry: it may contain operator names, site coordinates, freeze hashes, and external anchor IDs.

INSTRUMENT DOCTRINE / SHORT FORM

Kill switches 1-3

1. Array residual

Fires on: Analysis A agrees with its null and Analysis B's bootstrap maximum agrees with the time-slide null, evaluated per chain. The short-lag morphology is available only on baselines with τ_c much greater than $1/f_d$.

Blast radius: that chain's hypothesis. The array remains a disciplined SDR network.

2. Chromaticity

Fires on: the uncombined L1/L5 pair failing the registered delay class. A ratio near 1.339 may proceed, but passing is necessary, not sufficient: troposphere, multipath, and clock error are also delay-class.

Blast radius: the candidate, not the array. This switch cannot fire on a null.

3. Pipeline

Fires on: failed injection recovery, failure to return to null with injection off, disagreement between time-slide and bootstrap backgrounds, empirical false-alarm or coverage failure, common-clock calibration failure, or a drift spot check outside tolerance.

Blast radius: the campaign until repair. No science claim.

Separate families

A null on Chain S is not a null on Chain C. Name the chain every time you state a bound or switch result.

INSTRUMENT DOCTRINE / SHORT FORM

Kill switches 4-6

4. Möbius holonomy

Fires on: a controlled closed loop showing only standard Berry, Faraday, or Sagnac phase, with no extra discrete π .

Blast radius: Supplement S1 as physics; bookkeeping may remain useful.

5. Gravitating plenum

Status: already thrown by cosmology. Vacuum-energy ontology does not load the carrier-phase bound.

Blast radius: literal Dirac-sea ontology. The phase program never required it.

6. Simultaneity

Fires on: a short-lag excess that moves when an independent time-transfer method is substituted.

Blast radius: any non-local reading of that dataset. This switch is load-bearing on Chain C.

Firewall

These are instrument switches. Supplement S2 companion studies - aqueous, somatic, and Schumann - do not open or close Chain C.

EPISTEMIC LABELS

How to read a sentence

[E] Established

Experimental or textbook result: GPS, International GNSS Service products, the Beta law, the Holometer's optical null, or ionospheric delay scaling.

[I] Interpretive

Not required by the data. Supplement S1 belongs here.

[H] Hypothesis

Contingent and kill-switched. H_S and H_C are the two hypotheses the array is built to bound.

Closest optical precedent

Chou et al., *Physical Review Letters* 117, 111102 (2016), reported the Holometer's co-located optical cross-spectrum null. DSLV-ZPDI instead studies radio-frequency carrier phase across geographic baselines. The observable classes differ.

Data before ontology

A positive result is a data result first. Interpretation cannot bypass calibration, chromaticity, independent timing, hold-out confirmation, or the registered null.

BOUNDARY OF THE FIELD BOOK

What this handset will not do

- **Invent a residual, gamma-hat, or lag.**
- **Treat a handset GPS fix as carrier phase.**
- **Quote a Chain C bound tighter than the maximum of its co-located non-clock floor, isolated relative-clock contribution, and baseline atmospheric differential RSS.**
- **Call a near-zero-lag excess superluminal.** Common mode is not a signaling channel.
- **Move Supplement S1 ontology into the detection statistic.**

System boundary

Node software and the handset shell live in the public DSLVS-ZPDI project under package **labs.dynogator.dslvzpd**i. This app is the Rev 3.5 campaign book beside that array.

Care of the record

- Freeze and externally anchor before science entries; amendments preserve prior digests and require a fresh anchor after re-freeze.
- Export JSON at registry freeze, amendment re-freeze, calibration append, and campaign close, and before clearing site data or handing off the phone.
- A different hostname is a different book. A preview and the published origin do not share storage.
- Catalog budget rows are not measurements. Mark measured only after replacing a row with an observed value.
- Do not change `f_d`, block length, elevation mask, or tolerance after freeze and claim that the original hash still covers the run.

TROUBLESHOOTING / ACCESS

If installation fails

What you see	What to do
No Install app line	Use Add to home screen. Confirm the published HTTPS origin in a normal Vanadium tab.
Add to home screen does nothing	Drag the icon from the placement sheet onto the home screen.
Blank page	Allow network. If the page loaded but stayed white, allow JIT for this origin only.
Location error	Deny is allowed. Enter surveyed latitude and longitude; nothing is invented.
Next stays grey	Read the amber gate message below the buttons.
Edits rejected	The registry is frozen. Amend with a reason, re-freeze, create a fresh external anchor, record its ID, then export JSON.

Production address

Open <https://dslv-vac-probe.grok.me>. Deck, Walk, Bench, Book, and Switches are paths on this same origin.

TROUBLESHOOTING / INTEGRITY

If the record fails

What you see	What to do
Freeze shows only a handset timestamp	The hash is self-attested until externally anchored through OSF, a signed repository tag, or OpenTimestamps / RFC-3161.
Export prompt was skipped	Open Book and export campaign JSON before continuing. Record the milestone in the log.
Import did not parse	Use book JSON or campaign JSON produced by this app.
Two phones disagree	Expected: records do not sync. Keep the phone with the intended freeze hash.
Identity row fails	The app is wrong. Do not publish that row as a residual.

Stop rather than improvise

Do not repair a failed gate by inventing a coordinate, residual, timing result, calibration value, or anchor ID. Record the failure and fix the underlying condition.

Document: DSLV-ZPDI Rev 3.5 Install and User Guide. Prepared September 28, 2026 for the published field-book release.