



POD Translation
by *pod2pdf*

ajf@afco.demon.co.uk

Subscripts.pm

Table of Contents

Subscripts.pm

NAME	1
SYNOPSIS	1
DESCRIPTION	1
METHODS	1
new()	1
name()	1
lookup()	1
combining()	1
getCharSize()	1
TODO	1
AUTHORS	1
Ed Summers <ehs@pobox.com>	1

NAME

MARC::Charset::Subscripts - MARC8/UTF8 mapping for Subscripts

SYNOPSIS

```
use MARC::Charset::Subscripts;
my $cs = MARC::Charset::Subscripts->new();
```

DESCRIPTION

MARC::Charset::Subscripts provides a mapping between the MARC8 Subscript character set and Unicode(UTF8). It is typically used by MARC::Charset, so you probably don't need to use this yourself.

METHODS**new()**

The constructor, which will return you a MARC::Charset::Subscripts object.

name()

Returns the name of the character set.

lookup()

The workhorse method that does the lookup. Pass it an a character and you'll get back the UTF8 character.

combining()

Pass it a character and you'll get back a true value (1) if the character is a combining character, and false (undef) if it is not.

getCharSize()

Returns the number of bytes in each character of this character set.

TODO**AUTHORS**

Ed Summers <ehs@pobox.com>

