

Lab 9

CST8912\_011

Yuntian Du

du000086

March 12, 2025

Submitted to :

**Prof. Ragini Madaan**

# Evaluate the security and data privacy implications of various cloud solutions

## Introduction & Purpose

### Introduction:

Microsoft Azure includes tools to safeguard data according to your company's security and compliance needs.

Encryption at Rest is a common security requirement. In Azure, organizations can encrypt data at rest without the risk or cost of a custom key management solution. Organizations have the option of letting Azure completely manage Encryption at Rest. Additionally, organizations have various options to closely manage encryption or encryption keys.

Encryption is the secure encoding of data used to protect confidentiality of data. The Encryption at Rest designs in Azure use symmetric encryption to encrypt and decrypt large amounts of data quickly according to a simple conceptual model:

A symmetric encryption key is used to encrypt data as it is written to storage.

The same encryption key is used to decrypt that data as it is readied for use in memory.

Data may be partitioned, and different keys may be used for each partition. Keys must be stored in a secure location with identity-based access control and audit policies. Data encryption keys which are stored outside of secure locations are encrypted with a key encryption key kept in a secure location.

Encryption at rest provides data protection for stored data (at rest). Attacks

against data at-rest include attempts to obtain physical access to the hardware on which the data is stored, and then compromise the contained data. In such an attack, a server's hard drive may have been mishandled during maintenance allowing an attacker to remove the hard drive. Later the attacker would put the hard drive into a computer under their control to attempt to access the data.

Encryption at rest may also be required by an organization's need for data governance and compliance efforts. Industry and government regulations such as HIPAA, PCI and FedRAMP, lay out specific safeguards regarding data protection and encryption requirements.

How azure sql database encrypts data at rest:  
<https://www.youtube.com/watch?v=oMmKIUZQL5Q>

#### Purpose:

In this lab you will explore the security features offered by Microsoft for azure sql database.

- Protection against attacks such as SQL injection and data exfiltration.
- Ability to discover and classify database information into categories such as Confidential.
- Ability to audit database server and database queries and log events.

In this exercise, you will complete the following tasks:

Task 1: Deploy an Azure SQL Database

Task 2: Configure Advanced Data Protection

Task 3: Configure Data Classification

Task 4: Configure Auditing

Task 5: Clean resources created during lab

## Steps covered in the lab

### Task 1: Deploy an Azure SQL Database

#### Method1:

1. Configure Azure SQL database for Canada central region under your

resource group cst8912-demo, choose single database under sql databases in sql deployment option

2. Enter the following values in create database page and keep other properties with their default settings

Subscription: Select your Azure subscription

Resource group: CST8912demo

Database name: db8912

Server: Select Create new and create a new server with a unique name in any Canada central location. Use SQL authentication and specify your name as the server admin login and a suitably complex password (remember the password - you'll need it later!)

Server : db8912demo

Username:db8912yourname

Password: dfguyt@234!

Microsoft Azure Search resources, services, and docs (G+)

Home > SQL databases >

### Create SQL Database

Microsoft

Resource group \* ⓘ cst8912-demo [Create new](#)

#### Database details

Enter required settings for this database, including picking a logical server and configuring the compute and storage resources

Database name \* db8912 ✓

Server \* ⓘ (new) db8912demo1 (Canada Central) [Create new](#)

Want to use SQL elastic pool? ⓘ ☐ Yes ☒ No

Workload environment ☒ Development ☐ Production

Default settings provided for Development workloads. Configurations can be modified as needed.

[Review + create](#) [Next : Networking >](#)

Want to use SQL elastic pool?: No

Workload environment: Development

Compute + storage: Leave unchanged

Backup storage redundancy: Locally-redundant backup storage

Microsoft Azure Search resources, services, and docs (G+)

Home > SQL databases >


### Create SQL Database

Microsoft

Choose how your PITR and LTR backups are replicated. Geo restore or ability to recover from regional outage is only available when geo-redundant storage is selected.

Backup storage redundancy

- ☒ Locally-redundant backup storage
- ☐ Zone-redundant backup storage
- ☐ Geo-redundant backup storage
- ☐ Geo-Zone-redundant backup storage [Preview]



Cost summary

General Purpose (GP_S_Gen5_1)	
Cost per GB (in USD)	0.13
Max storage selected (in GB)	41.6

[Review + create](#) [Next : Networking >](#)

3. On the Create SQL Database page, select Next :Networking >, and on the Networking page, in the Network connectivity section, select Public endpoint. Then select Yes for both options in the Firewall rules section to allow access to your database server from Azure services and your current client IP address.

The screenshot shows the 'Create SQL Database' page in the Microsoft Azure portal. The 'Networking' tab is selected. The page title is 'Create SQL Database'. Below the title, there are tabs for 'Basics', 'Networking', 'Security', 'Additional settings', 'Tags', and 'Review + create'. The 'Networking' tab is active. The main content area is titled 'Network connectivity' and contains the following text: 'Configure network access and connectivity for your server. The configuration selected below will apply to the selected server 'db8912demo1' and all databases it manages. [Learn more](#)'. Below this, there is a section for 'Network connectivity' with the text: 'Choose an option for configuring connectivity to your server via public endpoint or private endpoint. Choosing no access creates with defaults and you can configure connection method after server creation. [Learn more](#)'. There are three radio button options: 'No access', 'Public endpoint' (selected), and 'Private endpoint'. Below this, there is a section for 'Firewall rules' with the text: 'Setting 'Allow Azure services and resources to access this server' to Yes allows communications from all resources inside the Azure boundary, that may or may not be part of your subscription. [Learn more](#)'. There are two toggle switches: 'Allow Azure services and resources to access this server' (set to 'Yes') and 'Add current client IP address' (set to 'Yes'). At the bottom, there are three buttons: 'Review + create', '< Previous', and 'Next : Security >'.

#### 4. Select Next: Security > and set the Enable Microsoft Defender for SQL option to Not now.

The screenshot shows the 'Create SQL Database' page in the Microsoft Azure portal. The 'Security' tab is selected. The page title is 'Create SQL Database'. Below the title, there are tabs for 'Basics', 'Networking', 'Security', 'Additional settings', 'Tags', and 'Review + create'. The 'Security' tab is active. The main content area is titled 'Microsoft Defender for SQL' and contains the following text: 'Protect your data using Microsoft Defender for SQL, a unified security package including vulnerability assessment and advanced threat protection for your server. [Learn more](#)'. Below this, there is a section for 'Microsoft Defender for SQL' with the text: 'Get started with a 30 day free trial period, and then 15 USD/server/month.' There are two radio button options: 'Start free trial' and 'Not now' (selected). Below this, there is a section for 'Ledger' with the text: 'Ledger cryptographically verifies the integrity of your data and detects any tampering that might have occurred. [Learn more](#)'. There is a 'Ledger' section with a 'Not configured' status and a 'Configure ledger' link. At the bottom, there are three buttons: 'Review + create', '< Previous', and 'Next : Additional settings >'.

#### 5. Select Next: Additional Settings > and on the Additional settings tab, set the Use existing data option to Sample (this will create a sample

database that you can explore later).

The screenshot shows the 'Create SQL Database' wizard in the Microsoft Azure portal. The 'Additional settings' tab is selected, showing options for 'Data source' and 'Database collation'. The 'Data source' section has three buttons: 'None', 'Backup', and 'Sample', with 'Sample' being the active selection. Below this, it states 'AdventureWorksLT will be created as the sample database.' The 'Database collation' section explains that the default is 'SQL\_Latin1\_General\_CP1\_CI\_AS' and provides a 'Learn more' link. A text box shows the selected collation 'SQL\_Latin1\_General\_CP1\_CI\_AS'. At the bottom, there are three buttons: 'Review + create', '< Previous', and 'Next : Tags >'. The 'Review + create' button is highlighted in blue.

6. Select Review + Create, and then select Create to create your Azure SQL database.

## Method 2:


1. In the Azure portal, in the Search resources, services, and docs text box at the top of the Azure portal page, type Deploy a custom template and press the Enter key.
2. On the Custom deployment blade, click the Build your own template in the editor option.
3. On the Edit template blade, click Load file , locate the <https://github.com/MicrosoftLearning/AZ500-AzureSecurityTechnologies/blob/master/Allfiles/Labs/11/azuredeploy.json> file and click Open.
4. On the Edit template blade, click Save.
5. On the Custom deployment blade, ensure that the following settings are configured (leave any others with their default values):

Setting	Value
Subscription	Azure subscription
Resource group	CST8912
Location	<b>Canada Central</b>

6. Click Review + Create and then click Create.

## Task 2: Configure Advanced Data Protection

1. On the SQL server blade, in the Security section, click Microsoft Defender for Cloud, select Enable Microsoft Defender for SQL.



2. On the SQL server blade, in the Security section, on the Microsoft Defender for Cloud page, in the Microsoft Defender for SQL: Enabled at the subscription-level (Configure) parameter, click (configure)
3. On the Server Settings blade, review the information about pricing and the trial period, VULNERABILITY ASSESSMENT SETTINGS and ADVANCED THREAT PROTECTION SETTINGS.



Home > Microsoft Defender for Cloud | Overview > Environment settings >

## Settings | Defender plans

Azure for Students

Search Save Settings & monitoring

Settings

- Defender plans
- Security policies
- Email notifications
- Workflow automation
- Continuous export

Microsoft Defender for Cloud provides comprehensive, cloud-native protections from development to runtime in multi-cloud environments.

Plan	Pricing*	Resource quantity	Monitoring coverage	Status
Servers	Plan 2 (\$15/Server/Month) <a href="#">Change plan &gt;</a>	0 servers	Full <a href="#">Settings &gt;</a>	Off <a href="#">On</a>
App Service	\$15/instance/Month <a href="#">Details &gt;</a>	0 instances	Full <a href="#">Settings &gt;</a>	Off <a href="#">On</a>
Databases	Selected: 4/4 <a href="#">Select types &gt;</a>	Protected: 1/1 instances	Partial <a href="#">Settings &gt;</a>	Off <a href="#">On</a>
Storage	\$10/Storage account/month \$0.15/GB scanned for On-Upload Malw. <a href="#">Details &gt;</a>	0 storage accounts	Full <a href="#">Settings &gt;</a>	Off <a href="#">On</a>
Containers	\$6.8693/VM core/Month <a href="#">Details &gt;</a>	0 container registries; 0 kubern	Partial <a href="#">Settings &gt;</a>	Off <a href="#">On</a>
AI workloads	Free (Preview) <a href="#">Details &gt;</a>			Off <a href="#">On</a>
Key Vault	\$0.25/Vault/Month <a href="#">Details &gt;</a>	0 key vaults	Full <a href="#">Settings &gt;</a>	Off <a href="#">On</a>
Resource Manager	\$5/Subscription/Month <a href="#">Details &gt;</a>		Full <a href="#">Settings &gt;</a>	Off <a href="#">On</a>

Microsoft Azure Search resources, services, and docs (G+/I) Copilot

Home > cst8912-demo > db8912demo1 | Microsoft Defender for Cloud >

## Server settings

db8912demo1

Save Discard Feedback

### MICROSOFT DEFENDER FOR SQL

**ON** OFF

**Microsoft Defender for SQL costs 15 USD/server/month. It includes Vulnerability Assessment and Advanced Threat Protection. We invite you to a trial period for the first 30 days, without charge.**

### VULNERABILITY ASSESSMENT SETTINGS


**SQL Vulnerability Assessment is enabled via express configuration. All databases will be scanned on a weekly basis. [Learn more](#)**

### ADVANCED THREAT PROTECTION SETTINGS

Advanced Threat Protection for SQL alerts emails are sent by Defender for Cloud.  
[Add your contact details to the subscription's email settings in Defender for Cloud.](#)

[Enable Auditing for better threats investigation experience](#)


- Back to Microsoft Defender for Cloud blade, review Recommendations and Security alerts.




### Task 3: Configure Data Classification

In this task, you will explore and classify data in SQL database for GDPR and data protection compliance.


1. On the SQL server blade, in the Settings section, click SQL Databases.



2. On the SQL database blade, in the Security section, click Data Discovery & Classification.
3. On the Data Discovery & Classification blade, click the Classification tab.



4. Click the text message We have found 15 columns with classification recommendations displayed on blue bar at the top of the blade.



5. Review the listed columns and the recommended sensitivity label.
6. Enable the Select all checkbox and then click Accept Selected Recommendations.

Microsoft Azure Search resources, services, and docs (G+/) Copilot

Home > cst8912-demo > db8912demo1 | SQL databases > db8912 (db8912demo1/db8912)

db8912 (db8912demo1/db8912) | Data Discovery & ... SQL database

Search Save Discard Add classification Feedback

Mirror database in Fabric (preview)

> Settings

> Data management

> Integrations

> Power Platform

> Security

Auditing

Ledger

**Data Discovery & Classification**

Dynamic Data Masking

Microsoft Defender for Cloud

Identity

Data Encryption

> Intelligent performance

> Monitoring

Currently database is using SQL Information Protection policy. Found 15 columns with classification recommendations

Overview Classification Learn more - Getting Started Guide

15 columns with classification recommendations (Click to minimize)

Accept selected recommendations

Dismiss selected recommendations

<input checked="" type="checkbox"/>	dbo	ErrorLog	
<input checked="" type="checkbox"/>	SalesLT	Address	A
<input checked="" type="checkbox"/>	SalesLT	Address	A
<input checked="" type="checkbox"/>	SalesLT	Address	C
<input checked="" type="checkbox"/>	SalesLT	Address	P
<input checked="" type="checkbox"/>	SalesLT	CustomerAddress	A
<input checked="" type="checkbox"/>	SalesLT	SalesOrderHeader	A
<input checked="" type="checkbox"/>	SalesLT	SalesOrderHeader	C
<input checked="" type="checkbox"/>	SalesLT	SalesOrderHeader	T

7. Once you have completed your review click Save.
8. Back on the Data Discovery & Classification blade Overview tab, note that it has been updated to account for the latest classification information.

Microsoft Azure Search resources, services, and docs (G+/) Copilot

Home > cst8912-demo > db8912demo1 | SQL databases > db8912 (db8912demo1/db8912)

db8912 (db8912demo1/db8912) | Data Discovery & ... SQL database

Search Save Discard Add classification Feedback

Mirror database in Fabric (preview)

> Settings

> Data management

> Integrations

> Power Platform

> Security

Auditing

Ledger

**Data Discovery & Classification**

Dynamic Data Masking

Microsoft Defender for Cloud

Identity

Data Encryption

> Intelligent performance

> Monitoring

Currently database is using SQL Information Protection policy.

Overview Classification Learn more - Getting Started Guide

SalesLT	Address	AddressLine1
SalesLT	Address	City
SalesLT	Address	PostalCode
SalesLT	Customer	EmailAddress
SalesLT	Customer	FirstName
SalesLT	Customer	LastName
SalesLT	Customer	PasswordHash
SalesLT	Customer	PasswordSalt


< Previous Page 1 of 2 Next >

No classification recommendations


## Task 4: Configure Auditing

In this task, you will first configure server level auditing and then configure database level auditing.


1. In the Azure portal, navigate back to the SQL Server blade.
2. On the SQL Server blade, in the Security section, click Auditing.
3. Set the Enable Azure SQL Auditing switch to ON to enable auditing
4. Select the Storage checkbox and entry boxes for Subscription and Storage Account will display (create new storage account if not selected)
5. Choose your Subscription from the dropdown list.
6. Click Storage account and choose Create new.





7. Back on the Auditing blade, under Advanced properties set Retention (days) to 5.



8. On the Auditing blade, click Save to save the auditing settings
  9. On the server blade, in the Settings section, click SQL Databases.
  10. On the SQL database blade, in the Security section, click Auditing.
- Note: This is database level auditing. Server-level auditing is already enabled.



11. On your SQL database Overview page in the Azure portal, select Query editor (preview) from the left menu. Try to sign in, you might fail on password, firewall rule for your IP address, everything gets audited. Try successful login as well, run query and you might find more details in audit logs



12. switch back to DB, Auditing and Click View Audit Logs.



Microsoft Azure Search resources, services, and docs (G+/) Copilot

db8912demo1 | SQL databases > db8912 (db8912demo1/db8912) | Auditing >

## Audit records

Refresh Filter Log Analytics View dashboard

**i** This blade provides a sample of audit logs with limited fields within 2 hours into the past from the selected End-Time (which is 'now' by default). Click here to learn more about methods for viewing analyzing audit records. [Learn more](#)

Audit source ⓘ

**Server audit** Database audit

Showing audit records up to Thu, 06 Mar 2025 01:17:04 UTC.

[Run in Query Editor](#) ⓘ

Event time (UTC)	Principal name	Event type	Action status
3/6/2025 1:16:23 AM	db8912yuntiandu	DATABASE AUTHENTICATION SUCCE...	Succeeded
3/6/2025 1:16:23 AM	db8912yuntiandu	BATCH COMPLETED	Succeeded
3/6/2025 1:16:01 AM	db8912yuntiandu	DATABASE AUTHENTICATION SUCCE...	Succeeded
3/6/2025 1:16:01 AM	db8912yuntiandu	BATCH COMPLETED	Failed
3/6/2025 1:15:45 AM	db8912yuntiandu	DATABASE AUTHENTICATION SUCCE...	Succeeded
3/6/2025 1:15:45 AM	db8912yuntiandu	BATCH COMPLETED	Succeeded
3/6/2025 1:15:40 AM	db8912yuntiandu	BATCH COMPLETED	Failed
<a href="https://go.microsoft.com/fwlink/?linkid=863...">https://go.microsoft.com/fwlink/?linkid=863...</a>	intiandu	DATABASE AUTHENTICATION SUCCE...	Succeeded

13. On the Audit records blade, note that you can switch between Server audit and Database audit.

## Task 5: Clean up resources created during this lab

**Deliverable:** Delete all the resources created during this lab and document all the steps with screenshots in lab report.

Microsoft Azure

Search resources, services, and docs (G+/)

Copilot

Home >

cst8912-den

Resource group

Search

Overview

Activity log

Access control (IAM)

Tags

Resource visualizer

Events

Settings

Deployments

Security

Deployment stacks

Policies

Properties

Locks

Cost Management

Monitoring

Insights (preview)

Delete a resource group

The following resource group and all its dependent resources will be permanently deleted.

Resource group to be deleted

cst8912-demo

Dependent resources to be deleted (4)

All dependent resources, including hidden types, are shown

Name	Resource type
db8912 (db8912demo1/db8912)	SQL database
db8912demo1	SQL server
master (db8912demo1/master)	SQL database
sa8912	Storage account

Enter resource group name to confirm deletion \*

cst8912-demo

Delete

Cancel

References  
None.