

Getting Started with Matplotlib

We need matplotlib.pyplot for plotting.

```
import matplotlib.pyplot as plt
import pandas as pd
```

About the Data

Plotting lines

```
fb = pd.read_csv(
    'fb_stock_prices_2018.csv', index_col='date', parse_dates=True
)
```

```
plt.plot(fb.index, fb.open)
plt.show()
```



```
%matplotlib inline
import matplotlib.pyplot as plt
import pandas as pd
```


```
fb = pd.read_csv(
    'fb_stock_prices_2018.csv', index_col='date', parse_dates=True
)
plt.plot(fb.index, fb.open)
```



Scatter plots

We can pass in a string specifying the style of the plot. This is of the form '[color][marker][linestyle]'. For example, we can make a black dashed line with 'k-' or a red scatter plot with 'ro':


```
plt.plot('high', 'low', 'ro', data=fb.head(20))
```



Histograms

```
quakes = pd.read_csv('earthquakes.csv')
plt.hist(quakes.query('magType == "ml"').mag)

(array([6.400e+01, 4.450e+02, 1.137e+03, 1.853e+03, 2.114e+03, 8.070e+02,
        2.800e+02, 9.200e+01, 9.000e+00, 2.000e+00]),
array([-1.26 , -0.624,  0.012,  0.648,  1.284,  1.92 ,  2.556,  3.192,
        3.828,  4.464,  5.1   ]),
<BarContainer object of 10 artists>)
```




Bin size matters

Notice how our assumptions of the distribution of the data can change based on the number of bins (look at the drop between the two highest peaks on the righthand plot):

```
x = quakes.query('magType == "ml"').mag
fig, axes = plt.subplots(1, 2, figsize=(10, 3))
for ax, bins in zip(axes, [7, 35]):
```

```
ax.hist(x, bins=bins)
ax.set_title(f'bins param: {bins}')
```




Plot components

```
fig = plt.figure()


<Figure size 640x480 with 0 Axes>
```

Creating subplots



As an alternative to using `plt.subplots()` we can add the Axes to the Figure on our own. This allows for some more complex layouts, such as picture in picture:


```
fig = plt.figure(figsize=(3, 3))
outside = fig.add_axes([0.1, 0.1, 0.9, 0.9])
inside = fig.add_axes([0.7, 0.7, 0.25, 0.25])
```



Creating Plot Layouts with gridspec

We can create subplots with varying sizes as well:

```
fig = plt.figure(figsize=(8, 8))
gs = fig.add_gridspec(3, 3)
top_left = fig.add_subplot(gs[0, 0])
mid_left = fig.add_subplot(gs[1, 0])
top_right = fig.add_subplot(gs[2, 1:])
bottom = fig.add_subplot(gs[2,:])
```



Saving plots

Use `plt.savefig()` to save the last created plot. To save a specific Figure object, use its `savefig()` method.

```
fig.savefig('empty.png')
```

Cleaning up

It's important to close resources when we are done with them. We use `Figure` to close or say 'all' to close all `plt.close()` to do so. If we pass in nothing, it will close the last plot, but we can pass the specific Figure objects that are open. Let's close all the Figure objects that are open with `plt.close()` :

```
plt.close('all')
```

Additional plotting options


Specifying figure size

Just pass the `figsize` parameter to `plt.figure()` . It's a tuple of (width, height):

```
fig = plt.figure(figsize=(10, 4))

<Figure size 1000x400 with 0 Axes>

fig, axes = plt.subplots(1, 2, figsize=(10, 4))
```



rcParams

```
import random
import matplotlib as mpl

rcparams_list = list(mpl.rcParams.keys())
random.seed(20) # make this repeatable
random.shuffle(rcparams_list)
sorted(rcparams_list[:20])

['animation.convert_args',
'axes.edgecolor',
'axes.formatter.use_locale',
'axes.spines.right',
'boxplot.meanprops.markersize',
'boxplot.showfliers',
'keymap.home',
'lines.markerfacecolor',
'lines.scale_dashes',
'mathtext.rm',
'patch.force_edgecolor',
'savefig.facecolor',
'svg.fonttype',
'text.hinting_factor',
'xtick.alignment',
'xtick.minor.top',
'xtick.minor.width',
'ytick.left',
'ytick.major.left',
'ytick.minor.width']
```

We can check the current default figsize using rcParams :

```
mpl.rcParams['figure.figsize']

[6.4, 4.8]
```

We can also update this value to change the default (until the kernel is restarted):

```
mpl.rcParams['figure.figsize'] = (300, 10)
mpl.rcParams['figure.figsize']

[300.0, 10.0]
```

Use rcdefaults() to restore the defaults

```
mpl.rcdefaults()
mpl.rcParams['figure.figsize']

[6.4, 4.8]
```

This can also be done via pyplot :

```
plt.rc('figure', figsize=(20, 20)) # change figsize default to (20, 20)
plt.rcdefaults() # reset the default
```