

**FLOODSENSE: AN ANDROID-BASED EXPERT SYSTEM FOR FLOOD
SUSCEPTIBILITY ASSESSMENT AND PRE-EVENT PREPAREDNESS IN
BACOR CITY**

Undergraduate Thesis
Submitted to the Faculty of the
Department of Computer Studies
Cavite State University - Bacoor City Campus
City of Bacoor, Cavite

In partial fulfillment of the
requirements for the degree
Bachelor of Science in Computer Science

**REYMART V. GOC-ONG
MARTIN LORENZ D. JUANITES
ROMAR T. PULAO**
May 2027

FloodSense: An Android-Based Expert System for Flood Susceptibility Assessment and Pre-Event Preparedness in Bacoor City

Reymart V. Goc-ong
Martin Lorenz D. Juanites
Romar T. Pulao

An undergraduate thesis manuscript submitted to the faculty of the Department of Computer Studies, Cavite State University - Bacoor City Campus, City of Bacoor, Cavite, in partial fulfillment of the requirements for the degree of Bachelor of Science in Computer Science with Contribution No. _____. Prepared under the supervision of

INTRODUCTION

Flooding is one of the most frequent and destructive natural hazards in the Philippines. The country's location within the typhoon belt exposes communities to rainfall events that cause inundation, displacement, damage to property, interruption of livelihood, and loss of life. National disaster statistics continue to document the widespread effects of natural hazards on Filipino families and communities (Philippine Statistics Authority [PSA], 2026). Bacoor City, Cavite, is among the localities that regularly experience flooding. Its low-lying areas and connection to the Imus and Bacoor river systems contribute to persistent inundation during periods of heavy rainfall. Flood-mitigation facilities in the Imus River Basin were established specifically to reduce peak floodwater volume in Cavite, including low portions of Bacoor and its tributaries (Japan International Cooperation Agency [JICA], 2021). These conditions establish the importance of accessible, understandable, and location-specific information that residents can consult before a flood event develops.

To assess the information problem, the researchers surveyed 50 residents across 12 barangays in Bacoor City, with respondents drawn largely from historically flood-affected communities. The findings revealed that flood warnings are commonly

disseminated through Short Message Service (SMS), social media, and barangay public-address systems, yet these channels do not consistently provide location-specific susceptibility information before flooding occurs. Only 20% of respondents felt well-informed about which areas in the city are flood-prone, meaning that 80% selected Somewhat Aware, Not Sure, or Not Aware at All. Most respondents also rated the timeliness, clarity, and quality of available flood information near the dissatisfied end of the scale. Most critically, 64% reported making a wrong decision, such as taking a flooded road, delaying evacuation, or misjudging flood conditions, because adequate area-specific information was unavailable. A key informant interview with the Bacoor Disaster Risk Reduction and Management Office (BDRRMO) confirmed that historical flood records and Geographic Information System (GIS)-based exposure information are maintained institutionally but are not presented to residents through an interactive public platform. A supplementary interview with the City Planning and Development Coordinator Office (CPDCO) also established the availability of elevation, flood hazard, land-use, and barangay-boundary information relevant to geographic assessment.

FloodSense addresses this gap through an Android application that connects expert-provided and expert-validated knowledge with the information and preparedness needs of Bacoor City residents. A Rule-Based Expert System organizes approved facts and conditional rules in a knowledge base and applies an inference process to the user's selected rainfall intensity, rainfall duration, and geographic area. Rule-based expert systems use a knowledge base and an inference procedure that applies rules to known facts to reach a conclusion (Buchanan & Shortliffe, 1984). In FloodSense, the conclusion is an explainable flood susceptibility assessment expressed as Low, Moderate, High, or Very High. The Decision Support System (DSS) then uses the assessment together with the user's situational inputs to present suitable pre-event preparedness guidance. This function supports, but does not make, the user's final decision; decision support systems organize relevant information and structured guidance for human decision-making (Power, 2002).

The current FloodSense prototype presents scenario-based susceptibility assessment through an interactive map. The user selects or confirms a hypothetical rainfall intensity and duration, selects a supported location manually or through an optional one-time foreground location request, and explicitly requests an assessment. The map can display demonstration susceptibility zones and a neutral reference layer representing the 47 current barangay identities; the reference layer is technically validated for geometry but is not City-issued, is not City-verified, and contains no flood-susceptibility facts. The custom Web Administration System currently provides authenticated dashboard access, read-only review of map and rainfall-reference data, parameter-governance views, and controlled workflows for Decision Support System content, evacuation-center records, source records, and audit history. Ordinary administrators do not edit raw Expert System rules, priorities, conflict-resolution logic, or algorithm code. A fixed-schema CSV export-and-import workflow for permitted values is a confirmed requirement, but it is not yet implemented. FloodSense does not provide real-time monitoring, official forecasting, autonomous alerts, or automatic evacuation orders.

Statement of the Problem

This study aimed to develop an Android application that provides location-specific flood susceptibility assessment and pre-event preparedness support for Bacoor City through a Rule-Based Expert System, a Decision Support System, and a dynamic geographic map. The research questions were grounded in the survey of 50 residents across 12 barangays, key informant interviews with the BDRRMO and CPDCO, and a review of related literature and official information. These sources were used to establish community needs, institutional knowledge sources, geographic requirements, rainfall parameters, preparedness content, and the functional boundaries of the proposed application and its Web Administration System.

In Bacoar City, flooding is a persistent and consequential reality. Survey results reveal that 92% of respondents have personally experienced flooding, with 58% describing the flooding as severe or waist-deep and higher. Despite this exposure, only 20% consider themselves well-informed about flood-prone areas. Mean satisfaction scores for information quality, timeliness, and clarity ranged from 2.62 to 2.72 on a 5-point scale, clustering at the lower end of the Neutral range and tending toward dissatisfaction. These information deficiencies have direct consequences: 64% of respondents reported making wrong decisions due to insufficient flood information, including taking flooded routes, failing to evacuate on time, and misjudging conditions. Open-ended responses further identified late or delayed information at 26% and insufficient or absent location-specific warnings at 20% as the leading concerns. How can an Android application using an Expert System provide residents with understandable, location-specific flood susceptibility assessments based on expert-validated knowledge, rainfall scenarios, and geographic information?

The problem also concerns the accessibility and operational maintenance of institutional knowledge. The BDRRMO maintains historical flood records, exposure information, preparedness protocols, and evacuation-center information, while the CPDCO maintains geographic and planning data. Current dissemination practices, including social media, email, and barangay coordination, do not fully address the public's need for on-demand, situation-specific guidance. A community-facing platform must therefore communicate approved information while ensuring that rules, map objects, preparedness content, rainfall parameters, data sources, and administrative accounts can be maintained by authorized personnel. How can a Rule-Based Expert System, dynamic GIS-style map, Decision Support System, and Web Administration System organize this institutional knowledge into an explainable assessment and appropriate pre-event preparedness guidance for Bacoar City residents?

Taken together, these gaps reveal a disconnect between institutional flood knowledge and the decisions residents must make before flooding occurs. The overarching question of the study is: How can FloodSense integrate expert-provided and expert-validated knowledge, rule-based inference, scenario-based rainfall input, interactive geographic visualization, Check My Area, evacuation-center information, and structured decision support to strengthen flood susceptibility awareness and pre-event preparedness in Bacoar City, while remaining a complementary public-information tool that does not perform real-time flood prediction or supersede official warnings?

Objectives of the Study

Generally, the study aimed to develop an Android application that uses a Rule-Based Expert System to assess flood susceptibility and a Decision Support System to provide pre-event preparedness support for residents of Bacoar City through explainable expert knowledge, rainfall scenarios, and dynamic geographic visualization.

Specifically, it aimed to:

1. identify the prevailing challenges, pain points, and needs of Bacoar City residents and relevant local government offices concerning flood information access, timeliness, clarity, location-specific awareness, and pre-event decision-making through a structured survey of 50 respondents across 12 barangays, a key informant interview with the Bacoar Disaster Risk Reduction and Management Office (BDRMO) to validate survey findings and assess institutional knowledge and data availability, and a supplementary key informant interview with the City Planning and Development Coordinator Office (CPDCO) to identify available geographic, elevation, flood-hazard, land-use, and barangay-

boundary information, all conducted during the Empathize phase of the Design Thinking methodology;

2. analyze expert-provided and expert-validated flood knowledge, BDRRMO historical flood records and preparedness protocols, CPDCO geographic information, PAGASA rainfall classifications, evacuation-center information, and user situational requirements to determine the facts, conditional rules, susceptibility levels, rainfall parameters, geographic entities, and DSS content required by the knowledge base and inference process;

3. develop an Android application using Flutter and Dart, supported by Django, Django REST Framework, GeoDjango, and PostgreSQL/PostGIS, that integrates a deterministic Rule-Based Expert System, scenario-based rainfall input, an interactive GIS-style map, manual location selection, optional one-time foreground location, explainable susceptibility output, and separate Decision Support System guidance; provide a custom Web Administration System for authorized review and maintenance of permitted content and records; protect raw Expert System rules and algorithm logic from ordinary administrator editing; and establish a fixed-schema CSV exchange requirement for permitted values without representing that requirement as operational until its routes, validation, interface, integration, and tests are completed;

4. test the system's core modules by implementing unit testing, integration testing, system testing, rule and inference validation, application programming interface communication testing, spatial-query testing, database-operation testing, map interaction testing, DSS decision-flow testing, role-based administrative testing, and end-to-end validation to ensure that susceptibility assessment, geographic selection, dynamic

visualization, preparedness guidance, and administrative data management operate accurately and consistently;

5. evaluate the system's overall level of user satisfaction in terms of accessibility, reliability, usability, security, maintainability, and portability of the system using ISO/IEC 25010.

Theoretical Framework

The theoretical framework of FloodSense system illustrates how a Rule-Based Expert System, a dynamic Geographic Information System map, and a separate Decision Support System are integrated into an Android and web platform to provide location-specific flood susceptibility information and pre-event preparedness support to residents of Bacoar City. Approved institutional data and expert-validated knowledge are managed through the Django Web Administration System and stored in PostgreSQL with PostGIS. The Flutter Android application communicates with the Django backend through secured application programming interfaces to request assessments, maps, explanations, preparedness guidance, and verified evacuation resources. The framework keeps susceptibility classification, preparedness guidance, spatial visualization, and administrative publishing as coordinated but clearly defined functions.

Authentication and Onboarding Module. This module manages resident registration and login using an email address and password. The Django backend verifies credentials, applies password rules, supports email-based password recovery, and issues the session or token required for protected mobile requests. A user's local application state cannot grant administrator privileges because every protected action is checked on the server. During first launch, the onboarding screen explains the purpose of FloodSense, the rainfall controls, map legend, susceptibility meanings, Check My Area procedure, Decision Support System role, data date or version, privacy information, and safety disclaimer. The disclaimer emphasizes that the application

provides scenario-based susceptibility and preparedness information rather than a live flood forecast or official warning.

PAGASA-Aligned Rainfall and Location Input Module. This module allows the resident to define the assessment scenario through plain-language rainfall intensity and duration selections. The baseline intensity labels are Light, Moderate, Heavy, Intense, and Torrential, while the supported durations may include 1, 3, 6, 12, and 24 hours. The internal thresholds and wording must follow the final PAGASA reference approved for the study. The resident may select a supported area from the map or manually place a pin through Check My Area. The selected rainfall values and location are planning inputs for the current request; they do not prove current weather conditions or the resident's actual physical location. Unsupported combinations produce a limitation response instead of an assumed classification.

Web Administration and Knowledge Management Module. This module is the controlled maintenance workspace used by authorized administrators. It manages geographic zones and map features, rainfall parameters, Expert System facts and rules, Decision Support System questions and branches, evacuation-center records, public explanations and disclaimers, source and provenance information, and permitted user-support actions. Institutional materials from BDRRMO, CPDCO, PAGASA, and other approved providers are entered or imported as controlled records and are associated with their source, review status, effective date, and version. Critical changes follow the sequence Draft, Validation, Review, Approval, and Publication. Published versions remain available for audit or rollback, and incomplete or unapproved records are not released to residents.

Django REST and GeoDjango Processing Module. This module provides the controlled connection between the Android application, administrative workspace, processing services, and database. Django handles server-side authentication, permissions, validation, business logic, and administrative functions. Django REST Framework receives and returns secured JSON and GeoJSON data for the mobile

application. GeoDjango provides the spatial models and operations used to store and query polygons and points. When Check My Area submits a coordinate, GeoDjango and PostGIS perform a point-in-polygon query and return the most specific supported zone. Neither the Android application nor the administrator's browser connects directly to the database; all operations pass through the controlled Django services.

Rule-Based Expert System Assessment Module. This module implements a deterministic Rule-Based Expert System. In rule-based expert-system theory, a knowledge base stores domain knowledge and an inference procedure applies rules to known facts to reach a conclusion (Buchanan & Shortliffe, 1984). FloodSense represents approved knowledge through geographic-zone facts, rainfall categories and durations, decision tables, structured IF-THEN rules, exceptions, priorities, sources, versions, and explanation text. Forward chaining begins with the resolved zone, rainfall scenario, active zone profile, and published rule set; it tests conditions and fires the applicable rules. The primary outputs are Low, Moderate, High, and Very High. Conflicting rules may return Uncertain, missing coverage may return Insufficient Data, and a point beyond approved boundaries returns Outside Supported Area.

Dynamic GIS Map and Check My Area Module. This module presents approved Bacoar City spatial data through a movable map rendered in Flutter using `flutter_map`. Residents can pan, zoom, tap supported zones, open information pop-ups, display map layers, read a text-supported color legend, view evacuation-center markers, and reposition the Check My Area pin. Supported polygons are colored Low in green, Moderate in yellow, High in orange, or Very High in red based on the current Expert System result. Changing the rainfall scenario causes the same approved polygons to be evaluated and recolored. Map precision is limited to the resolution of the approved boundary and zone data, and administrators cannot assign a public susceptibility class merely by painting a polygon color.

Results Summary and Explainable Result Module. This module presents the assessment in both summary and detailed form. The Results Summary lists

supported areas with their current susceptibility badges and may allow searching or filtering by barangay or class. The detailed result identifies the resolved area, parent barangay, rainfall intensity and duration, susceptibility class, plain-language meaning, matched rule or decision-table basis, summarized conditions, source and version information, update date, and any limitation state. The same zone, scenario, and published rule version must produce the same result on the map, in Check My Area, and in the context given to the Decision Support System. A result is marked outdated when its scenario, location, or controlling version changes.

Decision Support System Module. This module provides pre-event preparedness guidance through a deterministic, database-driven decision tree. Decision support systems organize relevant information and structured guidance to assist human decision-making (Power, 2002). FloodSense begins with the latest valid Expert System result as read-only context and combines it with the resident's answers to approved situational questions. The configured path may provide guidance concerning go-bag preparation, family communication, protection of documents and valuables, assistance for vulnerable household members, monitoring of official advisories, and evacuation readiness. The DSS is separate from the Expert System: it does not change the susceptibility class, predict live conditions, or issue an independent evacuation order.

Verified Evacuation Center Resource Module. This module displays only active evacuation-center records that have been verified from BDRRMO or another authorized city source. Each center is stored as a geographic point and may include its name, barangay, address, responsible office, verification status, validation date, and other information approved for public display. PostGIS can rank centers by straight-line geographic distance from the resident's selected pin, and the Android application can open the selected coordinates in an installed navigation application. A nearby ranking or external route does not guarantee that a road is safe or passable,

that a center is currently open or has available capacity, or that the suggested route is appropriate during an actual emergency.

User Account and Preferences Module. This module allows authenticated residents to view or update approved profile and convenience information, including their display name, email address, home barangay, optional default rainfall scenario, password actions, privacy information, and logout. Passwords are securely processed by Django and are never shown to administrators in plain text. A manually placed Check My Area coordinate and DSS answers are used to complete the requested operation and are not retained as continuous location or behavior history by default. Resident accounts do not permit editing of Expert System rules, Decision Support System content, official map geometry, rainfall references, or evacuation-center records.

PostgreSQL and PostGIS Database Module. All authoritative relational and spatial records are stored in PostgreSQL with the PostGIS extension. The database contains users and roles, rainfall references, barangays and susceptibility zones, geographic profiles, evacuation-center points, Expert System rules and conditions, Decision Support System nodes and branches, source and review metadata, published versions, and audit history. PostgreSQL enforces relational consistency, while PostGIS supports point-in-polygon and straight-line distance operations. The backend retrieves only the compatible active versions required for a request and returns only public approved data to residents. Internet access is required for fresh synchronization and server-side evaluation; any approved cached information must display its date and version when connectivity is unavailable.

Overall, the framework demonstrates how expert-validated knowledge, structured rule-based inference, geographic processing, explainable results, and a separate preparedness decision tree are combined in one community-accessible system. By converting approved institutional records and expert knowledge into a controlled mobile and web service, FloodSense aims to strengthen location-specific

flood susceptibility awareness and support better pre-event preparation without replacing the authority of BDRRMO, PAGASA, barangay officials, or emergency responders.

The diagram presents FloodSense through a top-to-bottom organization. The Internet connection appears above the FloodSense system, the resident and administrator actors appear on the left, approved institutional sources and external display services appear on the right, and the authoritative PostgreSQL/PostGIS database appears below. The stacked modules inside the system boundary show the functions that process user inputs, institutional knowledge, susceptibility rules, spatial data, results, preparedness guidance, evacuation resources, and account information.




Figure 1. System Architecture of FloodSense.

Significance of the Study

The development of FloodSense addresses a critical gap in flood information dissemination by translating expert-provided and expert-validated knowledge, institutional geographic information, and rainfall scenarios into an accessible susceptibility assessment, dynamic map, and pre-event preparedness support. The following stakeholders stand to benefit directly from the study.

For the Bacoor Disaster Risk Reduction and Management Office (BDRRMO). The study provides a prototype channel through which validated susceptibility information and pre-event preparedness guidance may eventually be communicated to residents. The custom Web Administration System currently supports controlled management of DSS guidance, evacuation-center records, source information, and audit history, together with read-only review of map, rainfall-reference, and parameter records. Ordinary administrators are not permitted to rewrite raw Expert System rules or inference logic. The proposed fixed-schema CSV workflow will permit only validated values within system-required fields after implementation and authorization. These functions complement rather than replace official advisories, warnings, and emergency directives.

For the City Planning and Development Coordinator Office - Bacoor (CPDCO). The study demonstrates a practical community use for geographic and planning information maintained by the office, including elevation, flood-hazard, land-use, and barangay-boundary data. The integration of verified geographic records into spatial polygons, point locations, and area-selection functions illustrates how institutional planning information can support public understanding of flood susceptibility without presenting FloodSense as a substitute for official technical maps.

For residents of historically flood-affected barangays. The Android application directly responds to the information deficits identified in the survey: 92% of respondents experienced flooding, only 20% felt well-informed about flood-prone areas, and 64% reported wrong decisions associated with insufficient information.

Residents can select a rainfall scenario, pan and zoom the dynamic map, inspect color-coded susceptibility polygons, use Check My Area, view verified evacuation-center locations, and receive preparedness guidance suited to the susceptibility result and their stated situation. Plain-language rainfall categories reduce the need to interpret technical meteorological measurements, while the disclaimer directs users to continue following BDRRMO and PAGASA advisories.

For future researchers. The study provides a locally grounded reference for combining knowledge engineering, rule-based inference, decision support, and geographic information in an Android disaster-preparedness application. The documented approach to expert knowledge acquisition, rule validation, spatial data management, dynamic map interaction, administrative maintenance, software testing, and ISO/IEC 25010 evaluation can inform related studies in other flood-prone communities, subject to validation with local experts, datasets, and user populations.

Time and Place of the Study

The research and development of the FloodSense application were conducted using the Design Thinking methodology, beginning with data-gathering activities before the formal study period. The official duration of the study spans from September 2026 to May 2027. Major activities, including requirements analysis, knowledge acquisition, rule structuring, system design, mobile and web development, geographic data preparation, testing, evaluation, and documentation, were carried out at the Department of Computer Studies, Cavite State University - Bacoar City Campus, located in Soldiers Hills IV, Molino, Bacoar City, Cavite. The campus served as the primary venue for software development, academic consultation, integration testing, and preparation of the research manuscript.

Initial data gathering commenced in early May 2026 during the Empathize phase of Design Thinking. A structured survey was administered to 50 residents across 12 barangays in Bacoar City, many of which have historically experienced flooding,

from May 5 to May 12, 2026, to capture prevailing challenges in flood information access, timeliness, clarity, and decision-making. On May 12, 2026, a key informant interview was conducted at the Bacoor Disaster Risk Reduction and Management Office (BDRRMO), located at the City of Bacoor Legislative and Disaster Resilience Building, Bacoor Government Center, Barangay Bayanan, Bacoor City. The interview aimed to validate survey findings, understand the office's workflows and information holdings, and assess the feasibility of a community-facing flood susceptibility and preparedness tool. A supplementary key informant interview was conducted on May 18, 2026 with the Officer-in-Charge of the Bacoor City Planning and Development Coordinator Office (CPDCO), located at the Bacoor Government Center, Barangay Bayanan, Bacoor City. The interview confirmed the availability of elevation maps, flood-hazard maps, land-use maps, and barangay-boundary maps and established the geographic context needed for the study. The outputs of the Empathize phase guided the identification of system requirements and the sources to be subjected to expert validation.

Following data gathering, the study proceeds through the Define, Ideate, Prototype, and Test phases within the research timeline. Requirements, interface wireframes, geographic data structures, susceptibility rules, DSS content, mobile screens, and Web Administration System functions are refined through consultations and development evidence. Final resident evaluation and system-quality analysis remain future activities. Results will be reported only after the approved instrument, sampling procedure, completed responses, and analysis are available.

Scope and Limitation of the Study

The study develops FloodSense as a scenario-based, pre-event flood-susceptibility assessment and preparedness-support system for Bacoor City. Its deterministic Rule-Based Expert System evaluates a user-confirmed rainfall scenario and supported location, while the separate Decision Support System presents

published preparedness guidance without changing the susceptibility result. The current prototype produces Low, Moderate, High, or Very High demonstration outputs and explanations. Operational use remains blocked until approved local susceptibility data, validated parameters, and institutional authorization are available. FloodSense does not provide real-time flood monitoring, official forecasts, warnings, evacuation orders, or safety guarantees.

The primary intended users of the Android application are Bacoor City residents. In the current mobile flow, a resident selects Light, Moderate, Heavy, Intense, or Torrential rainfall and a duration of 1, 3, 6, 12, or 24 hours, confirms the hypothetical scenario, selects or confirms a location, and explicitly requests an assessment. Resident registration, login, persistent profiles, and assessment history are not exposed in the current interface and remain unimplemented for the intended user flow.

The interactive map is limited to supported Bacoor City reference and demonstration data. It can pan and zoom, display scenario-dependent demonstration colors, accept manual area selection, and show a neutral 47-barangay administrative reference boundary. The boundary layer represents current barangay identities through a documented derivation and has passed technical geometry checks, but it is not automatically City-issued or City-verified and contains no flood-susceptibility facts. The map does not display live flood extent, water depth, traffic conditions, road closures, river level, center occupancy, or satellite rainfall imagery.

Location functions allow the user to select an area manually, place or adjust a map pin, or request the device's location once while the application is in the foreground. The application can propose a barangay from the coordinate and requires the user to confirm or correct it before assessment. The coordinate is used for the active request and is not continuously collected in the background. The current function does not find safe routes, verify road passability, or continuously track the resident.

The backend and custom Admin portal include an evacuation-center record workflow. This capability does not yet expose resident-facing nearby-center discovery, distance ranking, live capacity, operating status, or safe-route guidance. Any future resident display must rely on authorized and current records and must direct users to confirm emergency instructions through official channels.

The Decision Support System is confined to pre-event preparedness and remains separate from the susceptibility assessment. The current implementation can return published guidance associated with the assessment context. A resident-facing structured multi-question decision tree has not been verified as complete. The DSS does not alter the susceptibility class, issue autonomous evacuation orders, diagnose conditions, guarantee safety, or make the resident's final decision.

A separate custom Web Administration System provides authenticated access to a dashboard, read-only map-data and rainfall-reference review, parameter-governance views, and workflows for DSS content, evacuation-center records, data sources, and audit history. Ordinary administrators cannot directly edit raw Expert System rules, rule conditions, priorities, conflict-resolution logic, or the algorithm. Technical Django Admin remains a separate developer or research-maintenance interface. The confirmed fixed-schema CSV export-and-import workflow is not yet operational and will require routes, services, schema and value validation, interface controls, permissions, integration, and tests before it can be described as implemented.

The implementation stack uses Flutter and Dart for the mobile application; flutter_map for resident-facing mapping; Python Django and Django REST Framework for backend services and REST interfaces; GeoDjango for geographic operations; PostgreSQL with PostGIS for relational and spatial records; and Django templates with Leaflet for the custom administrative interface. The current prototype requires network access for integrated server functions. iOS support, fully offline operation, live sensors,

automated meteorological feeds, background polling, background GPS tracking, emergency dispatch, and machine-learning prediction are outside the current scope.

The reliability of any susceptibility assessment depends on the completeness, geographic resolution, provenance, institutional approval, and expert validation of the data and knowledge used. No approved operational susceptibility dataset is currently present in the repository. The available 47-barangay layer is an administrative reference only, while provisional research materials remain unvalidated or restricted. Demonstration results must therefore not be presented as official Bacoor City flood-hazard information.

Data privacy and security are addressed in accordance with Republic Act No. 10173, or the Data Privacy Act of 2012. The current location flow requests foreground permission only when the user chooses the location function, uses the coordinate for the active request, permits confirmation or correction of the detected barangay, and does not implement continuous background location tracking. Administrative functions require authenticated and authorized access. Evaluation findings will not be generalized until valid survey and system-evaluation data are available.

Definition of Terms

The following terms are defined operationally as they are used in this study to ensure clarity and consistency throughout the research:

Android Application. The resident-facing FloodSense software developed with Flutter. Its current interface supports scenario selection and confirmation, manual or one-time foreground location input, barangay confirmation or correction, assessment requests, map presentation, susceptibility results, explanations, and preparedness guidance. Resident accounts, assessment history, notifications, and offline operation are not currently exposed.

Check My Area. The location-selection flow that allows manual area selection, placement or adjustment of a map pin, and an optional one-time foreground location

request. A detected barangay is proposed for user confirmation or correction before assessment; the function does not continuously track the device.

Color-Coded Susceptibility Levels. The visual scheme used on the dynamic map in which green indicates Low, yellow indicates Moderate, orange indicates High, and red indicates Very High flood susceptibility for the active scenario.

CPDCO (City Planning and Development Coordinator Office). The Bacoor City office that maintains planning and geographic information, including elevation, land-use, flood-hazard, and barangay-boundary materials relevant to the study.

Decision Support System (DSS). The component separate from the Rule-Based Expert System that presents published pre-event preparedness guidance using the assessment context. It does not change the susceptibility result, issue an official warning or evacuation order, or make the user's final decision.

Dynamic Map. The interactive map that supports panning, zooming, scenario-dependent demonstration coloring, manual area selection, map-pin placement, and display of the neutral 47-barangay reference layer. The reference boundary is not an official flood-hazard dataset.

Expert-Provided and Expert-Validated Knowledge. Flood-related facts, parameters, rules, preparedness guidance, and supporting information that have been supplied or reviewed by an authorized source and recorded with adequate provenance. Repository presence or technical validation alone does not establish institutional approval.

Expert System. A knowledge-based computer system that applies stored facts and conditional rules through an inference process. In FloodSense, it produces an explainable susceptibility class for a supported geographic area and rainfall scenario.

Flood Susceptibility. The relative potential of a supported geographic area to experience rainfall-related flooding under a user-confirmed scenario. The current prototype demonstrates Low, Moderate, High, or Very High outputs but does not yet

contain an approved operational Bacoar City susceptibility dataset and is not a real-time prediction.

Geographic Information System (GIS). A system for organizing, analyzing, and presenting information associated with geographic locations. FloodSense uses GIS functions for polygons, points, containment queries, interactive visualization, and evacuation-center locations.

GeoDjango. The geographic extension of Django used by FloodSense to represent spatial data and perform geographic operations between backend services and the PostGIS database.

Inference Process. The procedure that matches facts from the selected rainfall scenario and geographic area against validated rules in the knowledge base to derive a susceptibility conclusion and supporting explanation.

Knowledge Base. The structured collection of expert-validated facts, conditional rules, geographic attributes, rainfall parameters, susceptibility categories, and related provenance used by the Expert System.

PAGASA-Aligned Rainfall Input. The current interface labels for Light, Moderate, Heavy, Intense, and Torrential rainfall and durations of 1, 3, 6, 12, or 24 hours. These selections are hypothetical scenario inputs. Their operational thresholds and use require authoritative source confirmation and validation before official deployment.

PostGIS. The spatial extension of PostgreSQL used to store and query FloodSense geographic polygons, points, boundaries, selected locations, and evacuation-center coordinates.

Preparedness Provenance. Information identifying the source, validation status, responsible actor, relevant date, and version of a preparedness item or related record. Provenance permits users and administrators to distinguish approved, provisional, and unsupported information.

Rainfall Parameters. The supported combination of rainfall intensity and duration selected by the user and applied as scenario facts during Expert System assessment.

Rule-Based Expert System. An Expert System in which domain knowledge is represented as conditional rules. FloodSense evaluates applicable rules against known scenario and geographic facts to produce a susceptibility assessment.

Web Administration System. The custom browser-based interface used by authorized administrators for the dashboard, read-only map and rainfall-reference review, parameter governance, DSS-content management, evacuation-center management, data-source management, and audit history. It does not expose raw rule editing. The separate technical Django Admin is reserved for developer or research maintenance. Fixed-schema CSV export and import is a confirmed but currently unimplemented requirement.

REVIEW OF RELATED LITERATURE

This chapter presents a review of related literature, articles, and studies that provide guidance in identifying and formulating the requirements needed to start the project. Moreover, this chapter was designed to examine relevant concepts, methods, challenges, and practices associated with flood-susceptibility assessment, geographic information systems, Rule-Based Expert Systems, and Decision Support Systems.

Related Foreign Literature

Flood Susceptibility and Scenario-Based Assessment

Flood susceptibility expresses the relative tendency of a location to experience flooding when relevant conditions are present. It differs from flood hazard, which concerns the probability and physical characteristics of an event; exposure, which concerns people or assets in affected places; vulnerability, which concerns the capacity to be harmed; and risk, which combines hazard and potential consequences. Membele, Naidu, and Mutanga (2022) found that flood-vulnerability mapping in developing countries varies substantially in terminology, indicators, spatial scale, data availability, and validation practice. Their review shows why a public system must name the type of assessment it performs and avoid presenting a general vulnerability or hazard map as a locally validated susceptibility conclusion.

Scenario-based assessment supports planning by holding selected conditions explicit instead of implying that the system is observing an event as it occurs. A hypothetical rainfall intensity and duration can be treated as assessment inputs only when their meanings, permitted combinations, and geographic applicability are documented. This supports the FloodSense interaction in which the resident selects or confirms a scenario before requesting assessment. It does not establish that the scenario is current, predicted, or officially issued, and it does not justify importing weights or thresholds derived for another place.

Deterministic Rule-Based Expert Systems and Knowledge Bases

A Rule-Based Expert System represents domain knowledge through facts, conditions, and production rules and applies an inference procedure to derive a conclusion. Buchanan and Shortliffe (1984) provide the foundational distinction between the knowledge base and the inference mechanism. More recently, Papadopoulos et al. (2022) reviewed technologies and standards used in rule-based decision-support systems and described how encoded knowledge and rules engines evaluate case-specific facts. Although their review concerns clinical systems, the architectural distinction is relevant to FloodSense: flood knowledge, scenario facts, geographic facts, and explanations belong to controlled knowledge structures, while the inference procedure determines which eligible rule applies.

Deterministic processing means that the same approved facts and the same published rule version should produce the same result. It does not imply that the rules are scientifically valid merely because the software executes them consistently. Knowledge acquisition, conflict handling, parameter definitions, version control, and expert or institutional validation remain necessary. Accordingly, ordinary FloodSense administrators may manage approved records and permitted values but do not rewrite raw rule conditions, priorities, conflict-resolution logic, or algorithm code. The confirmed fixed-schema CSV exchange is a future controlled-value workflow and is not evidence that such exchange is currently operational.

Explainable Inference

Explainability is necessary when a system produces a classification that may influence preparedness decisions. Kostopoulos, Davrazos, and Kotsiantis (2024) reviewed explainable decision-support approaches and emphasized transparency, interpretability, and human-understandable justification. Their review primarily addresses artificial-intelligence-based systems, but its communication principles apply to deterministic inference: a user should be able to understand the relevant inputs, the

basis of the result, and the limitations of the evidence without being required to inspect source code or raw rule definitions.

For FloodSense, an explanation should identify the confirmed rainfall scenario, resolved geographic context, susceptibility class, applicable basis, source or version information, and any limitation state. This supports accountability while preserving the distinction between explanation and rule administration. It also prevents a color or label from appearing authoritative without disclosing what it represents. Explainability does not remove the need for validated data, and a clear explanation cannot turn provisional information into an official local assessment.

Decision Support and Preparedness Guidance

A Decision Support System organizes information, alternatives, or recommended actions to assist human judgment. In flood preparedness, support may include understandable mitigation choices, household preparation, communication planning, protection of documents and valuables, assistance for vulnerable household members, attention to official advisories, and evacuation readiness. Mostafiz et al. (2022) observed that many web-based flood tools provide technical information but do not consistently provide locally actionable information for individuals and communities. Their review supports combining understandable risk communication with practical guidance while clearly stating the tool's authority and limitations.

FloodSense separates the susceptibility assessment from preparedness guidance. The deterministic Expert System produces the assessment, while the DSS presents source-backed pre-event guidance without changing the susceptibility class. Information about evacuation facilities may support readiness when its source, verification date, location, and operational limitations are known, but distance alone does not prove route safety, current opening, accessibility, or available capacity. The DSS therefore assists preparation and does not issue an official warning, evacuation order, or guarantee of safety.

GIS, Interactive Maps, and Spatial Databases

Geographic Information Systems organize, analyze, and present information associated with locations. Their value in flood research depends on the suitability of the layers, coordinate reference systems, spatial resolution, classification methods, and validation procedures. An administrative boundary can resolve the name of a barangay or provide map context, but it contains no flood-susceptibility fact unless appropriate hazard or susceptibility evidence has been associated with it. This distinction is important when users may interpret any colored polygon as an official hazard layer.

Spatial databases support the controlled storage and querying of geographic records. The PostGIS Development Group (2026) explains that PostGIS extends PostgreSQL with geometry and geography types, spatial indexes, spatial relationships, coordinate transformation, validity operations, and spatial processing. These capabilities are relevant to point-in-polygon queries, administrative-area lookup, map-feature storage, and provenance-linked geographic records. They provide technical infrastructure, not scientific validation: a valid geometry and a successful spatial query do not establish that a flood conclusion is institutionally approved.

Flood-Risk Communication

Flood-risk information must be understandable, actionable, and explicit about uncertainty. Mostafiz et al. (2022) identified gaps in web-based flood communication, particularly where tools provide information without sufficiently connecting it to decisions that residents can make. Clear terms, legends, labels, explanation text, and source notices help prevent non-specialists from treating model outputs as certain predictions. Communication should also distinguish long-term or scenario-based information from time-sensitive official warnings.

These principles support a guided FloodSense flow rather than an unexplained technical map. Susceptibility colors must be paired with text, the selected scenario,

and limitations. Preparedness information must direct users toward official channels during actual events. The interface must not imply that a neutral boundary layer, a demonstration color, or a provisional record represents a current flood condition.

Data Provenance and Geographic Validation

Provenance records where information originated, how it was transformed, which version was used, and what review or approval applies. Tullis and Kar (2021) connected provenance to ethical replicability and reproducibility in GIScience, including critical applications in which geographic data affect public decisions. Fakhruddin et al. (2022) similarly emphasized risk-informed data practices and the importance of understanding how disaster and climate data are produced, shared, interpreted, and governed.

For FloodSense, provenance should accompany susceptibility parameters, geographic layers, preparedness items, and resource information. Technical geometry validation may confirm coordinate-system consistency, valid shapes, or feature counts, but institutional validation concerns authority, currency, meaning, and permitted public use. The two forms of validation are related but not interchangeable. This distinction prevents a technically processed dataset from being represented as official Bacoor City flood information without documented approval.

Foreground Location and Privacy

Mobile location can reveal a person's position and may contribute to identification or tracking. Android Developers (2026) distinguishes foreground access, one-time access, and background access and recommends requesting only the permission needed for the active function. This supports a FloodSense flow in which location is obtained only after a user initiates location selection or assessment, while manual selection remains available when the resident declines permission or prefers another area.

Foreground acquisition does not imply continuous monitoring. FloodSense does not require background GPS tracking, automatic polling, or autonomous location-based alerts. Location handling should remain purpose-limited to the active assessment, use only the precision necessary for the supported geographic operation, and avoid retaining unnecessary movement information. The presentation must also allow the user to confirm or correct the detected barangay because device accuracy and boundary proximity can affect geographic resolution.

Software Testing and Quality Evaluation

Software testing establishes whether specified behavior is implemented under defined conditions, while quality evaluation examines broader product characteristics. ISO/IEC 25010:2023 defines a product-quality model with nine characteristics for specifying and evaluating information and communication technology products (International Organization for Standardization [ISO], 2023). The model can guide the selection of criteria for FloodSense, but it does not provide a ready-made acceptance result or replace an approved evaluation instrument.

A defensible evaluation must identify the tested build, participants or evaluators, tasks, criteria, scale, procedure, valid responses, and interpretation method. Repository tests and interface demonstrations can support implementation verification, but they are not resident-acceptance findings. Because the final FloodSense survey and evaluation are not complete, Chapter 2 uses ISO/IEC 25010 only as literature supporting future assessment and does not report quality scores.

Related Local Literature

Philippine Flood Conditions and Institutional Preparedness

Official Philippine statistics continue to record substantial effects from extreme events and disasters. The Philippine Statistics Authority (PSA, 2026) summarizes national information on disaster occurrence, affected populations, deaths, and

economic losses. These national figures establish the continuing relevance of disaster preparedness but do not identify the susceptibility of a particular Bacoor barangay or validate the inputs of a local application.

The National Disaster Risk Reduction and Management Council's National Disaster Response Plan identifies institutional responsibilities and coordinated actions for hydro-meteorological hazards (NDRRMC, 2024). The plan reinforces that warnings, response decisions, and emergency coordination belong to authorized government mechanisms. FloodSense may support pre-event understanding and preparedness, but residents must continue to follow PAGASA, local disaster offices, barangay authorities, and emergency responders during an actual event.

Official Hazard Information and Warning Authority

PAGASA operates rainfall and flood-information processes that use observations, forecasts, water-level information, and coordinated warning protocols. Its 2023 Annual Climate Bulletin explains the role of rainfall warning systems and the use of official warning levels for public action (PAGASA, 2024). FloodSense rainfall selections are hypothetical assessment inputs; they are not automatic updates from PAGASA, an interpretation of current rainfall, or an official warning product.

GeoRisk Philippines presents HazardHunterPH as a national platform for indicative hazard assessment while advising users that results depend on available government data and do not replace official hazard reports from mandated agencies (GeoRisk Philippines, n.d.). Its source notices and limitations demonstrate responsible hazard communication. The same principle applies to FloodSense: sources, dates, limitations, and validation status should remain visible, and an indicative or provisional record should not be represented as an absolute prediction.

Cavite, Bacoar City, and the Imus River Basin

The Japan International Cooperation Agency reported the inauguration of flood-mitigation facilities associated with the Imus River Basin and low-lying areas of Imus and Bacoar (JICA, 2021). This institutional record confirms the relevance of watershed and infrastructure conditions to the local context. It does not provide barangay susceptibility classifications, rainfall-rule thresholds, or validation for FloodSense, and it should not be treated as a substitute for hydrologic or hazard data.

Administrative geography in Bacoar has also changed. The PSA documented the 2023 merger and renaming of barangays and currently lists 47 barangays in the City of Bacoar (PSA, 2023, 2025). These records support the current identities used in a reference layer. They do not establish the accuracy of every derived polygon, City verification of a third-party boundary, or flood conditions within any barangay. Administrative reference and flood-susceptibility evidence must therefore remain separate.

Administrative Data Governance and Responsible Use

Government publications, local records, and research datasets differ in authority and permitted use. An official list of administrative units may verify names and codes, while an authorized hazard agency may provide hazard information, and a local office may validate operational records. Combining these sources requires documentation of ownership, date, scale, processing, approval, and restrictions. Provenance is particularly important when a dataset has been transformed, because technical processing can change geometry or attributes without changing the institution responsible for the original information.

FloodSense consequently distinguishes approved, provisional, technically validated, and unsupported information. The 47-barangay layer may serve as a current administrative reference after documented derivation and geometry checks, but it is not a flood-susceptibility layer and is not automatically City-issued or City-verified. No

operational susceptibility dataset should be described as established until the necessary source, method, expert review, institutional authority, and database integration are documented.

Philippine Data Privacy and Software-Quality Context

Republic Act No. 10173, the Data Privacy Act of 2012, requires personal-information processing to observe transparency, legitimate purpose, and proportionality. For a resident-facing location function, these principles support clear notice, user initiation, limited collection, secure handling, and avoidance of continuous background tracking. They also support role-controlled administrative access. The Act is legally authoritative despite falling outside the preferred publication period for recent literature.

Philippine software studies have also used ISO/IEC 25010 as an evaluation framework, but the criteria and edition must be identified accurately. An evaluation of another application cannot be transferred to FloodSense, and the presence of a questionnaire does not establish completed results. FloodSense quality conclusions will require its own approved instrument, respondents or evaluators, documented procedure, and completed analysis.

Related Foreign Studies

FloodAdapt: An Open-Source Application for Flood-Risk Scenario Modeling and Adaptation Planning

Deltares (2025) developed FloodAdapt as an open-source decision-support application for exploring flood risk under alternative present and future conditions. The application links the SFINCS flood model with Delft-FIAT impact assessment and allows users to define what-if events, future scenarios, and adaptation measures. Its outputs include mapped flooding and impacts, summary metrics, and cost-benefit

information intended for planners, analysts, and decision makers rather than for automatic public warning.

FloodAdapt shows how explicit scenarios can be compared without presenting them as observations of a current event. Its physics-based modeling, impact calculations, and adaptation analysis require specialized data and expertise, and the downloadable release does not supply Bacoor-specific inputs or institutional approval. The model configuration, damage functions, and scenario assumptions therefore cannot be transferred directly to Bacoor City.

FloodAdapt is similar to FloodSense in asking users to consider a defined scenario and in presenting mapped decision information. It differs in audience, scale, scientific method, and output: FloodSense uses a resident-confirmed rainfall scenario and deterministic rules to produce a bounded susceptibility class followed by separate preparedness guidance. FloodSense does not perform hydrodynamic simulation, damage estimation, adaptation comparison, or cost-benefit analysis.

GloFAS: An Operational Platform for Global Flood Forecasting and Monitoring

The Copernicus Emergency Management Service (2026) operates the Global Flood Awareness System, or GloFAS, as a global flood-forecasting and monitoring service. Its web interface provides map layers, forecast products, hydrological information, and data access intended to support preparedness and emergency-management activity across transnational river basins. The service draws on operational forecasting infrastructure and is maintained within the Copernicus Emergency Management Service and the European Centre for Medium-Range Weather Forecasts.

GloFAS demonstrates the institutional, computational, and data requirements of an operational forecast service. Global model resolution, forecast uncertainty, local river behavior, and the need for national or local interpretation limit direct use for

household-level decisions. Its products also do not constitute Bacoar City validation and cannot be converted into FloodSense rules without an approved methodology, local evidence, and appropriate institutional authority.

Both GloFAS and FloodSense use maps and flood-related categories to support understanding, but their functions are fundamentally different. GloFAS is an operational monitoring and forecasting service; FloodSense is a user-requested, scenario-based pre-event assessment. FloodSense does not ingest live GloFAS forecasts, update rainfall automatically, monitor rivers, or issue official warnings.

IFIS: A Public Web Platform for Real-Time Flood Information, Sensor Data, and Forecasts

The Iowa Flood Center (2024) describes the Iowa Flood Information System, or IFIS, as a publicly accessible platform that integrates a statewide sensor network, weather and hydrologic information, flood-inundation maps, and real-time forecasts. The system has evolved since its 2011 launch and supports residents, emergency managers, researchers, and other users through an interactive geographic interface. Its operation depends on Iowa-specific sensors, models, data streams, and institutional maintenance.

The Iowa Flood Center (n.d.) also states that the platform is under active development and that its maps and information are provisional and are not a substitute for official regulatory determinations. This qualification is important because technically sophisticated public maps can still have geographic, predictive, and legal limitations. IFIS does not provide an approved susceptibility dataset, rule base, or evaluation result for Bacoar City.

IFIS resembles FloodSense in offering location-oriented map information and understandable public presentation. It differs because IFIS uses real-time sensor and forecasting infrastructure, whereas FloodSense requires a resident to confirm a hypothetical scenario and explicitly request deterministic assessment. FloodSense has

no statewide sensor network, continuous monitoring, autonomous alerting, or real-time forecast function.

RAPT: A Geographic Information System for Community Resilience Planning and Data Visualization

The Federal Emergency Management Agency (FEMA, 2025) maintains the Resilience Analysis and Planning Tool, or RAPT, as a public geographic application for community resilience planning. The tool brings together more than one hundred layers concerning population, infrastructure, hazards, and community conditions and supports visualization, filtering, comparison, and export for planning, mitigation, response, and recovery activities in the United States.

RAPT illustrates the value of bringing contextual data and provenance into one map, but it is not limited to floods and does not convert every displayed layer into a location-specific hazard conclusion. Its United States datasets, administrative units, definitions, and legal context are not applicable to Bacoor without local substitution and validation. Layer availability also does not guarantee suitability for a particular decision.

RAPT and FloodSense both use geographic interfaces to organize information for decision support. FloodSense differs by applying a protected deterministic inference process to a resident-confirmed rainfall scenario and then presenting separate preparedness guidance. FloodSense does not reproduce RAPT's national data catalog, demographic analysis, resilience indicators, or export capabilities.

Check the Long Term Flood Risk for an Area in England

The Environment Agency (2024) supports England's national assessment of flood and coastal erosion risk, while GOV.UK (n.d.) offers the public Check the Long Term Flood Risk for an Area service, which allows a user to search a place and review long-term risk from rivers and the sea, surface water, reservoirs, and groundwater. The

service also provides contextual information on climate change and links users to planning and preparedness resources through an official government channel.

The service explicitly distinguishes area-level information from the risk of an individual property. That limitation reflects differences in spatial scale, source datasets, update cycles, and the uncertainty of local conditions. Its English hazard models, categories, responsibilities, and official status cannot be generalized to Bacoor City or used to validate FloodSense.

The location-search interaction and careful limitation statements are relevant to FloodSense's map and communication design. FloodSense, however, is not a national long-term-risk authority and does not cover multiple hazard mechanisms or property-level risk. It presents a bounded hypothetical-scenario susceptibility assessment and directs users to official agencies for current forecasts, warnings, and emergency instructions.

Related Local Studies

UP NOAH Know Your Hazards and NOAH Studio: Interactive Philippine Platforms for Hazard Mapping and Flood-Scenario Visualization

The UP NOAH Center (n.d.) maintains public location-based interfaces through Know Your Hazards and NOAH Studio. These platforms allow users to search places, view hazard layers, and examine flood scenarios such as the five-, twenty-five-, and one-hundred-year layers derived from simulations, satellite information, and historical or geographic datasets. Their public maps support awareness and exploration across Philippine locations.

UP NOAH also publishes disclaimers on the interpretation and authority of its layers, including the limits of administrative boundaries and the need to consult appropriate agencies. Return-period flood scenarios are not the same as the rainfall-intensity and duration selections used by FloodSense. The platform's layers, simulations, and classifications cannot be treated as imported or approved

FloodSense data unless provenance, permission, methodology, validation, and integration are separately established.

The UP NOAH interfaces are similar to FloodSense in their use of interactive maps and location-based flood communication. They differ in scenario definition, data production, geographic coverage, and institutional purpose. FloodSense does not claim to reproduce NOAH simulations, predict inundation extent, or provide the same nationwide hazard products.

HazardHunterPH: A Philippine Location-Based Application for Indicative Multi-Hazard Assessment

GeoRisk Philippines (n.d.) presents HazardHunterPH as a public web application that generates indicative multi-hazard assessment reports for a user-selected Philippine location. The platform combines hazard information from mandated government agencies and communicates the available layers, source institutions, and assessment limitations. It is intended to improve public access to location-based hazard information rather than to replace the official reports issued by responsible agencies.

HazardHunterPH's own guidance states that the report is indicative and should not be used as an official or legal document. Available results depend on the datasets supplied to the platform, and a location report does not eliminate the need for agency confirmation. These limitations are directly relevant to Bacoar because neither a national platform nor an administrative reference layer automatically establishes FloodSense's local susceptibility parameters.

HazardHunterPH and FloodSense both use a selected location and a map to communicate hazard-related information. HazardHunterPH retrieves available government hazard layers across multiple hazards, whereas FloodSense applies deterministic rules to a user-confirmed hypothetical rainfall scenario and presents separate preparedness guidance. FloodSense must preserve HazardHunterPH's

lesson on visible sources and limitations without implying that the two systems have the same data, authority, or output.

GeoMapperPH: A Governed Geospatial Application for Collecting Hazard, Exposure, Vulnerability, and Coping-Capacity Data

The Department of Science and Technology-Philippine Institute of Volcanology and Seismology (DOST-PHIVOLCS, 2022a) describes GeoMapperPH as a GeoRisk Philippines application used by trained local-government and agency personnel to collect information on hazards, exposure, vulnerability, and coping capacity. The platform supports standardized field data collection and contributes records to exposure databases that can be used in risk assessment and planning. Its documented training context shows that data collection is governed by authorized users, defined procedures, and institutional coordination.

GeoMapperPH is not presented as an unrestricted resident assessment application. The usefulness of its records depends on collection quality, classification consistency, source responsibility, access controls, and continued updating. Training materials or the existence of a collection application do not prove that its datasets have been approved for FloodSense or imported into the FloodSense database.

The application is relevant to FloodSense because it illustrates provenance, standardized schemas, permissions, and administrative data governance. FloodSense differs in serving a resident scenario-assessment flow and in protecting its deterministic rule logic from ordinary administrators. The confirmed fixed-schema CSV workflow would govern permitted values rather than reproduce GeoMapperPH's field-data collection functions, and that workflow is not yet operational.

PlanSmartPH Ready to Rebuild: A Web-Based Rehabilitation and Recovery Planning Application for Local Government Units

DOST-PHIVOLCS (2022b) describes PlanSmartPH Ready to Rebuild as a web application developed with national agencies and development partners to assist local governments in preparing rehabilitation and recovery plans. The platform organizes baseline data, damage and loss information, recovery needs, programs, and planning outputs so that local officials can develop structured post-disaster plans more efficiently.

PlanSmartPH operates in an institutional planning context and depends on the completeness and validation of local-government data. Its recovery-planning workflow, participating agencies, datasets, and user roles differ from a resident-facing pre-event susceptibility tool. It does not provide approved Bacoor rainfall-rule parameters or establish that FloodSense can make official recovery, response, or evacuation decisions.

Both applications demonstrate the value of structured data and decision support, but they support different phases of disaster management. PlanSmartPH assists post-disaster rehabilitation and recovery planning, while FloodSense supports pre-event scenario understanding and household preparedness. FloodSense therefore does not inherit PlanSmartPH's planning authority, damage assessment, financial estimates, or institutional outputs.

Web-Based Solution for Flood Warning Decision Support in Leyte: A Sensor-Based Flood-Monitoring and Warning Prototype

Bentoso et al. (2021) developed and tested a web-based flood-warning decision-support prototype for the Province of Leyte. The researchers used rainfall and water-level sensors, data communication, a web dashboard, graphical readings, warning thresholds, and notification functions to help responsible users monitor

conditions in flood-prone areas. The conference paper describes a prototype and its functional testing; it does not establish province-wide operational deployment.

The system's sensor locations, communication infrastructure, rainfall and water-level thresholds, and warning procedures were designed for its own context. Those elements cannot be transferred to Bacoar without a new scientific and institutional basis. A working prototype also does not prove the accuracy or authority of warnings outside the study setting.

The Leyte application and FloodSense both organize flood-related information through a digital interface and aim to support preparedness decisions. The difference is decisive: the Leyte prototype monitors sensors and generates warning information, while FloodSense has no continuous monitoring, background polling, autonomous alerts, or official warning authority. FloodSense remains a user-requested hypothetical scenario assessment with separate guidance.

Synthesis of the Reviewed Literature

The reviewed literature separates susceptibility from hazard, exposure, vulnerability, and risk. Membele et al. (2022) show why mapping concepts and validation methods must be identified before a result is communicated. Mostafiz et al. (2022) add that a technically informative map is less useful to residents when it does not connect its result to understandable action. Together, these works support FloodSense's separation of a user-requested susceptibility assessment from source-backed preparedness guidance.

The reviewed systems demonstrate different forms of geographic decision support. Deltares (2025) uses model-based what-if scenarios in FloodAdapt, while the Copernicus Emergency Management Service (2026) and Iowa Flood Center (2024) provide operational forecasts or monitoring information. In the Philippines, the UP NOAH Center (n.d.) and GeoRisk Philippines (n.d.) present location-based hazard

information, whereas DOST-PHIVOLCS (2022a, 2022b) documents agency-oriented data collection and recovery planning. Bentoso et al. (2021) instead investigated sensor-based warning in Leyte. Their data, geographic scale, intended users, and authority differ from those of FloodSense; their thresholds and findings cannot simply be applied to Bacoar City.

Tullis and Kar (2021) emphasize provenance in geographic work, and the Philippine platforms' own source and boundary notices illustrate why technical processing must be distinguished from institutional validation. For FloodSense, a 47-barangay administrative reference layer cannot by itself establish flood susceptibility. Deterministic rule matching may make a result repeatable and explainable, but its public validity still depends on locally appropriate data, documented rules, expert review, and authorized use.

Research Gap

Existing platforms already provide scenario simulation, official hazard-layer lookup, real-time monitoring, forecasts, and institutional planning. The reviewed evidence does not establish that these distinct functions are routinely combined for Bacoar residents in a single flow that starts with a user-confirmed hypothetical rainfall scenario, resolves a supported location, applies deterministic and explainable rules, and then presents separate pre-event preparedness guidance. This is a context-specific design gap, not a claim that FloodSense is the first flood application.

The gap also concerns evidence and authority. Bacoar-specific susceptibility inputs, rule thresholds, geographic layers, and guidance require source documentation and local expert or institutional validation before public conclusions can be treated as operational. FloodSense therefore remains a prototype for scenario-based

assessment and preparedness support, not a substitute for official forecasting, flood warnings, evacuation orders, or verified hazard certification.

Comparative Synthesis of Related Studies

The following comparisons summarize the documented approaches and contributions of the foreign and Philippine systems discussed above. Official platforms are identified by their responsible institutions; the methodology column describes the documented technical approach and does not imply that every platform is a peer-reviewed research study.

Table 1 compares the related foreign systems by responsible institution, documented approach, objective, and contribution.

Table 1. Comparison of related foreign studies

SYSTEM	AUTHOR(S) /YEAR	METHODOLOGY	OBJECTIVES	CONTRIBUTIONS
FloodAdapt	Deltares (2025)	Physics-based flood scenarios using SFINCS and Delft-FIAT impact assessment.	Help communities compare possible flood events, future conditions, and adaptation choices.	Produces flood and impact maps, metrics, and scenario comparisons for planning; it is not FloodSense's rule-based assessment.
Global Flood Awareness System (GloFAS)	Copernicus Emergency Management Service (2026)	Operational hydrological forecasting, observations, and web-map products.	Provide global and regional flood-monitoring and forecast information.	Presents time-sensitive forecast and monitoring layers; FloodSense neither monitors nor forecasts live conditions.

Table 1. Continued

SYSTEM	AUTHOR(S) /YEAR	METHODOLOGY	OBJECTIVES	CONTRIBUTIONS
Iowa Flood Information System (IFIS)	Iowa Flood Center (2024; n.d.)	Stream-stage sensors, inundation maps, and model-based forecasts presented online.	Make Iowa flood information understandable and accessible to the public.	Combines location-oriented maps with real-time data and forecasts; its Iowa data cannot be transferred to Bacoar.
Resilience Analysis and Planning Tool (RAPT)	Federal Emergency Management Agency (2025)	GIS integration of hazard, infrastructure, and community indicators.	Support emergency managers and partners in resilience analysis and planning.	Enables map-layer review and contextual comparisons; it does not make FloodSense's scenario-based rule conclusion.
Check the long term flood risk for an area in England	GOV.UK (n.d.); Environment Agency (2024)	Official area lookup based on national long-term flood-risk datasets.	Explain area-level risk from rivers, the sea, surface water, and other available sources.	Provides public place-based risk information and limitations; an area result is not an individual-property prediction.

Table 2 compares the related Philippine systems using the same categories.

Table 2. Comparison of related local studies

SYSTEM	AUTHOR(S) /YEAR	METHODOLOGY	OBJECTIVES	CONTRIBUTIONS
Know Your Hazards and NOAH Studio	UP NOAH Center (n.d.)	Point lookup and map layers from simulated, satellite, and historical hazard information.	Allow Philippine users to inspect mapped flood and other hazard conditions.	Offers location-based hazard views and return-period flood layers, with beta and data-limit notices; not a Bacoar rule assessment.
HazardHunterPH	GeoRisk Philippines (n.d.)	Point assessment using hazard layers supplied by mandated Philippine agencies.	Give users an indicative, location-specific, multi-hazard report.	Combines official-source layers with explicit method and boundary disclaimers; its output is not an official certification.

Table 2. Continued

SYSTEM	AUTHOR(S) /YEAR	METHODOLOGY	OBJECTIVES	CONTRIBUTIONS
GeoMapperPH	DOST- PHIVOLCS (2022a)	Structured web and mobile collection of hazard, exposure, vulnerability, and coping-capacity data.	Help trained agencies and local governments build exposure geodatabases.	Illustrates governed field-data collection and administrative roles, rather than resident-requested susceptibility assessment.
PlanSmartPH Ready to Rebuild	DOST- PHIVOLCS (2022b)	Baseline-data assessment and web-supported rehabilitation-and-recovery planning.	Assist technical staff and local governments in preparing recovery plans.	Supports institutional post-disaster planning, not household pre-event scenario assessment.
Web-Based Solution for Flood Warning Decision Support in the Province of Leyte, Philippines	Bentoso et al. (2021)	Rainfall and water-level sensors, web reports, graphical monitoring, and alert messages.	Monitor local flood conditions and support warning decisions in Leyte.	Reports a tested sensor-based warning prototype; its thresholds and deployment evidence do not transfer to Bacoar.

Table 3 identifies only features documented for each reviewed system. A blank cell means that the feature was not established by the inspected source; it does not prove that the system lacks the feature. The Proposed System column describes the verified FloodSense prototype, not unimplemented requirements or official flood-data approval.

Legend:

✓ - included in the documented system; blank - not established by the inspected source.

S1 - FloodAdapt

S2 - Global Flood Awareness System (GloFAS)

S3 - Iowa Flood Information System (IFIS)

S4 - Resilience Analysis and Planning Tool (RAPT)

S5 - Check the long term flood risk for an area in England

S6 - Know Your Hazards and NOAH Studio (UP NOAH)

S7 - HazardHunterPH

S8 - GeoMapperPH

S9 - PlanSmartPH Ready to Rebuild

S10 - Web-Based Solution for Flood Warning Decision Support in the Province of Leyte, Philippines

REFERENCES

- Android Developers. (2026). Request location permissions. <https://developer.android.com/develop/sensors-and-location/location/permissions>
- Bentoso, L. D., Juan, E. O., Brosas, D. G., Paragas, J. R., Nuevas, L. K., & Velarde, M. W. C. (2021). Web-based solution for flood warning decision support in the Province of Leyte, Philippines. In 2021 3rd International Conference on Research and Academic Community Services (ICRACOS) (pp. 185-190). IEEE. <https://doi.org/10.1109/ICRACOS53680.2021.9701990>
- Buchanan, B. G., & Shortliffe, E. H. (Eds.). (1984). Rule-based expert systems: The MYCIN experiments of the Stanford Heuristic Programming Project. Addison-Wesley.
- Copernicus Emergency Management Service. (2026). GloFAS homepage. European Centre for Medium-Range Weather Forecasts. <https://confluence.ecmwf.int/spaces/CEMS/pages/315561239/3.1+GloFAS+homepage>
- Deltares. (2025, December 2). FloodAdapt. <https://www.deltares.nl/en/software-and-data/products/floodadapt>
- Department of Science and Technology-Philippine Institute of Volcanology and Seismology. (2022a, December 6). DOST-PHIVOLCS conducts training on the use of GeoRiskPH platforms for the Municipality of General Luna, Quezon. GeoRisk Philippines Initiative. <https://www.georisk.gov.ph/articles/2022/12/dost-phivolcs-conducts-training-on-the-use-of-georiskph-platforms-for-the-municipality-of-general-luna-quezon>
- Department of Science and Technology-Philippine Institute of Volcanology and Seismology. (2022b, September 28). DOST-PHIVOLCS conducts PlanSmart Ready to Rebuild training of trainers. GeoRisk Philippines Initiative. <https://www.georisk.gov.ph/articles/2022/9/dost-phivolcs-conducts-plansmart-ready-to-rebuild-training-of-trainers>
- Environment Agency. (2024). National assessment of flood and coastal erosion risk in England 2024. GOV.UK. <https://www.gov.uk/government/publications/national-assessment-of-flood-and-coastal-erosion-risk-in-england-2024/national-assessment-of-flood-and-coastal-erosion-risk-in-england-2024>
- Fakhruddin, B., Kirsch-Wood, J., Niyogi, D., Guoqing, L., Murray, V., & Frolova, N. (2022). Harnessing risk-informed data for disaster and climate resilience. *Progress in Disaster Science*, 16, 100254. <https://doi.org/10.1016/j.pdisas.2022.100254>
- Federal Emergency Management Agency. (2025). Resilience Analysis and Planning Tool user guide. https://www.fema.gov/sites/default/files/documents/fema_rapt-user-guide_2025.pdf
- GeoRisk Philippines. (n.d.). HazardHunterPH: Hazard assessment at your fingertips. Retrieved September 21, 2026, from <https://hazardhunter.georisk.gov.ph/map>

- GOV.UK. (n.d.). Check the long term flood risk for an area in England.
<https://www.gov.uk/check-long-term-flood-risk>
- International Organization for Standardization. (2023). ISO/IEC 25010:2023 systems and software engineering - Systems and software Quality Requirements and Evaluation (SQuaRE) - Product quality model.
<https://www.iso.org/standard/78176.html>
- Iowa Flood Center. (2024). A strong purpose. IIHR Currents 2023-24. University of Iowa. <https://iihr.uiowa.edu/news/iihr-currents/iihr-currents-2023-24/strong-purpose>
- Iowa Flood Center. (n.d.). Iowa Flood Information System terms and conditions. University of Iowa. Retrieved September 21, 2026, from <https://s-iihr72.iihr.uiowa.edu/beta.ifis.iowawis.org/terms.php>
- Japan International Cooperation Agency. (2021, October 1). Flood risk protection project in Cavite inaugurated.
<https://www.jica.go.jp/english/overseas/philippine/information/press/2021/211001.html>
- Kostopoulos, G., Davrazos, G., & Kotsiantis, S. (2024). Explainable artificial intelligence-based decision support systems: A recent review. *Electronics*, 13(14), 2842. <https://doi.org/10.3390/electronics13142842>
- Membele, G. M., Naidu, M., & Mutanga, O. (2022). Examining flood vulnerability mapping approaches in developing countries: A scoping review. *International Journal of Disaster Risk Reduction*, 69, 102766.
<https://doi.org/10.1016/j.ijdr.2021.102766>
- Mostafiz, R. B., Rohli, R. V., Friedland, C. J., & Lee, Y.-C. (2022). Actionable information in flood risk communications and the potential for new web-based tools for long-term planning for individuals and community. *Frontiers in Earth Science*, 10, 840250. <https://doi.org/10.3389/feart.2022.840250>
- National Disaster Risk Reduction and Management Council. (2024). National disaster response plan 2024: Hydro-meteorological hazards.
https://ndrrmc.gov.ph/attachments/article/4125/National_Disaster_Response_Plan_NDRP_2024.pdf
- Papadopoulos, P., Soflano, M., Chaudy, Y., Adejo, W., & Connolly, T. M. (2022). A systematic review of technologies and standards used in the development of rule-based clinical decision support systems. *Health and Technology*, 12, 713-727. <https://doi.org/10.1007/s12553-022-00672-9>
- Philippine Atmospheric, Geophysical and Astronomical Services Administration. (2024). 2023 annual climate bulletin.
https://pubfiles.pagasa.dost.gov.ph/pagasaweb/files/cad/Climate%20Bulletin%202023_v5.pdf
- Philippine Statistics Authority. (2023). Third quarter 2023 PSGC updates.
<https://psa.gov.ph/classification/psgc/node/1684061390>
- Philippine Statistics Authority. (2025). City of Bacoar: Barangays in the City of Bacoar. <https://psa.gov.ph/classification/psgc/barangays/0402103000>
- Philippine Statistics Authority. (2026). Highlights of the Compendium of Philippine Environment Statistics 2016-2025, Component 4: Extreme events and disasters. <https://psa.gov.ph/statistics/environment-statistics/highlights/component-4-extreme-events-and-disaster>

- PostGIS Development Group. (2026). PostGIS manual: Introduction.
https://postgis.net/docs/manual-3.7/en/postgis_introduction.html
- Power, D. J. (2002). Decision support systems: Concepts and resources for managers. Quorum Books.
- Republic Act No. 10173. (2012). Data Privacy Act of 2012. Republic of the Philippines. <https://privacy.gov.ph/data-privacy-act/>
- Tullis, J. A., & Kar, B. (2021). Where is the provenance? Ethical replicability and reproducibility in GIScience and its critical applications. *Annals of the American Association of Geographers*, 111(5), 1318-1328.
<https://doi.org/10.1080/24694452.2020.1806029>
- UP NOAH Center. (n.d.). Know your hazards. University of the Philippines Resilience Institute. Retrieved September 21, 2026, from <https://noah.up.edu.ph/know-your-hazards>