# HSRP

Lab Activity

Topology

IP Plan

- R1
  - Loopback 50: 50.50.50.X/32
  - Peering: 100.100.XY.X(Y)/24
- VLAN A
  - Block: A.A.A.0/24
  - PC : A.A.A.A/24
  - Active/Standby: A.A.A.X(Y)/24
- OSPF
  - Process ID: 1
  - Area: 0
- HSRP
  - Virtual Router/GW: A.A.A.254/24

Basic Configuration

- Configure R1
  - Loopback and Interface IP
- Configure IP address for PC1 and PC2
- Configure trunk between switches
- ESW1 and ESW2
  - Configure interface VLAN IP
  - Configure STP root primary and secondary
- Configure OSPF among R1, ESW1 and ESW2
- ESW3
  - Configure access port with respective VLAN
- Ping R1 from PC1 and PC2

HSRP Configuration

- Configure HSRP
  - Interface VLAN IP
  - Standby IP
  - Priority
- Start unlimited ping to loopback 50 of R1 from PC1 and PC2
- Shutdown F1/0 of ESW1, check the ping report
- No shut F1/0 of ESW1
- Shutdown F1/0 of ESW2, check the ping report

Verification

- show standby brief
- show standby neighbor vlan <number>
- show standby
- show ip arp

ESW1

```
int fa1/1
  switchport mode trunk
int fa1/2
  switchport mode trunk
```

ESW3

```
int fa1/0
  switchport mode access
  switchport access vlan 10
int fa1/1
  switchport mode access
  switchport access vlan 20
int range fa1/2 - 3
  switchport mode trunk
```

ESW1

```
ip routing
int fa1/0
 no shutdown
 no switchport
 ip add 100.100.11.2 255.255.255.0
 ip ospf 1 area 0
 ip ospf network point-to-point
vlan 10,20
int vlan 10
 ip add 10.10.10.1 255.255.255.0
 ip ospf 1 area 0
int vlan 20
 ip add 20.20.20.1 255.255.255.0
 ip ospf 1 area 0
```

ESW1

```
spanning-tree vlan 10 root primary
spanning-tree vlan 20 root secondary
```

ESW1

```
interface vlan10
  standby 10 ip 10.10.10.254
  standby 10 priority 110
  standby 10 preempt
  standby 10 authentication md5 key-string ccnplab
  standby 10 timers msec 200 msec 700
interface vlan20
  standby 20 ip 20.20.20.254
  standby 20 priority 90
  standby 20 preempt
```

R1

```
int loopback 50
 ip add 50.50.50.50 255.255.255.255
 ip ospf 1 area 0
int g1/0
 no shutdown
 ip add 100.100.11.1 255.255.255.0
 ip ospf 1 area 0
 ip ospf network point-to-point
int g2/0
 no shutdown
 ip add 100.100.12.1 255.255.255.0
 ip ospf 1 area 0
 ip ospf network point-to-point
```

Verification: ESW1

```
ESW1#show standby brief
                     P indicates configured to preempt.
                     |
Interface    Grp  Pri P State    Active        Standby      Virtual IP
Vl10         10   110 P Active   local         10.10.10.2   10.10.10.254
Vl20         20   90  P Speak    20.20.20.2    Local        20.20.20.254
```

Verification: ESW1

```
ESW1#sh ip arp
Protocol   Address        Age (min)   Hardware Addr   Type   Interface
Internet   10.10.10.1        -        c201.eb83.0000  ARPA   Vlan10
Internet   10.10.10.2        0        c202.eb84.0000  ARPA   Vlan10
Internet   10.10.10.254      -        0000.0c07.ac0a  ARPA   Vlan10
Internet   20.20.20.1        -        c201.eb83.0000  ARPA   Vlan20
Internet   20.20.20.2        0        c202.eb84.0000  ARPA   Vlan20
Internet   100.100.11.1      1        ca05.eaf2.001c  ARPA   FastEthernet1/0
Internet   100.100.11.2      -        c201.eea3.f100  ARPA   FastEthernet1/0


ESW2#show ip arp
Protocol   Address        Age (min)   Hardware Addr   Type   Interface
Internet   10.10.10.1        2        c201.eb83.0000  ARPA   Vlan10
Internet   10.10.10.2        -        c202.eb84.0000  ARPA   Vlan10
Internet   20.20.20.1        2        c201.eb83.0000  ARPA   Vlan20
Internet   20.20.20.2        -        c202.eb84.0000  ARPA   Vlan20
Internet   20.20.20.254      -        0000.0c07.ac14  ARPA   Vlan20
Internet   100.100.12.1      3        ca05.eaf2.0038  ARPA   FastEthernet1/0
Internet   100.100.12.2      -        c202.eea4.f100  ARPA   FastEthernet1/0
```

Sample Configuration: PC1

```
PC1> ip 10.10.10.10 255.255.255.0 10.10.10.254
```

Verification:

```
PC1> arp

00:00:0c:07:ac:0a  10.10.10.254 expires in 18
seconds
```

Verification: PC1 and PC2

```
PC-1> trace 50.50.50.50
trace to 50.50.50.50, 8 hops max, press Ctrl+C to
stop
  1    10.10.10.1    7.699 ms   11.402 ms   11.063 ms
  2    100.100.11.1    71.034 ms


PC-2> trace 50.50.50.50
trace to 50.50.50.50, 8 hops max, press Ctrl+C to
stop
  1    20.20.20.2    5.103 ms   11.458 ms   11.650 ms
  2    100.100.12.1    89.031 ms
```

Verification: R1

```
R1#show ip route

Gateway of last resort is not set

      10.0.0.0/24 is subnetted, 1 subnets
O        10.10.10.0 [110/2] via 100.100.12.2, 00:07:13, GigabitEthernet2/0
                    [110/2] via 100.100.11.2, 00:07:13, GigabitEthernet1/0
      20.0.0.0/24 is subnetted, 1 subnets
O        20.20.20.0 [110/2] via 100.100.12.2, 00:07:13, GigabitEthernet2/0
                    [110/2] via 100.100.11.2, 00:07:13, GigabitEthernet1/0
      50.0.0.0/32 is subnetted, 1 subnets
C        50.50.50.50 is directly connected, Loopback0
      100.0.0.0/8 is variably subnetted, 4 subnets, 2 masks
C        100.100.11.0/24 is directly connected, GigabitEthernet1/0
L        100.100.11.1/32 is directly connected, GigabitEthernet1/0
C        100.100.12.0/24 is directly connected, GigabitEthernet2/0
L        100.100.12.1/32 is directly connected, GigabitEthernet2/0
```

Verification: R1

```
R1#traceroute 10.10.10.10
Type escape sequence to abort.
Tracing the route to 10.10.10.10
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.11.2 52 msec
    100.100.12.2 48 msec
    100.100.11.2 48 msec
  2  *
    10.10.10.10 44 msec 52 msec
```

Verification: PC1

```
PC-1> ping 50.50.50.50 -c 100

84 bytes from 50.50.50.50 icmp_seq=1 ttl=254 time=35.802 ms
84 bytes from 50.50.50.50 icmp_seq=2 ttl=254 time=31.467 ms
*10.10.10.1 icmp_seq=3 ttl=255 time=42.769 ms (ICMP type:3, code:1,
Destination host unreachable)
*10.10.10.1 icmp_seq=4 ttl=255 time=1.567 ms (ICMP type:3, code:1, Destination
host unreachable)
*10.10.10.1 icmp_seq=5 ttl=255 time=6.560 ms (ICMP type:3, code:1, Destination
host unreachable)
*10.10.10.1 icmp_seq=6 ttl=255 time=7.891 ms (ICMP type:3, code:1, Destination
host unreachable)
*10.10.10.1 icmp_seq=7 ttl=255 time=6.373 ms (ICMP type:3, code:1, Destination
host unreachable)
*10.10.10.1 icmp_seq=8 ttl=255 time=6.384 ms (ICMP type:3, code:1, Destination
host unreachable)
50.50.50.50 icmp_seq=9 timeout
84 bytes from 50.50.50.50 icmp_seq=10 ttl=254 time=61.904 ms
84 bytes from 50.50.50.50 icmp_seq=11 ttl=254 time=40.476 ms
84 bytes from 50.50.50.50 icmp_seq=12 ttl=254 time=35.700 ms
84 bytes from 50.50.50.50 icmp_seq=13 ttl=254 time=38.089 ms
```

Verification: ESW1

```
int fa1/0
 shutdown
```