

Components

Methods

CheckboxAdapter(props)

Source: [components/Checkbox.jsx, line 15](#)

Adapter between formik library and material-ui Checkbox

Parameters:

Name	Type	Description																									
props	Object	Properties																									
		<table><tr><th>Name</th><th>Type</th><th>Attributes</th><th>Default</th><th>Description</th></tr><tr><td>field</td><td>Object</td><td></td><td></td><td>formik field object</td></tr><tr><td>form</td><td>Object</td><td></td><td></td><td>formik form object</td></tr><tr><td>disabled</td><td>bool</td><td><optional></td><td>false</td><td></td></tr><tr><td>label</td><td>string</td><td><optional></td><td></td><td></td></tr></table>	Name	Type	Attributes	Default	Description	field	Object			formik field object	form	Object			formik form object	disabled	bool	<optional>	false		label	string	<optional>		
Name	Type	Attributes	Default	Description																							
field	Object			formik field object																							
form	Object			formik form object																							
disabled	bool	<optional>	false																								
label	string	<optional>																									

Returns:

React component

```
ConfirmationDialog(props)
```

Source: [components/ConfirmationDialog.jsx, line 24](#)

Confirmation dialog component

Parameters:

Name	Type	Description																												
props	Object	Properties <table><tr><th>Name</th><th>Type</th><th>Attributes</th><th>Description</th></tr><tr><td>children</td><td>*</td><td></td><td>modal content</td></tr><tr><td>open</td><td>bool</td><td></td><td>is modal opened</td></tr><tr><td>onClose</td><td>function</td><td></td><td>modal close callback</td></tr><tr><td>title</td><td>string</td><td><optional></td><td>modal title</td></tr><tr><td>dismiss</td><td>string</td><td><optional></td><td>dismiss button label</td></tr><tr><td>confirm</td><td>string</td><td><optional></td><td>confirm button label</td></tr></table>	Name	Type	Attributes	Description	children	*		modal content	open	bool		is modal opened	onClose	function		modal close callback	title	string	<optional>	modal title	dismiss	string	<optional>	dismiss button label	confirm	string	<optional>	confirm button label
Name	Type	Attributes	Description																											
children	*		modal content																											
open	bool		is modal opened																											
onClose	function		modal close callback																											
title	string	<optional>	modal title																											
dismiss	string	<optional>	dismiss button label																											
confirm	string	<optional>	confirm button label																											

Returns:

React component

FormikEffect(props)

Source: [components/FormikEffect.jsx, line 18](#)

Component adding onChange event workaround to formik instances

Parameters:

Name	Type	Description			
props	Object	Properties			
		Name	Type	Attributes	Description
		values	Object		formik values
		isValid	bool		formik isValid
		onChange	function	<optional>	change callback
		onValidChange	function	<optional>	valid change callback

Returns:

React component

SelectAdapter(props)

Source: [components/Select.jsx, line 23](#)

Adapter between formik library and material-ui Select. Passes through all usual props of material-ui Select

Parameters:

Name	Type	Description
------	------	-------------

Name	Type	Description																																								
props	Object	Properties																																								
		<table><tr><th>Name</th><th>Type</th><th>Attributes</th><th>Default</th><th>Description</th></tr><tr><td>field</td><td>Object</td><td></td><td></td><td>formik field object</td></tr><tr><td>form</td><td>Object</td><td></td><td></td><td>formik form object</td></tr><tr><td>disabled</td><td>bool</td><td><optional></td><td>false</td><td></td></tr><tr><td>label</td><td>string</td><td><optional></td><td></td><td></td></tr><tr><td>info</td><td>string</td><td><optional></td><td></td><td>helper text</td></tr><tr><td>items</td><td>Array.<Object></td><td></td><td></td><td></td></tr><tr><td>itemComponent</td><td>Component function</td><td><optional></td><td></td><td>component for item rendering</td></tr></table>	Name	Type	Attributes	Default	Description	field	Object			formik field object	form	Object			formik form object	disabled	bool	<optional>	false		label	string	<optional>			info	string	<optional>		helper text	items	Array.<Object>				itemComponent	Component function	<optional>		component for item rendering
Name	Type	Attributes	Default	Description																																						
field	Object			formik field object																																						
form	Object			formik form object																																						
disabled	bool	<optional>	false																																							
label	string	<optional>																																								
info	string	<optional>		helper text																																						
items	Array.<Object>																																									
itemComponent	Component function	<optional>		component for item rendering																																						

Returns:
React component

TextFieldAdapter(props)

Source: [components/TextField.jsx, line 16](#)

Adapter between formik library and material-ui TextField. Passes through all usual props of material-ui TextField

Parameters:

Name	Type	Description																																	
props	Object	Properties																																	
		<table><tr><th>Name</th><th>Type</th><th>Attributes</th><th>Default</th><th>Description</th></tr><tr><td>field</td><td>Object</td><td></td><td></td><td>formik field object</td></tr><tr><td>form</td><td>Object</td><td></td><td></td><td>formik form object</td></tr><tr><td>disabled</td><td>bool</td><td><optional></td><td>false</td><td></td></tr><tr><td>label</td><td>string</td><td><optional></td><td></td><td></td></tr><tr><td>info</td><td>string</td><td><optional></td><td></td><td>helper text</td></tr></table>				Name	Type	Attributes	Default	Description	field	Object			formik field object	form	Object			formik form object	disabled	bool	<optional>	false		label	string	<optional>			info	string	<optional>		helper text
Name	Type	Attributes	Default	Description																															
field	Object			formik field object																															
form	Object			formik form object																															
disabled	bool	<optional>	false																																
label	string	<optional>																																	
info	string	<optional>		helper text																															

Returns:
React component

ContextLocalization

Methods

`(inner) getStoredLocale() → {string|null}`

Source: [context/localization.jsx, line 16](#)

Get stored locale from local storage

Returns:

Stored locale

Type `string | null`

`(inner) IntlProxy(props)`

Source: [context/localization.jsx, line 83](#)

Proxy component providing intl instance

Parameters:

Name	Type	Description						
props	Object	<i>Properties</i> <table><tr><th>Name</th><th>Type</th><th>Description</th></tr><tr><td>children</td><td>*</td><td></td></tr></table>	Name	Type	Description	children	*	
Name	Type	Description						
children	*							

Returns:

React component

`(inner) LocalizationProvider(props)`

Source: [context/localization.jsx, line 104](#)

Provider component for intl localization context

Parameters:

Name	Type	Description						
props	Object	Properties <table> <tr> <th>Name</th><th>Type</th><th>Description</th></tr> <tr> <td>children</td><td>*</td><td></td></tr> </table>	Name	Type	Description	children	*	
Name	Type	Description						
children	*							

Returns:

React component

```
(inner) setStoredLocale(language)
```

Source: [context/localization.jsx, line 26](#)

Write locale into loacal storage

Parameters:

Name	Type	Description
language	string	

```
(inner) useLocalizationHook() → {Object}
```

Source: [context/localization.jsx, line 36](#)

Localization context hook

Returns:

Localization bag

Type **Object**

Documentation generated by *JSDoc 3.6.10* on Mon Feb 14 2022 10:05:45 GMT+0100 (czas środkowoeuropejski standardowy) using the *docdash* theme.

ContextNotifications

Methods

```
(inner) NotificationsProvider(props)
```

Source: [context/notifications.jsx, line 84](#)

Provider component for notifications context

Parameters:

Name	Type	Description						
props	Object	Properties <table><tr><th>Name</th><th>Type</th><th>Description</th></tr><tr><td>children</td><td>*</td><td></td></tr></table>	Name	Type	Description	children	*	
Name	Type	Description						
children	*							

Returns:

React component

```
(inner) useNotificationsHook() → {Object}
```

Source: [context/notifications.jsx, line 15](#)

Notifications context hook

Returns:

Notification methods bag

Type Object

ContextPickers

Methods

`(inner) PickerLocalizationProvider(props)`

Source: [context/pickers.jsx, line 62](#)

Provider component for picker localization context

Parameters:

Name	Type	Description						
props	Object	Properties <table><tr><th>Name</th><th>Type</th><th>Description</th></tr><tr><td>children</td><td>*</td><td></td></tr></table>	Name	Type	Description	children	*	
Name	Type	Description						
children	*							

Returns:

React component

`(inner) PickerUtilsProxy(props)`

Source: [context/pickers.jsx, line 41](#)

Proxy component providing date utils and locale

Parameters:

Name	Type	Description						
props	Object	Properties <table><tr><th>Name</th><th>Type</th><th>Description</th></tr><tr><td>children</td><td>*</td><td></td></tr></table>	Name	Type	Description	children	*	
Name	Type	Description						
children	*							

Returns:

React component

```
(inner) usePickerUtilsHook() → {Object}
```

Source: [context/pickers.jsx, line 18](#)

Pickers context hook

Returns:

Picker locales bag

Type **Object**

*Documentation generated by **JSDoc 3.6.10** on Mon Feb 14 2022 10:05:45 GMT+0100 (czas środkowoeuropejski standardowy) using the **docdash** theme.*

ContextTheme

Methods

(inner) LocalizedThemeProvider(props)

Source: [context/theme.jsx, line 70](#)

Provider component for theme localization context

Parameters:

Name	Type	Description						
props	Object	Properties <table><tr><th>Name</th><th>Type</th><th>Description</th></tr><tr><td>children</td><td>*</td><td></td></tr></table>	Name	Type	Description	children	*	
Name	Type	Description						
children	*							

Returns:

React component

(inner) LocalizedThemeProxy(props)

Source: [context/theme.jsx, line 48](#)

Proxy component providing theme and css baseline

Parameters:

Name	Type	Description						
props	Object	Properties <table><tr><th>Name</th><th>Type</th><th>Description</th></tr><tr><td>children</td><td>*</td><td></td></tr></table>	Name	Type	Description	children	*	
Name	Type	Description						
children	*							

Returns:

React component

```
(inner) useLocalizedThemeHook() → {Object}
```

Source: [context/theme.jsx, line 18](#)

Theme localization context hook

Returns:

Theme bag

Type **Object**

*Documentation generated by **JSDoc 3.6.10** on Mon Feb 14 2022 10:05:45 GMT+0100 (czas środkowoeuropejski standardowy) using the **docdash** theme.*

ContextValidation

Methods

```
(inner) useValidation() → {Object}
```

Source: [context/validation.js, line 11](#)

Validation context hook

Returns:

Validation methods bag

Type **Object**

*Documentation generated by **JSDoc 3.6.10** on Mon Feb 14 2022 10:05:45 GMT+0100 (czas środkowoeuropejski standardowy) using the **docdash** theme.*

ContextVoices

Methods

```
(inner) useVoicesHook() → {Object}
```

Source: [context/voices.js, line 9](#)

Text to speech available voices hook

Returns:

Available voices bag

Type **Object**

```
(inner) VoicesProvider(props)
```

Source: [context/voices.js, line 36](#)

Provider component for voices context

Parameters:

Name	Type	Description						
props	Object	<i>Properties</i> <table><tr><th>Name</th><th>Type</th><th>Description</th></tr><tr><td>children</td><td>*</td><td></td></tr></table>	Name	Type	Description	children	*	
Name	Type	Description						
children	*							

Returns:

React component

HooksSensors

Methods

```
(async, static) getGpsReadings() → {Object}
```

Source: [hooks/sensors.js, line 32](#)

Get internal GPS readings from the device

Returns:

GPS readings

Type **Object**

```
(async, static) getHelmReadings() → {Object}
```

Source: [hooks/sensors.js, line 11](#)

Get helm readings from the device

Returns:

Helm readings

Type **Object**

```
(async, static) getNmeaReadings() → {Object}
```

Source: [hooks/sensors.js, line 21](#)

Get NMEA 2k readings from the device

Returns:

NMEA 2k readings

Type **Object**

HooksSettings

Methods

```
(async, static) runCalibration()
```

Source: [hooks/settings.js, line 23](#)

Run IMU calibration on the device

Returns:

Server response

```
(async, static) runReboot()
```

Source: [hooks/settings.js, line 33](#)

Force reboot of the device

Returns:

Server response

```
(async, static) setSettings(params)
```

Source: [hooks/settings.js, line 13](#)

Set device settings

Parameters:

Name	Type	Description						
params	Object	<i>Properties</i> <table><tr><th>Name</th><th>Type</th><th>Description</th></tr><tr><td>beta</td><td>number</td><td>IMU filter beta</td></tr></table>	Name	Type	Description	beta	number	IMU filter beta
Name	Type	Description						
beta	number	IMU filter beta						

Returns:

Server response

ViewMain

Methods

```
(async, static) describeStatus(settings, readings, deps)
```

Source: [views/main/helpers.js, line 104](#)

Describe status with text to speech based on readings and settings

Parameters:

Name	Type	Description																				
settings	Object	Properties																				
		<table><tr><th>Name</th><th>Type</th><th>Attributes</th><th>Description</th></tr><tr><td>target</td><td>string</td><td></td><td>target reading to use in describing status</td></tr><tr><td>targetCourse</td><td>number</td><td><optional></td><td>target course</td></tr><tr><td>targetWind</td><td>number</td><td><optional></td><td>target wind</td></tr><tr><td>readingRate</td><td>number</td><td><optional></td><td>reading rate</td></tr></table>	Name	Type	Attributes	Description	target	string		target reading to use in describing status	targetCourse	number	<optional>	target course	targetWind	number	<optional>	target wind	readingRate	number	<optional>	reading rate
		Name	Type	Attributes	Description																	
		target	string		target reading to use in describing status																	
		targetCourse	number	<optional>	target course																	
		targetWind	number	<optional>	target wind																	
readingRate	number	<optional>	reading rate																			
readings	Object	Properties																				
		<table><tr><th>Name</th><th>Type</th><th>Attributes</th><th>Description</th></tr><tr><td>course</td><td>number</td><td></td><td>current course</td></tr><tr><td>rudder</td><td>number</td><td><optional></td><td>current rudder angle</td></tr><tr><td>wind</td><td>number</td><td><optional></td><td>current wind angle</td></tr></table>	Name	Type	Attributes	Description	course	number		current course	rudder	number	<optional>	current rudder angle	wind	number	<optional>	current wind angle				
		Name	Type	Attributes	Description																	
		course	number		current course																	
		rudder	number	<optional>	current rudder angle																	
wind	number	<optional>	current wind angle																			
deps	Object	Properties																				
		<table><tr><th>Name</th><th>Type</th><th>Description</th></tr><tr><td>voice</td><td>Object</td><td>voice instance</td></tr><tr><td>translate</td><td>function</td><td>translator function</td></tr></table>	Name	Type	Description	voice	Object	voice instance	translate	function	translator function											
		Name	Type	Description																		
voice	Object	voice instance																				
translate	function	translator function																				

```
(async, static) ensureApisEnabled()
```

Source: [views/main/helpers.js, line 64](#)

Force speechSynthesis and audio context permissions by running silent audio signal and text read

```
(static) getRelativeCourse(course, targetCourse) → {number}
```

Source: [views/main/helpers.js, line 77](#)

Get course relative to target course in range <-180,180>

Parameters:

Name	Type	Description
course	number	current course
targetCourse	number	target course

Returns:

relative course

Type number

```
(async, static) playSignal(frequency, duration, volume, type)
```

Source: [views/main/helpers.js, line 14](#)

Play audio signal using audio context oscillator

Parameters:

Name	Type	Description
frequency	number	signal frequency in Hz
duration	number	signal duration in ms
volume	number	signal volume in range <0,1>
type	string	signal wave type

```
(async, static) readText(text, readingVoice, readingRate, readingVolume)
```

Source: [views/main/helpers.js, line 47](#)

Read text using speech synthesis utterance

Parameters:

Name	Type	Description
text	string	text to read

Name	Type	Description
readingVoice	Object	voice instance
readingRate	number	rate of reading
readingVolume	number	reading volume in range <0,1>

(async, static) signalizeStatus(settings, readings, lastStatus)

Source: [views/main/helpers.js, line 172](#)

Signalize status with audio based on readings and settings

Parameters:

Name	Type	Description				
settings	Object	Properties				
		Name	Type	Attributes	Default	Description
		target	string			target reading to use in describing status
		targetCourse	number	<optional>		target course
		targetWind	number	<optional>		target wind
		referenceTone	bool	<optional>	false	play middle tone before error tone
		toneOnCourse	bool	<optional>	false	play middle tone when on course
		shortTones	bool	<optional>	false	play shorter tones
		broadTonalSpread	bool	<optional>	false	play error tones in broader tonal spread
		errorThreshold	number	<optional>	2	error threshold in degrees
		errorRange	number	<optional>	30	error range in degrees

Name	Type	Description												
readings	Object	Properties<table><tr><th>Name</th><th>Type</th><th>Attributes</th><th>Description</th></tr><tr><td>course</td><td>number</td><td></td><td>current course</td></tr><tr><td>wind</td><td>number</td><td><optional></td><td>current wind</td></tr></table>	Name	Type	Attributes	Description	course	number		current course	wind	number	<optional>	current wind
Name	Type	Attributes	Description											
course	number		current course											
wind	number	<optional>	current wind											
lastStatus	Object													

```
(async, static) wait(delay)
```

Source: [views/main/helpers.js, line 150](#)

Wait for N ms

Parameters:

Name	Type	Description
delay	number	delay in ms

```
(inner) FormSettings(props)
```

Source: [views/main/settings.jsx, line 80](#)

Settings form component

Parameters:

Name	Type	Description									
props	Object	<i>Properties</i> <table> <tr> <th>Name</th><th>Type</th><th>Description</th></tr> <tr> <td>settings</td><td>Object</td><td>current settings</td></tr> <tr> <td>onSettingsChange</td><td>function</td><td>settings change callback</td></tr> </table>	Name	Type	Description	settings	Object	current settings	onSettingsChange	function	settings change callback
Name	Type	Description									
settings	Object	current settings									
onSettingsChange	function	settings change callback									

Returns:

React component

```
(inner) ViewMain()
```

Source: [views/main/index.jsx, line 110](#)

Main view

Returns:
React component

*Documentation generated by **JSDoc 3.6.10** on Mon Feb 14 2022 10:05:45
GMT+0100 (czas środkowoeuropejski standardowy) using the **docdash**
theme.*

ViewNotFound

Methods

```
(inner) ViewNotFound()
```

Source: [views/notFound/index.jsx, line 34](#)

View displaying not found status

Returns:

React component

Documentation generated by [JSDoc 3.6.10](#) on Mon Feb 14 2022 10:05:45 GMT+0100 (czas środkowoeuropejski standardowy) using the [docdash](#) theme.

ViewSettings

Methods

```
(inner) ViewSettings()
```

Source: [views/settings/index.jsx](#), [line 44](#)

View allowing settings change, device calibration and reboot

Returns:

React component

Documentation generated by [JSDoc 3.6.10](#) on Mon Feb 14 2022 10:05:45 GMT+0100 (czas środkowoeuropejski standardowy) using the [docdash](#) theme.

