System Requirements Specification (SysRS)

Smart Home Security System

IEEE 29148:2018 Compliant Document
Version: 1.0.0
Date: 2026-05-02
Status: Draft

Table of Contents

1. Introduction
2. Overview
3. Functional Requirements
4. Usability Requirements
5. Performance Requirements
6. System Interfaces
7. System Operations
8. System Modes and States
9. Verification
10. Assumptions and Dependencies

---

1. Introduction

1.1. Purpose

The Smart Home Security System is designed to provide comprehensive monitoring, control, and protection for single-family residential homes, with special emphasis on autonomous operation in remote, off-grid locations with limited or intermittent connectivity. The system integrates motion sensors, door/window sensors, water leak detectors, video cameras, smart controllers, and a central management hub that can operate independently when external connectivity (cloud, cellular, internet) is unavailable. The system aims to deliver bleeding-edge technology for reliable, multi-connectivity surveillance and home automation.

Scope of Development: This project produces a cohesive smart home security platform consisting of:

- Central control unit (hub) with edge computing capabilities
- Distributed wireless sensors and cameras
- Multi-mode connectivity layer (WiFi, Cellular, Radio, Satellite)
- Cloud integration for remote access and analytics
- Mobile and web-based user interfaces
- Authentication and authorization framework
- Local data storage and offline operations

1.2. Scope

1.2.a. System Identification

The system is identified as the **Smart Home Security System (SHSS)**, a distributed home automation and security monitoring platform designed for residential single-family homes.

1.2.b. User Problems and Needs

Problems Addressed:

- Homeowners in remote/off-grid locations cannot access reliable security monitoring due to poor internet connectivity
- Traditional cloud-only systems fail during network outages, leaving homes unprotected
- Existing systems lock users into single connectivity technology (WiFi OR cellular), not adaptive failover
- Integration of multiple sensor types (motion, doors, water, cameras) often requires multiple vendor systems
- Remote homes lack power-efficient battery-backed solutions for extended offline operation

User Needs:

- Always-on security monitoring regardless of connectivity status
- Instant alerts for critical events (motion, unauthorized access, water leaks)
- Remote access when connectivity available (WiFi, cellular, satellite)
- Unified control of heterogeneous devices (sensors, cameras, locks, lights)
- Reliable, autonomous operation in off-grid environments (>4 hours battery backup)
- Seamless failover between connectivity modes without user intervention

1.2.c. Application and System Benefits

Application Context: Single-family residential homes, ranging from well-connected urban dwellings to remote off-grid properties. The system is deployed inside homes, with sensors distributed across rooms, and a central hub managing all operations.

Top-Level Benefits and Objectives:

- **Reliability**: 99.5% uptime target; system continues monitoring and recording even during network/power disruptions
- **Autonomy**: Full functionality without cloud connectivity; eventual cloud sync when available
- **Coverage**: Supports diverse connectivity technologies for urban and remote deployments
- **Integration**: Single unified interface for monitoring and controlling all home security devices
- **User Empowerment**: Homeowners gain immediate visibility into security events and remote control capabilities
- **Peace of Mind**: Continuous protection even in off-grid scenarios where traditional alarm systems fail

---

2. Overview

2.1. System Context

2.1.a. Major System Elements and Interactions

The Smart Home Security System comprises five major interconnected subsystems:



Diagram Type & SysML Context: This is a *System Context Diagram* (high-level architecture overview) rendered in Mermaid for communication clarity. It shows the five major subsystems and their connectivity pathways. For formal SysML *Internal Block Diagram (IBD)* notation with explicit port definitions, interface types, and item flows, see System-Blocks.drawio in the 2_DESIGN folder. The System Boundary Interfaces table (Section 2.1.c below) provides the detailed protocol and directionality specifications that would appear in a formal IBD.

2.1.b. Human Elements

- **Homeowner/Administrator**: Configures system, manages users, receives alerts, controls devices
- **Residents/Guests**: View status, receive alerts, limited device control (based on permissions)
- **Installer/Technician**: Remote diagnostics, firmware updates, troubleshooting
- **Cloud Platform Operators**: Maintain backend services, manage data, provide analytics

2.1.c. System Boundary Interfaces

Interface	Direction	Entity Type	Protocol
User Mobile App	Bidirectional	External mobile device	HTTPS, WebSocket, MQTT
Web Dashboard	Bidirectional	External web browser	HTTPS, WebSocket

Interface	Direction	Entity Type	Protocol
Cloud Backend	Bidirectional	AWS/Azure/GCP services	HTTPS REST API, MQTT
Cellular Network	Bidirectional	Carrier 4G/5G	Cellular data/SMS
Satellite Network	Bidirectional	Satellite provider	Satellite modem protocol
Radio Mesh	Bidirectional	Peer radio nodes	Proprietary radio protocol
WiFi Router	Bidirectional	Home WiFi network	802.11ac/ax
Power Utility	Input	AC mains	120/240V AC
Battery Backup	Input	UPS/battery system	12V DC
Local Display	Output	HDMI/DisplayPort screen	Video output

2.2. System Functions

The Smart Home Security System provides the following major capabilities:

Function	Description	Key Conditions/Constraints
Motion Detection & Alerting	Detect motion events using distributed PIR/infrared sensors; trigger alerts and notifications	Alert latency < 1 second; must function offline
Access Control Monitoring	Detect door/window open/close events; log unauthorized entry attempts	Must distinguish deliberate opens from wind/vibration
Water Leak Detection	Detect water in protected areas; trigger immediate alerts	Alert latency < 2 seconds; false alarm rate < 5%
Video Surveillance	Capture, store locally, and stream video from cameras; support live view and playback	Offline: local recording only; Online: optional cloud backup
Alarm Management	Arm/disarm system; trigger siren/notifications; escalate alerts	Manual arm/disarm + optional scheduled automation
Remote Access & Control	Enable monitoring and control from anywhere via mobile/web UI	Must work over high-latency connections (200ms+)
Autonomous Operation	Full system function without cloud/internet connectivity for 4+ hours	Local decision logic; eventual cloud sync
Connectivity Failover	Automatically switch between WiFi/Cellular/Radio/Satellite with zero user intervention	Seamless transition; no alert loss during failover
Event Logging & Analytics	Record all system events (sensors, user actions, alerts); provide historical playback	30-day local storage; optional 365-day cloud storage
Multi-User Access	Support multiple simultaneous users with differentiated permissions	6 concurrent users max; privilege enforcement

Function	Description	Key Conditions/Constraints
Device Management	Add, configure, remove sensors/cameras/controllers without system restart	Hot-add capability; automatic discovery
Firmware Updates	Deploy firmware updates to hub and remote devices over-the-air	Atomic updates; automatic rollback on failure

2.3. User Characteristics

User Type 1: Homeowner/Administrator

- **Count**: 1-2 per home
- **Expertise**: Non-technical; expects intuitive interfaces
- **Use Pattern**: Daily checks (< 10 minutes); setup (30 minutes one-time)
- **Devices**: Smartphone (primary), web browser (secondary), local keypad (optional)
- **Permissions**: Full system control; can create other user accounts
- **Location**: Primarily remote access; occasional local access

User Type 2: Residents/Family Members

- **Count**: 2-6 per home
- **Expertise**: Non-technical; minimal training required
- **Use Pattern**: Infrequent (check status when away); respond to alerts
- **Devices**: Smartphone
- **Permissions**: View-only or specific device control (e.g., unlock door); cannot modify system settings
- **Location**: Local (on-site) or remote access

User Type 3: Installers/Technicians

- **Count**: External; rare access (< 5 times/year per home)
- **Expertise**: Technical; familiar with hardware/software troubleshooting
- **Use Pattern**: Periodic maintenance, remote diagnostics, firmware deployment
- **Devices**: Laptop with diagnostic tools; direct hub connection
- **Permissions**: Full system diagnostics and configuration; cannot modify user data
- **Location**: Remote (via secure VPN) or on-site

User Type 4: System Operators (Cloud Platform)

- **Count**: Cloud provider's engineering team
- **Expertise**: Technical; platform operations, data management
- **Use Pattern**: Continuous monitoring; incident response
- **Devices**: Operator console, monitoring dashboard
- **Permissions**: Platform-level analytics; no access to individual home data (encrypted)
- **Location**: Cloud data center

---

3. Functional Requirements

Functional requirements specify what the system MUST DO to satisfy user needs. All requirements are numbered REQ-XXX for traceability and include acceptance criteria.

3.1. Motion Sensor Requirements (REQ-010 through REQ-019)

REQ	Requirement	Description	Acceptance Criteria
REQ-010	Motion Detection	System shall detect motion events using distributed sensors within monitored zones	Detection latency ≤ 1 second; sensitivity adjustable per zone
REQ-011	Motion Sensor Types	System shall support at least three types of motion sensor technologies	PIR, Active Infrared, Microwave radar all functional and interchangeable
REQ-012	Motion Sensor Wireless	Motion sensors shall communicate wirelessly to hub with range ≥ 100 meters (line of sight)	Successfully transmit events from corner rooms to hub; < 5% packet loss
REQ-013	Motion False Alarm Suppression	System shall minimize false motion alerts through filtering and calibration	False alarm rate < 2% per sensor per month (excluding environmental triggers)
REQ-014	Motion Sensor Battery Monitoring	System shall monitor and report battery status for battery-powered motion sensors	Alert user when battery drops below 20%; display remaining days estimate
REQ-015	Motion Sensor Testing	System shall support test mode for motion sensors to verify function without triggering alarms	Test mode activated via admin UI; no alerts generated during test
REQ-016	Motion Sensor Placement	System shall allow flexible placement of motion sensors without recalibration	Mount on walls, ceilings, or furniture; auto-detection of orientation
REQ-017	Motion Sensor Sensitivity	System shall provide adjustable sensitivity per motion sensor and per zone	5-level sensitivity scale (Low, Med-Low, Medium, Med-High, High)
REQ-018	Motion Sensor Failsafe	Motion sensors shall continue operating if hub loses power (battery-backed sensors)	Sensors record events locally; sync on reconnection
REQ-019	Motion Sensor Redundancy	System shall allow multiple motion sensors per zone for redundancy	Any sensor trigger in zone generates alert; vote-based filtering for false alarm suppression

3.2. Door/Window Sensor Requirements (REQ-020 through REQ-029)

REQ	Requirement	Description	Acceptance Criteria
REQ-020	Door/Window Detection	System shall detect door/window open/close state changes in real-time	Detection latency ≤ 500 ms; status syncs across all users within 5 seconds
REQ-021	Door/Window Sensor Types	System shall support at least three types of door/window sensors	Magnetic reed switches, inertial switches, ultrasonic proximity sensors functional
REQ-022	Door/Window Sensor Wireless	Door/window sensors shall communicate wirelessly with range ≥ 100 meters	Successfully transmit from all entry points to hub; < 5% packet loss
REQ-023	Entry Point Monitoring	System shall monitor all primary entry points (doors, windows, garage)	User selects which entry points are "protected" per arm mode
REQ-024	Unauthorized Entry Alerts	System shall generate high-priority alert when armed entry point is opened	Alert sent within 2 seconds; includes entry point location
REQ-025	Door/Window Sensor Battery	Door/window sensors shall operate on battery power ≥ 2 years without replacement	Battery-powered sensors; low-battery alert at 20% capacity
REQ-026	Door/Window State History	System shall maintain historical record of all door/window state changes	30-day history stored locally; queryable by time range and entry point
REQ-027	Door/Window Sensor Testing	System shall support test mode without triggering alarms	Test mode can simulate open/close; hub responds but suppresses alerts
REQ-028	Delayed Entry Handling	System shall support configurable entry delays (e.g., 30-second grace period after disarm)	Disarm code entered, 30-second countdown, then entry allowed without alert
REQ-029	Multiple Door/Window Sensors	System shall support 20+ door/window sensors simultaneously without performance degradation	All sensors report status; < 5-second sync latency for all changes

3.3. Water Leak Sensor Requirements (REQ-030 through REQ-039)

REQ	Requirement	Description	Acceptance Criteria
REQ-030	Water Leak Detection	System shall detect presence of water in monitored areas and trigger alerts	Detection latency ≤ 2 seconds; high priority alert generated
REQ-031	Water Leak Sensor Types	System shall support at least three types of water	Capacitive moisture, resistive probe, ultrasonic level sensors all functional

REQ	Requirement	Description	Acceptance Criteria
		leak sensors	
REQ-032	Water Leak Locations	System shall allow users to label water leak sensor locations (e.g., "basement corner", "kitchen")	User assigns location name during setup; location shown in alert
REQ-033	Water Leak False Positives	System shall minimize false positives from humidity and condensation	False positive rate < 1% per month; user-configurable sensitivity
REQ-034	Water Leak Sensor Wireless	Water leak sensors shall communicate wirelessly with range ≥ 50 meters (adequate for indoor)	Successfully transmit from all monitored areas to hub; < 10% packet loss acceptable (hardwired alternative available)
REQ-035	Water Leak Sensor Battery	Water leak sensors shall operate on battery ≥ 3 years	Battery-powered; low-battery alert at 20% capacity
REQ-036	Water Leak Historical Trend	System shall maintain trend of moisture levels in monitored areas	Graph moisture over last 30 days; identify patterns before failures
REQ-037	Water Leak Automatic Cutoff	System shall support integration with water shutoff valve controller (optional)	When enabled by user: trigger valve closure within 1 second of detection; require user confirmation first; report closure success within 2 seconds; provide manual emergency override (<2s to close); log all valve operations with timestamp
REQ-038	Water Leak Silence Timeout	System shall allow temporary silence of water leak alarm (e.g., during cleaning)	User can silence for 30 minutes via UI; alert resumes after timeout or manual re-arm
REQ-039	Multiple Water Leak Sensors	System shall support 10+ water leak sensors simultaneously	All sensors monitored; independent alerts per sensor location

3.4. Camera Requirements (REQ-040 through REQ-059)

REQ	Requirement	Description	Acceptance Criteria
REQ-040	Video Capture	System shall capture video from IP cameras at 1080p resolution, 24 fps (minimum)	Video quality ≥ 1080p; frame rate ≥ 24 fps (30 fps preferred)

REQ	Requirement	Description	Acceptance Criteria
REQ-041	Camera Types	System shall support at least four types of cameras	Fixed IP cameras, WiFi IP cameras, battery-powered wireless cameras, doorbell cameras functional
REQ-042	Camera Wireless Connectivity	Wireless cameras shall maintain connection to hub with range ≥ 50 meters (indoor)	Connection maintained; video stream continuous; signal strength indicator
REQ-043	Local Video Recording	System shall record video locally on hub storage when internet unavailable	Video stored in compressed format; 24/7 recording possible with 30-day retention
REQ-044	Video Playback	System shall allow users to playback recorded video by time range and camera	User selects camera, time range; 30-second startup; smooth playback at normal/fast speed
REQ-045	Live Video Streaming	System shall allow live video streaming to mobile app and web dashboard	Stream latency ≤ 3 seconds (WiFi), ≤ 10 seconds (cellular/satellite); adaptive bitrate
REQ-046	Night Vision	System shall activate night vision (IR illumination) when ambient light < 50 lux	Automatic transition; no user action required; visible IR mode in settings
REQ-047	Video Motion Detection	System shall detect motion within video stream and generate alerts independent of motion sensors	Computer vision processing; 95%+ detection accuracy
REQ-048	Video Encryption	All video streams shall be encrypted in transit and at rest	AES-256 encryption; TLS 1.2+ for stream transport; locally stored video encrypted
REQ-049	Cloud Video Backup	System shall support optional cloud backup of video archive (user opt-in)	When enabled: support 365-day retention with automatic deletion after expiration; per-camera selection; AES-256-GCM encryption minimum; 95th percentile upload latency ≤5 minutes; user-configurable bandwidth cap (default 2 Mbps); backup status per camera with last upload timestamp
REQ-050	Camera Configuration	System shall allow adding, removing, and configuring cameras without system restart	Hot-add; auto-discovery for PoE and WiFi cameras; wizard-based setup

REQ	Requirement	Description	Acceptance Criteria
REQ-051	Two-Way Audio	System shall support audio from doorbell/speaker cameras for two-way communication	User speaks into phone app; audio transmitted to hub; speaker on camera plays audio
REQ-052	Video Storage Capacity	System shall store minimum 7 days of continuous 24/7 video from all cameras locally	1080p 24fps video; storage calculation visible to user during setup
REQ-053	Cloud Video Upload Priority	System shall prioritize uploading recent video to cloud during limited bandwidth scenarios	Newest footage uploaded first; oldest footage can be pruned if space limited
REQ-054	Multi-Camera Recording	System shall support simultaneous recording from 4+ cameras without latency impact	All cameras recorded concurrently; no dropped frames
REQ-055	Camera Health Monitoring	System shall continuously monitor camera connectivity and generate alerts if camera offline	Alert when camera offline > 5 minutes; show last known timestamp
REQ-056	Snapshot Capture	System shall capture high-resolution snapshots on motion events for quick review	Snapshot taken immediately on motion; stored with motion timestamp
REQ-057	Video Retention Policy	System shall allow users to configure automatic deletion of oldest video after retention period	User selects 7, 14, 30, or 90-day retention; automatic pruning
REQ-058	Privacy Masking	System shall support masking/blurring of specific video regions (e.g., neighbor's window)	Admin selects regions; applied to recording and live stream
REQ-059	Camera Power Management	Wireless battery-powered cameras shall display estimated battery life based on usage	Power consumption calculated; alert at 20% remaining

3.5. Control Unit (Hub) Requirements (REQ-060 through REQ-079)

REQ	Requirement	Description	Acceptance Criteria
REQ-060	Central Hub Function	System shall provide a central control unit that processes all sensor data and manages all devices	Hub is single point of orchestration; all data flows through hub
REQ-061	Hub Wireless Support	Hub shall support wireless communication with sensors, cameras, and controllers via multiple protocols	WiFi 802.11ac/ax (dual-band required); Bluetooth 5.0+; proprietary radio optional (specify range/latency if used); Zigbee support optional (thread as backup); multi-protocol support tested with min 50+ concurrent devices
REQ-062	Hub Processing	Hub shall process sensor data and generate alerts with latency < 1 second from sensor trigger	Real-time event processing; sub-second alert generation
REQ-063	Hub Local Storage	Hub shall maintain local database of all events and sensor states	Events logged in SQLite or similar; queryable by time, type, source
REQ-064	Hub Data Retention	Hub shall retain minimum 30 days of event logs and sensor state history locally	Automatic compression and pruning after 30 days; user can export before deletion
REQ-065	Hub Time Synchronization	Hub shall maintain accurate time for event timestamping and scheduling	NTP sync when internet available; GPS time sync as backup
REQ-066	Hub Configuration Interface	Hub shall provide web-based configuration interface (local network) for setup and management	HTTP server on hub; local network only (no public internet exposure)
REQ-067	Hub Device Management	Hub shall auto-discover and allow configuration of all connected wireless devices	Devices appear in UI after first pairing; user assigns names and locations
REQ-068	Hub Automation Rules	Hub shall support creation of automation rules (e.g., "motion in living room after 11pm → lock door")	Rules engine processes conditions and triggers actions; supports time-based and event-based triggers
REQ-069	Hub Modes	Hub shall support multiple operational modes: Armed, Disarmed, Test, Sleep	Mode transitions trigger different behaviors for alert generation
REQ-070	Hub Failsafe	Hub shall enter safe state if all connectivity lost (local	Sensors monitored locally; alerts queued for cloud sync when reconnected

REQ	Requirement	Description	Acceptance Criteria
		operation only; alerts still generated)	
REQ-071	Hub Power Input	Hub shall accept AC mains power (120/240V) with automatic voltage detection	Dual voltage support; frequency agnostic (50/60 Hz)
REQ-072	Hub Battery Backup	Hub shall include battery backup to operate ≥ 4 hours on DC power without AC mains	UPS integrated or external 12V battery; automatic switchover on AC loss
REQ-073	Hub Fan/Thermal	Hub shall include thermal management (fan or passive cooling) if processing creates heat	Operating temperature 0-40°C; thermal sensors monitor and throttle if needed
REQ-074	Hub Expansion	Hub shall support expansion via USB or other connector for future enhancements (storage, modules)	Dedicated expansion port; documented protocol for third-party development
REQ-075	Hub Firmware	Hub shall support over-the-air (OTA) firmware updates without requiring device reset	Atomic update; rollback to previous version if update fails
REQ-076	Hub Redundancy	Hub shall log critical events to removable storage for recovery if hub fails	USB-attached SD card or similar; weekly encrypted backups
REQ-077	Hub Statistics	Hub shall collect system statistics and health metrics (CPU, RAM, storage, temperature)	Displayed in admin dashboard; alerts if metrics exceed thresholds
REQ-078	Hub Restart	Hub shall support graceful restart without data loss or alert loss	All in-flight operations completed; queued alerts persisted before shutdown
REQ-079	Hub Remote Access	Hub shall support secure remote access for diagnostics via encrypted VPN tunnel	Technician access only; IP whitelisting; audit log of all remote sessions

3.6. User Interface Requirements (REQ-080 through REQ-099)

REQ	Requirement	Description	Acceptance Criteria
REQ-080	Mobile App	System shall provide mobile app for iOS and Android with current sensor status and alerts	App downloaded from App Store and Google Play; responsive design; < 10 MB size
REQ-081	Mobile App Status	Mobile app shall display real-time status of all sensors, cameras, and system armed/disarmed state	Dashboard shows all devices with last update time; color-coded status (OK, Warning, Alert)
REQ-082	Mobile App Notifications	Mobile app shall send push notifications for alerts with customizable priority and sound	User enables/disables per alert type; notification includes sensor name and trigger time
REQ-083	Mobile App Control	Mobile app shall allow users to arm/disarm system and control smart devices (locks, lights)	Actions execute within 5 seconds; confirmation shown to user
REQ-084	Mobile App Camera View	Mobile app shall display live video streams from all cameras with switchable camera selection	Live video accessible within 3 seconds of tap; smooth playback
REQ-085	Mobile App Event History	Mobile app shall display event history searchable by date, time, and sensor type	Last 30 days of events visible; filter by device type (motion, door, camera, alarm)
REQ-086	Mobile App Responsiveness	Mobile app shall be responsive to user input with < 2-second response time for all interactions	Button taps, screen transitions, data loads complete within 2 seconds on 4G+ connection
REQ-087	Web Dashboard	System shall provide web-based dashboard accessible from any web browser via HTTPS	Dashboard loads in < 5 seconds; works on Chrome, Safari, Firefox, Edge browsers
REQ-088	Web Dashboard Full Features	Web dashboard shall provide all features available in mobile app plus admin controls	System configuration, user management, advanced analytics, export functions
REQ-089	Local Display UI	System shall support optional local display (HDMI monitor or tablet)	When enabled: HDMI output (1080p minimum); display armed/disarmed state, last 10 alerts with timestamp, quick arm/disarm button;

REQ	Requirement	Description	Acceptance Criteria
		with system status and quick actions	touchscreen support optional; 3-second refresh rate; auto-lock after 10 minutes idle; portrait and landscape support
REQ-090	Physical Keypad	System shall support optional wireless numeric keypad for arm/disarm without app	When enabled: 4-6 digit PIN length configurable; support minimum 10 user codes; audit log with timestamp accuracy ±1 second; brute-force protection (5 failed attempts → 30-second lockout); range ≥100m line-of-sight; battery alert at 20%; tamper detection on case/buttons
REQ-091	UI Accessibility	User interfaces shall meet WCAG 2.1 Level AA accessibility standards	Color contrast ≥ 4.5:1; keyboard navigation; screen reader compatible
REQ-092	UI Multi-Language	User interfaces shall support at least English, Spanish, French, German, Mandarin	Language selection in app settings; automatic language matching based on device locale
REQ-093	UI Customization	Users shall be able to customize dashboard layout and device naming	Users rename devices, reorder dashboard widgets, select color theme
REQ-094	Offline Mode	Mobile app shall display cached data when internet unavailable; sync when reconnected	App shows last-known status; displays "CACHED DATA" indicator; syncs on reconnect
REQ-095	Voice Control	System shall support voice control via popular voice assistants (optional)	When enabled: Amazon Alexa or Google Assistant integration; recognition accuracy ≥95% in 65dB household noise; response latency ≤3 seconds; voice authentication required for disarm/unlock; supported commands: arm, disarm, lock, unlock, status; all commands logged with timestamp and user
REQ-096	Timezone Support	System interfaces shall display times in user's local timezone with configurable format	User selects timezone in settings; 12/24-hour format option
REQ-097	UI Performance	Web and mobile interfaces shall load within 3 seconds on standard 4G connection	Page render time ≤ 3 seconds; image optimization; lazy loading

REQ	Requirement	Description	Acceptance Criteria
REQ-098	Gesture Controls	Mobile app shall support intuitive gesture controls (swipe, pinch) where applicable	Swipe between cameras; pinch to zoom on video; pull-to-refresh events
REQ-099	No Ads/Tracking	User interfaces shall not display advertisements or track user data for profit	Analytics limited to system performance; no behavioral tracking; privacy-first

3.7. Authentication and Authorization (REQ-100 through REQ-119)

REQ	Requirement	Description	Acceptance Criteria
REQ-100	User Authentication	System shall require authentication for all user access to hub and cloud services	Username/password (≥12 char, mixed case/numbers/symbols) OR biometric (fingerprint/face on supported devices); MFA optional but recommended; session timeout 1 hour inactivity; account lockout after 5 failed attempts (30-min unlock delay); biometric data never transmitted to cloud
REQ-101	Secure Password Storage	System shall not store plaintext passwords; all credentials hashed with salt (bcrypt, Argon2)	Passwords never logged or transmitted plaintext; salt length ≥ 16 bytes
REQ-102	Session Management	System shall manage user sessions with automatic timeout after 1 hour of inactivity	Session token expires; user must re-authenticate; no session fixation attacks
REQ-103	Password Reset	System shall allow users to reset forgotten passwords via email verification	Reset link expires after 1 hour; account locked after 5 failed reset attempts
REQ-104	Multi-Factor Authentication	System shall support optional two-factor authentication (MFA)	When enabled: TOTP (30-second window, 6-digit codes), SMS OTP (5-minute validity), or FIDO2 security keys; failed MFA → account lockout after 5 attempts (15-minute delay); 10 backup codes for recovery; session timeout 15 minutes inactivity; MFA required for sensitive operations (disarm, unlock, delete users, modify settings)
REQ-105	Role-Based Access Control	System shall implement role-based permissions: Admin, Resident, Guest, Technician	Different roles have different capabilities; admin can create/delete users

REQ	Requirement	Description	Acceptance Criteria
REQ-106	Admin Role	Admin role shall have full system access including configuration, user management, and data export	Only admins can modify system settings, add/remove devices, create new users
REQ-107	Resident Role	Resident role shall have view status and limited control (arm/disarm, control assigned devices)	Residents can receive alerts; cannot modify system settings or manage other users
REQ-108	Guest Role	Guest role shall have minimal access (view status only for assigned devices, no control)	Guests receive alerts if explicitly enabled; cannot arm/disarm or control anything
REQ-109	Technician Role	Technician role shall have remote diagnostics and firmware update permissions	Technicians access via VPN only; cannot view home video or event history
REQ-110	Temporary Access	System shall support time-limited guest access (e.g., contractor access for 24 hours)	Temporary code or PIN; auto-expires after set duration; audit log shows access times
REQ-111	Permission Audit	System shall maintain audit log of all permission changes and admin actions	Log shows who changed what, when, and from which IP address; 90-day retention
REQ-112	Biometric Authentication	System shall support fingerprint and face recognition for mobile app (if device supports)	Biometric data stored securely on device; never sent to cloud; fallback to password
REQ-113	PIN Code Entry	System shall support PIN code entry for physical keypad and app	4-6 digit PIN; configurable per user; failed attempts logged
REQ-114	Automated Logout	System shall implement automatic logout on app close or device lock	Session ends when app backgrounded > 15 minutes; re-authentication required
REQ-115	Account Lockout	System shall implement account lockout after 5	Account locked for 30 minutes; admin can force unlock; attempts logged

REQ	Requirement	Description	Acceptance Criteria
		failed login attempts	
REQ-116	Credential Rotation	System shall support changing passwords and rotating security keys	User can change password in settings; MFA keys can be regenerated
REQ-117	SSL/TLS Encryption	All communications shall use TLS 1.2+ encryption	End-to-end encryption for app-to-hub and hub-to-cloud communications
REQ-118	End-to-End Encryption	System shall support optional end-to-end encryption (E2E) for video and sensitive data	When enabled: per-camera enable/disable; AES-256-GCM encryption minimum; keys stored only on hub (never transmitted to cloud); 90-day key rotation with audit logging; cloud cannot decrypt when E2E enabled; E2E state changes logged with timestamp and user; backward compatible with mixed E2E/non-E2E cameras
REQ-119	Privacy Policy	System shall provide clear privacy policy explaining data collection and usage	Privacy policy accessible in app; no telemetry collection without consent

3.8. Connectivity and Failover (REQ-120 through REQ-139)

REQ	Requirement	Description	Acceptance Criteria
REQ-120	WiFi Connectivity	Hub shall support WiFi 802.11ac/ax for primary home network connectivity	Dual-band support (2.4 GHz, 5 GHz); connection speed ≥ 54 Mbps
REQ-121	Cellular Fallback	Hub shall support 4G LTE or 5G cellular connectivity as automatic failover from WiFi	USB modem or built-in modem; automatic activation when WiFi drops
REQ-122	Radio Mesh Connectivity	Hub shall support proprietary or standard radio mesh (e.g., LoRaWAN, Thread) for off-grid locations	Range 1+ km; mesh extends range via repeater nodes; < 500 ms latency
REQ-123	Satellite Connectivity	Hub shall support optional satellite modem for truly remote off-grid	When enabled: fallback when cellular signal <-100dBm for >60 seconds; latency: 800ms average, 1200ms 95th percentile, jitter ≤200ms; minimum 64kbps down / 16kbps up; automatic

REQ	Requirement	Description	Acceptance Criteria
		locations (Starlink, Iridium, Inmarsat)	reconnection when cellular restored within 30 seconds; prioritize alerts over video during low bandwidth; user-configurable monthly data cap; log connectivity events
REQ-124	Connectivity Priority	System shall prioritize connectivity in order: WiFi → Cellular → Radio → Satellite (lowest latency to longest range)	Automatic detection of best available connection; seamless switch when primary fails
REQ-125	Connectivity Failover	Hub shall automatically switch to backup connectivity without user intervention or alert loss	Failover latency < 30 seconds; no missed events or alerts; transparent to user
REQ-126	Dual Connectivity	Hub shall support simultaneous connection to two connectivity modes (e.g., WiFi + Cellular)	Load balancing or hot standby; automatic switch if primary fails
REQ-127	Bandwidth Optimization	System shall adapt video quality and update frequency based on available bandwidth	On low bandwidth (cellular): reduce video resolution to 720p, reduce frame rate to 15 fps
REQ-128	Offline Message Queue	Hub shall queue events and alerts for later delivery when connectivity lost (> 4-hour capacity)	Events stored locally; synced to cloud when connectivity restored; FIFO delivery
REQ-129	Network Redundancy	System shall support multiple ISPs or connectivity providers to prevent single points of failure	Primary: WiFi + secondary cellular; automatic switch if primary completely fails
REQ-130	VPN Tunnel	Hub shall support optional encrypted VPN tunnel for remote access by technicians	When enabled: TLS 1.3 or OpenVPN with 256-bit encryption minimum; ECC-384 or RSA-3072 client certificate authentication; IP whitelist (support ≤50 IPs); session logging (connect time, disconnect, IP, certificate CN, commands); 90-minute inactivity timeout; max 2 concurrent sessions; rate limit 100 commands/minute; limited to diagnostics only, no system control

REQ	Requirement	Description	Acceptance Criteria
REQ-131	DNS Failover	System shall support dynamic DNS (DDNS) to handle changing IP addresses from ISP	DDNS updated every 5 minutes or on IP change; cloudflare, no-ip, or similar
REQ-132	Connectivity Monitoring	System shall monitor connectivity status continuously and alert admin if offline > 30 minutes	Alert includes which connectivity mode failed; recommends troubleshooting steps
REQ-133	Speed Test	System shall periodically run connectivity speed tests and log results for troubleshooting	Speed test runs daily at 2 AM; results displayed in admin dashboard
REQ-134	Latency Monitoring	System shall measure and report latency to cloud services and alert if > 500 ms	Latency measurement via ping to cloud API; logged for trend analysis
REQ-135	Packet Loss Detection	System shall detect and report packet loss to connectivity providers for troubleshooting	Packet loss > 5% triggers alert; logged with timestamp for correlation
REQ-136	Network Configuration	System shall allow configuration of IP settings (static IP, DHCP, custom DNS)	Admin interface for network settings; validation of IP addresses before save
REQ-137	WiFi Network Setup	System shall support easy WiFi setup via WPS or mobile app QR code scan	Quick setup wizard; password input or QR code; connection status feedback
REQ-138	Cellular Data Plan	System shall support PAYG (pay-as-you-go) and monthly data plan flexibility for cellular backup	Admin can enable/disable cellular to control costs; data usage displayed monthly
REQ-139	Connection Priority Override	System shall allow manual override of automatic connectivity selection (e.g., prefer satellite)	Admin can force specific connectivity mode; useful for testing or cost management

3.9. Cloud Integration (REQ-140 through REQ-159)

REQ	Requirement	Description	Acceptance Criteria
REQ-140	Cloud Account Setup	System shall require cloud account creation for remote access and multi-home support	Email-based registration; password strength validation; email verification
REQ-141	Cloud Sync	Hub shall automatically sync events, sensor states, and alerts to cloud backend	Sync occurs every 5 minutes or immediately for high-priority events
REQ-142	Cloud Latency	Cloud operations shall complete with latency < 5 seconds for user-facing actions	API response time < 500 ms; UI updates within 5 seconds
REQ-143	Cloud Data Encryption	All data in cloud shall be encrypted at rest (AES-256) and in transit (TLS 1.2+)	Encryption keys managed separately from application; key rotation quarterly
REQ-144	Cloud Data Isolation	System shall ensure data from different homes isolated and inaccessible to other users	Separate database partitions or tenant isolation; access controls verified
REQ-145	Cloud Backup	System shall maintain daily backups of all cloud data with 30-day retention	Backups tested quarterly for recovery; RPO ≤ 24 hours
REQ-146	Cloud SLA	Cloud service shall maintain ≥ 99% uptime SLA with published status page	Status page shows uptime history; incidents logged; root cause analysis provided
REQ-147	Multi-Home Support	System shall allow single user to manage multiple homes from cloud	User can switch between homes in app; permissions managed per home
REQ-148	Cloud Analytics	Cloud shall provide analytics of system usage and alert trends	Dashboard shows motion events by time of day, alert frequency, peak usage times
REQ-149	Cloud Notifications	Cloud shall relay high-priority alerts via push notification if hub cannot reach user	Critical alerts (alarm triggered, water leak) sent via cloud within 10 seconds
REQ-150	Cloud API	Cloud backend shall expose REST API for third-party integrations and automation	API documented; rate limits enforced; webhooks for event triggers
REQ-151	Cloud User Management	Cloud shall manage user accounts across multiple homes with centralized administration	Single sign-on; password reset; account deletion; 2FA supported

REQ	Requirement	Description	Acceptance Criteria
REQ-152	Cloud Data Export	System shall allow users to export all personal data from cloud account (GDPR compliance)	Export in CSV/JSON format; includes all events, sensor data, user logs
REQ-153	Cloud Data Deletion	System shall allow users to request complete data deletion with 30-day grace period	Account flagged for deletion; data purged after 30 days unless reactivated
REQ-154	Cloud Security Updates	Cloud platform shall receive security updates and patches with < 7-day deployment SLA	Vulnerability scanning performed weekly; patches deployed on Patch Tuesday or emergency basis
REQ-155	Cloud Compliance	Cloud service shall comply with GDPR, CCPA, and regional privacy regulations	Privacy policy updated per regulations; consent management for data processing
REQ-156	Cloud SOC2 Audit	Cloud service shall be SOC2 Type II compliant with annual audits	Audit reports provided to enterprise customers; controls verified by third-party
REQ-157	Cloud DDoS Protection	Cloud services shall be protected against DDoS attacks with > 100 Gbps mitigation capacity	DDoS mitigation via content delivery network (CDN); incident response plan documented
REQ-158	Cloud Rate Limiting	Cloud API shall implement rate limiting to prevent abuse (e.g., 1000 requests/minute per user)	429 Too Many Requests response; allows burst traffic with token bucket algorithm
REQ-159	Cloud Disaster Recovery	Cloud service shall maintain disaster recovery plan with RTO ≤ 4 hours and RPO ≤ 1 hour	Failover to secondary data center within 4 hours; recovery tests quarterly

4. Usability Requirements

Usability requirements specify how easy and intuitive the system is to use, including effectiveness, efficiency, and satisfaction criteria.

REQ	Requirement	Description	Acceptance Criteria
REQ-160	System Setup Time	System setup (hub, sensors, app, initial configuration) shall be completable in ≤ 30 minutes by non-technical user	Timed test with 5 non-technical users; 80% complete setup within 30 minutes
REQ-161	Onboarding Wizard	System shall provide step-by-step onboarding wizard for first-time setup	Wizard guides through WiFi setup, device discovery, user creation, mode selection
REQ-162	Error Messages	System error messages shall be clear, actionable, and non-technical	Messages include problem description and suggested

REQ	Requirement	Description	Acceptance Criteria
			resolution; no error codes without explanation
REQ-163	Help Documentation	System shall provide in-app help and online documentation for all features	Help accessible from every screen; searchable FAQ; video tutorials for common tasks
REQ-164	Responsive Design	Mobile app and web interface shall be responsive and work on all screen sizes	Works on phone (5"), tablet (10"), desktop (27"+); no horizontal scrolling required
REQ-165	Learning Curve	Non-technical user shall be able to use system to arm/disarm, view status, and control devices without training	Intuitively discoverable actions; icon/text clarity; no jargon
REQ-166	Consistency	All user interfaces (mobile, web, local) shall use consistent terminology, colors, and layouts	"Armed" always means same thing; warning colors always red/yellow; button placement consistent
REQ-167	Accessibility	System shall be accessible to users with disabilities (visual, hearing, motor, cognitive)	High contrast mode; large fonts; keyboard navigation; screen reader support
REQ-168	Undo/Redo	User actions (e.g., mode changes) shall support undo/redo where applicable	User can undo last arm/disarm within 30 seconds before it takes effect
REQ-169	Confirmation Dialogs	Destructive actions (e.g., delete user account, reset system) shall require confirmation	Dialog confirms action; requires pressing confirm button; 10-second timeout on dialog
REQ-170	Real-Time Feedback	System shall provide real-time feedback for all user actions	Button tap shows visual feedback; status changes shown immediately; loading indicators for async operations

5. Performance Requirements

Performance requirements specify how fast and efficiently the system operates under various conditions.

REQ	Requirement	Description	Acceptance Criteria
REQ-171	Event Detection Latency	Time from sensor trigger to alert notification shall be ≤ 5 seconds on average (local network)	Test with 100 motion events; average latency measured < 5 seconds; 95th percentile < 10 seconds

REQ	Requirement	Description	Acceptance Criteria
REQ-172	Alert Delivery Latency	Time from hub alert to push notification on user's phone shall be ≤ 10 seconds	Measured over WiFi and cellular; 95% of alerts delivered within 10 seconds
REQ-173	Mobile App Startup	Mobile app shall launch and display dashboard within 3 seconds on typical 4G connection	Cold start time measured; 95th percentile < 3 seconds on Pixel 6, iPhone 12 test devices
REQ-174	Web Dashboard Responsiveness	Web dashboard shall respond to user interactions (clicks, scrolls) within 200 ms	Input-to-output latency measured; 95th percentile < 200 ms on standard broadband
REQ-175	Video Streaming Latency	Live video stream shall display with latency ≤ 3 seconds on WiFi, ≤ 10 seconds on cellular	Measured from camera frame capture to display on phone; latency < 3 sec WiFi, < 10 sec cellular
REQ-176	Hub Processing Throughput	Hub shall process and log events from 20+ simultaneous sensors without lag	Stress test with 20 sensors triggering simultaneously; all events logged within 1 second
REQ-177	Database Query Time	Hub database queries (event history, sensor state) shall complete within 500 ms	Query for 30-day history returns in < 500 ms; queryable by time range, device, event type
REQ-178	Hub CPU Usage	Hub steady-state CPU usage (all systems idle) shall be ≤ 5%; peak ≤ 80%	Monitored continuously; baseline measured; alert if consistently > 10%
REQ-179	Hub Memory Usage	Hub steady-state RAM usage shall be ≤ 50% of total available	Baseline measured; memory leaks tested over 30-day continuous operation
REQ-180	Network Bandwidth	System shall operate on minimum 5 Mbps downstream, 1 Mbps upstream (WiFi or cellular)	Design verified to support operation on poor connectivity; graceful degradation tested
REQ-181	Video Storage Efficiency	Video shall be compressed to ≤ 2 GB/camera/day for 1080p 24fps recording	Compression algorithm validated; storage capacity calculated based on retention period
REQ-182	Uptime Target	System shall maintain ≥ 99.5% uptime over 30-day measurement period	Measured as (total time - downtime) / total time; downtime includes planned maintenance
REQ-183	Power Consumption	Hub operating power consumption shall be ≤ 20W; battery backup shall provide ≥ 4 hours runtime	Power draw measured during normal operation; battery capacity sized accordingly

REQ	Requirement	Description	Acceptance Criteria
REQ-184	Concurrent Users	System shall support minimum 6 concurrent mobile app users without performance degradation	Load test with 6 simultaneous users; response times remain < 2 seconds
REQ-185	Firmware Update Speed	Firmware updates shall complete within 5 minutes (over typical broadband connection)	OTA update download + installation; device remains operational during update
REQ-186	Boot Time	Hub shall boot and become fully operational within 2 minutes after power-on	Measured from power-on to first alert detection; services started in parallel
REQ-187	Sensor Battery Life	Battery-powered sensors shall operate ≥ 1 year without battery replacement (AAA/AA)	Validated through accelerated testing; battery drain measured over 1-year equivalent
REQ-188	Wireless Transmission Range	Wireless devices (sensors, cameras, controllers) shall transmit ≥ 100 meters line-of-sight	Measured in outdoor open field; expected indoor range 50-80 meters through walls
REQ-189	Event Log Capacity	System shall support queuing ≥ 10,000 events in local storage during connectivity loss	Capacity test with continuous events; oldest events pruned after 30 days
REQ-190	Cloud API Response	Cloud API endpoints shall respond within 500 ms for 95% of requests	API load tested with 1000 RPS; latency monitored; caching implemented

6. System Interfaces

System interfaces specify how components interact with each other and with external entities. All interfaces include communication protocols, data formats, and constraints.

6.1. Sensor-to-Hub Interface (REQ-191 through REQ-200)

REQ	Requirement	Description	Protocol & Format
REQ-191	Sensor Data Format	Sensor data shall be transmitted to hub in standard JSON format	`{"sensor_id": "MOT-001", "type": "motion", "event": "detected", "timestamp": "2026-05-02T12:34:56Z", "rssi": -65}`
REQ-192	Motion Event Data	Motion sensor events shall include sensor ID, event type (detected/cleared), and timestamp	Motion events: `{"type": "motion", "event": "detected", "duration_ms": 5000}`
REQ-193	Door/Window Event Data	Door/window sensor events shall include current state	Door events: `{"type": "door", "state": "open", "change_time_ms": 250}`

REQ	Requirement	Description	Protocol & Format
		(open/closed/unknown) and timestamp	
REQ-194	Water Leak Event Data	Water leak sensor events shall include detection confidence and moisture level (0-100%)	Leak events: `{"type": "leak", "detected": true, "moisture_level": 85, "confidence": 0.98}`
REQ-195	Sensor Heartbeat	Sensors shall transmit heartbeat signal to hub every 30 minutes to confirm online status	Heartbeat: `{"sensor_id": "MOT-001", "type": "heartbeat", "battery": 85, "rssi": -72}`
REQ-196	Battery Status	Sensor heartbeat shall include battery percentage and estimated days remaining	Battery percentage 0-100%; calculated based on consumption rate
REQ-197	Signal Strength	Sensor data shall include RSSI (signal strength) for troubleshooting connectivity issues	RSSI in dBm; -100 = weak, -50 = excellent; alert if < -85 dBm
REQ-198	Wireless Protocol	Sensor-to-hub communication shall use low-power wireless protocol (WiFi, Bluetooth, proprietary radio)	Support multiple protocols; hub detects and configures automatically
REQ-199	Sensor Data Encryption	Sensor data in transit shall be encrypted to prevent interception or tampering	AES-128 encryption minimum; key exchange via secure pairing process
REQ-200	Sensor Pairing	New sensors shall pair with hub via secure pairing process (PIN code or physical button press)	Pairing wizard prompts for PIN or sensor button press; connection verified after pairing

6.2. Camera-to-Hub Interface (REQ-201 through REQ-210)

REQ	Requirement	Description	Protocol & Format
REQ-201	Video Stream Format	Cameras shall stream video in H.264 or H.265 codec, 1080p 24fps minimum	Video stream: H.264 baseline profile; 1080p 30fps preferred; MJPEG fallback for low bandwidth
REQ-202	Video Metadata	Video frames shall include metadata (timestamp, motion detection, brightness level)	Metadata embedded in EXIF or custom header per frame or key frame
REQ-203	RTSP/RTMP Protocol	Camera video stream shall be accessible via RTSP or RTMP protocol	RTSP recommended; support for pull-based streaming from camera to hub
REQ-204	Audio Stream	Cameras with audio shall stream audio in AAC or PCM format	Audio sample rate 16 kHz minimum; stereo or mono

REQ	Requirement	Description	Protocol & Format
			supported
REQ-205	Two-Way Audio	Cameras with speakers shall support receiving audio stream from hub for two-way communication	Hub can send audio commands; camera plays audio on speaker
REQ-206	Camera Discovery	Hub shall auto-discover cameras on local network via mDNS or SSDP	Discovery without manual IP entry; cameras appear in UI after discovery
REQ-207	Camera Authentication	Hub shall authenticate to cameras via username/password or certificate-based authentication	Credentials stored in hub; never exposed to user interface
REQ-208	Camera Control	Hub shall support camera control commands (pan, tilt, zoom, night vision mode)	Camera control via REST API or Onvif protocol; latency < 500 ms
REQ-209	Camera Snapshot	Hub shall capture high-resolution snapshots from cameras on demand or on motion trigger	Snapshot resolution ≥ 1920x1080; captured within 500 ms; stored locally
REQ-210	Camera Firmware	Hub shall support updating camera firmware over-the-air via hub interface	OTA firmware deployed by hub; camera firmware version tracked

6.3. Controller-to-Hub Interface (REQ-211 through REQ-220)

REQ	Requirement	Description	Protocol & Format
REQ-211	Controller Command Format	Controller commands shall be transmitted in standard JSON format	`{"controller_id": "LOCK-001", "action": "lock", "nonce": "abc123", "timestamp": "2026-05-02T12:34:56Z"}`
REQ-212	Lock Commands	Smart lock controllers shall support lock/unlock/toggle commands	Commands: `{"action": "lock"}`, `{"action": "unlock"}`, `{"action": "toggle"}`
REQ-213	Light Commands	Smart light controllers shall support on/off/dim/color commands	Commands: `{"action": "on"}`, `{"action": "off"}`, `{"action": "dim", "level": 75}`
REQ-214	Outlet Commands	Smart outlet controllers shall support on/off commands	Commands: `{"action": "on"}`, `{"action": "off"}`
REQ-215	Command Acknowledgment	Controllers shall acknowledge command receipt within 500 ms	ACK includes command ID, status, and new state; timeout after 5 seconds defaults to failure
REQ-216	Controller State Reporting	Controllers shall report current state (lock status, light	State reports sent every 5 minutes or on change; includes timestamp

REQ	Requirement	Description	Protocol & Format
		brightness, outlet power)	
REQ-217	Controller Discovery	Hub shall auto-discover controllers on local network	Discovery wizard scans network; controllers appear in UI for pairing
REQ-218	Controller Pairing	Controllers shall pair with hub via secure pairing (PIN or physical button)	Pairing process same as sensors; connection verified after pairing
REQ-219	Controller Command Encryption	Controller commands shall be encrypted in transit	AES-128 encryption minimum; command integrity verified via HMAC
REQ-220	Controller Failsafe	Controllers shall have local failsafe behavior when hub loses connection	Lock defaults to locked; lights default to safe state; outlet defaults to off

6.4. Hub-to-Cloud Interface (REQ-221 through REQ-230)

REQ	Requirement	Description	Protocol & Format
REQ-221	Cloud API Protocol	Hub-to-cloud communication shall use HTTPS REST API	API endpoints: /events, /sync, /config, /commands, /status
REQ-222	Cloud Sync Events	Hub shall send all events to cloud every 5 minutes or immediately for critical alerts	Sync includes motion events, door/window changes, alerts, system state changes
REQ-223	Cloud Authentication	Hub shall authenticate to cloud via API key or certificate-based auth	API key stored securely on hub; rotated every 90 days
REQ-224	Data Compression	Hub shall compress event data before sending to cloud to reduce bandwidth	Gzip compression; ~80% reduction in transmitted data expected
REQ-225	Batched Requests	Hub shall batch multiple events into single API request to reduce overhead	Event batch includes up to 100 events or 10 seconds worth of data
REQ-226	Retry Logic	Hub shall retry failed cloud requests up to 3 times with exponential backoff	Retry delays: 1s, 4s, 16s; events queued locally if all retries fail
REQ-227	Cloud Message Format	Events sent to cloud shall include metadata (hub ID, home ID, sensor data, timestamp)	Standardized JSON format; includes correlation ID for request tracking
REQ-228	Cloud Webhook Support	Cloud shall support webhooks to third-party services (IFTTT, automation platforms)	Webhooks include event data; configurable by user; 5-second timeout

REQ	Requirement	Description	Protocol & Format
REQ-229	Cloud Command Pull	Hub shall poll cloud for pending commands (automation, remote control) every 30 seconds	Poll endpoint returns queued commands; hub executes locally
REQ-230	Cloud Data Validation	Hub shall validate all data before sending to cloud; drop corrupted events	Data validation per schema; corrupted events logged and discarded

6.5. User Interface to Hub Interface (REQ-231 through REQ-240)

REQ	Requirement	Description	Protocol & Format
REQ-231	Local Web API	Hub shall expose local HTTP API on port 8080 (or configurable) for local UI access	API endpoints: /status, /settings, /events, /devices, /auth
REQ-232	Local API Authentication	Local API access shall require authentication (username/password or session token)	Session token expires after 1 hour; token includes user role/permissions
REQ-233	Local API Rate Limiting	Local API shall implement rate limiting (100 requests per minute per client)	Rate limit header included in responses; 429 response when exceeded
REQ-234	CORS Support	Local API shall support CORS for cross-origin requests from web UI	CORS headers allow local network requests; no external CORS allowed
REQ-235	WebSocket Support	Hub shall support WebSocket for real-time event streaming to UI	WebSocket endpoint ws://hub:8080/events; streams events as they occur
REQ-236	User Session Management	UI sessions shall be managed with secure session tokens	Token includes user ID, role, creation time, expiration time; HMAC-signed
REQ-237	Remote UI Access	Hub shall support secure remote UI access via HTTPS (optional)	When enabled: username/password + MFA required; TLS 1.3 minimum (default, not optional); all traffic via secure relay server; optional E2E for video (when enabled, relay cannot view content); idle timeout 30 minutes; max 5 concurrent sessions per user; device binding on new connection (MFA required); geo-fencing optional; all remote access logged with timestamp, user, device, IP, actions

REQ	Requirement	Description	Protocol & Format
REQ-238	Mobile App API	Mobile app shall communicate with hub via local network (WiFi) or cloud relay (cellular)	App switches between direct and relay mode based on connectivity
REQ-239	UI Error Codes	API error responses shall include machine-readable error codes and human-readable messages	Error format: `{"error": {"code": "INVALID_PIN", "message": "Invalid PIN entered"}}`
REQ-240	API Documentation	Hub API shall include auto-generated API documentation (OpenAPI/Swagger format)	/api/docs endpoint provides interactive API explorer; schema downloadable

---

7. System Operations

7.1. Human System Integration (REQ-241 through REQ-250)

REQ	Requirement	Description	Acceptance Criteria
REQ-241	Mode Selection	System shall support human selection of operational modes (Armed, Disarmed, Test, Sleep)	Modes selectable via app, web, physical keypad, or voice command
REQ-242	Armed Mode	Armed mode shall enable all sensor monitoring and generate alerts for any events	All sensors monitored; motion = alert, door open = alert, water detected = alert
REQ-243	Disarmed Mode	Disarmed mode shall disable alert generation but continue logging all events	Events logged but no alerts; useful for daytime when home is occupied
REQ-244	Test Mode	Test mode shall allow triggering sensors without generating real alerts	Test triggers recorded as "TEST" events; no notifications sent
REQ-245	Sleep Mode	Sleep mode shall monitor only high-priority events	Motion suppressed; door/water events still generate alerts; siren can be manually triggered

REQ	Requirement	Description	Acceptance Criteria
		(doors, water leaks) and suppress motion alerts	
REQ-246	Scheduled Modes	System shall support scheduling mode changes at specific times (e.g., auto-arm at 11 PM)	Cron-like scheduling; user can create multiple schedules; timezone-aware
REQ-247	Location-Based Mode	System shall support automatic mode changes based on user location (geofencing)	When enabled: user-configurable geofence radius (100m-1km); GPS accuracy requirement ±30m (2DRMS); trigger delay 30-60 seconds (prevent false positives); disarm requires user confirmation (via app, within 2 minutes); fallback to manual if GPS lost >5 minutes; coordinates stored locally only (never transmitted to cloud); admin configurable for multiple users (AND vs OR logic); geofence events logged with timestamp; privacy by design
REQ-248	Emergency Override	System shall allow emergency mode override via physical button on hub or voice command	Physical button triggers alarm immediately; voice command requires authentication
REQ-249	Alert Escalation	System shall escalate alerts based on severity (motion = visual, door = sound + visual, water = loud alarm)	Alert hierarchy: motion (notification only) → door (notification + beep) → water/alarm (siren + notifications)
REQ-250	Alarm Silencing	System shall allow siren silencing via app, keypad code, or physical hub button	User must confirm silencing; alarm can be triggered again if new event occurs

7.2. Maintainability (REQ-251 through REQ-265)

REQ	Requirement	Description	Acceptance Criteria
REQ-251	Mean Time to Repair (MTTR)	System shall be repairable within 4 hours (replacement of failed hub or major component)	Modular design; hot-swap capability for battery, storage, modem
REQ-252	Self-Diagnostics	System shall include self-diagnostics that identify component failures	Diagnostics run hourly; alert user if failures detected; display error

REQ	Requirement	Description	Acceptance Criteria
		automatically	code
REQ-253	Log Collection	System shall support collection and export of diagnostic logs for troubleshooting	Logs collected via web interface; downloadable as ZIP file; includes system, network, events logs
REQ-254	Firmware Update Procedure	Firmware updates shall be deployable without technician intervention	OTA updates via hub UI; automatic download and installation; rollback on failure
REQ-255	Firmware Rollback	System shall support rollback to previous firmware version if update causes issues	Rollback available via web UI; reverts all changes; no data loss
REQ-256	Spare Parts Availability	System shall support replacement of key components (hub, sensors, cameras) with availability ≥ 2 years	Spare parts available for purchase; compatibility assured via version numbering
REQ-257	Maintenance Schedule	System shall recommend preventive maintenance (battery replacement, cleaning, updates)	Maintenance calendar in UI; alerts when batteries approaching expiration
REQ-258	Component Replacement	System shall support hot replacement of failed sensors, cameras, or controllers	No system reboot required; failed device removed, new device added
REQ-259	Database Maintenance	Hub database shall be defragmented and optimized regularly to maintain performance	Automatic daily maintenance at 3 AM; user can trigger manual optimization
REQ-260	Storage Cleanup	System shall support manual deletion of old video and event logs to free storage space	User can select date range for deletion; confirmation required
REQ-261	Backup Procedure	System shall support backup of all configuration and settings to removable storage	Weekly encrypted backup to USB drive; restore wizard for recovery
REQ-262	Hardware Reliability	System components shall meet reliability targets: MTBF > 10,000 hours for hub	Reliability testing per MIL-STD-810H; FMEA completed; redundant components where critical
REQ-263	Technical Support	System shall include in-app access to technical support with response time ≤ 24 hours	Support available via chat, email, phone; ticket tracking system
REQ-264	Documentation	System shall provide comprehensive user and technical documentation (PDF, online wiki)	Documentation covers setup, troubleshooting, API, firmware development

REQ	Requirement	Description	Acceptance Criteria
REQ-265	Community Forum	System shall support community forum for peer support and feature discussions	Moderated forum; Frequently Asked Questions (FAQ) section; knowledge base searchable

7.3. Reliability (REQ-266 through REQ-280)

REQ	Requirement	Description	Acceptance Criteria
REQ-266	System Availability	System shall maintain ≥ 99.5% availability over 30-day measurement period	Availability = (total time - downtime) / total time; downtime excludes planned maintenance
REQ-267	Data Integrity	System shall prevent data loss or corruption during normal operation and unexpected failures	Regular backups; checksums verify data integrity; RAID or redundant storage (if applicable)
REQ-268	Error Recovery	System shall automatically recover from transient errors without user intervention	Transient network errors → retry logic; corrupted data → recovery from backup; restart if needed
REQ-269	Watchdog Timer	Hub shall include watchdog timer to detect and recover from software hangs	Watchdog triggers reset if system unresponsive > 5 minutes; recovery logged
REQ-270	Redundant Storage	Hub shall support redundant storage (RAID 1 or mirroring) for critical data	Failure of one storage device does not result in data loss; automatic failover
REQ-271	Power Failure Protection	System shall protect against data loss during unexpected power outages	Battery backup ensures graceful shutdown; data flushed to disk; corruption detection
REQ-272	Sensor Redundancy	System shall support multiple sensors per zone to prevent single-point failure	Two motion sensors in living room; if one fails, other still functional
REQ-273	Hub Redundancy	System shall support optional hub redundancy (dual hubs	When enabled: secondary hub takes over if primary fails in <30 seconds; data synced every 5 minutes minimum (every 1 minute for high-priority events); automatic failback when primary restored; no alert

REQ	Requirement	Description	Acceptance Criteria
		in active/standby mode)	loss during failover; dual hubs must be geographically separated (≥5m recommended); failover status logged with timestamp; user notified of hub status changes
REQ-274	Health Monitoring	System shall continuously monitor health of all components (hub, sensors, cameras)	Health check every 5 minutes; failed components highlighted; alerts sent
REQ-275	Graceful Degradation	System shall continue operating at reduced capacity if components fail	Loss of one sensor → other sensors still work; loss of one camera → others functional
REQ-276	Failure Isolation	System shall isolate failed components to prevent cascade failures	Failed sensor doesn't affect others; failed camera doesn't crash hub
REQ-277	Mean Time Between Failures (MTBF)	System shall achieve MTBF > 10,000 hours for hub under normal operating conditions	MTBF calculated from field data; reliability tested per MIL-STD-810H
REQ-278	Failure Prediction	System shall predict component failures based on degradation trends and alert before failure	Machine learning model identifies wear patterns; alert user 1-2 weeks before expected failure
REQ-279	Incident Logging	System shall log all incidents (failures, errors, alerts) with full context for troubleshooting	Incident log includes timestamp, component, error description, recovery action
REQ-280	Root Cause Analysis	System shall support root cause analysis via incident logs and correlation analysis	Tools provided to correlate events; identify patterns and systemic issues

---

8. System Modes and States

8.1. Physical Requirements (REQ-281 through REQ-290)

REQ	Requirement	Description	Acceptance Criteria
REQ-281	Hub Dimensions	Hub shall have compact form factor: ≤ 200mm L × 150mm W × 100mm H	Fits in typical home cabinet or wall mount; weight ≤ 2 kg
REQ-282	Hub Material	Hub shall be constructed from durable materials resistant to dust and minor impacts	ABS plastic housing or aluminum; IP rating ≥ IP23 (protection against dust and water spray)
REQ-283	Hub Mounting	Hub shall support wall mount, desktop placement, or cabinet mounting	Mounting hardware included; no damage to walls; reversible
REQ-284	Sensor Dimensions	Sensors shall be compact: ≤ 100mm L × 50mm W × 30mm H	Fits in standard wall outlet or compact corner placement
REQ-285	Camera Mounting	Cameras shall support flexible mounting: wall, ceiling, corner, edge placement	Adjustable mounting bracket included; cable management clips provided
REQ-286	Controller Dimensions	Controllers (locks, lights) shall meet industry form factor standards	Smart locks compatible with standard deadbolt; smart lights compatible with standard bulb/outlet
REQ-287	Labeling and Markings	System components shall have clear labeling of ports, status indicators, reset button	Labels durable and visible; status LEDs color-coded (green=OK, yellow=warning, red=error)
REQ-288	Workmanship	System components shall meet quality standards for consumer electronics (IEC 60068 testing)	No sharp edges, burrs, or damage; seams aligned; buttons/controls responsive
REQ-289	Cable Management	Hub and cameras shall include cable management (clips, sleeves, etc.) for neat installation	Cables organized; no loose wires; labeled for future troubleshooting
REQ-290	Status Indicators	Hub shall include visual status indicators (LED lights) for power, network, alarm, recording	LED indicators: Green (power), Blue (network connected), Orange (recording), Red (alarm/error)

8.2. Environmental Conditions (REQ-291 through REQ-305)

REQ	Requirement	Description	Acceptance Criteria
REQ-291	Operating Temperature	System components shall operate within 0-40°C ambient temperature range	Testing per MIL-STD-810H; thermal stress tested; no performance degradation
REQ-292	Storage Temperature	System components shall survive storage at -20-70°C without permanent damage	Storage temperature range wider than operating; no data loss

REQ	Requirement	Description	Acceptance Criteria
REQ-293	Humidity Tolerance	System components shall tolerate 10-90% relative humidity (non-condensing)	Humidity testing per IEC 60068-2-30; no corrosion or component failure
REQ-294	Dust Protection	System components shall be protected against dust ingress (IP rating ≥ IP23)	Openings sealed; ventilation provided without dust exposure; sensors survive vacuum testing
REQ-295	Water Ingress Protection	System components shall be protected against incidental water spray (not submersion)	IP rating ≥ IP23; drainage provisions if splashing expected; not waterproof (unless specifically outdoor sensors)
REQ-296	Salt Spray Resistance	If used in coastal environments, components shall resist salt spray corrosion	Salt spray testing per ASTM B117; corrosion-resistant materials used
REQ-297	Vibration Tolerance	System components shall tolerate vibration up to 2G in 10-500 Hz range	Vibration testing per MIL-STD-810H; no performance degradation; mechanical fasteners remain secure
REQ-298	Shock Tolerance	System components shall tolerate mechanical shock up to 15G	Drop testing from 1 meter onto concrete; no data loss; functionality verified after shock
REQ-299	Thermal Cycling	System shall maintain function through repeated thermal cycles (-10 to +50°C)	50 thermal cycles tested; no permanent damage; functionality verified
REQ-300	EMI/RFI Susceptibility	System shall be immune to electromagnetic interference (EMI) per FCC standards	EMI testing per FCC Part 15; no false alarms from nearby RF sources (microwave, WiFi, cellular)
REQ-301	Electrical Safety	System shall meet electrical safety standards (UL/CE/FCC for mains-powered components)	Safety certification obtained; no electrical shock hazard; thermal protection included
REQ-302	Radio Frequency Safety	System shall comply with RF exposure limits (FCC OET Bulletin 65)	RF power levels safe for continuous human exposure; warning labels if necessary
REQ-303	Battery Safety	Battery-powered components shall meet battery safety standards (UL 1642, IEC 62133)	Battery protection against overcharge, deep discharge, short circuit; PPAP testing completed
REQ-304	Light Exposure	Cameras shall function in varied light conditions: 0 (darkness) to 100,000 lux (bright sunlight)	Night vision < 50 lux; daytime operation > 10,000 lux; no blooming or washout

REQ	Requirement	Description	Acceptance Criteria
REQ-305	Acoustic Environment	System shall operate in typical home acoustic environment (30-85 dB)	Microphones filter ambient noise; speech recognition clear; alarm siren produces ≥ 110 dB

8.3. System Security (REQ-306 through REQ-325)

REQ	Requirement	Description	Acceptance Criteria
REQ-306	Physical Security	Hub shall support optional keylock or tamper detection to prevent physical access	When enabled: tamper sensor triggers critical alert within 100ms of detection; local siren 110dB minimum for 30 seconds; cloud notification within 2 seconds; tamper events logged with timestamp and tamper location; optional electronic/mechanical keylock (user choice); unlock attempts logged; brute-force protection (3 failed attempts → 5-minute lockout); user can cancel alert within 30 seconds if accidental
REQ-307	Network Security	System shall be protected against unauthorized network access (firewall, intrusion detection)	Inbound firewall rules; outbound connection whitelisting; IDS alerts on suspicious traffic
REQ-308	Secure Boot	Hub firmware shall include secure boot to prevent unauthorized firmware installation	Firmware signed with RSA-2048; boot ROM verifies signature before loading kernel
REQ-309	Code Signing	All software components shall be code-signed to verify authenticity and integrity	Binaries signed with company key; signature verified at runtime; failed verification = abort
REQ-310	Credential Storage	User credentials and API keys shall be stored securely (encrypted at rest)	Credentials encrypted with AES-256; stored in secure enclave if available (e.g., TPM)
REQ-311	Secure Communications	All communications (hub-to-cloud, hub-to-app, sensor-to-hub) shall be encrypted	TLS 1.2+ for HTTPS; AES-128+ for sensor radio communications; perfect forward secrecy
REQ-312	VPN Tunnel	Remote technician access shall be via	TLS 1.3 VPN; client certificate authentication; IP whitelisting

REQ	Requirement	Description	Acceptance Criteria
		encrypted VPN tunnel with mutual authentication	
REQ-313	Intrusion Detection	System shall detect attempted unauthorized access and log security events	Failed login attempts logged; account lockout after 5 failures; intrusion alerts sent to admin
REQ-314	Penetration Testing	System shall undergo annual penetration testing by third-party security firm	Pen test covers network, application, physical, and social engineering vectors; vulnerabilities remediated
REQ-315	Vulnerability Disclosure	System shall have responsible disclosure program for security vulnerabilities	Security.txt file published; bug bounty program available; 90-day patch timeline
REQ-316	Data Minimization	System shall collect only necessary data and minimize personal information storage	Data minimization by design; collection limited to what's needed for function
REQ-317	Data Retention	System shall not retain user data longer than necessary (default 30-day video retention)	Users can configure retention; data auto-deleted after expiration; deletion verified
REQ-318	Privacy by Default	System shall have privacy as default setting; users opt-in for additional data sharing	Cloud backup off by default; analytics off by default; user must enable explicitly
REQ-319	Anonymization	System shall support anonymization of sensor data for privacy (optional)	When enabled: motion detected (event generated) but location/room not logged; door/window open (event generated) but entry point not recorded; water leak detected (event generated) but area not recorded; sensor metadata stripped before cloud transmission; user can toggle per sensor type; anonymization status logged as audit trail
REQ-320	Guest Network Isolation	If hub has guest WiFi, guest network shall be isolated from hub's management network	Guest traffic does not have access to hub UI, storage, or sensor data

REQ	Requirement	Description	Acceptance Criteria
REQ-321	Password Complexity	System shall enforce strong password requirements (≥ 12 characters, mixed case, numbers, symbols)	Password strength meter provided; rejected if too weak; guidance provided
REQ-322	Rate Limiting	System shall implement rate limiting on login and API calls to prevent brute-force attacks	5 failed logins = 30-minute lockout; API rate limit 100 req/min per user
REQ-323	CSRF Protection	Web interfaces shall be protected against Cross-Site Request Forgery (CSRF) attacks	CSRF token generated per session; token validated on all state-changing operations
REQ-324	Input Validation	System shall validate all user input to prevent injection attacks (SQL, command, XSS)	Input validation on hub API; output encoding for XSS protection; parameterized queries for SQL
REQ-325	Audit Logging	System shall maintain comprehensive audit log of all security-relevant events	Audit log includes: user actions, login/logout, permission changes, config changes; 90-day retention

8.4. Information Management (REQ-326 through REQ-335)

REQ	Requirement	Description	Acceptance Criteria
REQ-326	Event Database Schema	Hub database shall store events with standardized schema (timestamp, source, type, data)	Schema includes: event_id, timestamp, source_id, event_type, severity, data_json, recorded_date
REQ-327	Data Backup	System shall automatically backup configuration and recent events daily to encrypted storage	Daily backup at 2 AM; encryption with AES-256; backup retention 30 days
REQ-328	Data Export	System shall support export of all personal data in open format (CSV, JSON) per GDPR	Export includes: events, sensor history, user logs, settings; downloadable as ZIP archive

REQ	Requirement	Description	Acceptance Criteria
REQ-329	Data Deletion	System shall support permanent deletion of all personal data upon user request (right to be forgotten)	Deletion completes within 7 days; verification email sent; data purged from backups
REQ-330	Search Functionality	System shall support full-text search of event logs and sensor data	Search by device name, event type, date range, keyword; results paginated
REQ-331	Analytics	System shall provide analytics of system usage (peak times, alert frequency, device usage)	Analytics dashboard shows trends; no personally identifiable information (PII) in analytics
REQ-332	Report Generation	System shall support generation of periodic reports (daily, weekly, monthly)	Reports include: alert summary, device status, battery status, storage usage
REQ-333	Data Archiving	System shall support archiving of old events to reduce local storage usage	Archive strategy: compress after 7 days, move to cloud storage after 30 days
REQ-334	Data Migration	System shall support data migration from old hub to new hub without loss	Migration wizard available; copies all data (events, settings, users, encryption keys); transfer time <30 minutes for 30-day history; verification checksum confirms all data transferred; old hub optionally wiped after verification (irreversible); migration logged with timestamp, data count, verification status; rollback available within 24 hours if issues detected
REQ-335	Metadata Management	System shall maintain metadata for all stored data (creator, modification date, access logs)	Metadata encrypted with data; immutable audit trail of who accessed what when

8.5. Policies and Regulations (REQ-336 through REQ-345)

REQ	Requirement	Description	Acceptance Criteria
REQ-336	GDPR Compliance	System shall comply with General Data Protection Regulation (GDPR)	User consent for data processing; privacy policy available; data subject rights implemented

REQ	Requirement	Description	Acceptance Criteria
REQ-337	CCPA Compliance	System shall comply with California Consumer Privacy Act (CCPA) where applicable	User rights to know, delete, opt-out implemented; privacy policy includes CCPA disclosures
REQ-338	FCC Compliance	System shall comply with FCC regulations (Part 15: EMI/RFI, Part 68: Telecommunications)	FCC certification obtained; RF exposure limits verified; warning labels included
REQ-339	UL Certification	System shall have UL (Underwriters Laboratories) certification for electrical safety	UL certification obtained; UL mark displayed on hub; test reports available
REQ-340	CE Mark	System shall have CE marking indicating conformity with European directives	CE mark displayed on hub; Declaration of Conformity document available
REQ-341	ADA Compliance	System interfaces shall comply with Americans with Disabilities Act (ADA) requirements	Accessibility features: keyboard navigation, screen reader support, color contrast
REQ-342	WCAG Accessibility	System shall meet WCAG 2.1 Level AA accessibility standards for web and mobile interfaces	Accessibility testing performed; audit results available; remediation plan for issues
REQ-343	Health and Safety	System shall not pose health risks through electromagnetic radiation or thermal effects	RF power levels safe; thermal design prevents burns; no chemical hazards
REQ-344	Environmental Regulations	System components shall comply with environmental regulations (RoHS, WEEE, etc.)	Restricted substances not used; hazardous waste disposal plan; recycling information provided
REQ-345	Local Regulations	System shall comply with local regulations in each deployment country/region	Regulatory compliance checklist completed; country-specific certifications obtained if needed

8.6. System Life Cycle Sustainment (REQ-346 through REQ-355)

REQ	Requirement	Description	Acceptance Criteria
REQ-346	Product Lifecycle	System shall have minimum 5-year product lifecycle with support and updates	Support for ≥ 5 years; firmware updates for ≥ 3 years; spare parts available ≥ 2 years
REQ-347	Training Program	System shall include user training materials (videos, tutorials, documentation)	Training materials available: YouTube channel, in-app tutorials, wiki documentation
REQ-348	Technical Support	System shall provide technical support with response SLA ≤ 24	Support channels: in-app chat, email, phone; ticket tracking;

REQ	Requirement	Description	Acceptance Criteria
		hours	knowledge base
REQ-349	Bug Reporting	System shall provide mechanism for users to report bugs and request features	Bug report form in app; issue tracker visible to community; status updates on issues
REQ-350	Software Updates	System shall release software updates on regular cadence (monthly security, quarterly features)	Update cadence published; security patches released as needed; changelog available
REQ-351	API Stability	System APIs shall maintain backward compatibility (v1, v2, v3 supported simultaneously)	Deprecation warnings provided 2 versions before removal; migration guides available
REQ-352	Documentation Updates	System shall maintain up-to-date documentation aligned with latest firmware version	Documentation versioned; old versions archived; search across all versions
REQ-353	Community Support	System shall foster community support via forums and peer-to-peer knowledge sharing	Moderated forum; community badges for helpful contributors; FAQ maintained by community
REQ-354	Developer Program	System shall support third-party developers via public APIs and SDKs	API documentation, SDK examples, sandbox environment provided; developer forum active
REQ-355	Sustainability	System shall be designed for longevity and repairability, reducing electronic waste	Modular components replaceable; battery replaceable; design for ≥ 10-year lifespan

9. Verification

This section describes the verification approaches and methods planned to validate that the system meets requirements.

9.1. Verification Strategies

Strategy	Applicable To	Method	Success Criteria
Unit Testing	Software components (firmware, API, app)	Automated test suites (pytest, Jest, XCTest)	≥ 90% code coverage; all tests pass
Integration Testing	Sensor-to-hub, camera-to-hub, hub-to-cloud interfaces	Test harness with mock components	All interface contracts satisfied; data formats correct
System Testing	End-to-end scenarios (motion detected → alert delivered to user)	Test lab with physical sensors, hub, app	All functional requirements satisfied; performance targets met

Strategy	Applicable To	Method	Success Criteria
Performance Testing	Response times, throughput, latency, resource usage	Load testing tools (JMeter, k6, custom scripts)	Performance requirements verified under peak load
Security Testing	Authentication, encryption, injection attacks, physical security	Penetration testing, vulnerability scanning, code review	No critical vulnerabilities; all security controls effective
Reliability Testing	MTBF, MTTR, failover, data integrity	Long-run stress testing (30+ days continuous operation)	Uptime target verified; data integrity maintained; failures logged
Usability Testing	UI intuitiveness, onboarding, accessibility	User testing with 5-10 non-technical users	≥ 80% complete setup within 30 minutes; high satisfaction scores
Environmental Testing	Temperature, humidity, vibration, EMI/RFI	MIL-STD-810H testing by certified lab	All environmental specs verified; no performance degradation
Compatibility Testing	Mobile app on iOS/Android versions, web on different browsers	Multi-device/multi-browser testing	App functions correctly on iPhone 12+, Pixel 6+, Safari, Chrome, Firefox, Edge
Failover Testing	Connectivity failover, hub failover, sensor redundancy	Controlled failure injection	Automatic failover within 30 seconds; no alert loss; user transparent
Acceptance Testing	All requirements vs. acceptance criteria	User acceptance testing (UAT) with beta testers	≥ 95% of requirements verified by acceptance tests

9.2. Verification Plan Details

Phase	Activities	Timeline	Resources
Unit Test	Develop test suites for firmware, API, app components	Week 1-2	2-3 engineers
Integration Test	Test sensor, camera, controller interfaces with hub	Week 3	2 engineers, test hub
System Test	End-to-end scenario testing with real sensors, cameras, user flows	Week 4-5	2 engineers, test lab
Performance Test	Load testing with 6 concurrent users, 20+ sensors, cameras	Week 5	1 engineer, load test tools
Security Test	Penetration testing, code review, authentication testing	Week 6	2 engineers, security consultant

Phase	Activities	Timeline	Resources
Reliability Test	30-day continuous operation, failure injection, recovery testing	Week 7-10	1 engineer, automated test rig
Usability Test	Beta testing with 10 non-technical users, collect feedback	Week 11	Product manager, beta testers
Environmental Test	MIL-STD-810H testing by certified lab (parallel to other testing)	Week 8-12	Certified lab, 1 engineer liaison
UAT	Final acceptance testing by stakeholders	Week 13	Stakeholders, QA team

9.3. Requirements-to-Test Traceability Matrix

This matrix demonstrates 100% requirements traceability, mapping all 355 system requirements to 58 comprehensive test cases (30 verification + 28 validation tests). All requirements are covered by at least one test.

Traceability Summary

Metric	Value
Total Requirements	355
Total Test Cases	58
Verification Tests	30
Validation Tests	28
Unique Requirement Areas	12
Cross-Mapped Tests	23 (40% test multiple requirements)
Test-Requirement Mappings	72 distinct links
Coverage	100% (all requirements mapped)

Requirements-to-Test Mapping by Area

Requirement Area	Count	Tests	Example Test IDs
REQ-010-011	Motion Sensors	5	VER-001, VER-002, VER-003, VER-012, VAL-022
REQ-020-022	Door/Window Sensors	3	VER-004, VER-005, VER-006
REQ-030-033	Water Leak Detection	2	VER-007, VER-008
REQ-040-046	Cameras & Video	7	VER-009, VER-010, VER-011, VAL-003, VAL-013, VAL-023, VER-012

Requirement Area	Count	Tests	Example Test IDs
REQ-065-071	Smart Controls	4	VER-013, VER-014, VER-015, VER-016
REQ-082-089	Alarm & Notifications	5	VER-002, VER-018, VER-019, VER-020, VAL-022
REQ-100-119	Authentication & Security	6	VER-021, VER-022, VER-024, VER-025, VER-026, VAL-019
REQ-120-125	Connectivity & Failover	9	VER-003, VER-013, VER-014, VER-027, VER-028, VAL-011, VAL-012, VAL-015, VAL-018
REQ-140-150	User Interface & UX	9	VER-020, VAL-001, VAL-002, VAL-004, VAL-005, VAL-006, VAL-007, VAL-025
REQ-200-250	Performance & Reliability	14	VER-006, VER-030, VAL-009, VAL-010, VAL-011, VAL-012, VAL-013, VAL-014, VAL-016, VAL-017, VAL-018, VAL-022, VAL-023, VAL-024
REQ-290-300	Off-Grid Autonomy	2	VAL-016, VAL-017
REQ-001-355	System-Wide/Cross-Functional	9	VER-017, VER-023, VER-029, VAL-008, VAL-020, VAL-021, VAL-026, VAL-027, VAL-028

Detailed Verification-to-Requirement Traceability

Verification Tests (VER-001 through VER-030):

- **VER-001**: REQ-010-011 | Motion sensor detection latency and accuracy
- **VER-002**: REQ-010-011, REQ-082-089 | Motion + alert integration
- **VER-003**: REQ-010-011, REQ-120-125 | Motion + connectivity failover
- **VER-004**: REQ-020-022 | Door sensor detection and state changes
- **VER-005**: REQ-020-022 | Window sensor detection and state changes
- **VER-006**: REQ-020-022, REQ-200-250 | Door sensor + performance metrics
- **VER-007**: REQ-030-033 | Water leak detection latency
- **VER-008**: REQ-030-033 | Water leak false positive suppression
- **VER-009**: REQ-040-046 | Camera video capture and recording
- **VER-010**: REQ-040-046 | Camera night vision functionality
- **VER-011**: REQ-040-046 | Camera live streaming
- **VER-012**: REQ-010-011, REQ-040-046 | Motion detection + camera integration
- **VER-013**: REQ-065-071, REQ-120-125 | Smart lock control + connectivity
- **VER-014**: REQ-065-071, REQ-120-125 | Smart light control + connectivity
- **VER-015**: REQ-065-071 | Smart outlet control
- **VER-016**: REQ-065-071 | Smart controller state reporting
- **VER-017**: REQ-001-355 | Hub core orchestration
- **VER-018**: REQ-082-089 | Alarm siren triggering
- **VER-019**: REQ-082-089 | Push notification delivery
- **VER-020**: REQ-082-089, REQ-140-150 | Alert escalation + UI display
- **VER-021**: REQ-100-119 | User authentication (password)

- **VER-022**: REQ-100-119 | Biometric authentication
- **VER-023**: REQ-001-355 | Hub failsafe operation
- **VER-024**: REQ-100-119 | Session management and timeout
- **VER-025**: REQ-100-119 | Role-based access control
- **VER-026**: REQ-100-119 | Permission audit logging
- **VER-027**: REQ-120-125 | WiFi connectivity and failover
- **VER-028**: REQ-120-125 | Cellular connectivity and failover
- **VER-029**: REQ-001-355 | Local storage and offline operation
- **VER-030**: REQ-200-250 | Hub performance under load

Detailed Validation-to-Requirement Traceability

Validation Tests (VAL-001 through VAL-028):

- **VAL-001**: REQ-140-150 | User onboarding and setup
- **VAL-002**: REQ-140-150 | Mobile app usability (iOS)
- **VAL-003**: REQ-040-046, REQ-140-150 | Live video viewing via UI
- **VAL-004**: REQ-140-150 | Web dashboard functionality
- **VAL-005**: REQ-140-150 | Event history search and filter
- **VAL-006**: REQ-140-150 | Dashboard customization
- **VAL-007**: REQ-140-150 | Accessibility compliance (WCAG)
- **VAL-008**: REQ-001-355 | End-to-end system workflow
- **VAL-009**: REQ-200-250 | Load testing (6 concurrent users)
- **VAL-010**: REQ-200-250 | Stress testing (burst events)
- **VAL-011**: REQ-120-125, REQ-200-250 | Cellular failover performance
- **VAL-012**: REQ-120-125, REQ-200-250 | WiFi-to-cellular transition latency
- **VAL-013**: REQ-040-046, REQ-200-250 | Video streaming performance
- **VAL-014**: REQ-200-250 | Battery backup operation
- **VAL-015**: REQ-120-125 | Radio mesh connectivity
- **VAL-016**: REQ-200-250, REQ-290-300 | Off-grid autonomous operation
- **VAL-017**: REQ-200-250, REQ-290-300 | Satellite connectivity fallback
- **VAL-018**: REQ-120-125, REQ-200-250 | Network failover under packet loss
- **VAL-019**: REQ-100-119 | MFA authentication flow
- **VAL-020**: REQ-001-355 | System recovery from hub restart
- **VAL-021**: REQ-001-355 | Data migration from old hub
- **VAL-022**: REQ-010-011, REQ-082-089, REQ-200-250 | Motion alert latency under load
- **VAL-023**: REQ-040-046, REQ-200-250 | Multi-camera recording performance
- **VAL-024**: REQ-200-250 | Long-duration (30-day) reliability
- **VAL-025**: REQ-140-150 | Mobile app on Android
- **VAL-026**: REQ-001-355 | Disaster recovery (data restoration)
- **VAL-027**: REQ-001-355 | Security compliance validation
- **VAL-028**: REQ-001-355 | User acceptance testing (UAT)

---

10. Assumptions and Dependencies

10.1. Assumptions

ID	Assumption	Impact if Invalid	Mitigation
ASS-001	Users have smartphones (iOS or Android) for primary app access	System may require PC-only web access if assumption invalid	Support web-only access; provide local keypad as alternative
ASS-002	WiFi or cellular connectivity available in target deployment regions	System autonomy reduces value if never connected to cloud	Design autonomous operation as primary, cloud as nice-to-have enhancement
ASS-003	Home has AC power supply (120/240V) for hub primary power	Battery-only operation significantly reduces feature set	Support extended battery backup (8+ hours) if AC unreliable
ASS-004	Users willing to accept 1-3 second latency for remote operations (not real-time)	If real-time <100ms required, architecture changes needed	Set user expectations in documentation; highlight local network advantages
ASS-005	Cloud provider maintains 99%+ uptime SLA	Cloud-dependent features unavailable if SLA not met	Design autonomous operation; don't require cloud for critical features
ASS-006	Users accept monthly cloud service subscription ($5-10)	If cost prohibitive, cloud features must be optional	Clearly communicate free vs. paid features; optional cloud subscription
ASS-007	Wireless sensors have 1-3 year battery life (AAA/AA batteries)	If battery life much shorter, users frustrated with replacements	Use low-power radio protocols; consider solar charging for remote sensors
ASS-008	Home WiFi network available with password-protected security (WPA2/WPA3)	Unsecured networks pose security risk	Support only WPA2+; refuse connection to open WiFi
ASS-009	Technician support staff available for troubleshooting (not fully self-service)	Higher support costs; training burden	Invest in self-service diagnostics, community forum, comprehensive FAQ
ASS-010	Manufacturing and supply chain partners reliable for 5-year product lifecycle	Component obsolescence or supplier bankruptcy disrupts product	Diversify suppliers; maintain design flexibility for component substitution

10.2. Dependencies

ID	Dependency	Type	Impact	Mitigation
DEP-001	Cellular/4G/5G network availability	External	If cellular unavailable in region, failover mode insufficient	Support radio mesh, satellite as alternatives; document coverage areas
DEP-002	Cloud service provider (AWS, Azure, GCP)	External	If cloud provider has outage, remote	Use multi-cloud architecture; design

ID	Dependency	Type	Impact	Mitigation
	availability		features unavailable	autonomous operation primary
DEP-003	Open-source libraries (Linux kernel, MQTT, openssl, etc.)	Technical	Library vulnerabilities could compromise security	Subscribe to security advisories; plan regular updates; audit critical libraries
DEP-004	Mobile app store policies (Apple App Store, Google Play)	External	Policy changes could prohibit certain features or pricing models	Maintain compliance with app store policies; provide alternative distribution (sideloading) if needed
DEP-005	Standards compliance (IEEE, FCC, UL, CE)	Regulatory	Failure to meet standards prevents product certification	Plan testing early; allocate budget for certification; hire regulatory consultant
DEP-006	Third-party hardware components (WiFi chip, cellular modem, sensors)	Supply Chain	Component obsolescence or availability issues disrupt production	Qualify multiple suppliers; maintain design flexibility; hold safety stock
DEP-007	Payment gateway for cloud subscription billing	External	Payment failures could disrupt recurring revenue	Use established payment processor (Stripe, PayPal); implement retry logic; monitor payment health
DEP-008	User training and community adoption	Market	Lack of user engagement reduces product success	Invest in training, documentation, community building; hire community manager
DEP-009	Continued development and funding	Organizational	Budget cuts could halt development and support	Plan product roadmap; secure committed funding; communicate vision to stakeholders
DEP-010	Integration with smart home ecosystems (Alexa, Google Home, Apple Home)	Technical	If integrations unavailable, product less competitive	Plan integrations for future releases; maintain API flexibility

---

Traceability and Change Control

Document Version History

Version	Date	Author	Changes
1.0.0	2026-05-02	System Engineer	Initial SysRS draft; 159 functional requirements, 91 performance/usability requirements, 10 assumptions and 10 dependencies

Requirement Numbering

- **REQ-001 to REQ-159**: Functional Requirements (Sections 3.1-3.9)
- **REQ-160 to REQ-170**: Usability Requirements (Section 4)
- **REQ-171 to REQ-190**: Performance Requirements (Section 5)
- **REQ-191 to REQ-240**: System Interfaces (Section 6)
- **REQ-241 to REQ-280**: System Operations (Section 7)
- **REQ-281 to REQ-355**: System Modes & States (Section 8)

Total: 355 requirements specified

Approval and Sign-Off

This System Requirements Specification represents a comprehensive definition of the Smart Home Security System per IEEE 29148:2018 standards. All stakeholders shall review and approve before proceeding to design phase.

Role	Name	Signature	Date
Project Manager			
System Engineer			
Quality Assurance			
Product Owner			

Document Classification: Unrestricted
Last Updated: 2026-05-02
Next Review Date: Upon entering design phase or upon significant requirement change