INF1a-CL

NFA DFA regex

-Tseytin
-Syllogisms
-DPLL
-The arrow rule
-Haskell coding in CL
-Sequent calculus
-Satisfiability and CNF
-Operations on machine languages
-Resolution
-Logic
-Karnaugh maps

Today regex NFA DFA
Monday Syllogisms Arrow Rule KM
Thursday Sequent Calculus CNF Tseytin
Friday DPLL Satisfiability





(d) For each of the following regular expressions, draw a non-deterministic finite state machine that accepts the language described by the regular expression.

i. x^*y
ii. $(x^*|y)$
iii. $(x^*y)^*$

(d) For each of the following regular expressions, draw a non-deterministic finite state machine that accepts the language described by the regular expression.

i. x^*y
ii. $(x^*|y)$
iii. $(x^*y)^*$



(d) For each of the following regular expressions, draw a non-deterministic finite state machine that accepts the language described by the regular expression.

i. x^*y
ii. $(x^*|y)$
iii. $(x^*y)^*$





(d) For each of the following regular expressions, draw a non-deterministic finite state machine that accepts the language described by the regular expression.

i. x^*y
ii. $(x^*|y)$
iii. $(x^*y)^*$







(d) For each of the following regular expressions, draw a non-deterministic finite state machine that accepts the language described by the regular expression.

i. x^*y
ii. $(x^*|y)$
iii. $(x^*y)^*$













DFA



X×Y

DFA



X×Y

DFA



X×Y

For the product construction we can ignore
black hole states in either component

DFA



X+Y

For the sum construction we must include
any black hole state in each component



Product : OK to ignore black hole



sum : must include black hole




5. Each diagram shows an FSM. In each case give a regular expression for the language accepted by the FSM, make a mark in the check box against each string that it accepts (and no mark against those strings it does not accept), make a mark in the DFA check box if it is deterministic, and draw an equivalent DFA if it is not.

[4 marks]

(a) aab ☐ aba ☐ bab ☐ aaa ☐ bbb ☐ DFA ☐ regex:

[4 marks]

(b) aab ☐ aba ☐ bab ☐ aaa ☐ bbb ☐ DFA ☐ regex:

[4 marks]

(c) aab ☐ aba ☐ bab ☐ aaa ☐ bbb ☐ DFA ☐ regex:

[4 marks]

(d) aab ☐ aba ☐ bab ☐ aaa ☐ bbb ☐ DFA ☐ regex:

[4 marks]

(e) aab ☐ aba ☐ bab ☐ aaa ☐ bbb ☐ DFA ☐ regex:

Page 6 of 6.



(b)



aab ☐
aba ☐
bab ☐
aaa ☐
bbb ☐
DFA ☐

(c)



aab ☐
aba ☐
bab ☐
aaa ☐
bbb ☐
DFA ☐

(d)



aab ☐
aba ☐
bab ☐
aaa ☐
bbb ☐
DFA ☐

(e)



aab ☐

aba ☐

bab ☐

aaa ☐

bbb ☐

DFA ☐

---

a) `(a|b(a|b))(a(a|b)|b(a|b(a|b)))*`

b) `(a|ba*b)((a|b)a*b)*|(b|a(a|b))(a|b(a|b))*`

c) `(a|ba*b)((a|b)a*b)*`

d) `a((a|b)(aa|bb))*|(aa|bb)((a|b)(aa|bb))*`

e) `a((a|b)(aa|bb))*`