



THREAT REPORT: UTA0560 AND JUNGLEBAMBOO LEVERAGE CHROME AND WINDOWS 0-DAY CVE-2026-85880

Visual Summary

Kill-Chain Reach — Critical (deepest phase reached: exfiltration)



Defensive Chokepoint — why this control is the priority



The control that most disrupts the attack (priority in crimson).

Summary

The threat actors UTA0560 and JungleBamboo are operating the GRIMWEDGE, SUPERSTOMP, and LONGTALE malware families to exploit CVE-2026-85880 in Chrome and Windows. Their campaign is directed at non-governmental organizations (NGOs) located in the United States. Priority should be given to auditing Windows Startup folders and Run/RunOnce registry keys for unauthorized entries and to patching CVE-2026-85880 on all affected systems.

Threat Overview

The source attributes this activity to UTA0560 and JungleBamboo, who employ the GRIMWEDGE, SUPERSTOMP, and LONGTALE malware families. They exploit the zero-day vulnerability

CVE-2026-85880 in both Chrome and Windows operating systems. The observed victims are NGOs operating within the United States.

Attack Chain and Priority Control

The observed chain begins with spearphishing links (T1566.002) that deliver a drive-by compromise (T1189) leveraging exploitation for client execution (T1203) of CVE-2026-85880. The payload then uses process hollowing (T1055.012) to inject malicious code, establishes persistence via Registry Run Keys / Startup Folder (T1547.001), harvests credentials from web browsers (T1555.003) and system information (T1082), and ultimately exfiltrates data over the C2 channel (T1041).

Priority technique: T1547.001 Registry Run Keys / Startup Folder

Priority control: Audit Windows Startup folders and Run/RunOnce registry keys for unauthorized entries; alert on .lnk or script creation in Startup by browser/email temp paths. In parallel, patch CVE-2026-85880 on all affected systems.

Infrastructure and Corroboration

Third-party enrichment indicates that the malicious infrastructure is hosted by BL Networks, as observed in the associated ASN data. AbuseIPDB does not flag any of the indicators with high confidence, and abuse.ch has not corroborated additional malware families.

Technical Appendix

Ground-truth telemetry from the source pulse; analytical scores are secondary and clearly labelled.

Observed Techniques (ATT&CK, expert-tagged by source)

- T1053.005 Scheduled Task
- T1113 Screen Capture
- T1056.001 Keylogging
- T1566.002 Spearphishing Link
- T1082 System Information Discovery
- T1005 Data from Local System
- T1140 Deobfuscate/Decode Files or Information
- T1185 Browser Session Hijacking
- T1555.003 Credentials from Web Browsers
- T1083 File and Directory Discovery
- T1057 Process Discovery
- T1041 Exfiltration Over C2 Channel
- T1547.001 Registry Run Keys / Startup Folder
- T1055.012 Process Hollowing
- T1068 Exploitation for Privilege Escalation
- T1102.002 Bidirectional Communication

- T1203 Exploitation for Client Execution
- T1189 Drive-by Compromise
- T1071.001 Web Protocols
- T1105 Ingress Tool Transfer

Analytical Scores

- Priority technique (graph chokepoint): T1547.001 Registry Run Keys / Startup Folder (centrality 0.2846).
- Operational risk: Critical (score 0.968, reaches exfiltration).

Behavioral Signature Cluster

- Method: technique-overlap cosine vs 170 MITRE ATT&CK Groups (top overlap 0.5379; reference threshold $\tau = 0.6$).
- These are behavioural resemblances for defensive playbook cross-referencing, not an identity assessment. Where the source pulse names an actor, that attribution is authoritative; the overlaps below neither confirm nor contest it.

Nearest historical profiles by behavioural overlap (resemblance only):

Historical Profile	Behavioural Overlap
APT37	0.5379
Stealth Falcon	0.4336
Confucius	0.4286
APT39	0.4232
Inception	0.4213

Enrichment Signal

- Highest AbuseIPDB confidence among IOCs: 0%.

Indicators of Compromise (defanged — non-clickable)

The network and file indicators observed in this activity are listed below for blocklisting:

Type	Indicator	Context
IP	206[.]166[.]251[.]164	AbuseIPDB 0% (NL) · AS399629 BL Networks
Domain	msbenefit[.]com	

Type	Indicator	Context
Domain	gitprogram[.]com	
Domain	cloud[.]shinewrist[.]net	
Domain	document[.]gitprogram[.]com	
Domain	ocr[.]opusaccel[.]top	
Domain	photos[.]msbenefit[.]com	
Domain	proof[.]gitprogram[.]com	
Domain	xyz0102[.]gitprogram[.]com	
URL	hxxps://cloud[.]shinewrist[.]net/	
URL	hxxps://ocr[.]opusaccel[.]top	
URL	hxxps://photos[.]msbenefit[.]com/fa/t3	
URL	hxxps://photos[.]msbenefit[.]com/fb/w3z	
URL	hxxps://proof[.]gitprogram[.]com/a4/j8	
URL	hxxps://xyz0102[.]gitprogram[.]com/a001	
Hash	337b48c1cd6dd6e7b8073327082a60e149517fa084ba17b180e041ffa3b130d	
Hash	3b71d721c39fad92a44ddd764bbb34afeae44a5db886d0a4827a399a5fbd367f	
Hash	51462a23ac25e1bd0e49b7cae7f3a71f8d2201e22d45175b587e4740b49863cc	
Hash	56eda0ac82e06ee609b034306025e67df161c5877399c305c8eaea136e80c951	
Hash	5995f42a828606705a7339d58a665c229936e81c4e539cdfa115eb46a2eb53d6	

Type	Indicator	Context
Hash	59dc108e22cb856c228bbf8a1ab955fb66f0844a07fe10fa0d9fc3823d2cbbcb	
Hash	5eb5645511b00e4f4d73125654eeb3a3930fcf09c65685dc7f03f725331492e3	
Hash	69c1603f3f9015beb0097d0a3bb0f17400c314e2eae65a7eceacd3b93ea570dc	
Hash	7a52ff23949edee8faa61ce0def6dbca8b7e5943c54d23376cc190762ea3985c	
Hash	b7b0cd6539464ab39c6526e499f86d611faa21c5af945535ebaf187cec543af1	
Hash	cd0c21f9b32b7feeda1787fccab622dec60ecdf84c0538c08bde3946856b0fa0	
Hash	d17053557bb90298f7b115432b4820a248fdb678bca31721529b1f51a82343b	
Hash	e2a59432ce2b0d83ded936374a11fca3d3defaf4aab90eb37fca58683eae32c0	

Reputation by AbuseIPDB · malware attribution by abuse.ch · Geo/ASN data by IP2Location LITE.

Flame Cell // Adversary Pivot [BETA]

BETA. A hypothetical tabletop projection, anchored to documented ATT&CK behaviour and technique co-occurrence across 170 tracked groups. It is not a prediction; treat it as a war-game prompt and review before acting. Spot a pivot that looks wrong? norbert@salacti.com

- **Control applied:** T1547.001 Registry Run Keys / Startup Folder (persistence)
- **Observed here:** T1547.001 Registry Run Keys / Startup Folder was the only persistence technique observed in this campaign, so the pivot is projected from cross-actor behaviour.
- **Projected pivot:** T1543 Create or Modify System Process (persistence)
- **Basis:** of the 18+ groups that use Registry Run Keys / Startup Folder, this pairing runs 1.8x above base rate, a disproportionately-coupled move rather than the obvious one.

With T1547.001 Registry Run Keys / Startup Folder blocked, UTA0560, JungleBamboo could preserve the same objective by pivoting to T1543 Create or Modify System Process, a technique disproportionately paired with it across tracked groups. Defensive countermeasure: Restrict service/daemon creation to admins; monitor service and driver installs.

Also plausible (same tactic): T1098 Account Manipulation (n=12, lift 2.0), T1112 Modify Registry (n=17, lift 1.7)

Detection and hardening for the pivot (T1543 Create or Modify System Process)

- **Telemetry:** Windows Security / System log; Sysmon
- **Detect:**
 - System 7045 (new service installed); Security 4697 (service installed)
 - Sysmon 1 for sc.exe / services created; unusual ImagePath or user-context services
 - Registry writes under HKLM\SYSTEM\CurrentControlSet\Services
- **Harden:**
 - Restrict service creation to admins; application control on service binaries
 - Baseline installed services and alert on new/anomalous ones
- **MITRE:** M1047 Audit, M1028 Operating System Configuration, M1026 Privileged Account Management · DS0019 Service, DS0024 Windows Registry, DS0009 Process

