


THREAT REPORT: DJINN STEALER CAMPAIGN

EXPLOITS CVE-2026-48558


Visual Summary

Kill-Chain Reach — Critical (deepest phase reached: exfiltration)



How far down the attack chain this campaign reached; deepest phase in crimson.

Defensive Chokepoint — why this control is the priority



The control that most disrupts the attack (priority in crimson).

Summary

The observed cluster of activity is distributing the Djinn Stealer and TaskWeaver malware families. Both families leverage the recently disclosed CVE-2026-48558 vulnerability. Victims have not been identified in the source material. Priority should be given to removing secrets from code, configuration files, and the registry, deploying a secrets manager, scanning repositories and hosts for credentials, and patching CVE-2026-48558 on all affected systems.

Threat Overview

The observed cluster of activity employs the Djinn Stealer and TaskWeaver malware families to exploit CVE-2026-48558. No specific countries, sectors, or organizations have been identified as targets.

Attack Chain and Priority Control

The adversary begins with **File and Directory Discovery (T1083)** to locate valuable data, followed by **Process Discovery (T1057)** to understand the execution environment. It then performs **Data from Local System (T1005)** collection, archives the harvested data (**Archive Collected Data, T1560**), and extracts credentials stored in files (**Credentials In Files, T1552.001**). Collected data is encrypted using **Asymmetric Cryptography (T1573.002)** before being sent out via **Exfiltration Over C2 Channel (T1041)**.

Priority technique: T1552.001 Credentials In Files

Priority control (as stated in the source):

Remove secrets from code/config/registry; deploy a secrets manager; scan repos and hosts for credentials. In parallel, patch CVE-2026-48558 on all affected systems.

Infrastructure and Corroboration

Third-party enrichment indicates that the malicious command-and-control infrastructure is hosted by Evoxet Sdn. Bhd. (as reported in the source pulse). AbuseIPDB does not flag any of the associated indicators with a confidence level of 80 % or higher, and abuse.ch has not linked any additional malware families to this activity.

Technical Appendix

Ground-truth telemetry from the source pulse; analytical scores are secondary and clearly labelled.

Observed Techniques (ATT&CK, expert-tagged by source)

- T1005 Data from Local System
- T1560 Archive Collected Data
- T1083 File and Directory Discovery
- T1552.001 Credentials In Files
- T1057 Process Discovery
- T1041 Exfiltration Over C2 Channel
- T1573.002 Asymmetric Cryptography

Analytical Scores

- Priority technique (graph chokepoint): T1552.001 Credentials In Files (centrality 0.4789).
- Operational risk: Critical (score 0.864, reaches exfiltration).

Behavioral Signature Cluster

- Method: technique-overlap cosine vs 170 MITRE ATT&CK Groups (top overlap 0.3059; reference threshold $\tau = 0.6$).

- These are behavioural resemblances for defensive playbook cross-referencing, not an identity assessment. Where the source pulse names an actor, that attribution is authoritative; the overlaps below neither confirm nor contest it.

Nearest historical profiles by behavioural overlap (resemblance only):

Historical Profile	Behavioural Overlap
Stealth Falcon	0.3059
RedCurl	0.3012
APT3	0.2809
Windigo	0.252
MuddyWater	0.2407

Enrichment Signal

- Highest AbuseIPDB confidence among IOCs: 0%.

Indicators of Compromise (defanged — non-clickable)

The network and file indicators observed in this activity are listed below for blocklisting:

Type	Indicator	Context
IP	96[.]126[.]130[.]126	AbuseIPDB 0% (JP) · AS149440 Evoxit Sdn. Bhd.
Hash	f4a72600a3735c2a4d843875ea61bbb6f935a1af51a81f2fbc992ce11ba94afc	

Reputation by AbuseIPDB · malware attribution by abuse.ch · Geo/ASN data by IP2Location LITE.

Flame Cell // Adversary Pivot [BETA]

BETA. A hypothetical tabletop projection, anchored to documented ATT&CK behaviour and technique co-occurrence across 170 tracked groups. It is not a prediction; treat it as a war-game prompt and review before acting. Spot a pivot that looks wrong? norbert@salacti.com

- **Control applied:** T1552.001 Credentials In Files (credential-access)
- **Observed here:** T1552.001 Credentials In Files was the only credential-access technique observed in this campaign, so the pivot is projected from cross-actor behaviour.
- **Projected pivot:** T1555 Credentials from Password Stores (credential-access)
- **Basis:** of the 15+ groups that use Credentials In Files, this pairing runs 3.5x above base rate, a disproportionately-coupled move rather than the obvious one.

With T1552.001 Credentials In Files blocked, the threat actor could preserve the same objective by pivoting to T1555 Credentials from Password Stores, a technique disproportionately paired with it across tracked groups. Defensive countermeasure: Restrict access to browser/OS credential stores; alert on credential-vault access; enforce disk encryption.

Also plausible (same tactic): T1003 OS Credential Dumping (n=18, lift 2.5), T1556 Modify Authentication Process (n=4, lift 4.0)

Detection and hardening for the pivot (T1555 Credentials from Password Stores)

- **Telemetry:** Sysmon (file/process); EDR
- **Detect:**
 - Access to browser credential stores (Login Data) and DPAPI master keys
 - Reads of password-manager vaults or Windows Credential Manager
 - Non-browser processes touching browser profile directories
- **Harden:**
 - Enterprise password manager with hardware-backed keys
 - EDR rules on credential-store access; disable browser password saving via policy
- **MITRE:** M1043 Credential Access Protection, M1027 Password Policies · DS0009 Process, DS0022 File