

# Do weather changes matter?

Marc Los Huertos

July 1, 2016

## 1 Introduction

According to the IPCC, the temperature has been changing about 0.X degrees per XX years – but how do these changes “map” onto a community that you care about? Can we find out how these changes will affect specific communities we care about? In other words, do weather changes matter to you?

### 1.1 Learning Goals

For this project, you will use weather station data to answer the questions above. How you answer the question is largely up to you, however, there are some learning goals associated with this project:

- Learn how to download and process weather data;
- Evaluate the trends in weather data;
- Determine the impact of weather in a human or non-human community; and
- Communicate your conclusions to the public.

### 1.2 Driving Question

Is my region’s climate changing?

How is climate change affecting my community?

### 1.3 Public Product

Narrative Blog...

with professional graphics and statistics.

shiny apps

## 1.4 Approach

Students will have the following tools available.

- NOAA website where data can be downloaded...
- R Studio Server with some scripts to help you develop analyses.
- Github to store project codes
- Shiny app templates that might be used as a container for interactive content

## 2 Project Stages (i.e. Scaffolding)

### 2.1 Day 1: How is temperature data collected?

#### 2.1.1 Land Based

#### 2.1.2 Marine Based

### 2.2 Day 2: How are the data store, curated and checked for quality?

## 3 Data 3: Data Sources

### 3.1 NOAA

### 3.2 Others

### 3.3 File Types and Software Tools

## 4 Using RStudio

### 4.1 Why R, Why Rstudio, and Why Open Source

Excel was not designed to handle large datasets, i.e. over 1 million rows. For most purposes, this might be enough. However, in many climate science data often exceed this number of samples.

## 5 R Coding an Analysis

```
library(tidyr)
library(dplyr)
```

```
##
## Attaching package: 'dplyr'
##
## The following objects are masked from 'package:stats':
##
##   filter, lag
##
## The following objects are masked from 'package:base':
##
##   intersect, setdiff, setequal, union

library(stringr)
library(reshape2)
source("summarySE.R")
```

```
# Uncompress the files.
# ghcnd_all
```

```
stationfile = "/home/CAMPUS/mw104747/github/Climate_Change_Narratives/Data/ghcnd-stations.txt"
```

## 5.1 Read Station Data into R

```
# read.table(stationfile, header=F, fill=T, row.names=NULL); head(stations)
stations = (read.fwf(stationfile, fill=T, widths= c(11, 9, 10, 7, 3, 32, 3, 4, 9), ))
names(stations)= c("ID", "LAT", "LONG", "ELEV", "STATE", "NAME", "GSN", "HCN_CRN", "WHOID")

head(stations)
```

	ID	LAT	LONG	ELEV	STATE				
## 1	ACW00011604	17.1167	-61.7833	10.1					
## 2	ACW00011647	17.1333	-61.7833	19.2					
## 3	AE000041196	25.3330	55.5170	34.0					
## 4	AEM00041194	25.2550	55.3640	10.4					
## 5	AEM00041217	24.4330	54.6510	26.8					
## 6	AEM00041218	24.2620	55.6090	264.9					
##						NAME	GSN	HCN_CRN	WHOID
## 1	ST JOHNS COOLIDGE FLD								NA
## 2	ST JOHNS								NA
## 3	SHARJAH INTER. AIRP						GSN		41196
## 4	DUBAI INTL								41194
## 5	ABU DHABI INTL								41217
## 6	AL AIN INTL								41218

Example of data:

AG000060680 22.8000 5.4331 1362.0 TAMANRASSET GSN 60680

## 5.2 Selecting and Example Location

Here's what the data look like:

ID 1-11 Character YEAR 12-15 Integer MONTH 16-17 Integer ELEMENT  
18-21 Character VALUE1 22-26 Integer MFLAG1 27-27 Character QFLAG1 28-  
28 Character SFLAG1 29-29 Character VALUE2 30-34 Integer MFLAG2 35-35  
Character QFLAG2 36-36 Character SFLAG2 37-37 Character . . . . .  
. VALUE31 262-266 Integer MFLAG31 267-267 Character QFLAG31 268-268  
Character SFLAG31 269-269 Character

Here's an example of data from Arizona...

```
stations[stations$ID=="US1AZMR0019",]  
  
##           ID      LAT      LONG  ELEV STATE  
## 48124 US1AZMR0019 33.5902 -111.9712 418.5    AZ  
##                                     NAME GSN HCN_CRN WHOID  
## 48124  SCOTTSDALE 8.8 SW                                     NA  
  
# head(stations[stations$HCN_CRN==" CRN",])
```

Let's get the a different site into R

I often forget how to make loops, so I often use simple examples that help me remember, for example,

```
# practicing loops  
for (year in c(2010,2011,2012,2013,2014,2015)){  
  print(paste("The year is", year))  
}  
  
## [1] "The year is 2010"  
## [1] "The year is 2011"  
## [1] "The year is 2012"  
## [1] "The year is 2013"  
## [1] "The year is 2014"  
## [1] "The year is 2015"
```

Since the data have a re-occurring set of variable names, I decided to create a vector of variable names, many of which are nearly the same. So, as you'll see, I had to create a loop to avoid having to type a ton (or 31 :-)) of different variables.

```
# Create New Variable Names  
MFLAG=NA; QFLAG=NA; SFLAG=NA; VALUE=NA
```

```

for (i in 1:31){
  VALUE[i] = paste("DATE", i, sep="")
  MFLAG[i] = paste("MFLAG", i, sep="")
  QFLAG[i] = paste("QFLAG", i, sep="")
  SFLAG[i] = paste("SFLAG", i, sep="")
}

# Vector of variable names converted from a transposed matrix
tmp = as.vector(t(matrix(data=c(VALUE, MFLAG, QFLAG, SFLAG), ncol=4)))
Names = c("ID", "YEAR", "MONTH", "ELEMENT", tmp); length(Names)

## [1] 128

```

### 5.3 Process Selected Data Files

```

setwd("/home/CAMPUS/mw104747/github/Climate_Change_Narratives/Data")

dly_list = list.files(pattern="*.dly"); head(dly_list)

## [1] "AGM00060515.dly" "US1AZCN0021.dly"

#for (i in 1:length(dly_list))
for (i in 1:1){
  tmp <- read.fwf(dly_list[i], widths = c(11, 4, 2, 4, rep(c(5, 1, 1, 1),31)))
  names(tmp) <- Names
  assign(dly_list[i], subset(tmp, ELEMENT=="TMAX", select=c(1:4, seq(5, by = 4, length.out=31))))
}

tmp1 = melt(AGM00060515.dly, id=c("ID", "YEAR", "MONTH", "ELEMENT"))
head(tmp1)

##           ID YEAR MONTH ELEMENT variable value
## 1 AGM00060515 1984      3      TMAX      DATE1 -9999
## 2 AGM00060515 1984      4      TMAX      DATE1   190
## 3 AGM00060515 1984      5      TMAX      DATE1 -9999
## 4 AGM00060515 1984      6      TMAX      DATE1 -9999
## 5 AGM00060515 1984      7      TMAX      DATE1   430
## 6 AGM00060515 1984      8      TMAX      DATE1 -9999

tmp1$Day = as.numeric(str_sub(tmp1$variable,6,7)); head(tmp1)

##           ID YEAR MONTH ELEMENT variable value Day
## 1 AGM00060515 1984      3      TMAX      DATE1 -9999 NA
## 2 AGM00060515 1984      4      TMAX      DATE1   190 NA

```

```
## 3 AGM00060515 1984      5      TMAX      DATE1 -9999 NA
## 4 AGM00060515 1984      6      TMAX      DATE1 -9999 NA
## 5 AGM00060515 1984      7      TMAX      DATE1  430 NA
## 6 AGM00060515 1984      8      TMAX      DATE1 -9999 NA

tmp1$value[tmp1$value==-9999] = NA; head(tmp1)

##           ID YEAR MONTH ELEMENT variable value Day
## 1 AGM00060515 1984      3      TMAX      DATE1    NA NA
## 2 AGM00060515 1984      4      TMAX      DATE1   190 NA
## 3 AGM00060515 1984      5      TMAX      DATE1    NA NA
## 4 AGM00060515 1984      6      TMAX      DATE1    NA NA
## 5 AGM00060515 1984      7      TMAX      DATE1   430 NA
## 6 AGM00060515 1984      8      TMAX      DATE1    NA NA

tmp1$Temperature = tmp1$value/10

drops <- c("variable","value")
tmp1 <-tmp1[ , !(names(tmp1) %in% drops)]
tmp1$DECADE = round(tmp1$YEAR, -1)
# names(tmp1)
```

## 6 Presenting the Results


```
# call summarySE function....somehow...

library(ggplot2)

summarydf <- summarySE(tmp1, "Temperature", "DECADE", na.rm=T)

## -----
## You have loaded plyr after dplyr - this is likely to cause problems.
## If you need functions from both plyr and dplyr, please load plyr
## first, then dplyr:
## library(plyr); library(dplyr)
## -----
##
## Attaching package: 'plyr'
##
## The following objects are masked from 'package:dplyr':
##
##   arrange, count, desc, failwith, id, mutate, rename, summarise,
##   summarize
```

```
ggplot(summarydf, aes(y=Temperature, x=DECADE, color= DECADE)) + geom_errorbar(aes(ymin=Temp
```



## 6.1 NOAA dataset

New NOAA Directory – <ftp://ftp.ncdc.noaa.gov/pub/data/noaa/>

```
library(raster)

## Loading required package: sp
##
## Attaching package: 'raster'
##
## The following object is masked from 'package:dplyr':
##
##   select
##
```

```

## The following object is masked from 'package:tidyr':
##
##      extract

library(XML)

coords.fwt <- read.fwf("ftp://ftp.ncdc.noaa.gov/pub/data/noaa/isd-history.txt",widths=c(6,1,
Names = c("USAF", "X1", "WBAN", "X2", "STATION_NAME", "X3", "CTRY", "X4", "ST", "X5", "CALL
Widths = c(6,      1,      5,      1,      29,      1,      2,      3,      2,      1,      4,

coords.fwt <- read.fwf("ftp://ftp.ncdc.noaa.gov/pub/data/noaa/isd-history.txt",widths=Widths

X4 ST X5

IA

ND
04
27
29

coords <- data.frame(ID=paste(as.factor(coords.fwt[,1])),WBAN=paste(as.factor(coords.fwt[,3]

## Warning in data.frame(ID = paste(as.factor(coords.fwt[, 1])), WBAN
= paste(as.factor(coords.fwt[, : NAs introduced by coercion
## Warning in data.frame(ID = paste(as.factor(coords.fwt[, 1])), WBAN
= paste(as.factor(coords.fwt[, : NAs introduced by coercion

```

### NOAA Locations

```

plot(Lat ~ Lon, data=coords, xlim=c(-180, 180) )

```



