

04_ Introduction to Constrained Systems

Invariance

Conceptions

Conditions of Invariant Set

Computation of Invariant Set

Control Invariance

Conceptions

Conditions of Controlled Invariant Set

Computation of Controlled Invariant Set

Control Invariant Set and Control Law

Polytopes and Polytopic Computation

Conceptions

Polytopes in MPC

Input Saturation

Magnitude Constraints

Rate Constraints

Integral Constraints

Computation of Pre-Set

Autonomous Systems

Controlled Systems

Equality Test

Convergence Discussion

Ellipsoids and Invariance

Summary

Invariance

Conceptions

::: definition

Invariance:

Region in which an **autonomous** system will satisfy the constraints

for all time

:::

::: definition

Positive Invariant Set:

A set \mathcal{O} is said to be a **positive invariant set** for the

autonomous system $x_{i+1} = f(x_i)$ if

$x_i \in \mathcal{O} \Rightarrow x_i \in \mathcal{O}, \forall i \in \{0, 1, \dots\}$

:::

Notes: The invariant set provides a set of **initial states** from which the trajectory will **never violate** the system constraints.

::: definition

Maximal Positive Invariant Set The set

$\mathcal{O}_\infty \subset \mathbb{X}$ is the **maximal invariant set** with respect to \mathbb{X} if $0 \in \mathcal{O}_\infty$.

\mathcal{O}_{∞} is invariant and \mathcal{O}_{∞} contains all invariant sets that contain the origin.

...

Notes: The maximal invariant set is the set of all states for which the system will remain feasible if it starts in \mathcal{O}_{∞} .

... definition

Preset: Given a set S and the dynamic system $x^{+}=f(x)$, the pre-set of S is the set of states that evolve into the target set S in one time step: $\text{pre}(S):=\{x \mid f(x) \in S\}$

...

Conditions of Invariant Set

A set \mathcal{O} is a positive invariant set **if and only if**
 $\mathcal{O} \subset \text{pre}(\mathcal{O})$

Computation of Invariant Set

Notes: The algorithm generates the set sequence

$\{\Omega_i\}_{i=0}^{\infty}$ satisfying

$\Omega_{i+1} \subseteq \Omega_i$ for all $i \in \mathbb{N}$ and it terminates when $\Omega_{i+1} = \Omega_i$ so that Ω_i is the maximal positive invariant set \mathcal{O}_{∞} for $x^{+}=f(x)$.

Control Invariance

Conceptions

... definition

Controlled Invariance:

Region for which there **exists** a controller so that the system satisfies the constraints for all time

...

... definition

Control Invariant Set: A set $\mathcal{C} \subseteq \mathbb{X}$ is said to be a control invariant set if

$x_i \in \mathcal{C} \Rightarrow \exists u_i \in \mathbb{U} \text{ such that } f(x_i, u_i) \in \mathcal{C} \text{ for all } i \in \mathbb{N}^{+}$

...

... definition

Maximal Control Invariant Set:

The set \mathcal{C}_{∞} is said to be the maximal control invariant set for the system $x^{+}=f(x, u)$ subject to the constraints $(x, u) \in \mathbb{X} \times \mathbb{U}$ if it is control invariant and contains all control invariant sets contained in \mathbb{X} .

...

::: definition

Preset:

$\operatorname{pre}(S) := \{x \mid \exists u \in \mathbb{U} \text{ s.t. } f(x, u) \in S\}$

:::

Conditions of Controlled Invariant Set

A set C is a positive invariant set **if and only if**

$C \subseteq \operatorname{pre}(C)$

Computation of Controlled Invariant Set

Control Invariant Set and Control Law

Polytopes and Polytopic Computation

Conceptions

::: definition

Convex Hull For any subset S of \mathbb{R}^d , the convex hull $\operatorname{conv}(S)$ of S is the intersection of all convex sets containing S .

Since the intersection of two convex sets is convex, it is the smallest convex set containing S .

:::

::: theorem

Minkowski-Weyl Theorem For $P \subseteq \mathbb{R}^d$, the following statements are equivalent:

- **P is a polytope, i.e., P is bounded and there exist $A \in \mathbb{R}^{m \times d}$ and $b \in \mathbb{R}^m$ such that $P = \{x \mid Ax \leq b\}$**
- **P is finitely generated, i.e., there exist a finite set of vectors $\{v_i\}$ such that $P = \operatorname{conv}(\{v_1, \dots, v_s\})$**

:::

::: definition

The intersection $I \subseteq \mathbb{R}^n$ of sets

$S \subseteq \mathbb{R}^n$ and $T \subseteq \mathbb{R}^n$ is

$I = S \cap T := \{x \mid x \in S \text{ and } x \in T\}$

:::

Notes: Intersection of polytopes in inequality form is easy:

$\begin{aligned}$

$\&S := \{x \mid Cx \leq c\} \setminus$

$\&T := \{x \mid Dx \leq d\}$

$\end{aligned} \quad S \cap T = \left\{x \mid \begin{bmatrix} C \\ D \end{bmatrix} x \leq \begin{bmatrix} c \\ d \end{bmatrix}\right\}$

$C \setminus$

D

```

\end{array}\right] x \leq \left[\begin{array}{l}
c \\
d
\end{array}\right]\right\}

```

::: definition

polytopic projection Given a polytope

$P = \left\{ (x, y) \in \mathbb{R}^n \times \mathbb{R}^d \mid Cx + Dy \leq b \right\}$,

find a matrix E and vector e , such that the polytope

$P_{\pi} = \{x \mid Ex \leq e\} = \{x \mid \exists y, (x, y) \in P\}$

:::

Polytopes in MPC

Input Saturation

```

\begin{gathered}
u_{\{l \ b\}} \leq u \leq u^{\{u \ b\}} \\
\Downarrow \\
\left[\begin{array}{c}
1 \\
-1
\end{array}\right] u \leq \left[\begin{array}{c}
c
\end{array}\right] \\
u^{\{u \ b\}} \\
-u_{\{l \ b\}} \\
\end{array}\right]
\end{gathered}

```

Magnitude Constraints

```

\begin{gathered}
\|C x\|_{\infty} \leq \alpha \\
\Downarrow \\
\left[\begin{array}{c}
c
\end{array}\right] \\
C \\
-C \\
\end{array}\right] x \leq 1 \ \alpha
\end{gathered}

```

Rate Constraints

```

\begin{gathered}
\left\|x_{\{i\}} - x_{\{i+1\}}\right\|_{\infty} \leq \alpha \\
\Downarrow \\
\left[\begin{array}{cc}
1 & -1 \\
-1 & 1
\end{array}\right] \left[\begin{array}{c}
x_{\{i\}} \\
x_{\{i+1\}}
\end{array}\right]

```

```
\end{array}\right) \leq \mathbf{1} \alpha\}
\end{gathered}
```

Integral Constraints

```
\begin{gathered}
|x|_1 \leq \alpha \\
\Downarrow \\
x \in \operatorname{conv}\left(e_i \alpha\right)
\end{gathered}
```

Computation of Pre-Set

Autonomous Systems

```
::: method
If  $S := \{x \mid F x \leq f\}$ , then
 $\operatorname{pre}(S) = \{x \mid F A x \leq f\}$ 
:::
```

Controlled Systems

Consider the system $x^+ = A x + B u$ under the constraints

$u \in \mathbb{U} := \{u \mid G u \leq g\}$ and the set

$S := \{x \mid F x \leq f\}$. $\begin{aligned}$

$\operatorname{pre}(S) = \{x \mid \exists u \in \mathbb{U}, A x + B u \in S\}$

$= \{x \mid \exists u \in \mathbb{U}, F A x + F B u \leq f\}$

$= \left\{x \mid \exists u, \begin{bmatrix} F A & F B \\ 0 & G \end{bmatrix} \begin{bmatrix} x \\ u \end{bmatrix} \leq \begin{bmatrix} f \\ g \end{bmatrix} \right\}$

$\begin{aligned}$

$\end{aligned}$

Notes: this is actually a projection operation.

Equality Test

One important problem is how to check whether two set are the same? i.e.

Is $P := \{x \mid C x \leq c\}$ contained in $Q := \{x \mid D x \leq d\}$?.

The statement is true if $P \subset \{x \mid D_{ix} < d_i\}$ for each row D_i of D .

Define the support function of the set P : $\begin{aligned}$

$h_P(D_i) = \max_{x \in P} D_i x$

$\& \text{ s.t. } C x \leq c$

$\end{aligned}$

if $h_p(D_1) \leq d_1$, then it is true, if not, it is false.

Notes: Do not try to translate to straight line representation. It can be directly understood by the definition of Q , if the false case happens, it means at least one of the constraints in Q is violated, because we use Q as \leq format.

Convergence Discussion

Another problem is: Does the invariant set algorithm guarantee finite step termination?

In general, **no!** The boundary of the maximal invariant set can be curvy, which needs infinite many half-spaces to define. In practice, to save memory and to ensure efficiency, the algorithm stops up to some **specific criteria or we use simpler convex set (i.e. box, ellipsoid)** to represent a smaller forward invariant set.

Ellipsoids and Invariance

Summary

This chapter introduces the content of invariant sets and controlled invariant sets and the methods to compute them.