

PLASTIC PACKAGE ULTRA MINIATURE PURE SILICON™ CLOCK OSCILLATORS

ASDM

Request Samples



Check Inventory



ESD Sensitive



2.5 x 2.0 x 0.85 mm

RoHS/RoHS II Compliant

MSL Level = 1

Features

- Low Power Consumption
- Exceptional Stability Over Temp. at -40°C to +85°C
- Low Cost-Compact QFN Plastic Packaging
- Compact Package design

Applications

- CCD Clock for VTR Camera
- Equipment Connected to PCs
- Low Profile Equipment
- Computers and Peripherals
- Portable Electronics
- Consumer Electronics
- Vibrant, Shock-Prone & Humid Environments for Industrial Equipment
- Demanding Military & Automotive Electronics

Common Key Electrical Specifications

Parameters		Min.	Typ.	Max.	Units	Notes
Frequency Range:		1.0		150	MHz	
Operating Temperature:		0		+70	°C	See options
Storage Temperature:		-55		+150	°C	
Supply Voltage (Vdd):		+1.8 ~ +3.3			V	See options
Supply Current (no load):	1.0 to 39.9999MHz		7	15	mA	Vdd=3.3V No load RL=∞ T=25°C
	40.0 to 79.9999MHz		8	15		
	80.0 to 124.9999MHz		9	15		
	125.0 to 150MHz		10	15		
Output Voltage:	V _{OH}	0.8*V _{dd}			V	15pF
	V _{OL}			0.2*V _{dd}		
Rise Time:	Tr		1.3	3.0	ns	15pF; T=25°C 20%/80%*VDD
Fall Time:	Tf		1.3	3.0		
Output Load:		15pF max / 10kΩ min.			pF	
Symmetry:		45		55	%	@1/2Vdd
Startup Time:			1.5	3.0	ms	
Disable Time:			20	100	ns	
Disable Stand-by Current:				15	uA	
Tri-state Function (Stand-by) :		"1" (VIH≥0.75*Vdd) or Open: Oscillation "0" (VIH<0.25*Vdd) : Hi Z			V	
Cycle to cycle jitter:			60		ps	F=100MHz
Aging:		-5.0		+5.0	ppm	First year



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 09-21-23

ABRACON IS
ISO9001-2015
CERTIFIED

PLASTIC PACKAGE ULTRA MINIATURE PURE SILICON™ CLOCK OSCILLATORS

ASDM

Request Samples



Check Inventory



ESD Sensitive



2.5 x 2.0 x 0.85 mm

RoHS/RoHS II Compliant

MSL Level = 1

Absolute Maximum Ratings

Item	Min.	Max.	Units	Condition
Supply Voltage	-0.3	+4.0	V	
Input Voltage	-0.3	Vdd+0.3	V	
Junction Temp.		+150	°C	
Storage Temp.	-55	+150	°C	
Soldering Temp.		+260	°C	40sec max
ESD			V	
HBM		2,000		
MM		200		
CDM		500		

PLASTIC PACKAGE ULTRA MINIATURE PURE SILICON™ CLOCK OSCILLATORS

ASDM

Request Samples 

Check Inventory 

 ESD Sensitive 

2.5 x 2.0 x 0.85 mm
RoHS/RoHS II Compliant
MSL Level = 1

Options and Part Identification (left blank if standard)

ASDM - MHz - -

Supply Voltage
1: 3.3 ± 0.3V
2: 3.0 ± 0.3V
3: 2.5 ± 0.2V
4: 1.8 ± 0.15V
5: 2.8 ± 0.2V

Frequency in MHz
e.g. 14.3181 MHz (Maximum 4 digits after decimal)

Operating Temp.
Blank: 0°C ~ +70°C
E: -20°C ~ +70°C
L: -40°C ~ +85°C

Overall Freq. Stability
Blank: ±100ppm
R: ±25ppm
C: ±50ppm

Packaging
Blank: 140pcs / Tube
T: 1,000pcs / reel

PLASTIC PACKAGE ULTRA MINIATURE PURE SILICON™ CLOCK OSCILLATORS

ASDM

Request Samples



Check Inventory



ESD Sensitive




2.5 x 2.0 x 0.85 mm


RoHS/RoHS II Compliant

MSL Level = 1

Mechanical Dimensions



Recommended Land Pattern



Note: Recommend using an approximately 0.01uF bypass capacitor between PIN 2 and 4.

Dimensions: mm(inches)

PLASTIC PACKAGE ULTRA MINIATURE PURE SILICON™ CLOCK OSCILLATORS

ASDM

Request Samples



Check Inventory



ESD Sensitive



2.5 x 2.0 x 0.85 mm

RoHS/RoHS II Compliant

MSL Level = 1

Reflow Profile [JEDEC J-STD-020]




Table 1

SnPb Eutectic Process

Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2

Pb-Free Process

Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm - 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum (T_{smin})	100°C	150°C
Temperature maximum (T_{smax})	150°C	200°C
Time (T_{smin} to T_{smax}) (t_s)	60 - 120 sec.	60 - 120 sec.
Average ramp-up rate (T_{smax} to T_p)	3°C/sec. max	3°C/sec. max
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60 - 150 sec.	60 - 150 sec.
Peak package body temperature (T_p)*	see Table 1	see Table 2
Time (t_p)** within 5°C of the specified classification temperature (T_c)	20 sec.	30 sec.
Ramp-down rate (T_p to T_{smax})	6°C/sec. max	6°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max
Reflow cycles	2 max	2 max

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

**Tolerance for time at peak profile temperature (t_p) is defined as supplier minimum and a user maximum.

PLASTIC PACKAGE ULTRA MINIATURE PURE SILICON™ CLOCK OSCILLATORS

ASDM

Request Samples



Check Inventory



ESD Sensitive




2.5 x 2.0 x 0.85 mm

RoHS/RoHS II Compliant

MSL Level = 1

Packaging

T= 1,000pcs/reel (D=180mm)



Dimensions: mm

ATTENTION: Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.



5101 Hidden Creek Ln Spicewood TX 78669
 Phone: 512-371-6159 | Fax: 512-351-8858
 For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 09-21-23

ABRACON IS
 ISO9001-2015
 CERTIFIED

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

[ASDM1-27.000MHZ-LC-T](#) [ASDM1-24.576MHZ-LC-T](#) [ASDM1-12.000MHZ-LC-T](#) [ASDM1-29.4912MHZ-LC-T](#) [ASDM1-80.000MHZ-LC-T](#) [ASDM1-60.000MHZ-LC-T](#) [ASDM1-25.000MHZ-LC-T](#) [ASDM1-10.000MHZ-LC-T](#) [ASDM1-4.000MHZ-LC-T](#) [ASDM1-33.000MHZ-LC-T](#) [ASDM1-33.333MHZ-LC-T](#) [ASDM1-11.0592MHZ-LC-T](#) [ASDM1-7.3728MHZ-LC-T](#) [ASDM1-24.000MHZ-LC-T](#) [ASDM1-16.000MHZ-LC-T](#) [ASDM1-30.000MHZ-LC-T](#) [ASDM1-14.7456MHZ-LC-T](#) [ASDM1-1.8432MHZ-LC-T](#) [ASDM1-8.000MHZ-LC-T](#) [ASDM1-48.000MHZ-LC-T](#) [ASDM1-100.000MHZ-LC-T](#) [ASDM1-44.000MHZ-LC-T](#) [ASDM1-50.000MHZ-LC-T](#) [ASDM1-14.31818MHZ-LC-T](#) [ASDM1-32.000MHZ-LC-T](#) [ASDM1-20.000MHZ-LC-T](#) [ASDM1-18.432MHZ-LC-T](#) [ASDM1-60.000MHZ-LR-T](#) [ASEM1-40.000MHZ-LC-T](#) [ASDM4-26.000MHZ-LR](#) [ASDM4-26.000MHZ-LR-T](#) [ASDM1-12.288MHZ-LC-T](#) [ASDM1-40.000MHZ-LC-T](#) [ASDM1-25.0000MHZ-LC-T](#)