TUNNEL TEMPERATURE TESTS

TUNNEL TEMPERATURE TESTS	SINGLE IMPULSE FAN OPERATION CHECK		23 23.1 '2 53 27.2 'C 53 24.7 'C 53 55.1 'C 53 37.2 'S 53 57. C 53 25.7 'S 53 55.7 'S 53	Fig. 12 Fig. 1	73 42 °C   58 26 42 °C   58 26 42 °C   50 4 40 5 °C   50 4 60 5 °C	2/35	53 33.4 °C (34 30.3 °C (11,1 25 °C (1),1 25 °C	SE 34-S .C NOTES - * OSCULATING BETWEEN 42°C AND 54°C	TEMPERATURE / SENSOR ARAKY
	1	- 1	60 0	-1	S. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.	33 25 9 C 33 25 9 C 35 25 C 35	1		54 31 °C d TE

### TEMPERATURE DISTRIBUTION

SINGLE IMPLIES FAN OFFRATION CHECK

TEST: MIS- / AR

TIME: 15:00

ないのので NO. (v) 13 35.0°C 1 NOTES - OSCILLATING MITHIN THE ري 17:02 スなる 20 100 0. <u>در</u> CD3 ;; (u) ?; , () DB 32.6°C 26.00 82  $\cup$ <u>.</u> 11. J (1) (1) 0334.4°C 773 28. 4°C 31.5 FH 63 × 83 78 8 0 90 57 70 8 ò." OB 33. 6 'C WB 28.4°C 3H 68 TEMPERATURE SENSOR ARRAY ON CAR I 39.4.0 6E 35.4°C 78 48 4 °C 178 45.8°C è. 28.8°C 25.1°C 53 00 (1) (2) W.O. 3.41.9°C 33 3.05 M/S 0.55.2° 3.52.0° U · 63 33.9 54 33.4 50 36.7 23,26.0°d WEST CONTRACTOR 1. 51.0°C なうしゃ

					.! () () ()			
	CHECK				=* 0	23.0		
. NOITO	OPERATION		VI .		. O		- 255 -	
JRE DISTRIBUTION	E FON				0 0 0	65 N	9	
TEMPERATURE	MPULSE			25.2	2 C C C C C C C C C C C C C C C C C C C	7.7 	SE 31.0 °C	TEMPERATURE TABLET CARTE
	DOUBLE		283	23 ZT.0 '2 ZZ-5 '2 T. 57.5 '2	75 52.00	8	(a)	1 0
	- 1B	16:00			10 00 00 00 00 00 00 00 00 00 00 00 00 0	1	1	3 6
8	TEST: MIS-	TIME: /	×	i.i.(	5.0 6.3 7.1 7.0 7.0 7.0	0.	53 29 2	5. 29.9
							T.	

TUNNEL TEMPERATURE

TEMPERATURE DISTRIBUTION

DOUBLE IMPULSE FAN OPERATION CHE

TEST: MIS- 18

Ýų.


TIME: 16:25

11. 5. V. O. S. TA 25.0 104 55.0 to 13 20.50 °C. 30 SG 03 8839.73 20.022.00 2775 コモルアとスインウェ 63 34.0 °C SE 31.2 2.5.95 = 67.0 % は一次には 33 4.60 375 154.55.1°C 3 28.5° 5. 1.05 kg C 53 30.1 °C 23 26.0°C 23.28.2° 17 0 17 0 17 0 17 0 20 4.50.0°C

TESTS
TEMPERATURE

## TEMPERATURE DISTRIBUTION

CHECK	,
PERFORMANCE	
AIR CONDITIONER	
TRAIN	
TEST: MIS- 2	TIME: 14:55




TEST: MIS- 2 R TIME: 16:20

AIR CONDITIONER PERFORMANCE TRAIN

03 848 0

0.87.69

10.88




TRAIN AIR CONDITIONER PERFORMANCE TEST: MIS- 2 R 16:20 TIME

CB 8458 C TENTETATURE 7.67.23 13.4.60 1 33 0 1 5,5 54.15.50 51.26.2 '0 Ö ,co 64 35.1 50 36.4 27 1 GO 1 42 · (1) ပ္ပ

- FO - O
- FMPEXALORE
TONNEL

TEMPERATURE DISTRIBUTION

YOOK	
POWER C	
PRACTION,	
SOFI	
SOY.	
30	1:05
TEST: MIS-	TIME: 13



50 28-50 CS

63 28-50 C

63 28-50 C

64 28-50 C

65 28

P.06 41

11496.5 OF TRACTION POWER CHECK 38 & A. G. C. . . . . . . . . . . . . ر) TUNNEL TEMPERATURE TESTS TEMPERATURE DISTRIBUTION 5. 8.9 E E3 0:10 50 30.1.0 0.9768 2 808 2 o. 0.9 8 es 60 48.5 7281.95 50,000 3 子os 80 000 de 00 a-S.4 #1/5 22.28.50 3. 26.80 [][]制 N N 2.0.87 29 12: FST: MIS-23 25.5°C TIME: E.√S S.⊹S

i,

TEMPERATURE

6E 28.5°C

53 78 ES

5A 28.5°C

TEMPERATURE DISTRIBUTION

LOSS OF TRACTION POWER IMPULSE FANS 7600 TEST: MIS- 3 B (d: 25 .. ||X||

 $\bigcirc$ \$2.50 り, 0 まか。 問

0743 0:40 2.8.9.0 73 29.0.0 に の い い い い い い 33 4.654/5 5.0.12.5 5.0.12.5 5C 47. 2.0.978

BRUTARBANDIA

O

9-26 83

							*						
						, i	gar) K s <sub>S</sub> ∩	- 1			::	] ; ·	
*		3	六				i(' '72,	1.3	i		[]		1
			TRACTION POWER CHECK									1!!	
	M		示ス				\	<b>\</b>			1:11	H k l	
	15 1-S		POW						iti		L	:-	
	田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田	RIBUTIC	20	FANS			10 col col	0		-	[]    []		i -
	RAT	DISTE	9071	-6-				. 2	1	į		j]	i
*	TEMPERATURE TESTS	TEMPERATURE DISTRIBUTION	T.R.	TWO IMPULSE			,6 : SO						4 (8/4)
		MPER/	O T	1848			(A)	-6	\S\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\			1.1-	
	TUNNEL	m	LOSS OF	, OQ					:"			. [.]	5
38	{	#* **-	7	1			9 / 0		63				5 5 5
	9		. ]	- 1	24		\\ \text{\tint{\text{\tin}\\ \text{\texi}\\ \text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\texi}\text{\text{\texi}\text{\text{\text{\text{\texi}\text{\text{\texi}\text{\text{\texi}\text{\text{\text{\tex{\text{\text{\text{\text{\text{\texi}\text{\texi}\text{\tex	S	Ċ.		5		
			BR	2						-			
	1	s <u>*</u>	S-3	3:05							1)	اد جا د	
		2)	TEST: MIS- 3BR	TIME: /					10 to				
	20		   [1]	1-				#2	1,0	;	1	°.	
16					1167				a a	3	<i>8</i> ,		

5 00 10 10 10 .0 0. Th 15 35 71-4 3 THE STATES OF THE PERSON OF TH . 7. 28 45.60 33 5. 4 WG ÷ €7,6 39 5. 28.5 53 78.2 2,0.67.5

TEMPERATURE

	50	
•		
7.		

TEST: MIS- 3 BR KOSS OF TRACTION POWER CHECK -	TWO IMPULSE FANS	11NE SOURCE 10 09 2 00 00 00 00 00 00 00 00 00 00 00 00 0		2 78. C 3	50 47.5° C St 1.5° C St 26.1° C	53 28.2 °C 307ES:- 54 28.5 °C 307ES:- 54 28.5 °C 307ES:-
TEST: N	TIME:	10 CE   10 CE	6	2000	909	65 A2
			1 100	7 B B B'		at .

TEMPERATURE DISTRIBUTION

RESTRICTED MANUOL PUNNING CHECK

TEST: MIS- 4 A

12:10

TIME

077 33 47.6 30 1:15 2:1 (1) ن (C) 15 XX 60 03 27.0 9 32.60 113 26.6°C ζ Λ <u>ධ</u> 27.6.0 ÷. 33.2.6 65 (D) Ca 87.50 87.60 87.60 87.60 87.60 87.60 30.4.℃ 0.0.00 :: 0.1.7. C!\r 6 03 Τ. () 0.31.00 3. 31.4.0 0 0 0 600 6 3.36.52 DON

	X		,								<i>i</i> 2			
	CHE	,				- 1	ijilli		92		1.5 \$ c.7	i i		
·	RUNNING CHECK	· (4)						+		26.				
NOITHBUTION	MANUAL				() () () () () () () () () () () () () (			ral .			6.7.5		1. (SEL)	
TEMPERATURE	TRICTED			07				2.7.07 e3	15		3.0.98		5.4.2	TEMPLOACIONS
	RESTI	-		1000				2.9.252	#2			<i></i>	55.37.4	10.5 1
	15- 4B	12:52						32	0.0.1875		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		33.6.2	33.1.5
	TEST: MIS-	工区位:			8 B						( i		m)	1.5

TEMPERATURE TESTS

TUNNEL

TEMPERATURE DISTRIBUTION .


RESTRICTED MANUAL RUNNING CHECK

14:18

TIME:

TEST: MIS-

5, 27-02 55 3 22.0°C 14.55 5, 8·97 E 7.02





. SETCH

TEMPERATURE DISTRIBUTION

RESTRICTED MONUEL RUNNIN


7.53

TIME:

TEST: MIS- AL

38 280 °C 2 5.54.00

90 ((()) 15 46.072 




-: SELON

... 52.0 %

2, 0.05 %

0.48 33.0 32 30.0 137 TE 14 25,0 10 10 100  $\omega$ U 4.00 T 3 AIR- FLOW CHACK TESTS 0.380 TEMPERATURE DISTRIBUTION 0.000 12 8 29 C 12 TEMPERATURE 0 の意 ...! !!\ THINNINE REVERSE 17. 1:0 (2:45 TEST: MISiu M



TEMPERATURE" DISTRIBUTION

TEST: MIS- 5 REVERSE AIR- FLOW TIME: 12:50

15 40.5 ° C · 23.2.8 ° C · 25.0 ° C · 25.0 ° C · 35.6 ° C · 34.6.8 ° C · 34.6.8 ° C · 34.6.8 ° C · 35.6 ° C


7.0 .() 7EST TUNNEL TEMPERATURE TESTS TEMPERATURE DISTRIBUTION 12 12 PUSH-OUT C 6.4.6 58 33.8 0, 202 00 3 6 3 E r No 7.7 TEMPERATURE SENSOR ARRAY ON CAR 1 TRAIN 0.50 33.51 0 O, 0.04 E C57.0 45.53 17 83 T 0 18 6 0 5111 88 2,75 8/5 10 35 50 10 35 50 10 35 50 0.20 L) U TEST: MIS- 6 TIME: 11:40 33.9 32.0 (1) (2) 7. 33. 7. 32. 43.00 38.90 3 (n)

h. O 3.5.0 25.5 r) ()~ \*\*\* ,O 6 10.00 25.2 49 0.2 T. (1) 3 ( )  $\circ$ ,° 12.01 25.0 SE 1270 O 13 TESTS 10.170 ტ 52 ίν. (1) m C) 88 1000 G TEMPERATURE DISTRIBUTION MOTES ů 25.6° . . . TEMPERATURE PUSH-OUT 3/.4 3 1,753 T. O. C.53 1 33.3 0 50 S. 0.02 KS 25.4°C :: WB 23.0 C 4 TEMPIRATURE SENSON ARRAY ON CAR I TRAIN 63 正 33.0 UNNEL 36.0 54.0 .0 7. 4:3:0°C . U % 33 40.0°C 26.6.0 9 22.6 2 Ω× H 80 3475 54 35.0°C 009-2.05 25 بر ال U TIME: 11:55 (: 32.2 TEST: MIS-٠ . ٥ 31.0 23.52.0 23 25.6 6 SUMP 23 ပ္ပ 3 S 30.0°C 1801

TUNNEL TEMPERATURE TESTS

TEMPERATURE DISTRIBUTION

PUSH - DUT TRAIN TIME: 12:10 TEST: 1:115- 6



0.55 J. 55.0 () 25 } 12 } 7:4 28.5 : <u>( )</u> CHECK TUNNEL TEMPERATURE TESTS 7 AVAILA BLE TEMPERATURE DISTRIBUTION SA 28.5 MANUAL READINGS 12 043 84 35.0°C 63 31.5 °C ., ٥ ۲ TEMPERATURE SENSOR ARRAY ON CAR I U C RESTRICTED 33.0 62 31.5 36.0.2 35.0°C .(1) ÷. J, 877 15: 1:C1 4.6 n n 52 33.0 °C ں S TEST: MIS- 7A TIME: 15:42 31.0 30.5 29.5 Ω Ω 63 3 1801

or

( s -s \ Li 3. 0.58 73: (\*) 27 55 1A 25.0 \$ |\O [3] i: (i' ຕາ Ç 27.4 (·) -: :4 CFちられ  $\circ$ TUNNEL TEMPERATURE TESTS 10A 39-0 (i) (C) TEMPERATURE DISTRIBUTION J. \$.6₹ , e MANUAL. 22.6 0 0.00 0.00 3 n) :: (1. 8C 55.57°C ÷. SS 38.0°C RESTRICTED 03 25.8 N-10 10 7 54.0 °C 45.0 °C 73 41.5 °C J. 4.82 ED F. 18.6 °C 5. 6. .. 65 17 54 35.6°C TEST: MIS- 7A TIME: 15 :45 32.0 90 TCX-

o r

TEMPERATURE SENSOR ARRAY

()

SA 30.0

()

3

ET FT

30.0


മ്പ

TEMPERATURE DISTRIBUTION  RESTRICTED MANUAL CHECK	CB 27.6	0	1 1	55 25.0°C 34 26.1°C	SE 24.5 °C NOTES:-	SENSOR ARALY
TEST: MIS - 78 TIME: 16:20		1.C	27.9.9.2	60 25.0 .0	63 23.6 °C	

TUNNEL TEMPERATURE TESTS

CHECK	
HANUAL	
RESTRICTED	
TEST: MIS- 78	TIME: 16:25

)* ·		5				
.0 .0  &	 			x .	2	
00 : C		00 00 00 00 00				
		.27				
08 26.2 WB 20.5 RH 56				11A 32.		
[O] [O] 52	, - 0 0			E)	-	
D D 31		36.0°C	<b>1.</b>			
0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0		* * C		U	NOTES:-	i I
03 31.2 13 25.4 24 62				9A 29.5	OZ	
· 0 · 0 ·		32.0°C #3.5°C 32.5°C		<u> </u>	5	
C3 28.6		80 32.0 80 43.5 8A 32.5		ان.	ان	ATURE ARRAY I
- 0 0 5		0 0 0		72 00 74	2, 2.9° 3	TEMPERATURE SENSOR ARRAY
23 26.8 32 22.9		73 33.0 72 41.0 73 29.5		99	- ما	
CA[ 5-1 , U]		20 S			· ·	Ä
		**************************************	8	٥	.0	.0
-	, F	× .	C    (36)  C	28.5	26.0	26.2
*	٥-	*		29	9	8
Wi .	0.4	-			¥	1 3
		1			*:	



TEST

OPERATIONS


NORMAL

TEST: MIS- 8

TUNNEL TEMPERATURE TESTS

0

TEMPERATURE DISTRIBUTION




TUNNEL TEMPERATURE TESTS
TEMPERATURE DISTRIBUTION

IMAULSE FAN INTERRUPTION TEST

15:40

TIME:

TEST: MIS- 9



TEMPERATURE DISTRIBUTION.


IMPULSE FAN INTERRUPTION TEST

TEST: MIS- 9


TIME:

42.25.0 27.2 60 (E) 22 46 5 5 | [] | | | | | | | | | | | **.** DB 25.2 27.0 11A 30.0 RH CO 0) 3, 078 ;: 7192 811 10 T. 10A 495 (C) A. 46 ... 3. 8.9 E NOTES 3.92 € 3C 5570°C C3 50.0 °C 0. 0.57 89 WB 26.2 'C 50 TEMPERATURE SENSOR ARRAY 6E 31.2 73 25.0°C 70 46,5°C 74 45,0°C DB 29.4 9 650 113 27. 1 (2) X /3 54 485°C 22 30.0 0 Ů SA 31.0 31.5 S15 39 129,5°C 24 315°C 28 26.5°C OKOS OKOS 68 - KOT


	3				E	44 23,5		-1	
TUNNEL TEMPERATURE TESTS TEMPERATURE DISTRIBUTION	IMFULSE FAW INTERRUPTION TEST		36.6°C 09 36.2°C 08 37.2°C 08 37.5°C 08 37.5°C 08 33.4°C WB 32.4°C	27 // ER 61 % CH		178 35.7°C   88 35.6°C   10A 34.7°C   10A 34	50 2%0 °C   9A 26.0 °C   11A 26.0 °C	DE 28.0 °C	TEMPERATURE SENSOR ARRAY ON CAR I
	MIS	TIME: 16:75		u W. C.	1CX — 3	12.29.0 °C 24 °C 2	6c 28.5°c	63 20.3 C	54 28.0°C



## LOCATION OF SENSORS



### TUNNEL TEMPERATURE TESTS BLOCK DIAGRAM RECORDING SYSTEM



UV1, UV2, UV3 ARE EACHT12 CHANNEL RECORDERS. ONLY 6 OF THE CHANNELS HAVE BUILT-IN CONDITIONING EQUIPMENT. HENCE THE NEED FOR A SEPARATE CONDITIONING UNIT ON THE TRAIN.

380 ISION PERCENTAGE SATURATION SPECIFIC VOLUME MOTHER TUNNEL TEMPERATURE TESTS PYSCHROMETRIC CHART

### Temperature/Humidity Log

Location	Ву :	
Test No.	 Designation :	0
Date :		- 11 <del> 11-</del>

Time	1.0	ocat:	ion	T	empera	iture		RH	
	F	С	R	Deg.	C db	Deg.	C wb	(%)	Remarks
				Y					
						10			
			•						
		<del></del>							
				10 100					
				· ·					
						+ Sec. (1)			
					•				8
			310.	. 81	*		*		
				- >	•				
-  -									
-									<del></del>
	8								(
						····			
	-								

Location :	Ву :
Test No. :	Designation :
Date :	
Tank Level :	
Time Heater/Boiler Ignition Compl	eted:
Time Heater/Boiler Shut-down Comp	leted :

Time	Water Tank	Consumption	Time	Gas Consumption Rate (1/m) Heaters Boilers					
	Level (cm)	Rate (1/m)	4.5	Heaters	Boilers				
•									
ti		***************************************							
	·			No. 2 (5) 4 (4) 4 (4) 44 (4) 44 (4) 44 (4) 44 (4) 44 (4) 44 (4) 44 (4) 44 (4) 44 (4) 44 (4) 44 (4) 44 (4) 44 (4)					
		× 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1							
				<u>, '</u>	14				
					1 <del>.2</del>				
		•							
				-					
TO ESCALISTA			·						
			*						
			ļ						
7.									
		7		Minima and a super					
		•							
7.37									
	<del> </del>								
	1	*							

Notes

Test No.	: "		77.						By:				· d
Date	:				_	1) (	gte	natio	n :				
Status Co	<u>le</u>	3				*\##;-=#	<u>l.i,</u>	ghto					
A B C D E	n E		x x	G	* reen reen * reen		Ye	# llow llow llow		* * * Red			
Unit No.	1	2	3	4	5	6	7	8	9	10	11	12	Remarks
						2					1/2		. 1)
y x <sup>360</sup>			1									,	(A)
	-									AV			
·									-		,		
												ļ	
1													
6												*	
Jan Sin								·					
							-						
	3												
*									_				
			<u> </u>										
													<u> </u>
3	er reca			-	8 ( H)	#0.	- *:***						
	in antere					****	0212TH						
			l i	-		(1 = £2	(*************************************						
	a -e e e e e	L	ļ,	1	1	) /		ļ.	F				