

The UDUNITS-2 Package

Steven R. Emmerson

Copyright © 2007 University Corporation for Atmospheric Research

Permission to use, copy, modify, and distribute this software and its documentation for any purpose without fee is hereby granted, provided that the above copyright notice appears in all copies, that both that copyright notice and this permission notice appear in supporting documentation, and that the name of the University Corporation for Atmospheric Research (UCAR) not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. UCAR makes no representations about the suitability of this software for any purpose. It is provided “as is” without express or implied warranty. It is provided with no support and without obligation on the part of UCAR to assist in its use, correction, modification, or enhancement.

Table of Contents

1	Introduction.....	1
2	How This Package Differs from the Original UDUNITS Package	2
3	Obtaining this Package.....	3
4	Installing this Package	4
4.1	Short Installation Instructions.....	4
4.2	Long Installation Instructions	4
4.3	What Gets Installed.....	5
5	Support for this Package.....	7
	Index	8

1 Introduction

The UDUNITS-2 package provides support for units of physical quantities. Its three main components are: 1) [\[a C library\]](#), [page](#) [\[a utility\]](#), [page](#) [\[a utility\]](#); for obtaining the definition of a unit and for converting numeric values between compatible units; and 3) an extensive database of units.

2 How This Package Differs from the Original UDUNITS Package

The UDUNIT-2 package differs from the original UDUNITS package in the following ways:

- **Support for non-ASCII characters.** The original UDUNITS package only supports the ASCII character set. The UDUNITS-2 package supports the following character sets: ASCII, ISO 8859-1 (Latin-1), and the UTF-8 encoding of ISO 10646 (Unicode). This means that unit string specifications like "F" are now supported (your viewer must support UTF-8 to display this string correctly).
- **Support for logarithmic units.** The unit string specification "0.1 lg(re 1 mW)" specifies a deciBel unit with a one milliwatt reference level. Such units are fully integrated into the package and all meaningful operations and conversions are supported.
- **Persistent value converters.** It is now possible to obtain a *converter* data-object, which can be used to convert numeric values in one unit to numeric values in another, compatible unit. The values can be `float`, `double`, or one-dimensional arrays of `floats` or `doubles`.
- **Improved API.** Due to the above changes, it was not possible to keep the application programming interface of the original UDUNITS package. The new interface, however, is easily understood and easy to use.
- **XML unit database.** The unit database is encoded using human-readable XML rather than a custom format. The XML parser included in the package supports an `<import>` element to allow easy and convenient customization.
- **No Fortran or Perl API.** Interfaces for these languages have not yet been created. Contact support-udunits@unidata.ucar.edu if you are interested in helping to create these interfaces.

One thing that has not changed is that all unit string specifications understood by the original UDUNITS package are also understood by the new UDUNITS-2 package.

3 Obtaining this Package

Get this package from its download-page at <http://www.unidata.ucar.edu/downloads/udunits/> and unpack it in an appropriate place, e.g.,

```
cd /usr/local/src
gunzip -c udunits-2.0.3.tar.gz | pax -r
```

4 Installing this Package

4.1 Short Installation Instructions

Not all development environments can build and install this package. See the long instructions in the next section for details.

The following assumes that you are familiar with autoconf-based package-installation. If you're not, then follow the long instructions in the next section.

```
./configure [--prefix=root] [--disable-shared] [CC=path]
make
make check      # optional; requires CUNIT installation
make install
make install-info install-html install-pdf
make clean
```

By default, the installation root is `/usr/local`.

If you encounter problems, then follow the instructions in the next section.

4.2 Long Installation Instructions

1. Go to the top-level source-directory of this package, e.g.,

```
cd udunits-2.0.3
```

2. Because some `make` utilities cannot build this package correctly, locate the operating system that is closest to yours in the following table and determine the *make* utility that you will use.

O/S	make Utility
-----	--------------

3. If necessary, clean-up from a previous installation attempt by making the `distclean` target using the *make* utility from step 2:

```
make distclean
```

4. Because some compilers cannot build this package correctly, locate the operating system closest to yours in the following table and determine the compiler that you will use and any required option for the `configure` script.

O/S	Compiler	configure Option
-----	----------	------------------

The option `--disable-shared` causes the build process to create a static library only: a sharable library is not created. This option is necessary if the `libtool` utility that's included in this package can't build a sharable library using the given compiler.

The following table lists the build environments that do not work — so don't use them:

O/S	Compiler	configure Option
-----	----------	------------------

5. Execute the `configure` script. Specify the installation prefix, the compiler from the previous step, and any required option. For example, if you are on an HP-UX system and want to use the `/bin/c89` compiler and install under `/opt`, then the following command is appropriate:

```
./configure --prefix=/opt --disable-shared CC=/bin/c89
```

If the installation prefix is not specified, then the default is to install under `/usr/local`.

If the compiler isn't specified, then the default is to use `gcc`.

6. Build this package by making the default target using the *make* utility from step 2:

```
make
```

7. If you wish to verify that this package works correctly, then make the `check` target using the *make* utility from step 2:

```
make check
```

This step is only effective if the `configure` script found an installed CUNIT unit-testing package. If that package wasn't found, then the above command will quickly exit without testing this package.

8. Install the `<undefined>` [library], page `<undefined>`, `<undefined>` [utility], page `<undefined>`, header-files, and units-database by making the `install` target using the *make* utility from step 2:

```
make install
```

9. If desired, install the documentation by making one or more of the following targets using the *make* utility from step 2:

```
make install-info install-html install-pdf
```

10. Clean up by making the `clean` target using the *make* utility from step 2:

```
make clean
```

4.3 What Gets Installed

By default, the following files are created or installed under the installation directory:

```
bin/:
udunits2                # Unit <undefined> [utility], page <undefined>

include/:
converter.h             # API for value converters
udunits2.h              # API for units

lib/:
libudunits2.a           # Static unit <undefined> [library], page <undefined>
libudunits2.la          # libtool(1) reference for unit <undefined> [library],
page <undefined>
libudunits2.so           # Link to shared <undefined> [library], page <un
defined>
libudunits2.so.0        # Link to shared <undefined> [library], page <un
defined>
libudunits2.so.0.0.0    # Shared <undefined> [library], page <undefined>

share/:
doc                     # Directory. Created if it doesn't exist
info                    # Directory. Created if it doesn't exist
```



```

udunits2.xml           # Default unit database
udunits2-accepted.xml  # Units accepted for use with the SI
udunits2-base.xml      # SI base units
udunits2-common.xml    # Common, non-SI units
udunits2-derived.xml   # Derived units of the SI
udunits2-prefixes.xml  # SI unit prefixes

share/doc:
udunits                # Directory. Created if it doesn't exist

share/doc/udunits:
udunits2.html          # HTML documentation on this package
udunits2lib.html       # HTML documentation on the unit <undefined> [library],
page <undefined>
udunits2lib.pdf        # PDF documentation on the unit <undefined> [library],
page <undefined>
udunits2.pdf           # PDF documentation on this package
udunits2prog.html      # HTML documentation on the unit <undefined> [utility],
page <undefined>
udunits2prog.pdf       # PDF documentation on the unit <undefined> [utility],
page <undefined>

share/info:
dir                    # Top-level "info" file. Created if it doesn't exist
udunits2.info          # INFO documentation on this package
udunits2lib.info       # INFO documentation on the unit <undefined> [library],
page <undefined>
udunits2prog.info      # INFO documentation on the unit <undefined> [utility],
page <undefined>

```

5 Support for this Package

The home-page for this package can be found at <http://www.unidata.ucar.edu/software/udunits/>. ■

Bug reports should be sent to support-udunits@unidata.ucar.edu.

Index

I		P	
installing this package	4	package, support.....	7
Introduction.....	1		
O		S	
obtaining this package	3	support.....	7