

Indoor Mobile Robot Localization and Mapping

Darrah Beebe
Advisor: Dr. Suruz Miah

Department of Electrical and Computer Engineering
Bradley University
1501 W. Bradley Avenue
Peoria, IL, 61625, USA

June 11, 2020

1 Introduction

2 Project So Far

- Network Diagram
- DB - Remote AT Command
- Previously Done
- Current Progress

3 Future Directions

Introduction

Goal of project is to implement XBee modules to localize a mobile robot using Cayley-Menger determinant's based on signal strength.

Network Diagram

Diagram of ZigBee network




Figure: ZigBee network diagram

DB - Remote AT Command




Figure: Getting RSSI with Remote AT Command

Previously Done

- XCTU
- Powershell
- Backbone to XBee (linux c code)

Current Progress

- Calculate Distance - Ongoing?
- Putting together documentation - Ongoing

Current Progress

```
debian@beaglebone:~/localization/Darrah$ ./TestTableProg
```

Beacon #	RSSI	Distance
Beacon 1	-0x0C dBm	0.039573m
Beacon 2	-0x24 dBm	0.627185m
Beacon 3	-0x2D dBm	1.767649m

Figure: RSSI+Distance(FreeSpace) Output Table

```
debian@beaglebone:~/localization/Darrah$ ./TestTableProg
```

Beacon #	RSSI	Distance
Beacon 1	-0x0C dBm	7.079458m
Beacon 2	-0x26 dBm	0.354813m
Beacon 3	-0x2F dBm	0.125893m

Figure: RSSI+Distance(Miah) Output Table

Future Directions

- Calculate Distance?
- Localization with Cayley-Menger
- Putting together documentation
- Wiki Page